

Project	<b>IEEE 802.16 Broadband Wireless Access Working Group</b> < <a href="http://ieee802.org/16">http://ieee802.org/16</a> >	
Title	<b>A Contribution to TGa: ARQ Feedback Payload</b>	
Date Submitted	<b>2002-02-25</b>	
Source(s)	Lei Wang Brian Gieschen  Wi-LAN Inc. 2891 Sunridge Way, NE Calgary, AB, Canada, T1Y 7K7	Voice: (403)273-9133 Fax: (403)273-5100  Email: <a href="mailto:LeiW@wi-lan.com">LeiW@wi-lan.com</a> ; <a href="mailto:BrianG@wi-lan.com">BrianG@wi-lan.com</a> ;
Re:	This is a contribution to the IEEE 802.16 TGa.	
Abstract	This contribution provides an enhanced description to the piggybacked ARQ feedback.	
Purpose	To Enhance the piggybacked ARQ feedback description in 802.16a/D2.	
Notice	This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.	
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate text contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE s name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE s sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.	
Patent Policy and Procedures	The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures (Version 1.0) < <a href="http://ieee802.org/16/ipr/patents/policy.html">http://ieee802.org/16/ipr/patents/policy.html</a> >, including the statement IEEE standards may include the known use of patent(s), including patent applications, if there is technical justification in the opinion of the standards-developing committee and provided the IEEE receives assurance from the patent holder that it will license applicants under reasonable terms and conditions for the purpose of implementing the standard.  Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair < <a href="mailto:r.b.marks@ieee.org">mailto:r.b.marks@ieee.org</a> > as early as possible, in written or electronic form, of any patents (granted or under application) that may cover technology that is under consideration by or has been approved by IEEE 802.16. The Chair will disclose this notification via the IEEE 802.16 web site < <a href="http://ieee802.org/16/ipr/patents/notices">http://ieee802.org/16/ipr/patents/notices</a> >.	

## 1 Introduction

This document provides an enhanced description of piggybacked ARQ feedback.

## 2 Reference

[TG1/D5] IEEE P802.16/D5 - 2001.

[TGa/D2] IEEE 802.16a/D2 - 2002.

## 3 Suggested Text for replacing line 17 to line 39 on page 46

### 6.2.3.4.3.1 Piggybacked ARQ Feedback

The ARQ feedback may be piggybacked on an existing connection. The piggybacked ARQ feedback is not in the form of sub-header, instead it is in the form of packed payload of the MAC PDU. The presence of the piggybacked ARQ feedback payload is indicated by the value of the TYPE field in the generic MAC header. When the piggybacked ARQ feedback payload is present, it shall be the first packed payload of the MAC PDU. Similar to other packed payloads, the ARQ feedback payload is also preceded by a packing sub-header. However, the FSN field shall be ignored for the ARQ feedback payload and the FC bits shall be set to 00.

Both non-ARQ connections and ARQ connections can piggyback ARQ feedback, but with different packing sub-headers. For example, Table 146 defines two type values, 0x0A and 0x0C, for the piggybacked ARQ feedback present, where TYPE=0x0A is for non-ARQ connection to piggyback ARQ feedback with non-ARQ packing sub-header; TYPE=0x0C is for ARQ connection to piggyback ARQ feedback with ARQ packing sub-header.

Figure 136 illustrates the examples of MAC PDU with piggybacked ARQ feedback.

Generic MAC Header (TYPE=0x0A)	non-ARQ packing sub-header	ARQ feedback payload (one or more ARQ feedback IEs)	non-ARQ packing sub-header	payload (one MAC SDU or fragment)	CRC-32
--------------------------------	----------------------------	---	----------------------------	-----------------------------------	--------

**(a) Non-ARQ Connection Piggybacking ARQ Feedback**

Generic MAC Header (TYPE=0x0C)	ARQ packing sub-header	ARQ feedback payload (one or more ARQ feedback IEs)	ARQ packing sub-header	payload (one MAC SDU or fragment)	CRC-32
--------------------------------	------------------------	---	------------------------	-----------------------------------	--------

**(b) ARQ Connection Piggybacking ARQ Feedback**

Generic MAC Header (TYPE=0x0B)	Grant Management sub-header	non-ARQ packing sub-header	ARQ feedback payload (one or more ARQ feedback IEs)	non-ARQ packing sub-header	payload (one MAC SDU or fragment)	CRC-32
--------------------------------	-----------------------------	----------------------------	---	----------------------------	-----------------------------------	--------

**(c) Non-ARQ Connection Piggybacking ARQ Feedback and Grant Management Sub-header Present (UL only)**

Generic MAC Header (TYPE=0x0D)	Grant Management sub-header	ARQ packing sub-header	ARQ feedback payload (one or more ARQ feedback IEs)	ARQ packing sub-header	payload (one MAC SDU or fragment)	CRC-32
--------------------------------	-----------------------------	------------------------	---	------------------------	-----------------------------------	--------

**(d) ARQ Connection Piggybacking ARQ Feedback and Grant management Sub-header Present (UL only)**

**FIGURE 136 Examples of MAC PDU with Piggybacked ARQ Feedback**