

Project	IEEE 802.16 Broadband Wireless Access Working Group < http://ieee802.org/16 >	
Title	Adjacent Carrier Permutation for OFDMA	
Date Submitted	2002-05-21	
Source(s)	Phil Kelly BeamReach Networks 755 N. Mathilda Ave Sunnyvale, CA 94086 USA	Voice: 408-869-8700 Fax: 408-869-8701 mailto:pkelly@beamreachnetworks.com
Re:	Call for Contributions on P802.16a Mergers and Consolidation Document Number: IEEE 802.16a-02/22, April 15, 2002. URL: < http://ieee802.org/16/docs/02/80216-02_22.pdf >	
Abstract	Describes an adjacent carrier permutation for OFDMA.	
Purpose	Addresses an interoperability concern within OFDMA not addressed by C802.16a-02/49. Make proposed changes to P802.16a/D3.	
Notice	This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.	
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate text contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.	
Patent Policy and Procedures	<p>The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures (Version 1.0) <http://ieee802.org/16/ipr/patents/policy.html>, including the statement "IEEE standards may include the known use of patent(s), including patent applications, if there is technical justification in the opinion of the standards-developing committee and provided the IEEE receives assurance from the patent holder that it will license applicants under reasonable terms and conditions for the purpose of implementing the standard."</p> <p>Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair <mailto:r.b.marks@ieee.org> as early as possible, in written or electronic form, of any patents (granted or under application) that may cover technology that is under consideration by or has been approved by IEEE 802.16. The Chair will disclose this notification via the IEEE 802.16 web site <http://ieee802.org/16/ipr/patents/notices>.</p>	

Adjacent Carrier Permutation for OFDMA

Phil Kelly

Purpose

This contribution, in conjunction with C802.16-02/49, achieves complete harmonization of the OFDMA2 PHY mode with the previous OFDMA PHY mode.

Comment

Page	Line	Section
212	55	8.3.4.5
Comment		
Merge the OFDMA2 mode into the OFDMA mode		
Remedy		
Move (with editorial modifications) the text from line 57 down to line 30 in page 213 to a new section. The modified text should read:		
8.3.4.4.3.3 Adjacent Carrier Permutation		
<p>Implementation of AAS systems is optional. AAS systems An OFDMA-BS may use the distributed carrier permutations specified in defined in (section 8.3.4.4.3) or the adjacent carrier permutation specified in this clause. An OFDMA-SS shall be compatible with both permutations. With the adjacent carrier permutation, symbol data within a subchannel is assigned to adjacent carriers and the pilot and data carriers are assigned fixed positions in the frequency domain within an OFDM symbol.</p>		
<p>Table ?: Carrier Allocations for the Adjacent Carrier permutation</p>		
<pre> =====+ Parameter Value =====+ Number of dc carriers 1 =====+ Number of Guard Carriers, Left 176 =====+ Number of Guard Carriers, Right 175 =====+ Nused Number of Used Carriers N 1696 =====+ Total Number of Carriers 2048 =====+ Number of Variable-Location Pilots 0 =====+ Number of Fixed-location Pilots 160 =====+ Number of Variable-Location Pilots which 0 coincide with Fixed-Location Pilots =====+ Total Number of Pilots 160 =====+ Number of data carriers 1536 =====+ Nsubchannels 32 =====+ Nsubcarriers 53 =====+ Number of data carriers per subchannel 48 =====+ BasicFixedLocationPilots { 5,16,27,38,49} within each subchannel =====+ </pre>		