

Project	IEEE 802.16 Broadband Wireless Access Working Group < http://ieee802.org/16 >	
Title	Keep Alive Mechanism For Session Information Management	
Date Submitted	2004-05-18	
Serving(s)	Dongkie Lee, DongIl Moon, DongRyul Lee, JongKuk Ahn, Sungho Ha SK Telecom 15F, Seoul Finance Center, 84, Taepyungpro 1 ga, Chung-gu, Seoul, 100-768, Korea	Voice: +82-2-6323-3147 Fax: +82-2-6323-4493 [mailto: {galahad,dimoon,drlee,jgahn,ss23}@sktelecom.com]
Re:	Response to IEEE 802.16-04/19 (Recirculation Ballot #14a Announcement)	
Abstract	In order to minimize the session information which are inactive for long time, Keep Alive mechanism is introduced. After configured number of unresponsiveness to Keep Alive message, BS purges inactive session information to optimal utilize the session information storage.	
Purpose	Discuss and Adopt as the session information management mechanism	
Notice	This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.	
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.	
Patent Policy and Procedures	The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures < http://ieee802.org/16/ipr/patents/policy.html >, including the statement "IEEE standards may include the known use of patent(s), including patent applications, provided the IEEE receives assurance from the patent holder or applicant with respect to patents essential for compliance with both mandatory and optional portions of the standard." Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair < mailto:chair@wirelessman.org > as early as possible, in written or electronic form, if patented technology (or technology under patent application) might be incorporated into a draft standard being developed within the IEEE 802.16 Working Group. The Chair will disclose this notification via the IEEE 802.16 web site < http://ieee802.org/16/ipr/patents/notices >.	

Keep Alive Mechanism for Session Information Management

Dongkie Lee, DongRyul Lee, DongIl Moon, JongKuk Ahn
SK Telecom

1. Problem Statements

Current IEEE 802.16d/e standard does not specify session information purge procedure. Previously, main target of 802.16 was fixed broadband wireless access and session purging procedure caused by mobility was not considered. During the traversal(or handoff), target BS may retrieves session information from source BS and may requests to source BS to purge all the session related information. But if the target BS somehow does not get source BS ID from MSS, or MSS does not request source BS to purge all the session information before traversal, then session information will not be purged by BS. Inactive session information grows over time and may cause system failure due to database drainage if appropriate measure is not taken.

2. Overview of Proposed Solution

To differentiate between connection and session, *session* is defined as below. Session is established when registration is complete, but to extensively define all the shared-information between MSS and BS, information obtained after registration procedure like Service Flow Parameters, IP Address are also included in Session Information.

connection: A unidirectional mapping between base station (BS) and subscriber station (SS) medium access control (MAC) peers for the purpose of transporting a service flow's traffic. Connections are identified by a connection identifier (CID). All traffic is carried on a connection, even for service flows that implement connectionless protocols, such as Internet Protocol (IP).

Session: A session refers to a shared state between the BS and MSS and it is established after registration is complete. Session information includes Basic CID, Primary Management CID, Secondary Management CID, Security Association, MSS capabilities, MAC Address. Transport CID, Service Flow Parameters, IP Address of SS, NAI etc also are included in session information.

The MSS and BS shall monitor the traffic flowing on the downlink connection and uplink connection, respectively, directed to-or-from the MSS. If either the MSS or the BS detects a period of inactivity of at least *Session Close Time/ Number of KeepAlive* minutes, it may send a KeepAliveRequest message. The recipient of the message shall respond by sending the KeepAliveResponse message. When a KeepAliveResponse message is received, the recipient shall not send another KeepAliveRequest message for at least *Session Close Time/Number of KeepAlive* minutes. If either the MSS or the BS does not detect any traffic from the other-side directed to it for a period of at least *Session Close Time* minutes, it shall purge the session information of that MSS and all the other information related with the MSS. If the value of *of Session Close Time* is set to zero, the MSS and BS shall not send or expect keep-alive messages, and shall disable the transitions occurring as a consequence of not receiving these messages.

Name	Length	Description
Session Close Time	2 byte	Default is 2880, that is 48 hours. 0 means disable keepAlive messages; all other values are in minutes.
Number of KeepAlive	1 byte	Default is 3.

3. Proposed Changes to IEEE 802.16e/D2

3.1 Option 1-Addition of New messages *KeepAlive*

3. Definitions

[Add the following text to section 3:]

3.2 Session:

A session refers to a shared state between the BS and MSS and it is established after registration is complete. Session information includes Basic CID, Primary Management CID, Secondary Management CID, Security Association, MSS capabilities, MAC Address, Transport CID, Service Flow Parameters, IP Address of SS, NAI etc also are included in session information.

[Add the following after 6.3.21 MSS Idle Mode]

6.3.22 Session Information Management

A session is established when registration is complete, and session information includes Basic CID, Primary Management CID, Secondary Management CID, Security Association, MSS capabilities, MAC Address. But information obtained after registration procedure like Service Flow Parameters, IP Address are also referred to as session information.

The MSS and BS shall monitor the traffic flowing on the downlink connection and uplink connection, respectively, directed to-or-from the MSS. If either the MSS or the BS detects a period of inactivity of at least *Session Close Time/ Number of KeepAlive* minutes, it may send a KeepAliveRequest message. The recipient of the message shall respond by sending the KeepAliveResponse message. When a KeepAliveResponse message is received, the recipient shall not send another KeepAliveRequest message for at least *Session Close Time/Number of KeepAlive* minutes and extend the *Session Close Time* with *Session Close Time/Number of KeepAlive* minutes. If either the MSS or the BS does not detect any traffic from the other-side directed to it for a period of at least *Session Close Time* minutes, it shall purge the session information of that MSS and other information related with the MSS. If the value of *Session Close Time* is set to zero, the MSS and BS shall not send or expect keep-alive messages, and shall disable the transitions occurring as a consequence of not receiving these messages.

[in Section 6.3.2.3 MAC Management messages]

[Change Table 14a as shown]

Type	Message	Message Description	Connection
60	MOB-HO-IND	HO indication message	basic
61	KA-REQ	KeepAlive request message	primary
62	KA-RSP	KeepAlive response message	primary
6163-255	reserved		

[Add the following after 6.3.2.3.58 BS Broadcast Paging(MOB_PAG-ADV) message]

6.3.2.3.59 KeepAlive request(KA-REQ) message

This message is sent when either the MSS or the BS detects a period of inactivity of at least *Session Close Time/ Number of KeepAlive* minutes.

Table 1 KA-REQ message format

Syntax	Size	Notes
KeepAlive Message Format(){		
Management Message Type = 61	8 bits	
Transaction ID	16 bits	
TLV Encoded Attributes	Variable	TLV specific

}		
---	--	--

6.3.2.3.60 KeepAlive response(KA-RSP) message

This message is sent when either the MSS or the BS receives KeepAlive request message. When a KeepAliveResponse message is received, the recipient shall not send another KeepAliveRequest message for at least *Session Close Time/Number of KeepAlive* minutes.

Table 2 KA-RSP message format

Syntax	Size	Notes
KeepAlive Message Format(){		
Management Message Type = 62	8 bits	
Transaction ID	16 bits	
Confirmation Code	8 bits	
TLV Encoded Attributes	Variable	TLV specific
}		

11.7 REG-REQ/RSP management message encodings

[Insert immediately before the start of section 11.8]

11.7.11 Keep Alive parameters

11.7.11.1 Session Close Time

The value of this field specifies the inactivity period, in minutes, after which both the MSS and the BS purges the session information related with the MSS.

Type	Length	Value	Scope
20	2	Default is 2880, that is 48 hours. 0 means disable keepAlive messages; all other values are in minutes.	REG-RSP

11.7.11.2 Number of KeepAlive

The value of this field specifies the number of times KeepAlive messages shall be sent during Session Close Time.

Type	Length	Value	Scope
21	1	Default is 3.	REG-RSP

[Change 12.1.1.4.8 as shown]

12.1.1.4.8 REG-RSP

- Secondary Management CID
- Uplink CID Support
- Vendor ID Encoding (if present in REG-REQ)
- PKM Flow Control (if present in REG-REQ or changed from default)
- DSx Flow Control (if present in REG-REQ or changed from default)
- MCA Flow Control (if present in REG-REQ or changed from default)
- IP version (if present in REG-REQ or changed from default)
- MAC CRC support (if present in REG-REQ or changed from default)
- Multicast Polling Group CID support (if present in REG-REQ or changed from default)
- Vendor-specific information (Compound, only allowed if Vendor ID present in REG-REQ, and extensions provided)
- Vendor ID

- Vendor-specific extensions
- [Session Close Time\(default = 2880 min\)](#)
- [Number of KeepAlive\(default = 3\)](#)
- HMAC Tuple

3.2 Option 2-Using Exiting RNG-REQ/RSP messages for *Awake mode MSS*

[6.3.22 Connection Information Management](#)

[If the T27 timer expires *Number of KeepAlive* times of successive grants without receiving RNG-REQ for awake mode MSS, it shall purge the connection information of that MSS and the connection information includes the whole information related with the MSS like security context, ARQ states, MAC address etc.](#)

[When the serving BS successfully transferred connection information to target BS and is notified the success of handoff, it may purge all the connection information of the MSS based on the local policy.](#)

6.3.2.3.5 Ranging Request (RNG_REQ) message

The following parameters shall be included in the RNG-REQ message when the MSS is attempting to perform re-entry, association or hand-over:

Serving BS ID

The BS ID of the BS to which the MSS is currently connected (has completed the registration cycle and is in Normal Operation). Serving BS ID shall not be included if interval timer is timed-out (Serving BS ID AGINGTIMER, see Table 264a). Inclusion of Serving BS ID in the RNG-REQ message signals to the Target BS that the MSS is currently connected to the network through the serving BS and is performing association or is in the process of either hand-over or network re-entry.

[Number of KeepAlive](#)

[When T27 timer expires *Number of KeepAlive* times of successive grants without receiving RNG-REQ, BS shall purge the connection information of that MSS.](#)

11.5 RNG-REQ message encodings

[Add the following rows to table 318:]

Table 318a-RNG-REQ Message Encodings

Name	Type(1 byte)	Length	Value
Serving BS ID	4	6	The unique identifier of the former Serving BS
Basic CID	6	2	Basic CID allocated from the former Serving BS
Number of KeepAlive	8	1	Number of T27 expiration of successive grants allowed until session information purge