

Project	<b>IEEE 802.16 Broadband Wireless Access Working Group</b> < <a href="http://ieee802.org/16">http://ieee802.org/16</a> >	
Title	<b>WirelessMAN-OFDMA System Profiles</b>	
Date Submitted	<b>2004-11-12</b>	
Source(s)	Ivy Kelly John Humbert  Sprint BWTD KSOPHD0302 - 3B254 6220 Sprint Pkwy Overland Park, KS 66251 USA  Sean Cai Jason Hou Irving Wang  ZTE San Diego Inc. 10105 Pacific Heights Blvd. San Diego, CA 92121 USA	<a href="mailto:Ivy.Y.Kelly@mail.sprint.com">Ivy.Y.Kelly@mail.sprint.com</a> <a href="mailto:John.J.Humbert@mail.sprint.com">John.J.Humbert@mail.sprint.com</a>  Voice: 913-794-3337  <a href="mailto:scai@ztesandiego.com">scai@ztesandiego.com</a> <a href="mailto:jhou@ztesandiego.com">jhou@ztesandiego.com</a> <a href="mailto:iwang@ztesandiego.com">iwang@ztesandiego.com</a>  Voice: 858-554-0387 Fax: 858-554-0894
Re:	Response to Sponsor Ballot on IEEE802.16e/D5a document	
Abstract	This contribution describes the missing WirelessMAN-OFDMA system MAC and PHY profiles.	
Purpose	To incorporate the text changes proposed in this contribution into the 802.16e/D6 draft.	
Notice	This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.	
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.	
Patent Policy and Procedures	The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures < <a href="http://ieee802.org/16/ipr/patents/policy.html">http://ieee802.org/16/ipr/patents/policy.html</a> >, including the statement "IEEE standards may include the known use of patent(s), including patent applications, provided the IEEE receives assurance from the patent holder or applicant with respect to patents essential for compliance with both mandatory and optional portions of the standard." Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair < <a href="mailto:chair@wirelessman.org">mailto:chair@wirelessman.org</a> > as early as possible, in written or electronic form, if patented technology (or technology under patent application) might be incorporated into a draft standard being developed within the IEEE 802.16 Working Group. The Chair will disclose this notification via the IEEE 802.16 web site < <a href="http://ieee802.org/16/ipr/patents/notices">http://ieee802.org/16/ipr/patents/notices</a> >.	

# WirelessMAN-OFDMA System Profiles

*Ivy Kelly, John Humbert*  
**Sprint**

*Sean Cai, Jason Hou, Irving Wang*  
**ZTE San Diego Inc.**

## 1. Problem Statement

In order to reflect new opportunities for providing broadband service in the 2.5 to 2.7 GHz bands, the FCC in June 2004, among other things, renamed the Multipoint Distribution Service (MDS) in the U.S. to become the Broadband Radio Service (BRS). Also, it renamed the Instructional Television Fixed Service (ITFS) in the same bands the Educational Broadband Service (EBS) for the same reason. The bands remain known as either MDS or the Multichannel, Multipoint Distribution Service (MMDS) in many other parts of the world. The FCC decision also expanded the original BRS/EBS (aka MDS-ITFS) band by adding to it five megahertz of additional spectrum from the Mobile Satellite Service below 2500 MHz, which increases the total size of the higher band to 194 megahertz.

There are missing WirelessMAN-OFDMA mobile system profile definitions in **Table 411** of IEEE Standard 802.16-2004. The 2.3GHz band for WiBro service in Korea should be also addressed in the profile definition.

## 2. Proposed solutions

We would like to propose 5MHz, 8.75MHz, 10Mhz, and 20MHz channel profiles (TDD only) to 2.3-2.7GHz licensed band.

## 3. Specific text changes

==== Start text changes =====

*[Insert the following text to **Table 411a** in section 12.4 **WirelessMAN-OFDMA and WirelessHUMAN(-OFDMA) system profiles** ]*

**Table 411a—WirelessMAN-OFDMA mobile profiles for 2.3-2.7GHz licensed band**

<b>Identifier</b>	<b>Description</b>
OFDMA_profM2	WirelessMAN-OFDMA basic packet PMP MAC Profile supporting mobility
OFDMA_profP8	WirelessMAN-OFDMA 5 MHz channel basic PHY profile for mobility
OFDMA_profP9	WirelessMAN-OFDMA 8.75 MHz channel basic PHY profile for mobility
OFDMA_profP10	WirelessMAN-OFDMA 10 MHz channel basic PHY profile for mobility
OFDMA_profP11	WirelessMAN-OFDMA 20 MHz channel basic PHY profile for mobility

==== End text changes =====

==== Start text changes =====

*[Insert the following sections before section 12.4.3]*

#### **12.4.2.2 Basic Packet PMP WirelessMAN-OFDMA MAC Profile for Mobility**

Profile identifier: OFDMA\_profM2.

Mandatory Features:

- Support of Packet convergence sublayer.
- Support of Internet Protocol Ipv4.
- CRC functionality shall be supported for all connections.
- Support of dynamic services.
- Support of UGS/CG services.
- Support of Real time services.
- Support of Best effort services.
- Support of Non-Real-Time Polling services.
- Support of CDMA based Initial and Periodic Ranging.
- Support of Contention based CDMA bandwidth requests.
- Support of Sleep Mode.
- Support of Idle Mode/Paging.
- Support of neighbor scanning procedures.
- Support of Break-Before-Make Handover
- Support of FBSS handover.
- Support of ARQ.

##### **12.4.2.2.1 Conventions for MAC Management Messages**

The following rules shall be followed when reporting parameters in MAC Management messages:

- Service Class Names should not be used.
- No TLVs besides Error Encodings and HMAC Tuples shall be reported back in DSA-RSP and DSC-RSP messages.
- No TLVs besides HMAC Tuples shall be reported back in DSA-ACK messages.
- DSC-REQ messages shall not contain Request/Transmission Policy, Fixed vs. Variable Length SDU Indicator, SDU Size, ATM Switching, or Convergence Sublayer Specification TLVs.

##### **12.4.2.2.2 MAC Management Message Parameter Transmission Order**

Systems implementing the profile OFDMA\_ProfM2 shall transmit the TLV encoded parameters for mandatory features in the respective messages. Those systems only include the parameters listed under the respective message in its transmission of said messages plus any parameters necessary for optional features. Parameters for optional features shall occur after those listed for support of mandatory features. For the required features, the relevant parameters shall be transmitted in order of increasing Type value of the parameter's TLV key. Parameters with defined default values should be omitted if the desired value coincides with the default one.

==== End text changes =====

==== Start text changes =====

*[Insert the following sections before section 12.4.4]*

#### **12.4.3.11 WirelessMAN-OFDMA 5 MHz channel basic PHY Profile for Mobility**

Profile identifier: OFDMA\_ProfP8.

Systems implementing OFDMA\_ProfP8 shall meet the minimum performance requirements listed in Table 422a:

**Table 422a—Minimum Performance requirements for OFDMA\_ProfP8**

Capability	Minimum Performance
Channel bandwidth	5 MHz
Operation mode	TDD (licensed bands only)

FFT Size	512
BER performance threshold, BER=10 <sup>-6</sup> (using all subchannels BS/SS)	
QPSK-1/2	≤ -85 dBm
QPSK-3/4	≤ -82 dBm
16QAM-1/2	≤ -78 dBm
16QAM-3/4	≤ -75 dBm
64QAM-2/3 (if 64-QAM supported)	≤ -71 dBm
64QAM-3/4 (if 64-QAM supported)	≤ -69 dBm
(Add $10 \cdot \log_{10} \left( \frac{\text{NumberOfSub ChannelsUsed}}{\text{TotalNumberOfSubchannels}} \right)$ to sensitivity when not all subchannels are used in the BS/SS Rx)	
Reference frequency tolerance BS to BS BS SS to BS synchronization tolerance	Synchronized with common time base  ≤ ± 2*10 <sup>-6</sup> ≤ 50 Hz
Frame duration code set	{2} (5ms)

**12.4.3.12 WirelessMAN-OFDMA 8.75 MHz channel basic PHY Profile for Mobility**

Profile identifier: OFDMA\_ProfP9.

Systems implementing OFDMA\_ProfP9 shall meet the minimum performance requirements listed in Table 422b:

**Table 422b—Minimum Performance requirements for OFDMA\_ProfP9**

Capability	Minimum Performance
Channel bandwidth	8.75 MHz
Operation mode	TDD (licensed bands only)
FFT Size	1024
BER performance threshold, BER=10 <sup>-6</sup> (using all subchannels BS/SS)	
QPSK-1/2	≤ -82.5 dBm
QPSK-3/4	≤ -79.5 dBm
16QAM-1/2	≤ -75.5 dBm
16QAM-3/4	≤ -72.5 dBm
64QAM-2/3 (if 64-QAM supported)	≤ -68.5 dBm
64QAM-3/4 (if 64-QAM supported)	≤ -66.6 dBm
(Add $10 \cdot \log_{10} \left( \frac{\text{NumberOfSub ChannelsUsed}}{\text{TotalNumberOfSubchannels}} \right)$ to sensitivity when not all subchannels are used in the BS/SS Rx)	
Reference frequency tolerance BS to BS BS SS to BS synchronization tolerance	Synchronized with common time base  ≤ ± 2*10 <sup>-6</sup> ≤ 50 Hz

Frame duration code set	{2} (5ms)
-------------------------	-----------

#### 12.4.3.13 WirelessMAN-OFDMA 10 MHz channel basic PHY Profile for Mobility

Profile identifier: OFDMA\_ProfP10.

Systems implementing OFDMA\_ProfP10 shall meet the minimum performance requirements listed in Table 422c:

**Table 422c—Minimum Performance requirements for OFDMA\_ProfP10**

Capability	Minimum Performance
Channel bandwidth	10 MHz
Operation mode	TDD (licensed bands only)
FFT Size	1024
BER performance threshold, BER=10 <sup>-6</sup> (using all subchannels BS/SS)	
QPSK-1/2	≤ -82 dBm
QPSK-3/4	≤ -79 dBm
16QAM-1/2	≤ -75 dBm
16QAM-3/4	≤ -72 dBm
64QAM-2/3 (if 64-QAM supported)	≤ -68 dBm
64QAM-3/4 (if 64-QAM supported)	≤ -66 dBm
(Add $10 \cdot \log_{10} \left( \frac{\text{NumberOfSub ChannelsUsed}}{\text{TotalNumberOfSubchannels}} \right)$ to sensitivity when not all subchannels are used in the BS/SS Rx)	
Reference frequency tolerance	Synchronized with common time base
BS to BS	
BS	≤ ± 2*10 <sup>-6</sup>
SS to BS synchronization tolerance	≤ 50 Hz
Frame duration code set	{2} (5ms)

#### 12.4.3.14 WirelessMAN-OFDMA 20 MHz channel basic PHY Profile for Mobility

Profile identifier: OFDMA\_ProfP11.

Systems implementing OFDMA\_ProfP11 shall meet the minimum performance requirements listed in Table 422d:

**Table 422d—Minimum Performance requirements for OFDMA\_ProfP11**

Capability	Minimum Performance
Channel bandwidth	20 MHz
Operation mode	TDD (licensed bands only)
FFT Size	2048

BER performance threshold, BER=10 <sup>-6</sup> (using all subchannels BS/SS)  QPSK-1/2 QPSK-3/4 16QAM-1/2 16QAM-3/4 64QAM-2/3 (if 64-QAM supported) 64QAM-3/4 (if 64-QAM supported)  (Add $10 \cdot \log_{10} \left( \frac{\text{NumberOfSub ChannelsUsed}}{\text{TotalNumberOfSubchannels}} \right)$ to sensitivity when not all subchannels are used in the BS/SS Rx)	$\leq -79$ dBm $\leq -76$ dBm $\leq -72$ dBm $\leq -69$ dBm $\leq -65$ dBm $\leq -63$ dBm
Reference frequency tolerance BS to BS BS SS to BS synchronization tolerance	Synchronized with common time base $\leq \pm 2 \cdot 10^{-6}$ $\leq 50$ Hz
Frame duration code set	{2} (5ms)

==== End text changes =====

## 4. References

- [1] IEEE Standard 802.16e/D5a-2004
- [2] IEEE Standard 802.16-2004