

Project	<b>IEEE 802.16 Broadband Wireless Access Working Group</b> < <a href="http://ieee802.org/16">http://ieee802.org/16</a> >	
Title	<b>The Enhancement For Authorization Policy Negotiation In SBC Exchange</b>	
Date Submitted	<b>2005-05-05</b>	
Source(s)	Li Rui, Tian Feng, Chen JianYong, Zhao Jie, Li YuanWei  ZTE corporation ZTE Plaza , Keji Road South , Hi-tech Industrial Park , Nanshan District , Shenzhen , P.R.China , 518057	Voice: [86-0755-26772016] Fax: [86-0755-26772004] <a href="mailto:li.rui2@zte.com.cn">[mailto:li.rui2@zte.com.cn]</a>
Re:	Response to Sponsor Ballot on IEEE802.16e/D7 document	
Abstract	This contribution describes the enhancement of authorization policy negotiation in SBC exchange.	
Purpose	To incorporate the text changes proposed in this contribution into the 802.16e/D8 draft.	
Notice	This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.	
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.	
Patent Policy and Procedures	The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures < <a href="http://ieee802.org/16/ipr/patents/policy.html">http://ieee802.org/16/ipr/patents/policy.html</a> >, including the statement "IEEE standards may include the known use of patent(s), including patent applications, provided the IEEE receives assurance from the patent holder or applicant with respect to patents essential for compliance with both mandatory and optional portions of the standard." Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair < <a href="mailto:chair@wirelessman.org">mailto:chair@wirelessman.org</a> > as early as possible, in written or electronic form, if patented technology (or technology under patent application) might be incorporated into a draft standard being developed within the IEEE 802.16 Working Group. The Chair will disclose this notification via the IEEE 802.16 web site < <a href="http://ieee802.org/16/ipr/patents/notices">http://ieee802.org/16/ipr/patents/notices</a> >.	

# The Enhancement For Authorization Policy Negotiation In SBC Exchange

*Li Rui, Tian Feng, Chen JianYong, Zhao Jie, Li YuanWei*  
**ZTE corporation**

## 1. Problem Statement

The authorization policies for initial network entry and re-entry are negotiated between MS and BS in the SBC exchange in current P802.16e/D7. But the re-authorization policy is not negotiated between MS and BS in current specification. MS and BS need to execute re-authorization procedure during the re-entry network. But re-authorization procedure between MS and BS will be taken place in some other cases besides the re-entry. MS will execute the authorization procedure according to the authorization policy negotiated in SBC exchange when MS is in re-entry network, such as in handover or in the new connection with BS. What is the re-authorization policy and how to execute re-authorization when the AK lifetime is expired or H/OMAC\_PN\_U is overflowing or H/OMAC\_PN\_D is overflowing?

## 2. Proposed solutions

We suggest that the authorization policy negotiation for re-entry in SBC exchange shall be changed to the authorization policy negotiation for re-authorization.

## 3. Specific text changes

==== Start text changes =====

### 11.8.4.2 Authorization policy support

The 'Authorization policy support' field indicates authorization policy used by the MS and BS to negotiate and synchronize. A bit value of 0 indicates "not supported" while 1 indicates "supported."

Type	Length	Value
25.1	1	Bit #0: PKM version 1 Bit #1: PKM version 2 Bit #2-7: <i>Reserved</i> . Set to 0

Type	Length	Value
25.2	1	Bit# 0: RSA-based authorization at the initial network entry Bit# 1: EAP-based authorization at the initial network entry Bit# 2: Authenticated EAP-based authorization at the initial network entry Bit# 3: <i>Reserved</i> . Set to 0

	Bit# 4: RSA-based authorization at <del>re-entry re-authorization</del> Bit# 5: EAP-based authorization at <del>re-entry re-authorization</del> Bit# 6: Authenticated EAP-based authorization at <del>re-entry re-authorization</del> Bits #7: <i>Reserved. Set to 0</i>
--	---

Authenticated EAP-based authorization basically means that a message containing EAP payload is protected by OMAC Digest. The OMAC\_KEY\_U and OMAC\_KEY\_D are generated with the EIK obtained from RSA-based authorization or EAP-based authorization.

The PKMv2 Auth-Request/Reply/Reject/Acknowledgement messages shall be used in the RSA-based authorization procedure.

The PKMv2 EAP-Transfer message shall be used in the EAP-based authorization procedure. The PKMv2 Authentication EAP-Transfer message shall be used in the Authenticated EAP-based authorization procedure.

Bit# 4–6 are only applied to the SBC-REQ message. Those bits shall be set to 0 in the SBC-RSP message. MS and BS will execute the re-authorization procedure according to the re-authorization policy negotiated in SBC exchange when MS is in some cases, such as in handover or AK lifetime is expired and so on.

The MS should support at least one authorization policy and inform BS of all supportable authorization policies by the SBC-REQ message. The BS negotiates the authorization policy. If all bits of this attribute included in the SBC-RSP message are 0, then no authorization is applied. Both BS and MS shall not use the authorization function.

==== End text changes =====

## 4. References

- [1] IEEE Standard 802.16e/D7-2004
- [2] IEEE Standard 802.16-2004