

Project	IEEE 802.16 Broadband Wireless Access Working Group < http://ieee802.org/16 >
Title	Fix the Problem of Scan/Association Type Indication in MOB_SCN-REQ/RSP Message
Date Submitted	2005-07-18
Source(s)	Rui Cai, Phillip Barber, Jim Carlo, David Xiang, Duke Dang, mailto: john_lee@huawei.com Lucy Chen, John Lee HUAWEI
Re:	Call for contribution and comments.
Abstract	This contribution proposes method to fix the problem of scan/association type in MOB_SCN-REQ/RSP message.
Purpose	Adoption
Notice	This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.
Patent Policy and Procedures	The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures < http://ieee802.org/16/ipr/patents/policy.html >, including the statement "IEEE standards may include the known use of patent(s), including patent applications, provided the IEEE receives assurance from the patent holder or applicant with respect to patents essential for compliance with both mandatory and optional portions of the standard." Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair < mailto:chair@wirelessman.org > as early as possible, in written or electronic form, if patented technology (or technology under patent application) might be incorporated into a draft standard being developed within the IEEE 802.16 Working Group. The Chair will disclose this notification via the IEEE 802.16 web site < http://ieee802.org/16/ipr/patents/notices >.

Fix the Problem of Scan/Association Type Indication in MOB_SCN-REQ/RSP Message

Rui Cai, Phillip Barber, Jim Carlo, David Xiang, Duke Dang, Lucy Chen, John Lee
 HUAWEI

Problem

Three Levels of scan /association are defined in 802.16e D9:

- Association Level 0 – Scan/Association without coordination
- Association Level 1 – Association with coordination
- Association Level 2 – Network assisted association reporting

BS and MS need to indicate the scan/association type in MOB_SCN-REQ & MOB_SCN-RSP messages. Currently a 3-bits field “association type” is defined in MOB_SCN-REQ / MOB_SCN-RSP messages and a method to indicate scan/association type using this field is described as following :

- Association type=0b000 : Association level 0 with scanning: association without coordination.
- Association type=0b001 : Association level 1 with scanning: association with coordination.
- Association type=0b010 : Association level 2 with scanning: NW assisted association reporting.
- Association type=0b011 : No association with scanning

One problem is that, while SCN-RSP was changed to allow the MS to report scanning results per neighbor BS with differentiated Association Type, the SCN-REQ was not similarly changed. That is, the MS can report that for neighbor BS 1, it used Association type 0, while for neighbor BS 2, it used Association type 1. So while the MS could report the differentiated Association type per neighbor BS scanned, the MS has no method to actually request to use different Association type per neighbor BS. The SCN-REQ message permits and requires designation of a single Association type method to be used for all neighbor BS designated in the message. Fortunately, this problem is easily fixed by using a similar method employed in SCN-RSP and applying it to SCN-REQ.

Another problem is that Association type in SCN-REQ was previously, correctly, changed to support the option of Scanning without Association. SCN-RSP was not similarly changed. Since Association is an optional feature, the SCN-REQ & SCN-RSP messages must support an Association Type selection that is Scanning without Association only. And certainly the use of Association Type in the two messages should match. However, the change in Association Type done in SCN-REQ was poorly performed. Because of the priority of sequencing in 11.8.3.7.16 Association type support, the option of Scanning without Association must occur as the first value of the option. Similar change must be performed in 11.8.3.7.16 to support the negotiated option of scanning without Association. Again, Association is an optional feature, so the negotiation of 11.8.3.7.16 must contain an option of Scanning without Association. Also, the use of the term ‘Association Type’ is entirely misleading since it implies that all scanning is for Association, which is certainly not true. Finally, 11.8.3.7.16 is not PHY specific and should be moved to general SBC capabilities negotiation from the OFDMA PHY specific subsection. And delete the duplicate section 11.8.3.7.16.

Remedy

Fortunately, the identified Association type specification discontinuity problem between SCN-REQ & SCN-RSP is easily fixed by using a similar method employed in SCN-RSP and applying it to SCN-REQ.

And Association type support for scanning without Association is easily accommodated by adding a new value to Association type. Note that, due to selection precedence in 11.8.3.7.16 Association type support, the new value must be added as option '0'. Also, change 11.8.3.7.16 to correctly support the selection of no support for the optional Association feature. Also, change the term 'Association type' into the more correct term 'Scanning type'. Finally, 11.8.3.7.16 needs to be moved to 11.8.8. And delete the duplicate section 11.8.3.7.15.

[Phil Barber] Added needed changes and fixes to invoking paragraph of 6.3.2.3.49, per C802.16e-05/333.

[Phil Barber] Added needed changes and fixes to invoking paragraph of 6.3.21.1.2, per C802.16e-05/333.

[Phil Barber] Modified the contribution to correct other instances of 'Scan type' and 'Association Type' in the D9 document.

Proposed changes to text

[In 6.3.2.3.48 Scanning Interval Allocation Request (MOB_SCN-REQ) message, page 102, Table 108h—MOB_SCN-REQ message format, modify Table as:]

Table 108h—MOB_SCN-REQ message format

Syntax	Size (bits)	Notes
MOB_SCN-REQ_Message_format() {	--	--
Management Message Type = 54	8	
Scan duration	8	Units are in frames.
Association type	3	0b000: Association level 0 with scanning; association without coordination; 0b001: Association level 1 with scanning; association with coordination; 0b010: Association level 2 with scanning; NW assisted association reporting; 0b011: No association with scanning 0b100-0b111: Reserved
Interleaving interval	8	Units are frames.
Scan Iteration	8	In frames
Comp NBR BSID IND	1	1 = use compressed BS ID
Padding	4 <u>7</u>	Shall be set to zero
If (Comp_NBR_BSID_IND == 1) {		
Configuration change count for MOB_NBR_ADV	8	Configuration Change Count value of referring MOB_NBR_ADV message
}		
N_Recommended_BS	8	Number of neighboring BS's to be scanned/associated
For (j=0; j<N_Recommended_BS; j++) {		
If (Comp_NBR_BSID_IND == 1) {		
Neighbor_BS_index	8	BS index corresponds to position of BS in MOB_NBR_ADV message

} Else {		
Recommended BS_ID	48	
}		
Association-Scanning type	<u>3</u>	0b000: Scanning without Association Association level 0 with scanning- association without coordination- 0b001: Scanning with Association level 0: association without coordination Association level 1 with scanning- association with coordination- 0b010: Scanning with Association level 1: association with coordination Association level 2 with scanning- NW assisted association reporting- 0b011: Scanning with Association level 2: NW assisted association No association with scanning 0b100-0b111: Reserved
}		
Padding	variable	If needed for alignment to byte boundary.
TLV encoded information	variable	
}		

[In 6.3.2.3.48 Scanning Interval Allocation Request (MOB_SCN-REQ) message, page 104, lines 3-5, modify as:]

Association-Scanning type

Type of scanning or association to be used by the MS and coordinated by the Serving BS (if Association type \geq ~~0b010~~0b011).

[In 6.3.2.3.49 Scanning Interval Allocation Response (MOB_SCN-RSP) message, page 104, line 32-37, modify as:]

A MOB_SCN-RSP message shall be transmitted by the BS either unsolicited or in response to an MOB_SCN-REQ message sent by an MS. A BS may transmit MOB_SCN-RSP to start MS scan reporting with or without scanning allocation. A BS may allocate the scanning allocation for MS scanning with Scanning type = 0b000, or MS non-contention Association ranging with Scanning type = 0b010 or 0b011. The message shall be transmitted on the Basic CID.

[In 6.3.2.3.49 Scanning Interval Allocation Response (MOB_SCN-RSP) message, page 107, line 21- 22, modify as:]

In case scanning type = 0b000 or 0b001 the parameter is not applicable and shall be encoded as 0.

[In 6.3.21.1.2 MS Scanning of neighbor BSs, page 171, line 28-49, modify as:]

When the Trigger Action in the DCD message is encoded as 0x3, the MS shall send the MOB_SCN-REQ message to the BS to begin the neighbor BS scanning process when the trigger condition is met. In the MOB_SCN-REQ message the MS (the MOB_SCN-RSP message the BS) shall indicate group of neighbor BSs for which only Scanning or Scanning with Association are requested by MS (recommended by BS). Presence of those BSs for which Association is requested (recommended) is indicated by encoding of Scanning type \geq 0b001. The BS may negotiate over the backbone with a BS Recommended for Association allocation unicast ranging opportunities. Then the MS will be informed on Rendezvous time to conduct Association ranging with the Recommended BS. When conducting initial ranging to a BS recommended for Association, MS shall use allocated unicast ranging opportunity, if available. Regardless of the presence of Recommended BS IDs, MS may determine and perform any scanning or Association activities during Scanning Interval at its own discretion. When the Report Mode is 0b10 in the MOB_SCN-RSP message, the MS shall scan all BSs within the Recommended BS list of the message and then report the scanning result with the MOB_SCN-REP message as conditioned by specified trigger event. Particularly if the Trigger Function in the most recently-received DCD channel encoding is 0x5 or 0x6, the MS shall include all recommended BSs of the MOB_SCN RSP within the MOB_SCN-REP. Otherwise, the MS shall add only the BSs which met the Trigger Function conditions within the MOB_SCN-REP message. The scanning duration performed by the MS on all neighbor BSs shall be no longer than the parameter Max_Dir_Scan_Time (as specified in Section 10.1) to limit the time before a report is sent to the BS.

[In 6.3.21.3 Association Procedure , page 172, line 41, modify as:]

The BS may direct the MS to associate with recommended BSs by setting ~~Association type to 0b01 or 0b10~~ scanning type to 0b010 or 0b011 in this message .

[In 6.3.21.3.1 Association Level 0 - Scan / Association without coordination, page 172, line 51-54, modify as:]

When this association level is chosen by the network, the Serving BS and the MS negotiate about the association duration and intervals via MOB_SCN-REQ with ~~ASSOCIATION_TYPE = 0b000~~ scanning type=0b001) and MOB_SCN-RSP).

[In 6.3.21.3.2 Association Level 1 - Scan / Association with coordination, page 173, line 7-8, modify as:]

The MS may request to perform association with coordination by sending the MOB_SCN-REQ message to the Serving BS with ~~ASSOCIATION_TYPE = 0b001~~ scanning type=0b010.

[In 6.3.21.3.2 Association Level 2 - NW Assisted Association Reporting, page 174, line 18-19, modify as:]

The MS may request to perform association with NW assisted association reporting by sending the MOB_SCN-REQ message to the Serving BS with ~~ASSOCIATION_TYPE = 0b010~~ scanning type=0b011

[In 6.3.2.3.49 Scanning Interval Allocation Response (MOB_SCN-RSP) message, page 104, Table 108i—MOB_SCN-RSP message format, modify Table as:]

Table 108i—MOB_SCN-RSP message format

Syntax	Size (bits)	Notes
MOB_SCN-RSP_Message_format() {		
Management Message Type = 55	8	
Scan duration	8	In units of frames. When Scan Duration is set to zero, no scanning parameters are specified in the message. When MOB_SCN-RSP is sent in response to MOB_SCN-REQ, setting Scan Duration to zero denies MOB_SCN-REQ.
Report mode	2	0b00: no report 0b01: periodic report 0b10: event triggered report 0b11: reserved
<i>reserved</i>	6	Shall be set to zero
Report period	8	Available when the value of Report Mode is set to 0b01. Report period in frames.
Report metric	8	Bitmap indicating metrics on which the corresponding triggers are based: Bit 0: BS CINR mean Bit 1: BS RSSI mean Bit 2: Relative delay Bit 3: BS RTD; this metric shall be only measured on serving BS/anchor BS. Bits 4-7: <i>reserved</i> ; shall be set to zero
if (Scan Duration !=0) {		
Start frame	4	
<i>reserved</i>	1	Shall be set to zero.
Interleaving interval	8	Duration in frames
Scan iteration	8	
Comp_NBR_BSID_IND	1	
<i>padding</i>	3	Shall be set to zero.
If (Comp_NBR_BSID_IND == 1) {		
Configuration change count for MOB_NBR_ADV	8	Configuration Change Count value of referring MOB_NBR_ADV message
}		
N_Recommended_BS	4	Number of neighboring BS's to be scanned/associated
For (j=0; j<N_Recommended_BS; j++) {		
If (Comp_NBR_BSID_IND == 1) {		
Neighbor_BS_index	8	BS index corresponds to position of BS in MOB_NBR_ADV message
} Else {		
Recommended_BS_ID	48	BS IDs of BSs that MS shall scan
}		
Association-Scanning_type	3	0b000: Scanning without Association Scanning with association level 0: association without coordination 0b001: Scanning with Association level 0: association without coordination Scanning with association level 1: association with coordination 0b010: Scanning with Association level 1: association with coordination Scanning with association level 2: NW assisted association reporting 0b011: Scanning with Association level 2: NW assisted association

		0b0110b100 -0b111: Reserved
If (Association type == 0b001) OR (Association type == 0b010) {		
Rendezvous time	8	Units are frames
CDMA code	8	From initial ranging codeset
Transmission_opportunity offset	8	Units are transmission opportunity
}		
}		
<i>Padding</i>	<i>variable</i>	
}		
TLV encoded information	<i>variable</i>	
}		

[In 6.3.2.3.49 Scanning Interval Allocation Response (MOB_SCN-RSP) message, page 106, lines 33-34, modify as:]

Association-Scanning type

Type of scanning or association ~~to be~~ used by the MS and coordinated by the Serving BS (if scanning type >=0b010).

[In 11.8.3.7.16 Association type support, page 542, modify Table as:]

Type	Length	Value	Scope
167	1	0: Scanning without Association: Association not supported 01: Association level 0: Scanning or association without coordination. 12: Association level 1: association with coordination. 23: Association level 2: NW assisted association reporting . 4-255 reserved	SBC-REQ (see 6.3.2.3.23) SBC-RSP (see 6.3.2.3.24)

[Relocate 11.8.3.7.16 Association type support, page 542, to new subsection 11.8.8:]

[Delete duplicate section 11.8.3.7.15 Association type support, page 542; note: 11.8.3.7.15 is duplicate to 11.8.3.7.16, but 11.8.3.7.16 has some different, more correct language after the Table, so should kill .15 not .16]