

Project	IEEE 802.16 Broadband Wireless Access Working Group < http://ieee802.org/16 >
Title	Corrections on some TLVs in UCD and DCD for OFDMA
Date Submitted	2005-10-06
Source(s)	Jungnam Yun, jnyun@posdata-usa.com POSDATA Co., Ltd. Phillip Barber pbarber@broadbandmobiletech.com Huawei JaeWeon Cho, Yeongmoon Son, jaeweon.cho@samsung.com Panyuh Joo Samsung Electronics Co., Ltd
Re:	IEEE P802.16e/D11.
Abstract	This presentation corrects some TLVs in UCD and DCD of 16e for consistency with Cor1.
Purpose	Review and adoption of the proposed text change into IEEE P802.16e/D12.
Notice	This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.
Patent Policy and Procedures	The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures < http://ieee802.org/16/ipr/patents/policy.html >, including the statement "IEEE standards may include the known use of patent(s), including patent applications, provided the IEEE receives assurance from the patent holder or applicant with respect to patents essential for compliance with both mandatory and optional portions of the standard." Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair < mailto:chair@wirelessman.org > as early as possible, in written or electronic form, if patented technology (or technology under patent application) might be incorporated into a draft standard being developed within the IEEE 802.16 Working Group. The Chair will disclose this notification via the IEEE 802.16 web site < http://ieee802.org/16/ipr/patents/notices >.

1 Corrections on some TLVs in UCD and DCD for OFDMA

2
3
4
5
6
7
8
9

Jungnam Yun
POSDATA Co., Ltd.

Phillip Barber
Huawei Technologies Co., Ltd.

[JaeWeon Cho, Yeongmoon Son, Panyuh Joo](#)
[Samsung Electronics Co., Ltd](#)

101. Problem Statements

11

12In 802.16e/D11, 11.3.1 UCD channel encodings, Table 349 is titled “UCD channel encodings”. The original title for the table is
13“UCD common channel encodings” in IEEE 802.16-2004. Also, there is no “PHY scope” column in the original table 349 in IEEE
14802.16-2004. Type 7, ‘HO_ranging_start’ and Type 8, ‘HO_ranging_end’ are common encodings for SCa, OFDM, and OFDMA. So,
15we may leave them with a note below the table ‘SCa, OFDM, OFDMA (mobile only)’. However, Type 9, ‘Initial ranging backoff
16start’, Type 10, ‘initial ranging backoff end’, Type 11, ‘Bandwidth request backoff start’, Type 12, ‘Bandwidth request backoff end’,
17Type 13, ‘Uplink burst profile for multiple FEC types’, and Type 175, ‘Normalized C/N override2’ are all OFDMA specific channel
18encodings and hence they should be moved to table 353.

19

20Type 175, ‘Normalized C/N override2’ has conflicting has conflicting type number with ‘Normalized C/N override’. So, we need to
21change the type number from 175 to 177.

22

23In 802.16e/D11, 11.3.1 UCD channel encodings, Table 353a UCD PHY-specific channel encodings WirelessMAN-OFDMA, the
24editorial instruction on page 534, line 19 says, ‘*Insert the following rows to Table 353:*’ when many of the TLV items in Table 353a
25already exist in Table 353 in 802.16-2004 and/or Cor1/D5. This would, in effect, create duplicate lines in the Table.

26

27In the same Table, ‘Start of ranging codes Group’, Type 155 in the Table was not changed to reflect changes to Section 8.4.7.3 in
2816e/D11 and a description line added in Cor1/D5.

29

30In the same Table, ‘Permutation base’, Type 156, ‘UL allocated subchannels bitmap’, Type 157, ‘Optional permutation UL Allocated
31subchannels bitmap’, Type 158, and ‘HARQ ACK delay for UL burst’, Type 171 are copied into 16e/D11 here with no change from
32802.16-2004, and fail to reflect changes made in Cor1/D5.

33

34In the same Table, ‘Band AMC Allocation Threshold’, Type 159, ‘Band AMC Release Threshold’, Type 160, ‘Band AMC Allocation
35Timer’, Type 161, ‘Band AMC Release Timer’, Type 162, ‘Band Status Reporting MAX Period’, Type 163, and ‘Band AMC Retry
36Timer’, Type 164 all are copied from 802.16-2004, no changes in Cor1/D5, changes in 16e/D11 but with no editorial markup
37indicating the changes.

38

39In the same Table, ‘Initial ranging codes’, Type 150, ‘Periodic ranging codes’, Type 151, ‘Bandwidth request codes’, Type 152,
40‘Periodic ranging backoff start’, Type 153, ‘Periodic ranging backoff end’, Type 154, ‘Safety Channel Allocation Threshold’, Type
41165, ‘Safety Channel Release Threshold’, Type 166, ‘Safety Channel Allocation Timer’, Type 167, ‘Safety Channel Release Timer’,
42Type 168, ‘Bin Status Reporting MAX Period’, Type 169, ‘Safety Channel Retry Timer’, Type 170, and ‘Band AMC Entry Average
43CINR’, Type 185 all are inappropriately copied into this Table either from 802.16-2004 or Cor1/D5 (according to the Editorial
44instruction in 16e/D11, to be inserted into Table 353 again) in 16e/D11 without any change whatsoever.

45

46

47~~In 802.16e/D11, 11.4.1 DCD, Table 358 – DCD channel encodings, Type 30 – ‘DL allocated subchannel bitmap for optional AMC~~
48~~permutation’ does not reflect changes from Cor1 (Type 22, ‘DL AMC allocated physical bands bitmap’ is added in Cor1 for the same~~
49~~purpose and with clear text). We need to remove the TLV type 30 from the Table 358.~~

50

51In the same Table 358, Type 148, ‘MAC version’ is duplicate without any change from IEEE 802.16-2004.

52

12. Remedy

2

3/[11.3.1 UCD channel encodings]

4

51. *Page (line): 531 (39) -534(18) : replace the existing text, including Editorial markup, and Tables, and replace Editorial instructions with:*

6

7
8[Insert the following rows to Table 349:]

9

10

Table 349 UCD common channel encodings

Name	Type (1 byte)	Length	Value
HO_ranging_start*	7	1	Initial backoff window size for MS performing initial ranging during handover process, expressed as a power of 2. Range: 0-15 (the highest order bits shall be unused and set to 0).
HO_ranging_end*	8	1	Final backoff window size for MS performing initial ranging during handover process, expressed as a power of 2. Range: 0-15 (the highest order bits shall be unused and set to 0).

11 ** SCa, OFDM, OFDMA (mobile only)*

12

132. *Pages (line): 534(19) – 537(57), replace the existing text, including Editorial markup, and Tables, and replace Editorial instructions with:*

14

15
16[Change Table 353 as indicated:]

17

18

Table 353 UCD PHY-specific channel encodings WirelessMAN-OFDMA

Name	Type (1 byte)	Length	Value
Start of ranging codes group	155	1	Indicates the starting number, S, of the group of codes used for this uplink. If not specified, the default value shall be set to zero. All the ranging codes used on this uplink will be between S and $((S+O+N+M+L) \bmod 256)$. Where, N is the number of initial-ranging codes M is the number of periodic-ranging codes L is the number of bandwidth-request codes O is the number of handover-ranging codes The range of values is $0 \leq S \leq 255$.
Band AMC Allocation Threshold	159	1	dB unit threshold of the maximum of the standard deviations of the individual bands CINR measurements over time to trigger mode transition from normal subchannel to Band AMC
Band AMC Release Threshold	160	1	dB unit threshold of the maximum of the standard deviations of the individual bands CINR measurements over time to trigger mode transition from Band AMC to normal subchannel
Band AMC Allocation Timer	161	1	Frame unit Minimum required number of frames to measure the average and standard deviation for the event of Band AMC triggering
Band AMC Release Timer	162	1	Frame unit Minimum required number of frames to measure the average and standard deviation for the event triggering from Band AMC to normal subchannel
Band Status Reporting MAX Period	163	1	Frame unit Maximum period between refreshing the Band CINR measurement by the unsolicited REP-RSP
Band AMC Retry Timer	164	1	Frame unit Backoff timer between consecutive mode transitions from normal subchannel to Band AMC when the previous request is failed

6

3

1
2
3
4[\[Insert the following rows to Table 353:\]](#)**Table 353 UCD PHY-specific channel encodings WirelessMAN-OFDMA**

Name	Type (1 byte)	Length	Value
Normalized C/N override 2	177	8	Bit#0~7: It shall be interpreted as signed integer in dB. It corresponds to the normalized C/N value in the first line (counting except for header cell of table). Bit#8~63: This is a list of numbers, where each number is encoded by one nibble, and interpreted as a signed integer. The nibbles correspond in order to the list define by Table 334, starting from the second line (counting except for the header cell of table), such that the LS nibble of the first byte corresponds to the second line in the table. The number encoded by each nibble represents the difference in normalized C/N relative to the previous line in the table.
UpperBound_{AAS_PREAMB}	186	1	Signed in units of 0.25 dB
LowerBound_{AAS_PREAMB}	187	1	Signed in units of 0.25 dB
Allow AAS Beam Select Messages	188	1	Boolean to indicate whether unsolicited AAS Beam Select messages (see 6.3.2.3.41) should be sent by the MS. The default value is 1, with possible values of 0-1: 0 — MS should not send AAS Beam Select Messages 1 — MS may send AAS Beam Select Messages
Use COICH indication flag	189	1	The N MSB values of this field represents the N-bit payload value on the Fast Feedback channel reserved as indication flag for MS to initiate feedback on the Feedback header, where N is the number of payload bits used for S/N measurement feedback on the Fast Feedback channel. The value shall not be set to all zeros.
MS-specific up power offset adjustment step	190	1	Unsigned in units of 0.01 dB
MS-specific down power offset adjustment step	191	1	Unsigned in units of 0.01 dB
Minimum level of power offset adjustment	192	1	Signed in units of 0.1 dB
Maximum level of power offset adjustment	193	1	Signed in units of 0.1 dB
Handover Ranging Codes	194	1	Number of handover ranging CDMA codes. Possible values are 0-255.
Initial ranging interval	195	1	Number of frames between initial ranging interval allocation.
Tx Power Report	196	3	Bit#0~3: Tx Power Report Threshold. It is unsigned integer and shall be read in dB scale. When 0b111 it means infinite. Bit#4~7: It is unsigned integer whose value is d. Its value d shall be interpreted as Tx Power Report Interval =2^d. When 0b111 it means infinite. Bit#8~11: α_{p_avg} in multiples of 1/16 (range [1/16,16/16]) Bit#12~15: Tx Power Report Threshold. It is unsigned integer and shall be read in dB scale. When 0b111 it means infinite. It shall be used when COICH is allocated to the SS. Bit#16~19: It is unsigned integer whose value is d. Its value d shall be interpreted as Tx Power Report Interval =2^d. When 0b111 it means infinite. It shall be used when COICH is allocated to the SS. Bit#20~24: α_{p_avg} in multiples of 1/16 (range [1/16,16/16]). It shall be used when COICH is allocated to the SS.

Normalized C/N for Channel Sounding	197	1	Signed integer for the required C/N (dB) for Channel Sounding. This value shall override C/N for the channel sounding in Table 334a.
Initial ranging backoff_start	198	1	Initial backoff window size for initial ranging contention, expressed as a power of 2. Values of n range 0-15 (the highest order bits shall be unused and set to 0) This TLV shall be used in NBR-ADV message only to represent corresponding values that appear in UCD message fields.
Initial ranging backoff_end	199	1	Final backoff window size for initial ranging contention, expressed as a power of 2. Values of n range 0-15 (the highest order bits shall be unused and set to 0) This TLV shall be used in NBR-ADV message only to represent corresponding values that appear in UCD message fields.
Bandwidth_request_backoff_start	201	1	Initial backoff window size for contention BW requests, expressed as a power of 2. Values of n range 0-15 (the highest order bits shall be unused and set to 0). This TLV shall be used in NBR-ADV message only to represent corresponding values that appear in UCD message fields.
Bandwidth_request_backoff_end	202	1	Final backoff window size for contention BW requests, expressed as a power of 2. Values of n range 0-15 (the highest order bits shall be unused and set to 0). This TLV shall be used in NBR-ADV message only to represent corresponding values that appear in UCD message fields.
Uplink burst profile for multiple FEC types	203	1	May appear more than once (see 6.3.2.3.3 and 8.4.5.5). The length is the number of bytes in the overall object, including embedded TLV items.

5
6
7
8

9[11.4.1 DCD channel encodings]

10
11

121. **Pages (line): 540(19) – 537(57), Remove following TLVs from Table 358]**

Name	Type (1 byte)	Length	Value	PHY Scope
MAC version	148	1	See 11.1.3	All

13
14

153. References

16

17[1] IEEE Std 802.16-2004, “IEEE Standard for Local and metropolitan area networks Part 16: Air Interface for Fixed
18 Broadband Wireless Access Systems,” Oct. 2004.

19[2] IEEE P802.16-Cor1/D5, “Corrigendum to IEEE Standard for Local and Metropolitan Area Networks - Part 16: Air
20 Interface for Fixed Broadband Wireless Access Systems,” Sep. 2005.

21[3] IEEE P802.16e/D11, “Draft Amendment to IEEE Standard for Local and Metropolitan Area Networks Part 16: Air
22 Interface for Fixed and Mobile Broadband Wireless Access Systems —Amendment for Physical and Medium
23 Access Control Layers for Combined Fixed and Mobile Operation in Licensed Bands,” Sep. 2005.

24