Project	IEEE 802.16 Broadband Wireless Access Working Group http://ieee802.org/16 >	
Title	Proposed text for P802.16m Requirements Document Section 8	
Date Submitted	2007-02-25	
Source(s)	Jean-Pierre Balech Alcatel-Lucent, France	jean-pierre.balech@alcatel-lucent.fr +33 (1) 3077 4459
	Torsten Fahldieck Alcatel-Lucent, Germany	torsten.fahldieck@alcatel-lucent.de +49 (711821) 32163
	Peretz Feder Alcatel-Lucent, New Jersey	pfeder@alcatel-lucent.com +1 973 386 6976
	Dan Gal Alcatel-Lucent, New Jersey	dgal@alcatel-lucent.com +1 973 428 7734
	Hardy Halbauer Alcatel-Lucent, Germany	hardy.halbauer@alcatel-lucent.de +49 (711821) 34182
	Ashok Rudrapatna Alcatel-Lucent, New Jersey	anr1@alcatel-lucent.com +1 973 386 7730
	Joerg Schaepperle Alcatel-Lucent, Germany	Joerg.Schaepperle@alcatel-lucent.de +49.711.821-32266
	Antoine Soulie Alcatel-Lucent, France	antoine.soulie@alcatel-lucent.com +33 (1) 40 76 1652
	Philippe Sehier Alcatel-Lucent, France	philippe.sehier@alcatel.fr
	Reinaldo Valenzuela (& team) Alcatel-Lucent, New Jersey	rav@alcatel-lucent.com +1 732 888 7031
Re:	IEEE 802.16m-07/004r1 – Call for	Contributions for P802.16m Requirements
Abstract	Proposed draft text for 802.16m	Requirements Document Section 8
Purpose	Incorporate into the draft-802.16m Requirements Document	
Notice	This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.	
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.	
Patent Policy and Procedures	The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures http://ieee802.org/16/ipr/patents/policy.html , including the statement "IEEE standards may include the known use of patent(s), including patent applications, provided the IEEE receives assurance from the patent holder or applicant with respect to patents essential for compliance with both mandatory and optional portions of the standard." Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair mailto:chair@wirelessman.org as early as possible, in written or electronic form, if patented technology (or technology under patent application) might be incorporated into a draft standard being developed within the IEEE 802.16 Working Group. The Chair will disclose this notification via the IEEE 802.16 web site http://ieee802.org/16/ipr/patents/notices .	

2007-02-25 IEEE C802.16m-07/<mark>011</mark>

2007-02-25 IEEE C802.16m-07/<mark>011</mark>

Proposed Text for P802.16m Requirements Document – Section 8

Alcatel-Lucent 16m team

8.0 Deployment-related requirements

8.1 Legacy Support

8.2 Spectrum Requirements

Channel bandwidths

At least the following channel bandwidths should be supported: 1.25, 2.5, 3.5, 5, 7, 8.75, 10, 14, 20, 28, 40, 56, 100 MHz. Bandwidths above 20 MHz should be optional for the terminals.

For channel-bandwidths larger than those currently supported in the "dot16" standard [2], [3], both scaled-up and multi-carrier solutions should be considered.

Channel bandwidth flexibility

16m should offer better frequency assignment support by allowing better granularity. This would facilitate an optimized utilization of variable spectrum block sizes. Optimization/adaptation of channel bandwidth should also utilize the OFDMA capability to switch off channel-edge sub-carriers.

8.3 System Architecture

BS Cell size

A wide range of cell radii from tens of meters up to tens of Kilometers should be supported. The focus shall be on cellular infrastructure deployments with typical cells sizes of 100 meters to several Kilometers

Architecture

The 802.16m amendment should support, and be optimized for, an All IP and Ethernet architecture. It should support the various flavors of IP and Ethernet architecture: One-node and two nodes Radio Access Network (RAN) architecture The architectures must cover a wide range of deployment scenarios, including macro, micro and femto environments, as well as both out-door and in-building applications.

The 802.16m amendment shall provide a protocol-independent packet convergence sublayer that supports multiple protocols over 802.16m air interface.

Furthermore, where feasible and not excessively complex, in order to maximize system performance, both inter-BS diversity and simplex (no soft hand-off, but with fast cell switching capability) options should be supported.

The 802.16m amendment should be able to support advanced Macro Diversity techniques such as Network MIMO, if practical ways can be devised to incorporate them.

The 802.16m amendment shall support all the Network Control and Management Services (NCMS) network elements and procedures described in the IEEE 802.16g amendment.

Support for Multi-hop Relay

Support for scaled-up Multi-hop Relay devices should be included in the 16m architecture.

8.4 System Migration