

```

25c25
< LAST-UPDATED "200404211200Z" -- 21 Apr 2004 12:00:00 UTC
---
> LAST-UPDATED "200503091200Z" -- 03 Mar 2005 12:00:00 UTC
36a37,45
> "200503081200Z" -- 08 Mar 2005 12:00:00 UTC
> DESCRIPTION
> "Fix minor MIB specification issues.
> These come in two categories:
> Incorrect choices for MIB only definitions (e.g. the range for
> the various TimeElapsed variables)
> Inconsistencies between the MIB and main document clauses
> (e.g. the units for rprIfAtdTimer)."
```

```

> REVISION
258,259c267,268
< SYNTAX Unsigned32 (1..200)
< UNITS "50 milliseconds"
---
> SYNTAX Unsigned32 (1..10)
> UNITS "100 milliseconds"
263c272
< "Indicates the protection slow timer value in 50 ms units.
---
> "Indicates the protection slow timer value in 100 ms units.
267c276
< is 20 units of 50 ms, i.e. 1sec."
---
> is 1 unit of 100 ms, i.e. 100 ms."
270c279
< DEFVAL { 20 }
---
> DEFVAL { 1 }
274,275c283,284
< SYNTAX Unsigned32 (1..200)
< UNITS "50 milliseconds"
---
> SYNTAX Unsigned32 (1..10)
> UNITS "seconds"
281c290
< Default value is 20 units of 50 ms, i.e. 1sec."
---
> Default value is 1 second."
284c293
< DEFVAL { 20 }
---
> DEFVAL { 1 }
288c297
< SYNTAX Unsigned32 (2..50)
---
> SYNTAX Unsigned32 (2..200)
298c307
< "IEEE 802.17 Subclause 11.2.3, keepaliveTime"
---
> "IEEE 802.17 Subclause 11.6.2.2 keepaliveTimeout"
665c674
< SYNTAX Unsigned32 (0..899)
---
> SYNTAX Unsigned32 (0..910)
1035c1044
< rprTopoImageStationIfIndex InterfaceIndex,
---
> rprTopoImageStationIfIndex InterfaceIndexOrZero,
1095c1104
< SYNTAX InterfaceIndex
---
> SYNTAX InterfaceIndexOrZero
```

```
1099c1108,1109
<      "The station ifIndex."
---
>      "The station ifIndex. A value of zero indicates an interface index that has
>      yet to be determined."
2461c2471
<      SYNTAX      Unsigned32 (0..899)
---
>      SYNTAX      Unsigned32 (0..910)
4201c4211
<      SYNTAX      Unsigned32 (0..899)
---
>      SYNTAX      Unsigned32 (0..910)
5579c5589
<      SYNTAX      Unsigned32 (0..899)
---
>      SYNTAX      Unsigned32 (0..910)
```