

Project	IEEE 802.20 Working Group on Mobile Broadband Wireless Access <http://iee802.org/20/>
Title	QFDD Requirements Compliance Report
Date Submitted	2005-10-28
Source(s)	Jim Tomcik Qualcomm, Incorporated 5775 Morehouse Drive San Diego, CA, 92121 Voice: 858-658-3231 Fax: 858-658-2113 E-Mail: jtomcik@qualcomm.com
Re:	MBWA Call for Proposals
Abstract	This contribution (part of the QFDD proposal package for 802.20), contains the QFDD Requirements Compliance Report.
Purpose	For consideration of 802.20 in its efforts to adopt an FDD proposal for MBWA.
Notice	This document has been prepared to assist the IEEE 802.20 Working Group. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.20.
Patent Policy	The contributor is familiar with IEEE patent policy, as outlined in Section 6.3 of the IEEE-SA Standards Board Operations Manual <http://standards.ieee.org/guides/opman/sect6.html#6.3> and in <i>Understanding Patent Issues During IEEE Standards Development</i> <http://standards.ieee.org/board/pat/guide.html> .

System Requirements Compliance Report

#	Requirement	SRD ¹ Section #	Requirement Type		Compliance Level	
			Shall	Should	Yes	Notes
1	PAR requirements	1.3	•		X	See Section 2 of [1]
2	VoIP Services	2.1	•		X	See Section 3.3 of [3]
3	Broadcast – Multicast services	2.2	•		X	See Sections 7.5 and 10.2 in [3]
4	Non-line of sight outdoor to indoor scenarios and indoor coverage	3.1	•		X	See link budget calculation in Section 3.5 of [1].
5	Layered architecture and separation of functionality between user, data and control	3.1	•		X	See Chapter 1 of [3]
6	Spectral efficiency – DL @ 3 km/hr: 2.0b/s/Hz/sector	4.1.1	•		X	2.20 b/s/Hz/sector, see Section 4.3 of [1]
7	Spectral efficiency – DL @ 120km/hr: 1.5b/s/Hz/sector	4.1.1	•		X	1.96 b/s/Hz/sector, see Section 4.3 of [1]
8	Spectral efficiency – UL @ 3km/hr: 1.0b/s/Hz/sector	4.1.1	•		X	1.38 b/s/Hz/sector, see Section 4.3 of [1]
9	Spectral efficiency – UL @ 120km/hr: .75b/s/Hz/sector	4.1.1	•		X	1.18 b/s/Hz/sector, see Section 4.3 of [1]
10	Block assignment support	4.1.2	•		X	Support different block assignments between 5 and 20 MHz, see Chapter 8 of [3]
11	Duplexing Scheme	4.1.3	•		X	See Section 9.1 of [3]
12	Support for Half Duplex FDD subscriber station.	4.1.3		○	X	See Sections 2.5.8.1 and 6.5.6.3.1 of [3]
13	Support for different mobility rates	4.1.4	•		X	See Section 3.3 of [1]
14	Aggregated data rate consistent with item 6	4.1.5	•		X	10.9 Mbps, see Section 4.4 of [1]
15	Aggregated data rate consistent with item 7	4.1.5	•		X	9.6 Mbps, see Section 4.4 of [1]

¹ SRD: IEEE802-20-PD-06 “System Requirements for IEEE 802.20 Mobile Broadband Wireless Access Systems – Version 14”

#	Requirement	SRD ¹ Section #	Requirement Type		Compliance Level	
			Shall	Should	Yes	Notes
16	Aggregated data rate consistent with item 8	4.1.5	•		X	6.9 Mbps, see Section 4.4 of [1]
17	Aggregated data rate consistent with item 9	4.1.5	•		X	5.9 Mbps, see Section 4.4 of [1]
18	Peak User Data Rate (DL) of 4.5 Mbps in 1.25 MHz	4.16	•		X	DL peak rate is 66 Mbps for users in 5 MHz deployment. If the assignment is restricted to 1.25 MHz, the peak rate is 16.5 Mbps, see Section 4.2 of [1]
19	Peak User Data Rate (UL) of 2.25 Mbps in 1.25 MHz	4.16	•		X	UL peak rate is 9.8 Mbps for users in 5 MHz deployment. If the assignment is restricted to 1.25 MHz, the peak rate is 2.45 Mbps, see Section 4.2 of [1]
20	Peak User Data Rate (DL) of 18 Mbps in 5.0 MHz	4.16	•		X	66 Mbps, See Section 4.2 of [1]
21	Peak User Data Rate (UL) of 9 Mbps in 5.0 MHz	4.16	•		X	9.8 Mbps, See Section 4.2 of [1]
22	MAC layer to control >100 simultaneous active sessions per sector. (See section for conditions.)	4.1.7		○	X	MACID space for greater than 2000 active sessions in a 5 MHz. REQ opportunity every 5.5 ms for active sessions. See Section 7.4 and Section 7.6 of [3].
23	QoS support per requirements in section 4.1.8	4.1.8	•		X	See Section 3.3 of [3] and Section 3 of [2].
24	Support the configuration of a flexible set variety of traffic classes (see section 4.1.8.1)	4.1.8.1	•		X	See Section 3.3 Data Transport of [3] and QoS section of [2].
25	MAC/PHY features to support multi-antenna capabilities at the BS	4.1.9	•		X	Support MIMO, STTD, precoding, SDMA and QORL, see Sections 17, 20, 21, 22 and 23 of [2]
26	Base station antenna diversity	4.1.10		○	X	Support RL diversity antenna and QORL, see Section 17 of [2]
27	Support coverage enhancing technologies	4.1.11	•		X	Support frequency reuse, beamforming and precoding. See Sections 18 and 21 of [2]
28	BS authentication	4.1.12	•		X	See Sections 4.2 and 5.5 of [3]
29	MT authentication	4.1.12	•		X	See Sections 4.2 and 5.5 of [3]

#	Requirement	SRD ¹ Section #	Requirement Type		Compliance Level	
			Shall	Should	Yes	Notes
30	Network and mobile terminal perform mutual entity authentication and session key agreement protocol	4.1.12.1	•		X	See Sections 4.2 and 5.5 of [3]
31	Privacy and message integrity methods	4.1.12.2	•		X	See Chapter 5 of [3]
32	Support for encryption across the air interface	4.1.12.2	•		X	See Chapter 5 of [3]
33	Protection from unauthorized disclosure of the device permanent identity to passive attackers	4.1.12.3	•		X	UATI is not derived from AT HW ID. See Chapter 2 of [3].
34	Protection against Denial of Service (DOS) attacks	4.1.12.4	•		X	Provides encryption and authentication of all messages and data. See Chapters 4 & 5 of [3].
35	AES Support	4.1.12.5	•		X	See Section 5.6 of [3]
36	Automatic selection of optimized user data rates that are consistent with the RF environment constraints and application requirements	4.2.1	•		X	Support CQI reporting, HARQ, rate adaptation and RLP, See Chapter 7 and Section 3.3 in [3]
37	Graceful reduction or increase of user data rates, on the downlink and uplink	4.2.1	•		X	Support CQI reporting, HARQ and rate adaptation, See Chapter 7 in [3]
38	Link adaptation	4.2.1	•		X	Support CQI reporting, HARQ and rate adaptation, See Chapter 7 in [3]
39	BS and MS transmit power control mechanisms and exchange control and monitoring information	4.2.1		○	X	Support FL and RL power control, active set management and overhead messages. See Section 6.5 and 6.6 of [3] and Section 15 of [2].

#	Requirement	SRD ¹ Section #	Requirement Type		Compliance Level	
			Shall	Should	Yes	Notes
40	Application in dense urban, urban, suburban, rural, outdoor-indoor, pedestrian, and vehicular environments and the relevant channel models	4.2.2	•		X	See Section 3.3 of [1] for robust link performance under different speed and multipath. See Section 3.5 of [1] for link budget.
41	Physical layer Measurements – BS	4.2.4	•		X	See Section 6.5 of [3].
42	Physical layer Measurements – MS	4.2.4	•		X	See Sections 6.6 and 7.6 of [3].
43	Design extensible to wider channels	4.3	•		X	Support multiple blocks. See Chapter 8 of [3].
44	Mechanisms for quality of service (QoS) control and monitoring	4.4.1	•		X	See Section 3.3 of [3].
45	Interfaces and procedures that facilitate the configuration, negotiation, and enforcement of QoS policies	4.4.1	•		X	See Section 3.3 of [3].
46	Support both IPv4 and IPv6	4.5	•		X	See Section 3.3 of [3].
47	Handoff methods	4.5.1	•		X	See Section 2 and 16 of [2].
48	Allow the use of either MobileIPv4, MobileIPv6 or of SimpleIP	4.5.1.1	•		X	See Section 2 of [2] and Section 3.3 of [3].
49	Mechanism to enable the provisioning and collection of metrics	4.5.2	•		X	Provides additional independent transport for provisioning and collection of metrics, see Section 3.4 of [3]. MIBs to be defined in an independent document.

#	Requirement	SRD ¹ Section #	Requirement Type		Compliance Level	
			Shall	Should	Yes	Notes
50	Not preclude proprietary scheduling algorithms, so long as the standard control messages, data formats, and system constraints are observed	4.6	•		X	Provide mobile and sector information to support proprietary scheduling algorithms. See Section 3.4 and 7.6 of [3] and Section 8 of [2].
51	Power conservation features to improve battery life for idle mobile terminals	4.7	•		X	Support idle state and selected interlace operation. See Section 6.3 and 6.4 of [3].

References

- [1] IEEE C802.20-05/61 “QFDD Performance Report 1.”
- [2] IEEE C802.20-05/68 “QFDD and QTDD: Technology Overview.”
- [3] IEEE C802.20-05/69 “QFDD and QTDD: Proposed Draft Air Interface Specification.”