

Project	IEEE 802.20 Working Group on Mobile Broadband Wireless Access < http://grouper.ieee.org/groups/802/20/ >	
Title	Irregular Repeat-Accumulate LDPC Code Proposal – Technology Overview	
Date Submitted	2007-03-05 (March 5, 2007)	
Source(s):	Thierry Lestable Samsung Electronics Research Institute, UK	Email : thierry.lestable@samsung.com
	Joseph Cleveland Samsung Telecommunications America	Email: j.cleveland@samsung.com
	Anna Tee Samsung Telecommunications America	Email: atee@sta.samsung.com
Re:	IEEE 802.20 Call for Proposals	
Abstract	This document introduces a new coding scheme based on Irregular Repeat Accumulated (IRA) Codes which is proved to be suitable for small packet lengths produced by VoIP-like applications, and thus proposed to be included into Mobile Broadband Wireless Access Systems as an alternative to Convolutional Codes.	
Purpose	For consideration and adoption as a feature for 802.20 standards draft	
Notice	This document has been prepared to assist the IEEE 802.20 Working Group. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.	
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.20.	
Patent Policy	The contributor is familiar with IEEE patent policy, as outlined in Section 6.3 of the IEEE-SA Standards Board Operations Manual < http://standards.ieee.org/guides/opman/sect6.html#6.3 > and in <i>Understanding Patent Issues During IEEE Standards Development</i> < http://standards.ieee.org/board/pat/guide.html >.	

I. INTRODUCTION

In the current draft [1] defining the Air Interface of Mobile Broadband Wireless Access Systems, two different mandatory coding schemes are used depending on the information block length to be transmitted over the air.

Indeed, whilst the rate $R_c=1/3$ Convolutional Code (CC) is employed for short packets whose length is below (or equal) 128 information bits, a rate $R_c=1/5$ Parallel Concatenated Convolutional Code (PCCC) i.e. Turbo code is preferred for higher packet length.

We thus propose hereafter an alternative optional coding scheme for encoding short packets, by taking advantage of outstanding performances from Irregular Repeat Accumulate (IRA) Codes.

Besides offering a linear encoding complexity w.r.t packet length, these codes inherit some advantages from both Turbo-Codes, and Low-Density Parity Check (LDPC) Codes. They thus induce semi-parallel architectures, resulting in high-throughput decoders, together with being decodable by Message-Passing algorithms only, or by Turbo-like decoding algorithms.

II. BASICS OF IRREGULAR REPEAT ACCUMULATE (IRA) CODES

Repeat Accumulate (RA) Codes [3], together with their enhanced version Irregular Repeat Accumulate (IRA) Codes [4] are part of Sparse Graph Codes family, and as such can be seen as a subset of LDPC Codes. On the other hand, we'll see in the sequel that they can also be seen as a concatenated coding scheme. They were introduced first by Divsalar et al. in [3], and have drawn initial interest due to their simplicity for theoretical studies.

Besides, it can be easily demonstrated that these family of codes offer a linear time encoding, which makes them attractive compared with Turbo-Codes or LDPC Codes [15].

The structure of such RA Codes is depicted in Figure II-1 below, where the concatenated framework is highlighted:




Figure II-1 Repeat Accumulate (RA) Code : Concatenated Structure

Each of the k information bits forming the packet to be transmitted over the air, are first repeated q times. This can be seen as a repetition code of rate $1/q$. Those $n=kq$ bits are then interleaved and fed into a simple accumulator. This accumulator can be described as a rate-1 convolutional code, with a generator polynomial $1/(1+D)$.

As such, a RA code is the Serial concatenation of two different coders: repetition code, and convolutional code.




Figure II-2 Tanner Graph of RA Codes

Moreover, such codes as subset of LDPC Codes can also be easily represented by means of their Tanner Graph, cf. Figure II-2: a bipartite graph with bit and parity nodes. This means their decoding can be realized by means of any Message-Passing algorithms, and offer advantageous inherited parallel architecture.

III. INTERLEAVER DESIGN

As outlined in the concatenated structure, the interleaving is a key process whilst designing such IRA codes, together with the distribution of the repetitions.

We are thus going to propose in the sequel two different kinds of interleavers, and evaluate their suitability to the encoding of short packets.

A. Pseudo-Random Interleaver (Algorithm A)

We reuse here the ‘S-Random’ algorithm [6], by adapting the ‘S’ factor w.r.t. the repetition factor of each variable node (Irregular Code).

Let’s define the following polynomial: $\sigma(y) = \sum_i \sigma_i \cdot y^{S_i}$.

where σ_i means a fraction of indices, such that, for any two indices m, n from this fraction, the following condition is fulfilled:

$$|m - n| < S_i \Rightarrow |\Pi(m) - \Pi(n)| \geq S_i$$

where $\Pi(m), \Pi(n)$ are the resulting indices after permutation.

Note that some $i S$ could be more than $N / 2$ but all $i S$ must be more than i . A disadvantage of the approach is that the interleaver requires memory to store numbers and it is not possible to design it on fly.

B. Algebraic Interleaver with induced Randomness (Algorithm B)

We propose here to use an Algebraic Interleaver which can be generated on the fly, and can be fully defined by only few parameters. We particularly focus here on the circular shifting interleaver even though many other techniques can be found in [8].

IV. SIMULATION RESULTS

In order to illustrate our results, we’ve decided to evaluate the two proposed schemes, namely IRA-A (Pseudo-Random), and IRA-B (Algebraic) codes, for the particular transmission of short packets generated by an EVRC vocoder. This is an opportunity indeed to draw attention on VoIP-like applications. Such vocoder will produce 3 different kinds of information block length, respectively 172, 80 and 16 bits (cf. [9]).

As a result, our evaluation will be compared with a Convolutional Code, since this is mainly the coding scheme in use for such lengths.

With a target FER of 1%, the Algorithm A (IRA-A) ends up with 0.8dB improvement compared with the convolutional code (cf. below Figure IV-1).




Figure IV-1 Algorithm A, BER/FER Vs E_b/N_0 : Full Rate EVRC (172 bits)

Now, for the same information length, 172 bits, the second code IRA-B results in 0.5dB gain w.r.t. the convolutional case (Figure IV-2).




Figure IV-2 Algorithm B, BER/FER Vs E_b/N_0 : Full Rate EVRC (172 bits)

It is then interesting to evaluate if this gain is maintained whilst decreasing the packet length, since it is well known, this is a challenging field for Iterative coding schemes such as Sparse graph codes (LDPC Codes).

In the Figure IV-3 (80 bits) and Figure IV-4 (16 bits) below, the IRA-B code still outperforms the convolutional code by respectively 0.5dB and 0.7dB.




Figure IV-3 Algorithm B, BER/FER Vs E_b/N_0 : $R_c=1/2$ EVRC (80 bits)




Figure IV-4 Algorithm B, BER/FER Vs E_b/N_0 : $R_c=1/8$ EVRC (16 bits).

V. CONCLUSIONS

In this proposal, Irregular Repeat Accumulate (IRA) codes have been demonstrated to be suitable candidate technology whilst transmitting short packet length (between 16 and 172 bits). Besides, their performance outperforms current Convolutional codes by 0.5dB to 1dB.

Since these codes offer a linear time encoding, together with parallel decoder architecture resulting in very high throughput decoders, it could make sense then to consider them as an optional alternative for short packet lengths (<128 bits).

References

- [1] 'Draft Standard for Local and Metropolitan Area Networks - Standard Air Interface for Mobile Broadband Wireless Access Systems Supporting Vehicular Mobility - Physical and Media Access Control Layer Specification', IEEE P802.20/D2.1, May 2006.
- [2] 3GPP2 C.S0014-A, "Enhanced Variable Rate Codec, Speech Service Option 3 for Wideband Spread Spectrum Digital Systems", April 2004
- [3] D. Divsalar, H. Jin, and R. J. McEliece, "Coding theorems for turbo-like codes," in 36th Allerton Conference on Communications, Control, and Computing, Sept. 1998, pp. 201--210.

- [4] H. Jin, A. Khandekar and R. J. McEliece, "Irregular repeat-accumulate codes," Proceedings of the Second International Symposium on Turbo Codes and Related Topics, pp. 18, Brest, France, September 2000
- [5] G.D. Forney, Jr., "Codes on graphs: normal realizations," IEEE Transactions on Inform. Theory, vol. 47, no. 2, pp. 520-548, Feb 2001
- [6] Tanner R.M. A Recursive Approach to Low Complexity Codes / R.M. Tanner // IEEE Transaction on Information Theory. – 1981. –Vol. IT-27, № 9. – P.533-547.
- [7] MacKay D. Information theory, inference and learning algorithms, Cambridge University Press, New York, NY, 2002. 550 pp
- [8] S. Dolinar and D. Divsalar "Weight Distribution for turbo codes using random and non-random permutation" JPL Progress report 42-122 pp 56-65, Aug 15, 1995
- [9] 3GPP2 C.S0002-D, "Physical Layer Standard for cdma2000 Spread Spectrum Systems", Revision D, February 13, 2004
- [10] iLBC Internet Low Bitrate Vocoder, <<http://www.vocal.com/ilbc.html>>
- [11] D. Chase, "Code-combining - a maximum likelihood decoding approach for combining an arbitrary number of noisy packets," IEEE Trans. on Commun., vol. 33, May 1985.
- [12] 3GPP2 C.S0047-0 Link-Layer Assisted Service Options for Voice-over-IP: Header Removal (SO60) and Robust Header Compression (SO61)
- [13] RFC 3095 - RObust Header Compression (ROHC): Framework and four profiles: RTP, UDP, ESP, and uncompressed, The Internet Society (2001).
- [14] H. D. Pfister, I. Sason and R. Urbanke, "Capacity-achieving ensembles for the binary erasure channel with bounded complexity," IEEE Trans. on Information Theory, vol. 51, no. 7, pp. 2352-2379, July 2005.
- [15] T. Lestable, M. Ran et al., "Error Control Coding Options for Next Generation Wireless Systems", White paper from WWRP#17, Heidelberg, Germany, Nov. 2006.