

Backwards Compatibility Considerations for 100G

Macau – 50G / NGOATH Study Group

Mark Gustlin, Xilinx

Eric Baden, Broadcom

Chris Cole, Finisar

Yong Kim, Broadcom


Vasu Parthasarathy, Broadcom

Rob Stone, Broadcom

Supporters


Green Field Cases Being Discussed (all new silicon and hosts) – 100G PHYs

Green Field Case 1:



- Optimal PMD design, leverage FEC
- Architectural Commonality with 802.3bs

Green Field Case 2:




- Optimal PMD design, leverage FEC (maybe at reduced gain / burst error protection)
- Enable *new* 25G Host to communicate with 50G Host, w/ 50G based PMD

- **Neither of these cases addresses legacy backwards connectivity, as the host silicon is all new**
 - For GF case 2, allows re-use of existing 25G serdes IP but ***requires new PCS / FEC logic, and new 26G based module development for lower density applications – questionable business case?***
 - Questionable whether the GF Case 2 4 x 26.6G PCS has BMP / Distinct Identity (as it does nothing to improve IO density, latency, or backwards compatibility with existing PHYs)
 - Adoption of a new PCS for 26G NRZ will make millions of 100GBASE-xR4 ports incompatible – unlikely to be embraced by the industry


Backwards Compatibility Cases (at least one “legacy” host / silicon) – 100G

Brown Field Option A:



- Enables Legacy host to communicate with new 50G capable host
- Introduces an “adapter” module with 2:1 bit mux
- Impacts PMD choice due to lower performance FEC (differs from Greenfield case on previous slide)

Brown Field Option B:




- Enables Legacy host to communicate with new 50G capable host
- Introduces an “adapter” module with 2:1 bit mux and RS-544 FEC
- No limitations on PMD choice due to FEC
- Requires module and host support for FEC extender sub-layer

Summary


All New PHY cases

Compatibility Cases


Greenfield Case 1
(CAUI-4 hosts, RS-544 end – end)




Greenfield Case 2
(CAUI-4 Host to CAUI-2 Host RS-544 end – end)



Brownfield Option A
(CAUI-4 Host, RS-528 end – end over PMD and CAUI-2 interface)



Brownfield Option B
(CAUI-4 Host, RS-544 in module, over PMD and CAUI-2 interface)



compatible with existing silicon / standards*	No	No	Yes	Yes
Uses existing host management software	N/A	N/A	Yes	No, due to extender sub-layer
maximizes PMD reach / FEC leverage	Yes	No, due to interleaving	No	Yes
FEC used to protect optical PMD / 50G AUI	RS-544	RS-544	RS-528	RS-544
Maximizes new host IO density	Yes	Yes	Yes	Yes

*With appropriate adapter module if needed

Summary / Next Steps

- **There is strong interest in providing streamlined backwards compatibility between existing 100GE 4 lane ports and new 100GE 2 lane ports**
 - Will be a large number of 100G 4 lane interfaces deployed (~ 15M in 2018)
 - A streamlined way of connecting to such devices will likely be desired
- **IEEE is the right venue to do this work, in order to enable maximum adoption and minimize fragmentation**
- **However, work remains to be done before we can write an appropriate objective:**
 - Analysis of candidate PMDs which can be supported by either brownfield A, or B – and the number of module types this leads to
 - Potentially definition of extender sub-layer (to support brownfield B)
- **Propose that an appropriate objective is added by the taskforce once assessment is made of both brownfield options, associated with at least one PMD**



Thanks!