

# Objectives

## IEEE 802.3 Beyond 400 Gb/s Ethernet Study Group

John D'Ambrosia,  
Chair, IEEE 802.3 Beyond 400 Gb/s Ethernet Study Group  
Futurewei, U.S. Subsidiary of Huawei

August 12, 2021

# B400G Adopted Objectives

- **Non-Rate Specific**

- Support full-duplex operation only \*
- Preserve the Ethernet frame format utilizing the Ethernet MAC \*
- Preserve minimum and maximum FrameSize of current IEEE 802.3 standard \*
- Support a BER of better than or equal to  $10^{-13}$  at the MAC/PLS service interface (or the frame loss ratio equivalent) \*\*
- Provide support to enable mapping over OTN \*\*\*

- **200 Gb/s Related**

- Support a MAC data rate of 200 Gb/s ##
- Support optional single-lane 200 Gb/s attachment unit interfaces for chip-to-module and chip-to-chip applications ##
- Define a physical layer specification that supports 200 Gb/s operation:
  - over 1 pair of SMF with lengths up to at least 500 m ##
  - over 1 pair of SMF with lengths up to at least 2 km ##

- **400 Gb/s Related**

- Support a MAC data rate of 400 Gb/s ##
- Support optional two-lane 400 Gb/s attachment unit interfaces for chip-to-module and chip-to-chip applications ##
- Define a physical layer specification that supports 400 Gb/s operation:
  - over 2 pairs of SMF with lengths up to at least 500 m ##

# B400G Adopted Objectives

- **800 Gb/s Related**

- Support a MAC data rate of 800 Gb/s \*
- Support optional eight-lane 800 Gb/s attachment unit interfaces for chip-to-module and chip-to-chip applications \*\*\*\*
- Support optional four-lane 800 Gb/s attachment unit interfaces for chip-to-module and chip-to-chip applications \*\*\*\*
- Define a physical layer specification that supports 800 Gb/s operation:
  - over eight lanes of twin axial copper cables with a reach up to at least 2 meters @
  - over eight lanes over electrical backplanes supporting an insertion loss  $\leq 28\text{dB}$  at 26.56GHz @
  - over 8 pairs of MMF with lengths up to at least 50 m \*
  - over 8 pairs of MMF with lengths up to at least 100 m \*
  - over 8 pairs of SMF with lengths up to at least 500 m \*
  - over 8 pairs of SMF with lengths up to at least 2 km #
  - over 4 pairs of SMF with lengths up to at least 500 m \*
  - over 4 pairs of SMF with lengths up to at least 2 km \*
  - over 4 wavelengths over a single SMF in each direction with lengths up to at least 2 km \*
  - over a single SMF in each direction with lengths up to at least 10 km \*
  - over a single SMF in each direction with lengths up to at least 40 km \*

- **1.6 Tb/s Related**

- Support a MAC data rate of 1.6 Tb/s #
- Support optional sixteen-lane 1.6 Tb/s attachment unit interfaces for chip-to-module and chip-to-chip applications ###
- Support optional eight-lane 1.6 Tb/s attachment unit interfaces for chip-to-module and chip-to-chip applications #
- Define a physical layer specification that supports 1.6 Tb/s operation:
  - over 8 pairs of SMF with lengths up to at least 500 m #
  - over 8 pairs of SMF with lengths up to at least 2 km #

# Adoption History

- \* Adopted by B400G SG, Apr 2021
- \*\* Adopted by B400G SG Apr 26, 2021
- \*\*\* Adopted by B400G SG May 3, 2021
- \*\*\*\* Adopted by B400G SG May 17, 2021
- # Adopted by B400G SG Jun 3, 2021
- ## Adopted by B400G SG Jul 13, 2021
- ### Adopted by B400G SG Jul 20, 2021
- @ Adopted by B400G SG Aug 12, 2021