

# Working Objectives :

## >10 Mb/s long-reach SPE

G. Zimmerman/ADI, APL Group, Cisco,  
CommScope, Marvell, SenTekSe

10/13/2021

# Suggested Basic PHY Objectives

---

## Consensus:

1. Preserve the IEEE 802.3/Ethernet frame format at the MAC client service interface.
2. Preserve minimum and maximum frame size of the current IEEE 802.3 standard.
3. Do not preclude meeting FCC and CISPR EMC requirements
4. Support for optional single-pair Auto-Negotiation
5. Do not preclude the ability to survive industrial fault conditions (e.g., shorts, overvoltage, EMC)
6. Do not preclude working within an Intrinsically Safe device and system as defined in IEC 60079

## Need consensus built:

1. Not require any changes to the IEEE 802.3 MAC
2. (PHY to) Be compatible with (existing?) (IEEE 802.3?) single-pair DC powering techniques

# Speed-Specific Objectives (100 Mb/s)

---

## Consensus:

1. Support a speed of 100 Mb/s at the MAC/PLS service interface.
2. Support 100 Mb/s single-pair Ethernet operation in industrial environments (e.g., EMC, temperature ).
3. Maintain a bit error ratio (BER) at the MAC/PLS service interface of less than or equal to  $10^{-10}$
4. Do not preclude operation with latency  $\leq$  TBD msec

## To work:

1. Define performance characteristics of a link segment with a single balanced pair of conductors supporting up to 10(TBD) inline connectors for up to at least (TBD: 1 km/500m/(TBD,  $\geq$  300m) reach, and a PHY supporting point-to-point full duplex operation over the link segment.

# Speed-Specific Objectives (1000 Mb/s)

---

Should consider all the 100 Mb/s rewording on the previous page, and need presentations supporting these & the CSDs (especially reach & tech feasibility from a PHY SME perspective)

1. Support a speed of 1000 Mb/s at the MAC/PLS service interface.
2. Support 1000 Mb/s single-pair Ethernet operation in industrial environments (e.g., EMC, temperature ).
3. Define performance characteristics of a link segment with a single balanced pair of conductors supporting up to **10(TBD)** inline connectors for up to at least (**TBD: 100m/300m/500m (TBD,  $\geq 100\text{m}$ )**) reach, and a PHY supporting point-to-point full duplex operation over the link segment.
4. Maintain a bit error ratio (BER) at the MAC/PLS service interface of less than or equal to **TBD ( $10^{-10}$ )**
5. **Latency objective?**

# POTENTIAL ADDITIONAL FEATURE OBJECTIVES

---

Consensus:

- Power:
  - Specify one or more optional power distribution techniques for use in conjunction with 100 Mb/s single-pair Ethernet PHYs over one or more of the single-pair segments

May need wordsmithing:

- EEE:
  - Support optional Energy Efficient Ethernet (possibly additional qualifiers or “energy efficiency”)

To Consider – do we need this for long-reach?

- Startup:
  - Support fast-startup operation using predetermined configurations which enables the time from power\_on=FALSE to a state capable of transmitting and receiving valid data to be less than 100ms