


Choose Signaling Method First

Justin Gaither Xilinx



Where are we?

Multiple camps limiting consensus





Signaling proposals

- Unified (NRZ/Duobinary)
 - Xilinx anderson_01_1104.pdf
 - IBM abler_01_0904.pdf
 - LSI liu_01_0904.pdf
 - Vitesse multiple
 - Lucent adamiecki_01_1104.pdf, sinsky_01_0904.pdf
- PAM4
 - Agere brink_02_0704.pdf
 - Synopsys -
- PR4
 - Intel altmann_02_0904.pdf



Vote Signaling First

- Signaling spreadsheet as a tool to select signaling method will be uncorrelatable
 - Different signaling methods, simulators, assumptions will have too many variances
 - This was shown in anderson_01_1104.pdf
- Choosing Channel first creates a multi-dimensional problem.
 - By selecting Signaling method, the problem is reduce to 1 dimension (how much complexity must be added to support specific channel)
- Any Signaling method can solve a channel given sufficient complexity.
 - Bad Channels increase power and complexity for all signaling methods
- There is a plurality in support/contribution of one signaling method.




Why Unified Signaling


- Large industry support behind Unified Signaling
 - Showing feasibility over many of the channels of interest
- Reduced industry support for PAM4, lack of information on PR4
- Multiple vendors have shown NRZ and Duobinary Receivers working over most channels of interest.
 - Working with similar DFE, FFE taps, similar complexity.
- Consensus that C_d tap in TX equalizer is acceptable
- For feasibility we only need to show a single compliant architecture can solve the channel in order to be feasible. (lower burden of proof)



Channel Problem Spaces vs. Transceiver Solution Spaces

Reasonable NRZ Reference Rx





Channel Comparison

- Use signaling spreadsheet to analyze channel impact tradeoffs.
 - Easily analyze cost in complexity & power for each legacy channel
 - Channels are not competing against each other, they are only competing against complexity they require.
 - Simpler problem to solve

