

# Channel Modelling Ad Hoc

## Task 1 – Static Channel Model

- Several meetings held –
- Review of Gen67, OM3 and CTM approaches by Task 1
- Outcomes include (motions to this meeting)
  - Confirm 108 fiber set and Gen67 Monte Carlo sets as recommended baseline 62.5 $\mu$ m FDDI-grade fiber models for 10GBASE-LRM specifications (Jonathan and John A)
  - Adoption of wavelength scaled Monte Carlo set for OM3 (Petar)
  - Adoption of Connector Transfer Matrix approach for dealing with connectors (John E and Petar)
  - Decision to carry out (low level) development of OM2 models

# FDDI and OM3 Fiber Models

- Following models available on web site
  - 108 fiber set for FDDI (support Jonathan Ingham)
  - Monte Carlo fiber sets (Gen54 and Gen67) – assuming Gen67 adopted at this meeting, this should be version used. – NB 500MHz.km truncation agreed (John Abbott)
  - Wavelength scaled Monte Carlo set for OM3 (Petar Pepeljugoski)
- Models being widely used, for example by
  - Acuid, Agilent, Big Bear, Broadcom, Corning, JDSU, Georgia Tech, OFS, Optium, Panduit, Phyworks, RSoft etc
- Model outputs and documentation available at  
<http://www.ieee802.org/3/aq/public/tools/index.html>

# Connector Transfer Matrix (CTM) for FDDI Grade

- Methodology based on Petar Pepeljugoski's approach for OM3 (already distributed)
- Connector transfer matrices generated by John Ewen and Petar Pepeljugoski
- Allows generation of simulation sets for connectors
- Ewen/Pepeljugoski CTM checked against independently generated Cunningham approach
- Good agreement, even without using exactly the same parameters, indicates calculations not extremely sensitive to these choices
- CTMs available as Matlab and Excel files
- Motion to this meeting