

Cl 00 SC 0 P L # 11
 CHOU, JOSEPH REALTEK SEMICON

Comment Type TR Comment Status D

The meaning and value of TX_LP_IDLE and RX_LP_IDLE are not clearly defined in the draft but are used in the following clauses:

TX_LP_IDLE: 24.2.2, 24.2.2.5, 24.2.3.1, and 36.2.4.12a

RX_LP_IDLE: 24.2.2, 24.2.2.5, 24.2.3.1, 35.2.2.9a, and 36.2.4.12a

SuggestedRemedy

Need to define them or replace them with actual contents

Proposed Response Response Status O

Cl 00 SC 0 P L # 244
 Diab, Wael Broadcom

Comment Type E Comment Status D

Revision history is inconsistent and inaccurate across draft

SuggestedRemedy

Suggest having consistency or deleting altogether

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Will clear revision history.

Cl 00 SC 0 P 19 L 14 # 17
 Maguire, Valerie Siemon

Comment Type E Comment Status D

Insert text to reference the TIA cabling equivalent to ISO class D. This revision is consistent with text in other locations of the document (see clause 78.1.1, page 237, line 27).

SuggestedRemedy

Insert text as follows:

"...for operation over 0 m to at least 100 m of ISO/IEC 11801:1995 Class D, ANSI/TIA/EIA-568-A-1995 category 5, or better cabling."

Proposed Response Response Status O

Cl 00 SC 0 P 19 L 37 # 14
 Maguire, Valerie Siemon

Comment Type E Comment Status D

Insert text to reference the TIA cabling equivalent to ISO class D. This revision is consistent with text in other locations of the document (see clause 78.1.1, page 237, line 27).

SuggestedRemedy

Revise sentence as follows:

"The medium for 10BASE-Te is a channel meeting or exceeding the requirements of the Class D channel specified by ISO/IEC 11801:1995 or the category 5 channel specified by ANSI/TIA/EIA-568-A-1995."

Proposed Response Response Status O

Cl 00 SC 0 P 21 L 4 # 15
 Maguire, Valerie Siemon

Comment Type E Comment Status D

Insert text to reference the TIA cabling equivalent to ISO class D. This revision is consistent with text in other locations of the document (see clause 78.1.1, page 237, line 27).

SuggestedRemedy

Revise sentence as follows:

"...so that it matches the worst case insertion loss for a Class D channel as specified in ISO/IEC 11801:1995 or for a category 5 channel as specified in ANSI/TIA/EIA-568-A-1995."

Proposed Response Response Status O

Cl 00 SC 0 P 25 L 20 # 16
Maguire, Valerie Siemon

Comment Type E Comment Status D

Insert text to reference the TIA cabling equivalent to ISO class D and add a note (similar to the existing ISO note) indicating that the latest version of the standard specifies a media that exceeds the minimum requirements of the standard. This revision is consistent with text in other locations of the document (see clause 78.1.1, page 237, line 27).

Note: ANSI/TIA-568-C.2 is anticipated to be published August, 2008.

SuggestedRemedy

Insert text as follows:

"...the requirements of the Class D channel specified by ISO/IEC 11801:1995 or the category 5 channel as specified in ANSI/TIA/EIA-568-A-1995.

NOTE - ANSI/TIA-568-C.2 provides a specification for category 5e media that exceeds the minimum requirements of this standard."

Leave the note related to ISO as it stands.

Proposed Response Response Status O

Cl 01 SC 1 P 15 L 1 # 105
Barrass, Hugh Cisco

Comment Type E Comment Status D

This header may be useful but it doesn't need to be repeated for every clause - it's a waste of electrons!

SuggestedRemedy

Delete ", Clause 1"

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Editor will check with 802.3 Chair/vice chair on their recommendation on the use of a header to distinguish between a new clause and changes to existing clauses.

Cl 01 SC 1 P 15 L 14 # 106
Barrass, Hugh Cisco

Comment Type E Comment Status D

The editor's note with revision history and comments has not been kept up to date since July 2008. Therefore it is clearly not considered useful by either editors or commenters.

SuggestedRemedy

Delete the editor's note box.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Will clear revision history

See response to comment 244

Cl 01 SC 1.3 P 15 L 31 # 102
Barrass, Hugh Cisco

Comment Type E Comment Status D

Status was checked during 802.3-2008 revision.

SuggestedRemedy

Delete editor's note box & subclause heading.

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 01 SC 1.4 P 15 L 39 # 103
Barrass, Hugh Cisco

Comment Type E Comment Status D

After 4 drafts, it is clear that no commenters think that there are more terms to add.

SuggestedRemedy

Delete the editor's note box.

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 01 **SC 1.5** **P 16** **L 12** # **246**
 Diab, Wael Broadcom

Comment Type **E** **Comment Status** **D**

This section is intended to be an expansion of abbreviations, not an explanation

SuggestedRemedy
 Delete the words "label to indicate" and the " "

Proposed Response **Response Status** **W**
 PROPOSED ACCEPT.

Cl 01 **SC 1.5** **P 16** **L 3** # **104**
 Barrass, Hugh Cisco

Comment Type **E** **Comment Status** **D**

After 4 drafts, it is clear that no commenters think that there are more abbreviations to add.

SuggestedRemedy
 Delete editor's note box & the bogus subclause heading.

Proposed Response **Response Status** **W**
 PROPOSED ACCEPT.

Cl 01 **SC 1.5** **P 16** **L 8** # **245**
 Diab, Wael Broadcom

Comment Type **E** **Comment Status** **D**

There seems to be a heading issue. Section 1.1 appears under 1.5

SuggestedRemedy
 Delete 1.1

Proposed Response **Response Status** **W**
 PROPOSED ACCEPT.

Cl 14 **SC 14** **P 17** **L 1** # **109**
 Barrass, Hugh Cisco

Comment Type **E** **Comment Status** **D**

It's not necessary to have this boilerplate text for every clause.

SuggestedRemedy
 Delete all the boilerplate text up to the Clause heading.

Proposed Response **Response Status** **W**
 PROPOSED ACCEPT.

Cl 14 **SC 14.1** **P 19** **L 23** # **231**
 GUPTA, SUJAY Infosys Technologies

Comment Type **E** **Comment Status** **D**

The section talks about MAU, so the keyword maybe removed as it is understood.

SuggestedRemedy
 j) Provides for operation with reduced transmit amplitude for a type 10BASE-Te (optional).

Proposed Response **Response Status** **W**
 PROPOSED ACCEPT IN PRINCIPLE.

Change (j) to:
 j) Provides for operation with reduced transmit amplitude for type 10BASE-Te (optional).

Cl 14 **SC 14.10.4.5.12** **P 26** **L 28** # **108**
 Barrass, Hugh Cisco

Comment Type **E** **Comment Status** **D**

After 4 drafts, it is clear that no commenters think that any further PICS items are required.

SuggestedRemedy
 Delete the editor's note box.

Proposed Response **Response Status** **W**
 PROPOSED ACCEPT.

Cl 14 **SC 14.3.1.2.1** **P 23** **L 27** # **174**
 Grimwood, Michael Broadcom

Comment Type **T** **Comment Status** **D**

For 10BASE-Te, TP_IDL and data should be tested against the same twisted-pair model. This means that the voltage template requirements for transmission of TP_IDL should be met with the 10BASE-Te twisted-pair model.

SuggestedRemedy
 Change:
 ".with the load connected through the twisted-pair model as defined in Figure 14-7 and Figure 14-8."
 To:
 ".with the load connected through the twisted-pair model as defined in Figure 14-7 and Figure 14-8 for 10BASE-T and Figure 14-7a and Figure 14-8 for 10BASE-Te."

Proposed Response **Response Status** **W**
 PROPOSED ACCEPT.

Cl 14 SC 14.3.1.2.1 P 24 L 3 # 175
Grimwood, Michael Broadcom

Comment Type T Comment Status D

For 10BASE-Te, the link test pulse and data should be tested against the same twisted-pair model. This means that the voltage template requirements for transmission of the link test pulse should be met with the 10BASE-Te twisted-pair model.

SuggestedRemedy

".with the load connected through the twisted-pair model as defined in Figure 14-7 and Figure 14-8."

To:

".with the load connected through the twisted-pair model as defined in Figure 14-7 and Figure 14-8 for 10BASE-T and Figure 14-7a and Figure 14-8 for 10BASE-Te."

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Change on line 3 from ".with the load connected through the twisted-pair model as defined in Figure 14-7 and Figure 14-8."

To:

".with the load connected through the twisted-pair model as defined in Figure 14-7 and Figure 14-8 for 10BASE-T and Figure 14-7a and Figure 14-8 for 10BASE-Te."

And on line 25 from "with the load connected through the twisted-pair model as defined in Figure 14-7 and Figure 14-8."

To:

"with the load connected through the twisted-pair model as defined in Figure 14-7 and Figure 14-8 for 10BASE-T and Figure 14-7a and Figure 14-8 for 10BASE-Te."

Cl 14 SC 14.4 P 25 L 3 # 107
Barrass, Hugh Cisco

Comment Type E Comment Status D

After 4 drafts, it is clear that no commenters think that there are further link segment specifications to make.

SuggestedRemedy

Delete the editor's note box.

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 22 SC P L # 247
Diab, Wael Broadcom

Comment Type E Comment Status D

Several of the cross-refs appear in blue

SuggestedRemedy

If this is not intentional, please change back to black

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

The cross references that appear in blue have no link within this amendment. However, this is not documented anywhere in the draft - causing comments such as this.

Add a sentence to the editing instructions on page 15:

Cross-references that do not point to text in this amendment are shown in Dark Blue and have no active link.

Cl 22 SC 22 P 27 L 1 # 112
Barrass, Hugh Cisco

Comment Type E Comment Status D

It's not necessary to have this boilerplate text for every clause.

SuggestedRemedy

Delete all the boilerplate text up to the Clause heading.

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 22 SC 22 P 27 L 3 # 110
Barrass, Hugh Cisco

Comment Type E Comment Status D

Editor's note is no longer needed.

SuggestedRemedy

Delete the editor's note box.

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 22 SC 22.2 P 29 L 12 # 232
 GUPTA, SUJAY Infosys Technologies

Comment Type E Comment Status D

In Carrier_Status is dependent independently on the basic MII CRS plus our new addition the LPI SM. Recommending to change the language clause.

The CARRIER_STATUS parameter can take one of two values: CARRIER_ON or CARRIER_OFF. The values CARRIER_ON and CARRIER_OFF are derived from the MII signal CRS and from the transmit LPI state machine.

SuggestedRemedy

The CARRIER_STATUS parameter can take one of two values: CARRIER_ON or CARRIER_OFF. The values CARRIER_ON and CARRIER_OFF can be derived from the MII signal CRS and also from the transmit LPI state machine.

Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 22 SC 22.2 P 30 L 40 # 224
 GUPTA, SUJAY Infosys Technologies

Comment Type E Comment Status D

The MAC should wait for the resolved time before asserting out of LPI. So changing; The MAC device should not assert TX_EN for valid transmit data until after the wake up time specified for the PHY.

SuggestedRemedy

The MAC device should not assert TX_EN for valid transmit data until after the resolved wake up time specified for the PHY.

Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 22 SC 22.2.1.3.3 P 29 L 20 # 40
 Dietz, Bryan Alcatel-Lucent

Comment Type T Comment Status D

Note that this paragraph was the subject of a maintenance request at the last meeting. The first sentence is supposed to be removed, either by 802.3az or another project.

SuggestedRemedy

Proposed Response Response Status W
 PROPOSED ACCEPT.

Comment type changed to a T

Cl 22 SC 22.2.2.2 P 29 L 47 # 176
 Grimwood, Michael Broadcom

Comment Type T Comment Status D

In figure 24-11a, the transition from the state IDENTIFY JK to the state START OF STREAM J is initially triggered by the sequence 11111 (/I) followed by 11000 (/J). This can be the same initial sequence that leads to a transition to the state START_RX_SLEEP (...111 11 000..). However, before the actual transition is complete, implementations may extend RX_CLK as described in the last paragraph of page 15 of 802.3-2005_section2.pdf. In the event that RX_CLK is extended as triggered by the bit sequence 11111 11000, the specification should be modified to allow this extension not only for the IDENTIFY JK to START of STREAM J state but also for the IDENTIFY JK to the START_RX_SLEEP state since the bit sequences that cause these transitions are initially indistinguishable.

SuggestedRemedy

On page 15 of 802.3-2005_section2.pdf in Section 22.2.2.2 (pertaining to the RX_CLK), append the following sentence to the last paragraph:

"For low power operation, when the receiver transitions from the IDENTIFY JK state to the START_RX_SLEEP state at the transition from the IDLE code-group /I/ to the SLEEP code-group /P/, the PHY may extend a cycle of RX_CLK by holding it in either the high or low condition for an interval that shall not exceed twice the nominal clock period."

Proposed Response Response Status W
 PROPOSED ACCEPT.

Note that this brings 22.2.2.2 into the draft.

CI 22 SC 22.2.2.6a P 30 L 33 # 6
Marris, Arthur Cadence

Comment Type TR Comment Status D

It is not the MAC that controls LPI transitions it is the LPI client.

SuggestedRemedy

Change 'MAC device' to 'LPI client' and put in a cross-reference to Clause 78

Do the same in 22.2.2.9a on page 32.

Also in 22.7a on page 33.

Add LPI client to Figure 22-20a removing mention of station management.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Change "MAC device" to "LPI client"

p.30, l.33; p.32, l.28; p.33, l.9 & l.11

Change "station management" to "LPI client service interface" - p.33, l20 & l36

Add at the beginning of 22.7a:

"Low Power Idle operation and the LPI client are described in Clause 78.1."

CI 22 SC 22.2.2.6a P 31 L 4 # 32
Traeber, Mario Infineon Technologies

Comment Type T Comment Status D

"> minimum LPI assertion time" in Figure 22-6a became obsolete in one of the last drafts and is not referred somewhere else anymore.

SuggestedRemedy

Remove it from the drawing

Proposed Response Response Status W

PROPOSED ACCEPT.

Comment type changed to a T

See also #26

CI 22 SC 22.7 P 34 L 7 # 229
GUPTA, SUJAY Infosys Technologies

Comment Type E Comment Status D

Need a figure for logical location of the LPI SM, which layer it interfaces. Can be mentioned in figure 22-20a, page 33.

SuggestedRemedy

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

There is no need for a new figure, however it needs to be stated explicitly in the text describing Fig 22-20a how the LPI transmit state machine is involved.

At the end of the second paragraph in 22.7a (p.33, l.44) add the following sentence:

"The timing of PLS_CARRIER.indication when used for the LPI function is controlled by the LPI transmit state machine."

CI 22 SC 22.7 P 35 L 4 # 111
Barrass, Hugh Cisco

Comment Type E Comment Status D

Editor's note is no longer needed.

SuggestedRemedy

Delete the editor's note box.

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 22 SC 22.7a P 33 L 1544 # 41
Dietz, Bryan Alcatel-Lucent

Comment Type E Comment Status D

Clarify explanation of LPI operation by editing text. The following sentence is unclear and hard to read.

"Similarly, RX_ER and RXD<3:0> are mapped to PLS_DATA.indication except when LP_IDLE is detected and CRS is mapped to PLS_CARRIER.indication except when LP_IDLE.request is asserted or the wake timer has yet to expire."

SuggestedRemedy

Restructure the following paragraph:

"The LPI assertion and detection mechanism fits conceptually between the PLS Service Primitives and the MII signals as shown in Figure 22-20a. The definition of TX_EN, TX_ER and TXD<3:0> is derived from the state of PLS_DATA.request (22.2.1.1), except when it is overridden by an assertion of LP_IDLE.request. Similarly, RX_ER and RXD<3:0> are mapped to PLS_DATA.indication except when LP_IDLE is detected and CRS is mapped to PLS_CARRIER.indication except when LP_IDLE.request is asserted or the wake timer has yet to expire."

to read (use bullets for the sub points)

"The LPI assertion and detection mechanism fits conceptually between the PLS Service Primitives and the MII signals as shown in Figure 22-20a.

" The definition of TX_EN, TX_ER and TXD<3:0> is derived from the state of PLS_DATA.request (22.2.1.1), except when it is overridden by an assertion of LP_IDLE.request.

" Similarly, RX_ER and RXD<3:0> are mapped to PLS_DATA.indication, except when LP_IDLE is detected

" CRS is mapped to PLS_CARRIER.indication, except when LP_IDLE.request is asserted or the wake timer has yet to expire."

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 22 SC 22.7a.2 P 35 L # 36
Traeber, Mario Infineon Technologies

Comment Type TR Comment Status D

Figure 22-21 TX LPI State Diagram does not include the case when the MAC is allowed to assert LPI first after a link-up. In particular this could cause problems in 100BASE-TX modes since the state-diagram suggests that the MAC could signal an LPI assertion directly after reset, i.e. during ANEG (which is useless) or link-up of 100BASE-TX. This in turn could cause link-up instabilities.

SuggestedRemedy

Introduce a state "WAIT_ON_LINKUP" into which a transition goes after reset. Only after Link-Up has been indicated via Management Registers the MAC is allowed to assert LPI. In case of a Link-Down or reset a re-transition into "WAIT_ON_LINKUP" is required.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

The suggested remedy will not have the desired effect. The TX LPI state machine does not restrict the signaling of LPI from the LPI client to the PHY, it only controls the flow of data from the MAC to the PHY during wake.

Alternative solution:

In 22.7a.1 LPI messages (p.34, l.3) add the following:

"LP_IDLE.request shall not be set to ASSERT unless the attached link is operational (i.e. link_status = READY, see 28.2.6.1.1). LP_IDLE.request shall remain to be set to DEASSERT for 1 second following link_status changing state to READY."

Cl 22 SC 22.7a.2.2 P 34 L 30 # 26
Healey, Adam LSI Corporation

Comment Type T Comment Status D

It has been established that no PHY, within the scope of P802.3az, requires a minimum LPI assertion time.

SuggestedRemedy

Delete the definition of li_timer and its use in the Transmit LPI state diagram (Figure 22-21).

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 22 SC 22.7a.2.2 P 34 L 3035 # 228
 GUPTA, SUJAY Infosys Technologies

Comment Type T Comment Status D

Suggesting timer name change;

SuggestedRemedy

Call li_timer -> lp_intimer
 and tw_timer -> lp_outtimer, the term tw is overloaded.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Li_timer is deleted by #26.

tw_timer is an appropriate name for the function.

Cl 22 SC Figure 22-6a P 31 L 19 # 1
 Marris, Arthur Cadence

Comment Type T Comment Status D

What is the relevance of PLS.CARRIER.indication in this description of transmit operation?

SuggestedRemedy

Consider deleting PLS.CARRIER.indication from this diagram. Or maybe it should be moved to Figure 22-9a which describes receive operation?

Proposed Response Response Status W

PROPOSED REJECT.

PLS.CARRIER.indication is used, along with a Clause 4A MAC, to prevent the MAC from sending data before the wake timer has expired.

This mechanism is based on the proposal from a noted Ethernet expert shown by the following link:

http://www.ieee802.org/3/efm/public/jan02/marris_1_0102.pdf

Cl 24 SC 24 P 37 L 1 # 115
 Barrass, Hugh Cisco

Comment Type E Comment Status D

It's not necessary to have this boilerplate text for every clause.

SuggestedRemedy

Delete all the boilerplate text up to the Clause heading.

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 24 SC 24.2.2.1.1 P 42 L # 34
 Traeber, Mario Infineon Technologies

Comment Type ER Comment Status D

PCS code group P does not properly specify the MII (TXD/RXD) which is "undefined". In general this would also hold true for the Idle "I" group.

SuggestedRemedy

Make a link into clause 22 specifying the coding of P at the MII or alternatively inserting "0001" and a footnot commenting on TX_EN and TX_ER coding.

Proposed Response Response Status W

PROPOSED REJECT.

There is no codegroup P transmitted or received during the Quiet state while MII is sending or receiving 0001. Therefore, one cannot equate a code in MII to the code P in PCS.

Cl 24 SC 24.2.2.5 P 43 L 22 # 243
 Bennett, Michael LBNL

Comment Type TR Comment Status D

The values in Table 24-2 do not match the values in table 78-2

SuggestedRemedy

according to slide 12 in chou_02_0708.pdf, which was adopted as a baseline, the values in 78-2 are correct. Make the tables consistent

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

It is true that the value between Table 24-2 and Table 78-2 are inconsistent. Based on the final resolution of comment #62 of draft 1.2.1, There is a statement: " Change the default value of lpi_tx_ts_timer, lpi_rx_ts_timer, and lpi_tx_tr_timer to 200us - 220us."

Therefore, Table 78-2 need to be updated with the timer value according to the following changes:

Ts 200 us (min) 220 us (max)
 Tq 20,000 us (min) 22,000 s (max)
 Tr 200 us (min) 220 us (max)

Cl 24 **SC 24.2.2.5** **P 43** **L 5** # **113**
 Barrass, Hugh Cisco

Comment Type E **Comment Status D**
 Editor's note is no longer needed.

SuggestedRemedy
 Delete the editor's note box.

Proposed Response **Response Status W**
 PROPOSED ACCEPT.

Cl 24 **SC 24.2.3.4** **P 45** **L 24** # **177**
 Grimwood, Michael Broadcom

Comment Type T **Comment Status D**
 With the current allowable range of lpi_rx_ti_timer and considering the PCS receive state diagram of Figure 24-11b, it is possible to get into an endless loop due to the following sequence:

1. Erroneously enter RX_SLEEP (due to bit errors or misalignment)
2. Receive a minimum IPG (0.96 usec) of IDLE causing a transition to WAIT_IDLE.
3. Receive data before lpi_rx_ti_timer is done causing a transition back to RX_SLEEP.
4. Repeat 2. and 3.

SuggestedRemedy
 Modify lpi_rx_ti_timer such that its maximum value is less than the minimum IPG.

Change:

"The timer shall have a period between 1.0 us to 1.2 us."

To:

"The timer shall have a period between 0.8 us to 0.9 us."

Proposed Response **Response Status W**
 PROPOSED ACCEPT.

Cl 24 **SC 24.2.4.2** **P 47** **L 10** # **12**
 CHOU, JOSEPH REALTEK SEMICON

Comment Type TR **Comment Status D**
 The value of LP_IDLE in Figure 24-8 is not defined here. It is apparently the codeword 0001 specified in Table 22-1 and also defined as TX_LP_IDLE in 24.2.3.1. This LP_IDLE is used in several places in this figure.

SuggestedRemedy
 Either replace LP_IDLE with TX_LP_IDLE and define TX_LP_IDLE clearly in 24.2.3.1 or replace it with the value 0001.

Proposed Response **Response Status W**
 PROPOSED ACCEPT IN PRINCIPLE.

Replace LP_IDLE with TX_LP_IDLE.
 Refine the definition of TX_LP_IDLE in line 10 page 44 as follows.
 "A value 0001 of transmit nibble-wide Data signals (TXD) combining with the deassertion of TX_EN and the assertion of TX_ER on the MII used to communicate the status or request of low power transmit state, as specified in 24.2.2."

Cl 24 **SC 24.2.4.2** **P 47** **L 12** # **27**
 Healey, Adam LSI Corporation

Comment Type T **Comment Status D**
 Now that lpi_tx_ts_timer and lpi_tx_tr_timer are of the same duration, the states TX_SLEEP and TX_REFRESH are essentially identical in that they execute the same actions and share the same exit conditions. The state diagram could be simplified by merging them.

SuggestedRemedy
 Merge the TX_SLEEP and TX_REFRESH states.

Proposed Response **Response Status W**
 PROPOSED ACCEPT.

However, I would like to keep Refresh state in the draft context. The following area of draft need to be changed accordingly:

1. Remove state TX_REFRESH of Figure 24-8. Add "tx_quiet<=FALSE" action to TX_SLEEP state.
2. Remove description of lpi_tx_tr_timer in page 46.
3. Modify the row containing Refresh in Table 24-2 to make it refer to the Sleep state.
4. Rewrite the description of Refresh State in line 42 of page 43 to make it similar to Sleep state.

Cl 24 SC 24.2.4.4 P 49 L # 35
Traeber, Mario Infineon Technologies

Comment Type TR Comment Status D

The RX_SLEEP state does not encode all possible cases for a state-transition leading to a hand-up of the FSM in case of Transmitter false behavior. In particular this happens when the lpi_rx_ts_timer expires but still signal power is present (which might be subject to a transmitter false behavior).

SuggestedRemedy

Introduce a state-transition to RX_LPI_LIN_FAIL when signal_status=ON*lpi_rx_ts_timer_done

Proposed Response Response Status W
PROPOSED REJECT.

The hang-up condition will rarely happen as the commenter suspects.

When lpi_rx_ts_timer expires, if Signal_status is still ON, it will wait for two conditions to proceed:

1. If the signal_status turns OFF, then FSM moves to START_RX_QUIET.
2. Or, an IPG comes in which will lead to WAIT_IDLE.

Therefore, the only situation that this FSM will stuck at RX_SLEEP state is that it indefinitely receives data stream without IPG.

In this situation, even normal receiving PCS state machine (Figure 24-11a) will hang-up.

Cl 24 SC 24.2.4.4 P 49 L 13 # 13
CHOU, JOSEPH REALTEK SEMICON

Comment Type TR Comment Status D

The value of LP_IDLE in Figure 24-11b is not defined here. It is apparently the codeword 0001 specified in Table 22-2 and also defined as RX_LP_IDLE in 24.2.3.1. This LP_IDLE is used in several places in this figure.

SuggestedRemedy

Either replace LP_IDLE with RX_LP_IDLE and define RX_LP_IDLE clearly in 24.2.3.1 or replace it with the value 0001.

Proposed Response Response Status W
PROPOSED ACCEPT IN PRINCIPLE.

Replace LP_IDLE with RX_LP_IDLE.
Refine the definition of RX_LP_IDLE in line 14 page 44 as follows.
"A value 0001 of receive nibble-wide Data signals (RXD) combining with the deassertion of RX_DV and the assertion of RX_ER on the MII used to communicate the status or request of low power transmit state, as specified in 24.2.2."

Cl 24 SC 24.3 P 51 L 6 # 230
GUPTA, SUJAY Infosys Technologies

Comment Type E Comment Status D

It should be "PMA_LPILINKFAIL.request" instead of PMA_LPILINK.request primitive.

SuggestedRemedy

Proposed Response Response Status W
PROPOSED ACCEPT.

Cl 24 SC 24.3 Figure 24-11b P 49 L 26 # 225
GUPTA, SUJAY Infosys Technologies

Comment Type T Comment Status D

RX_WAKE->RX_QUIET on condition sig_status=OFF, Need to start the lpi_rx_tq timer again

SuggestedRemedy

Proposed Response Response Status W
PROPOSED REJECT.

The transition from RX_WAKE to RX_QUIET is added to eliminate an erroneous glitch condition during Quiet state when wake-up energy is too short to decode any valid symbol.

The quiet timer should not be restarted under such circumstance. That's why state START_RX_QUIET is introduced.

Cl 24 SC 24.4.1 P 53 L 53 # 42
Dietz, Bryan Alcatel-Lucent

Comment Type E Comment Status D

Typo:

SuggestedRemedy

Typo: change "the Energy Efficient Ethernet" to "Energy Efficient Ethernet".

Proposed Response Response Status W
PROPOSED ACCEPT.

Cl 24 **SC 24.4.1.5** **P 54** **L 35** # **43**
 Dietz, Bryan Alcatel-Lucent
Comment Type **E** *Comment Status* **D**
 Typo:
SuggestedRemedy
 Insert space between "4" and "Figure 24-8".
Proposed Response *Response Status* **W**
 PROPOSED ACCEPT.

Cl 24 **SC 24.8.2.2** **P 55** **L 20** # **114**
 Barrass, Hugh Cisco
Comment Type **E** *Comment Status* **D**
 Editor's note is no longer needed.
SuggestedRemedy
 Delete the editor's note box.
 also on page 56, line 3
Proposed Response *Response Status* **W**
 PROPOSED ACCEPT.

Cl 25 **SC 25** **P 57** **L 1** # **119**
 Barrass, Hugh Cisco
Comment Type **E** *Comment Status* **D**
 It's not necessary to have this boilerplate text for every clause.
SuggestedRemedy
 Delete all the boilerplate text up to the Clause heading.
Proposed Response *Response Status* **W**
 PROPOSED ACCEPT.

Cl 25 **SC 25.3** **P 57** **L 9** # **116**
 Barrass, Hugh Cisco
Comment Type **ER** *Comment Status* **D**
 Editor's note appears to highlight some inconsistencies in the draft.
 If these are real - fix them, otherwise the editor's note is incorrect.
 In either case - delete the editor's note!
SuggestedRemedy
 Delete the editor's note box.
Proposed Response *Response Status* **W**
 PROPOSED ACCEPT.

Cl 25 **SC 25.4** **P 59** **L 34** # **117**
 Barrass, Hugh Cisco
Comment Type **E** *Comment Status* **D**
 The editor tries...
 It appears that the editor has been successful - hoorah!
SuggestedRemedy
 Delete the editor's note box.
Proposed Response *Response Status* **W**
 PROPOSED ACCEPT.

Cl 25 **SC 25.5.1** **P 65** **L 8** # **118**
 Barrass, Hugh Cisco
Comment Type **E** *Comment Status* **D**
 Editor's note is no longer needed.
SuggestedRemedy
 Delete the editor's note box.
Proposed Response *Response Status* **W**
 PROPOSED ACCEPT.

Cl 28C **SC 28C** **P 256** **L 8** # **120**
 Barrass, Hugh Cisco
Comment Type **E** *Comment Status* **D**
 Editor's note is no longer needed.
SuggestedRemedy
 Delete the editor's note box.
Proposed Response *Response Status* **W**
 PROPOSED ACCEPT.

Cl 28C **SC 28C.12** **P 256** **L 44** # **28**
 Healey, Adam LSI Corporation
Comment Type **T** *Comment Status* **D**
 "...with at least two unformatted next pages that contain information defined in 45.2.7.13a."
 There is currently only one unformatted next page following the message page.
SuggestedRemedy
 Change to "...with at least one unformatted next page..."
Proposed Response *Response Status* **W**
 PROPOSED ACCEPT.

Cl 30 **SC 30** **P 66** **L 1** # **122**
 Barrass, Hugh Cisco
Comment Type **E** *Comment Status* **D**
 It's not necessary to have this boilerplate text for every clause.
SuggestedRemedy
 Delete all the boilerplate text up to the Clause heading.
Proposed Response *Response Status* **W**
 PROPOSED ACCEPT.

Cl 30 **SC 30** **P 67** **L 3** # **121**
 Barrass, Hugh Cisco
Comment Type **T** *Comment Status* **D**
 The editor's note highlights a deficiency in the draft.
SuggestedRemedy
 Add MIB object definitions based on the text in Clause 78 & copying the style of 802.3at MIB definitions.
 Delete the editor's note
Proposed Response *Response Status* **W**
 PROPOSED ACCEPT.

Cl 35 **SC 35** **P 68** **L 1** # **125**
 Barrass, Hugh Cisco
Comment Type **E** *Comment Status* **D**
 It's not necessary to have this boilerplate text for every clause.
SuggestedRemedy
 Delete all the boilerplate text up to the Clause heading.
Proposed Response *Response Status* **W**
 PROPOSED ACCEPT.

Cl 35 **SC 35** **P 69** **L 4** # **123**
 Barrass, Hugh Cisco
Comment Type **E** *Comment Status* **D**
 Editor's note is no longer needed.
SuggestedRemedy
 Delete the editor's note box.
Proposed Response *Response Status* **W**
 PROPOSED ACCEPT.

Cl 35 SC 35.1.1 P 69 L 25 # 37
Booth, Brad AMCC

Comment Type E Comment Status D

Sentence is a bit confusing.

SuggestedRemedy

Change to read:

The GMII may also support low power idle signaling as defined for Energy Efficient Ethernet in Clause 78.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

The GMII may also support low power idle signaling as defined for Energy Efficient Ethernet in Clause 78 for some PHY types.

Cl 35 SC 35.2.2.4 P 70 L 912 # 44
Dietz, Bryan Alcatel-Lucent

Comment Type E Comment Status D

Editorial change: use of "and" to join two unlike clauses.

SuggestedRemedy

Replace paragraph:

"While TX_EN is de-asserted and TX_ER is asserted, TXD<7:0> are used to request the PHY to generate an assertion of low power idle; Carrier Extend or Carrier Extend Error code-groups. The use of TXD<7:0> during the transmission of a frame with carrier extension is described in 35.2.2.5 and low power idle transitions are described in 35.2.2.6a. Carrier extension shall only be signaled immediately following the data portion of a frame."

With:

"While TX_EN is de-asserted and TX_ER is asserted, TXD<7:0> are used to request the PHY to generate an assertion of low power idle, Carrier Extend or Carrier Extend Error code-groups. The use of TXD<7:0> during the transmission of a frame with carrier extension is described in 35.2.2.5. Carrier extension shall only be signaled immediately following the data portion of a frame. The use of TXD<7:0> to signal low power idle transitions is described in 35.2.2.6a."

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 35 SC 35.2.2.6a P 70 L 47 # 7
Marris, Arthur Cadence

Comment Type TR Comment Status D

It is not the MAC that controls LPI transitions it is the LPI client.

SuggestedRemedy

Change 'MAC device' to 'LPI client' and put in a cross-reference to Clause 78.

Also 35.2.2.9a on page 72.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Change "MAC device" to "LPI client"

p.70, l.47, l.51; p.71, l.1; p.72, l.45, l.48

At the beginning of 35.2.2.6a, insert:

"Low Power Idle operation and the LPI client are described in Clause 78.1."

Cl 35 SC 35.2.2.7 P 71 L 35 # 45
Dietz, Bryan Alcatel-Lucent

Comment Type E Comment Status D

Editorial change: use of "and" to join two unlike clauses.

SuggestedRemedy

Replace paragraph:

"While RX_DV is de-asserted, the PHY may provide a False Carrier indication or assert low power idle by asserting the RX_ER signal while driving the specific value listed in Table 35-2 onto RXD<7:0>. See 36.2.5.2.3 for a description of the conditions under which a PHY will provide a False Carrier indication and low power idle transitions are described in 35.2.2.9a."

"While RX_DV is de-asserted, the PHY may provide a False Carrier indication or assert low power idle by asserting the RX_ER signal while driving the specific value listed in Table 35-2 onto RXD<7:0>. See 36.2.5.2.3 for a description of the conditions under which a PHY will provide a False Carrier indication. Low power idle transitions are described in 35.2.2.9a."

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 35 **SC 35.5** **P 73** **L 48** # **124**
 Barrass, Hugh Cisco
Comment Type **E** *Comment Status* **D**
 Editor's note is no longer needed.
SuggestedRemedy
 Delete the editor's note
Proposed Response *Response Status* **W**
 PROPOSED ACCEPT.

Cl 36 **SC 36** **P 75** **L 1** # **132**
 Barrass, Hugh Cisco
Comment Type **E** *Comment Status* **D**
 It's not necessary to have this boilerplate text for every clause.
SuggestedRemedy
 Delete all the boilerplate text up to the Clause heading.
Proposed Response *Response Status* **W**
 PROPOSED ACCEPT.

Cl 36 **SC 36** **P 76** **L 4** # **130**
 Barrass, Hugh Cisco
Comment Type **E** *Comment Status* **D**
 Editor's note is no longer needed.
SuggestedRemedy
 Delete the editor's note box.
Proposed Response *Response Status* **W**
 PROPOSED ACCEPT.

Cl 36 **SC 36.2.5.1.3** **P 77** **L 16** # **128**
 Barrass, Hugh Cisco
Comment Type **T** *Comment Status* **D**
 (comment originally from Velu)
 Also, applies to receive state diagram (fig 36-9b)
 Reverse the effect of comment #166 from the previous draft :-)
 There is a requirement for a variable that has the same definition as rx_lpi_mode used to have.
SuggestedRemedy
 Restore the definition of rx_lpi_mode and the control of that variable in the receive state diagram.
 Change the variable name to rx_lpi_active; change the 2 states to TRUE (formerly ON) and FALSE(formerly OFF).
Proposed Response *Response Status* **W**
 PROPOSED ACCEPT.

Cl 36 **SC 36.2.5.2.2** **P 81** **L 5** # **129**
 Barrass, Hugh Cisco
Comment Type **T** *Comment Status* **D**
 (comment originally from Velu)
 fig 36-7a PCS receive state diagram
 The state machine needs to stay in state LPIDLE_MODE during LP idle.
SuggestedRemedy
 Change all 3 exit conditions from state LPI_K to include "(rx_lpi_active = FALSE)"
Proposed Response *Response Status* **W**
 PROPOSED ACCEPT.

Cl 36 **SC 36.2.5.2.6** **P 83** **L 47** # **3**
Marris, Arthur Cadence

Comment Type T **Comment Status D**
Missing underline on added paragraph

SuggestedRemedy
Underline the penultimate paragraph on page 83.

Proposed Response **Response Status W**
PROPOSED ACCEPT.

Cl 36 **SC 36.2.5.2.8** **P 86** **L 20** # **127**
Barrass, Hugh Cisco

Comment Type T **Comment Status D**
Effectively the same as comment #89 from the previous draft.

Is is really necessary to "de-bounce" signal_detect = FAIL?

The value of signal_detect is communicated from the PMA sublayer to indicate that the PMD detects the presence of a signal AND that the PMA is able to synchronize to that signal. This is unlikely to be tricked by the power-down transient of the link partner transmitter.

SuggestedRemedy
Remove RX_DEACT state and delete the definition of rx_deact_timer.

Proposed Response **Response Status W**
PROPOSED ACCEPT.

Cl 36 **SC 36.2.5.2.8** **P 86** **L 39** # **126**
Barrass, Hugh Cisco

Comment Type T **Comment Status D**
(comment originally from Velu)

Effectively the same as comment #128 from the previous draft. Fig 36-9b LPI receive state diagram.

Make the same changes as were accepted for Clause 49, wake time fault.

SuggestedRemedy
Add new state RX_WTF, counter wake_error_counter and timer rx_wf_timer - both as in Clause 49.

Exit conditions from the new state are the same as RX_WAKE.

Proposed Response **Response Status W**
PROPOSED ACCEPT.

Cl 36 **SC 36.2.5.2.9** **P 86** **L** # **99**
Pillai, Velu Broadcom

Comment Type TR **Comment Status D**
LPI status bits are added 3.1 register. 1000Base-X PCS does not have any definition in Cl45, 3.1 register. If new bits are added then standard has to defined the meaning of rest of the bits that register (Ex: fault)

SuggestedRemedy
Add the 1000Base-X PCS LPI status in different register.

Proposed Response **Response Status W**
PROPOSED REJECT.

Many of the bits in register 3.1 are already defined to be meaningful for certain PHYs and not others. None of the bits pose any special problems for 1000BASE-X PHYs.

Cl 36 **SC 36.7** **P 87** **L 48** # **131**
Barrass, Hugh Cisco

Comment Type E **Comment Status D**
Editor's note is no longer needed.

SuggestedRemedy
Delete the editor's note

Proposed Response **Response Status W**
PROPOSED ACCEPT.

Cl 36 SC Fig 36-7a P 81 L # 95
Pillai, Velu Broadcom

Comment Type TR Comment Status D

Without "rx_lpi_active" transition from LPI_K to IDLE_D can happen during transitioning in and out of quiet mode (transition from LPI_K to IDLE_D).
To avoid this AND detect_idle with rx_lpi_active. Please refer to page 9 of pillai_01_0409.

SuggestedRemedy

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

See #128, 129 for details.

Cl 36 SC Fig 36-9b P 86 L # 96
Pillai, Velu Broadcom

Comment Type TR Comment Status D

PCS LPI transmit state diagram need rx_lpi_active. Please refer to page 10 of pillai_01_0409.

SuggestedRemedy

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

See #128, 129 for details.

Cl 36 SC Figure 36-7a P 81 L 4 # 2
Marris, Arthur Cadence

Comment Type T Comment Status D

RXD<7:0> <= 0000 0001 should be add to LP_IDLE state actions.

SuggestedRemedy

as above

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 40 SC 40 P 89 L 1 # 133
Barrass, Hugh Cisco

Comment Type E Comment Status D

It's not necessary to have this boilerplate text for every clause.

SuggestedRemedy

Delete all the boilerplate text up to the Clause heading.

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 40 SC 40.1.3 P 90 L 4 # 25
Healey, Adam LSI Corporation

Comment Type T Comment Status D

Additional test modes should be defined to facilitate verification of a device's compliance to the specification.

SuggestedRemedy

Presentation to be submitted for Task Force review.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Pending review of the cited presentation.

Cl 40 SC 40.2.11 P 95 L 8 # 19
McIntosh, James Vitesse

Comment Type ER Comment Status D

There is a subclause numbering problem starting here. There are two subclause 40.2.11s. The first is on page 94, line (PMA_LPIMODE.indication) and the second is on page 95, line 8 (PMA_LPIREQ.request).

SuggestedRemedy

Renumber subclauses 40.2.xx starting here (page 95, line8):
40.2.12 PMA_LPIREQ.request

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 40 SC 40.5.1.1 P 111 L 25 # 20
 McIntosh, James Vitesse

Comment Type ER Comment Status D
 Register 3.22 in Table 40.3 is called "1000BASE-T wake error counter" here, but called "EEE wake error counter" in clause 45.

SuggestedRemedy
 Rename to "EEE wake error counter".

Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 40 SC 40.5.1.2 P 111 L 39 # 30
 Healey, Adam LSI Corporation

Comment Type T Comment Status D
 This text should be updated to describe the additional next page exchanges for Energy Efficient Ethernet.

SuggestedRemedy
 Update the text accordingly.

Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 40 SC 40.5.1.2 P 112 L 20 # 31
 Healey, Adam LSI Corporation

Comment Type T Comment Status D
 Table 40-4 is missing the EEE Technology Message page.

SuggestedRemedy
 Define Page 3 as a Message next page with the EEE technology message code. Page 4 would then be the Unformatted next page currently defined as Page 3.

Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 40 SC 40.5.1.2 P 112 L 27 # 24
 Healey, Adam LSI Corporation

Comment Type T Comment Status D
 Unformatted next page 4 serves no purpose and need not be sent.

SuggestedRemedy
 Delete Page 4 (Unformatted next page) from Table 40-4.

Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 40 SC 40.6.1.2.5 P 111 L 47 # 178
 Grimwood, Michael Broadcom

Comment Type T Comment Status D
 Clarify that MASTER clock jitter specifications be met in low-power mode.

SuggestedRemedy
 In section 40.6.1.2.5 change:

When in the normal mode of operation as the MASTER, the peak-to-peak value of the MASTER TX_TCLK jitter relative to an unjittered reference shall be less than 1.4 ns.

To:

When in the normal or low power modes of operation as the MASTER, the peak-to-peak value of the MASTER TX_TCLK jitter relative to an unjittered reference shall be less than 1.4 ns.

Proposed Response Response Status W
 PROPOSED REJECT.

"Low power mode of operation" is too broad since there is no reason to verify the requirement when the PHY is in the WAIT_QUIET, QUIET, WAKE, or WAKE_SILENT states since no signal or a known non-compliant signal is being transmitted.

The standard is already clear regarding when the transmitter must deliver a compliant signal. The definition of lpi_wakemz_timer (40.4.5.2) is:
 "This timer defines the time allowed for the PHY transmitter to achieve compliant operation following activation."
 This not only includes jitter, but signal levels, distortion, etc. and represents a superset of the proposed text.

For these reasons, no change appears to be required.

CI 40 SC 40.6.1.2.7 P 112 L 36 # 180
Grimwood, Michael Broadcom

Comment Type T Comment Status D

The transmitter wake signal specification has several elements that are either unclear or undefined. Why is there not a single threshold? (For example, If the wake signal is at 90% of nominal idle level 600 nsec after the beginning of Wake, this is outside of the two threshold values so does this mean that the signal is non-compliant?). Also, symbols ratio is not defined. Why is an additional 10% tolerance applied?

This comment suggest simplifying this specification to make it clear.

SuggestedRemedy

Change:

The wake signal shall be between 50 and 75% of the nominal idle levels with a symbols ratio within 10% of a nominal idle signal. These requirements shall be met within 700 ns following entry into the WAKE state.

To:

The wake signal shall be at least 75% of the analog signal levels corresponding to a nominal PAM3 {+2, 0, -2} idle signal. These requirements shall be met within 700 ns following entry into the WAKE state.

Proposed Response Response Status W
PROPOSED ACCEPT IN PRINCIPLE.

Refer to #29.

CI 40 SC 40.6.1.2.7 P 112 L 36 # 29
Healey, Adam LSI Corporation

Comment Type T Comment Status D

1. There is no need to define an upper bound on the signal level that is delivered after 700 ns. A PHY that delivers a full amplitude signal should still be compliant.

2. The concept of "symbols ratio" is not clearly defined in the draft, but for the purpose of the wake signal is seems that nothing more than the signal level needs to be defined.

SuggestedRemedy

Change:

"The wake signal shall be between 50 and 75% of the nominal idle levels with a symbols ratio within 10% of a nominal idle signal. These requirements shall be met within 700 ns following entry into the WAKE state."

To:

"The wake signal shall be no less than 50% of the nominal idle levels within 700 ns following entry into the WAKE state."

Proposed Response Response Status W
PROPOSED ACCEPT.

CI 45 SC 45 P 116 L 1 # 136
Barrass, Hugh Cisco

Comment Type E Comment Status D

It's not necessary to have this boilerplate text for every clause.

SuggestedRemedy

Delete all the boilerplate text up to the Clause heading.

Proposed Response Response Status W
PROPOSED ACCEPT.

CI 45 SC 45 P 117 L 3 # 134
Barrass, Hugh Cisco

Comment Type E Comment Status D

Editor's note is no longer needed.

SuggestedRemedy

Delete the editor's note box.

Proposed Response Response Status W
PROPOSED ACCEPT.

Cl 45 SC 45.2 P 120 L 11 # 226
GUPTA, SUJAY Infosys Technologies

Comment Type T Comment Status D

Instead of mentioning state transition is undefined, it can be made dependent on the latch register status.
Applies to the recv register as well.

SuggestedRemedy

The behavior if read is reliable only if the Transmit low power idle received(45.2.3.2.1a) latch register indicates the same state.

Proposed Response Response Status W

PROPOSED REJECT.

The proposed response does not work in all cases - for example when the PHY has come out of LPI and the indication bit reads 0 whereas the latched bit stays 1. Even if it did work, it doesn't give any more information than stating that the behavior is undefined if read during a state transition (unreliable = undefined).

Cl 45 SC 45.2 P 121 L 21 # 227
GUPTA, SUJAY Infosys Technologies

Comment Type T Comment Status D

Keep a room for mentioning the error counter size.(can be changed later)

SuggestedRemedy

This counter is of size 4bytes.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Change "This counter shall be reset..." to "This 16 bit counter shall be reset..."

Cl 45 SC 45.2.3.2 P 119 L 21 # 21
McIntosh, James Vitesse

Comment Type ER Comment Status D

LL is defined in Table 45-84 as Latching Low. LH is not defined here, but I assume that it stands for Latching High.

SuggestedRemedy

Add footnote to bottom of Table 45-84:
LH = Latching High

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 45 SC 45.2.3.9a P 120 L 46 # 179
Grimwood, Michael Broadcom

Comment Type T Comment Status D

Introduce capabilities and advertisement bits related to 10BASE-Te to allow management selection of the transmitter mode when devices support both 10BASE-T and 10BASE-Te.

SuggestedRemedy

Introduce 10BASE-Te capability bit to 3.20.0 and 10BASE-Te advertisement bits to 7.60.0 and 7.61.0.

A presentation will be submitted for the April/May EEE interim detailing the rationale and rules for resolving the mode.

Proposed Response Response Status W

PROPOSED REJECT.

10BASE-T and 10BASE-Te are in all respects compatible and interoperable on supported media. The media is not part of negotiation or management, therefore advertisement would be redundant.

Furthermore, the justification for 10BASE-Te was based largely on the physical constraints of producing low power devices on small geometry silicon (particularly related to multi-speed devices). If 10BASE-T is supported, there is no benefit to support 10BASE-Te in addition, therefore support of both should not be expected.

Cl 45 SC 45.2.3.9a.5 P 121 L 15 # 22
McIntosh, James Vitesse

Comment Type ER Comment Status D

We reference subclause 40.2.11 here and in subcluse 45.2.7.13a.5 (page 122, line 53) as the definition of support of EEE operation for 1000BASE-T. This does not seem correct. Would 40.1.3 be a better reference?

SuggestedRemedy

Change reference/link to 40.1.3 (or the appropriate reference).

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 45 SC 45.2.3.9a.6 P 121 L 19 # 23
McIntosh, James Vitesse

Comment Type ER Comment Status D

We reference subclause 25.4.11 here and in subcluse 45.2.7.13a.6 (page 123, line 3) as the definition of support of EEE operation for 100BASE-TX. This does not seem correct. Would 24.1.1 be a better reference?

SuggestedRemedy

Change reference/link to 24.1.1 (or the appropriate reference).

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 45 SC 45.2.3.9b P 121 L 25 # 18
McIntosh, James Vitesse

Comment Type E Comment Status D

I realized the acronym WTF clearly has the technical meaning of "Wake Time Fault" in this context, but there is another common use of this acronym among the internet community that is inappropriate.

SuggestedRemedy

Avoid use of acronym WTF, or replace with a different one.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Replace "WTF" with "fault"

Cl 45 SC 45.5 P 124 L 4 # 135
Barrass, Hugh Cisco

Comment Type E Comment Status D

Editor's note is no longer needed.

SuggestedRemedy

Delete the editor's note

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 46 SC 46 P 125 L 1 # 141
Barrass, Hugh Cisco

Comment Type E Comment Status D

It's not necessary to have this boilerplate text for every clause.

SuggestedRemedy

Delete all the boilerplate text up to the Clause heading.

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 46 SC 46 P 126 L 4 # 139
Barrass, Hugh Cisco

Comment Type E Comment Status D

Editor's note is no longer needed.

SuggestedRemedy

Delete the editor's note box.

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 46 SC 46.3 P 126 L 34 # 10
Marris, Arthur Cadence

Comment Type TR Comment Status D

The proposed use of a new type of idle for 10G has a big impact on existing implementations and seems unnecessary when sequence ordered sets could be used for link status signalling.

SuggestedRemedy

Please consider defining a new sequence ordered set to indicate LPI for 10Gbit Ethernet (see Table 46-5 in existing 802.3 standard). This would have less impact on existing implementations and could be transported by existing network infrastructure.

Proposed Response Response Status W

PROPOSED REJECT.

Current implementations will not support transitioning power states or interrupting the data stream to support sleep/wake cycles as required by the new standard, so compatibility with existing systems (while signaling LPI) is not an issue.

Cl 46 SC 46.3.1.5a P 127 L 44 # 8

Marris, Arthur

Cadence

Comment Type TR Comment Status D

It is not the MAC that controls LPI transitions it is the LPI client.

SuggestedRemedy

Change 'MAC device' to 'LPI client' and put in a cross-reference to Clause 78.

Also 46.3.2.4a on page 130.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Change "MAC device" to "LPI client"

p.127, l.44, l.48, l.51; p.130, l.6, l.8

Add at the beginning of 46.3.1.5a and 46.3.2.4a:

"Low Power Idle operation and the LPI client are described in Clause 78.1."

Cl 46 SC 46.3.1.5a P 128 L # 97

Pillai, Velu

Broadcom

Comment Type TR Comment Status D

- TXC needs to be high during IDLE
- This diagram should show TXC<3:0>, TXD<31:24>, TXD<23:16>, TXD<15:8>, TXD<7:0>.
- Page 127, line 51 is not correct. TXC<3:0> is 0XF during IDLE and LPI.

SuggestedRemedy

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

See #137

Cl 46 SC 46.3.1.5a P 128 L 12 # 137

Barrass, Hugh

Cisco

Comment Type T Comment Status D

(comment originally from Velu)

In fig 46-7a TXC should be shown HIGH during IDLE after wake.

Also, make it clear in the diagram and the text that TXC & TXD are the same for all 4 lanes.

SuggestedRemedy

As per comment.

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 46 SC 46.3.1.5a P 128 L 2 # 46

Dietz, Bryan

Alcatel-Lucent

Comment Type E Comment Status D

Typo

SuggestedRemedy

Delete one of the two periods.

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 46 SC 46.3.2.4a P 130 L # 98

Pillai, Velu

Broadcom

Comment Type TR Comment Status D

- RXC needs to be high during IDLE
- This diagram should show RXC<3:0>, RXD<31:24>, RXD<23:16>, RXD<15:8>, RXD<7:0>.
- Line 9 is not correct. RXC<3:0> is 0XF during IDLE and LPI

SuggestedRemedy

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

See #138

Cl 46 **SC 46.3.2.4a** **P 130** **L 23** # **138**
 Barrass, Hugh Cisco

Comment Type T **Comment Status D**
 (comment originally from Velu)

In fig 46-8a RXC should be shown HIGH during IDLE after wake.

Also, make it clear in the diagram and the text that RXC & RXD are the same for all 4 lanes.

SuggestedRemedy
 As per comment.

Proposed Response **Response Status W**
 PROPOSED ACCEPT.

Cl 46 **SC 46.5** **P 131** **L 4** # **140**
 Barrass, Hugh Cisco

Comment Type E **Comment Status D**
 Editor's note is no longer needed.

SuggestedRemedy
 Delete the editor's note

Proposed Response **Response Status W**
 PROPOSED ACCEPT.

Cl 46 **SC CI46.3.1.5a** **P 128** **L** # **100**
 Pillai, Velu Broadcom

Comment Type TR **Comment Status D**
 During Idle TXC<3:0> = 0xF, TXD<31:24>, TXD<23:16>, TXD<15:8>, TXD<7:0> are 0x07 each
 During LP Idle TXC<3:0> = 0xF, TXD<31:24>, TXD<23:16>, TXD<15:8>, TXD<7:0> are 0x06 each

SuggestedRemedy
 Show data and control for all four lanes

Proposed Response **Response Status W**
 PROPOSED ACCEPT IN PRINCIPLE.

Duplicate of #97

Cl 46 **SC CI46.3.2.4a** **P 130** **L** # **101**
 Pillai, Velu Broadcom

Comment Type TR **Comment Status D**
 During Idle RXC<3:0> = 0xF, RXD<31:24>, RXD<23:16>, RXD<15:8>, RXD<7:0> are 0x07 each
 During LP Idle RXC<3:0> = 0xF, RXD<31:24>, RXD<23:16>, RXD<15:8>, RXD<7:0> are 0x06 each

SuggestedRemedy
 Show data and control for all four lanes

Proposed Response **Response Status W**
 PROPOSED ACCEPT IN PRINCIPLE.

Duplicate of #98

Cl 46 **SC Figure 46-7a** **P 128** **L 11** # **9**
 Marris, Arthur Cadence

Comment Type TR **Comment Status D**
 TXC should show high for regular idle and FB start of frame.

SuggestedRemedy
 Have TXC high for everything except the three Xs indicating frame data at the right hand side of the figure.

Also do the same for RXC in Figure 46-8a

Proposed Response **Response Status W**
 PROPOSED ACCEPT.

See #137, 138

Cl 46 **SC Table 46-3** **P 127** **L 14** # **4**
Marris, Arthur Cadence

Comment Type **T** **Comment Status** **D**

Delete '(in all lanes)'. This does not seem to make sense.

SuggestedRemedy

As above

Proposed Response **Response Status** **W**

PROPOSED ACCEPT IN PRINCIPLE.

The "in all lanes" indicates that LPI must be asserted in all lanes simultaneously.

Change "(in all lanes)" to "(asserted in all lanes simulataneously)" - in Table 46-3 and Table 46-4.

Cl 48 **SC 2.3** **P 133** **L 4** # **250**
Chadha, Mandeep Vitesse Semiconducto

Comment Type **T** **Comment Status** **D**

In figure 48-3a, LI is only indicated in Lane 1 and is as such inconsistent with clause 46.3.1.5a and table 46-3 which indicate LI in all the lanes.

SuggestedRemedy

Modify figure 48-3a to indicate LI in all the lanes.

Proposed Response **Response Status** **W**

PROPOSED ACCEPT.

Cl 48 **SC 48** **P 131** **L 30** # **146**
Barrass, Hugh Cisco

Comment Type **E** **Comment Status** **D**

Editor's note is no longer needed.

SuggestedRemedy

Delete the editor's note box.

Proposed Response **Response Status** **W**

PROPOSED ACCEPT.

Cl 48 **SC 48** **P 132** **L 1** # **148**
Barrass, Hugh Cisco

Comment Type **E** **Comment Status** **D**

It's not necessary to have this boilerplate text for every clause.

SuggestedRemedy

Delete all the boilerplate text up to the Clause heading.

Proposed Response **Response Status** **W**

PROPOSED ACCEPT.

Cl 48 **SC 48.2.3** **P 132** **L 45** # **209**
Parnaby, Gavin Solarflare Communica

Comment Type **E** **Comment Status** **D**

'The ability to transmit or receive Low Power Idle is an option for certain PHYs to support Energy Efficient Ethernet' isn't very clear. The ability to transmit or receive LPI is a requirement for PHYs that support EEE.

SuggestedRemedy

Change text to something like

'Certain PHYs may support Energy Efficient Ethernet. PHYs that support Energy Efficient Ethernet are able to transmit and receive Low Power Idle characters.'

Proposed Response **Response Status** **W**

PROPOSED ACCEPT.

CI 48 SC 48.2.6.1.3 P 135 L 26 # 143
Barrass, Hugh Cisco

Comment Type T Comment Status D
(comment originally from Velu)

Also, applies to receive state diagram (fig 48-9b)

Reverse the effect of comment #167 from the previous draft :-)

There is a requirement for a variable that has the same definition as rx_lpi_mode used to have.

SuggestedRemedy

Restore the definition of rx_lpi_mode and the control of that variable in the receive state diagram.

Change the variable name to rx_lpi_active; change the 2 states to TRUE (formerly ON) and FALSE(formerly OFF).

Proposed Response Response Status W
PROPOSED ACCEPT.

CI 48 SC 48.2.6.1.3 P 135 L 38 # 208
Parnaby, Gavin Solarflare Communica

Comment Type E Comment Status D
delete is in 'is set to FALSE'

SuggestedRemedy

Proposed Response Response Status W
PROPOSED REJECT.

The sentence would make no sense as suggested.

CI 48 SC 48.2.6.2 P 138 L 21 # 142
Barrass, Hugh Cisco

Comment Type T Comment Status D
(comment originally from Velu)

fig 48-9 PCS receive state diagram

The state machine needs to stay in state LPIDLE_MODE during LP idle.

SuggestedRemedy

Change exit condition from state LPIDLE_MODE to (rx_lpi_active = FALSE) * AUDI

Also, delete state RECEIVE_LPI and take exit path from LPIDLE_MODE directly to RECEIVE.

Proposed Response Response Status W
PROPOSED ACCEPT.

CI 48 SC 48.2.6.2.5 P 141 L 19 # 144
Barrass, Hugh Cisco

Comment Type T Comment Status D
Effectively the same as comment #89 from the previous draft.

Is is really necessary to "de-bounce" signal_detect = FAIL?

The value of signal_detect is communicated from the PMA sublayer to indicate that the PMD detects the presence of a signal AND that the PMA is able to synchronize to that signal. This is unlikely to be tricked by the power-down transient of the link partner transmitter.

SuggestedRemedy

Remove RX_DEACT state and delete the definition of rx_deact_timer.

Proposed Response Response Status W
PROPOSED ACCEPT.

Cl 48 SC 48.2.6.2.5 P 141 L 40 # 145
Barrass, Hugh Cisco

Comment Type T Comment Status D

(comment originally from Velu)

Effectively the same as comment #128 from the previous draft. Fig 48-9b LPI receive state diagram.

Make the same changes as were accepted for Clause 49, wake time fault.

SuggestedRemedy

Add new state RX_WTF, counter wake_error_counter and timer rx_wf_timer - both as in Clause 49.

Exit conditions from the new state are the same as RX_WAKE.

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 48 SC 48.7 P 143 L 5 # 147
Barrass, Hugh Cisco

Comment Type E Comment Status D

Editor's note is no longer needed.

SuggestedRemedy

Delete the editor's note

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 48 SC Fig 48-9 P 138 L # 93
Pillai, Velu Broadcom

Comment Type TR Comment Status D

PCS_receive state diagram shown in Fig 48-9 needs changes to avoid asserting non LI during transitioning in and out of quiet mode. Using rx_lpi_active as shown in page 7 of pillai_01_0409 will help to avoid the wrong assertion. RECEIVE_LPI is not needed either.

SuggestedRemedy

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

See #142

Cl 48 SC Fig 48-9b P 141 L # 94
Pillai, Velu Broadcom

Comment Type TR Comment Status D

RX_ACTIVE and RX_SLEEP needs rx_lpi_active. LPI_fail_timer is not needed in RX_LINK_FAIL state. Please refer to page 8 of pillai_01_0409.

SuggestedRemedy

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

See #143, 145

Cl 48 SC Fig48-3a P 133 L # 79
Pillai, Velu Broadcom

Comment Type TR Comment Status D

LI should be asserted on all four lanes

SuggestedRemedy

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 48 SC Figure 48-3a P 133 L 4 # 5
Marris, Arthur Cadence

Comment Type T Comment Status D

Should it not be LI in all lanes? Not just in lane 0?

SuggestedRemedy

As above

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Yes it should, show LI in all lanes.

Cl 49 SC 49 P 144 L 1 # 156
 Barrass, Hugh Cisco
 Comment Type E Comment Status D
 It's not necessary to have this boilerplate text for every clause.
 SuggestedRemedy
 Delete all the boilerplate text up to the Clause heading.
 Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 49 SC 49.2.13.2.2 P 150 L 2 # 153
 Barrass, Hugh Cisco
 Comment Type T Comment Status D
 (comment originally from Velu)
 Also, applies to receive state diagram (fig 49-15)
 Reverse the effect of comment #81 from the previous draft :-)
 There is a requirement for a variable that has the same definition as rx_lpi_mode used to have.
 SuggestedRemedy
 Restore the definition of rx_lpi_mode and the control of that variable in the receive state diagram.
 Change the variable name to rx_lpi_active; change the 2 states to TRUE (formerly ON) and FALSE(formerly OFF).
 Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 49 SC 49.2.13.3 P 153 L 20 # 152
 Barrass, Hugh Cisco
 Comment Type T Comment Status D
 (probably an artifact of FrameMaker)
 receive state diagram (fig 49-15)
 Exit condition from state RX_C (towards flag "E") is missing its end.
 SuggestedRemedy
 Change exit condition to "R_TYPE(rx_coded) = LI"
 Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 49 SC 49.2.13.3 P 153 L 5 # 150
 Barrass, Hugh Cisco
 Comment Type T Comment Status D
 (comment originally from Velu)
 receive state diagram (fig 49-15)
 State machine needs to stay in state RX_LI while rx_lpi_active is true.
 SuggestedRemedy
 For the 2 exit conditions, change "signal_ok" to "rx_lpi_active = FALSE."
 Delete the loop around transition (it is redundant anyway).
 Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 49 SC 49.2.13.3 P 153 L 5 # 149
 Barrass, Hugh Cisco
 Comment Type T Comment Status D
 (comment originally from Velu)
 receive state diagram (fig 49-15)
 In state RX_LI, rx_raw should be fixed to LI so that garbage is suppressed during wake-up.
 SuggestedRemedy
 Change "DECODE(rx_coded)" to "/LI/"
 Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 49 SC 49.2.13.3 P 153 L 7 # 151
Barrass, Hugh Cisco

Comment Type T Comment Status D
(comment originally from Velu)

receive state diagram (fig 49-15)

If an /L/I/ code is received during a non-IPG state then an error must be flagged.

SuggestedRemedy

Change exit condition from RX_INIT state from "R_TYPE(rx_coded) = (E + D + T)" to "R_TYPE(rx_coded) = (E + D + T + LI)"

Change exit condition from RX_D state from "R_TYPE(rx_coded) = (E + C + S)" to "R_TYPE(rx_coded) = (E + C + S + LI)"

Proposed Response Response Status W
PROPOSED ACCEPT.

Cl 49 SC 49.2.4.4 P 145 L 54 # 47
Dietz, Bryan Alcatel-Lucent

Comment Type E Comment Status D
Typo

SuggestedRemedy

Replace trailing right parenthesis with period.

Proposed Response Response Status W
PROPOSED ACCEPT.

Cl 49 SC 49.2.9 P 147 L 24 # 154
Barrass, Hugh Cisco

Comment Type T Comment Status D
(comment originally from Velu)

The BER state machine (Fig 49-13) needs to be changed so that high BER is not reported during the shutdown & restart phases. BER should only be monitored when the PCS is locked.

SuggestedRemedy

Change fig 49-13.

Change "!block_lock" to "!rx_block_lock"

Proposed Response Response Status W
PROPOSED ACCEPT.

Cl 49 SC 49.3 P 158 L 4 # 155
Barrass, Hugh Cisco

Comment Type E Comment Status D
Editor's note is no longer needed.

SuggestedRemedy

Delete the editor's note

Proposed Response Response Status W
PROPOSED ACCEPT.

Cl 49 SC 49-16 P 154 L # 90
Pillai, Velu Broadcom

Comment Type TR Comment Status D

TX_REFRESH is still shown in this state diagram. This will not handle the PHY when FEC is enabled. In March pillai_01_0309 proposed changes to KR phy when FEC is enabled. In order to handle that proposal this statemachine needs the changes as shown in page 4 of pillai_01_0409.

SuggestedRemedy

Proposed Response Response Status W
PROPOSED ACCEPT IN PRINCIPLE.

It appears that the only functional difference between the state machine shown on page 4 of pillai_01_0409 is that PHYs with scrambler_reset_enable = TRUE will bypass the scrambler during refresh as well as wake.

There does not appear to be any benefit to this and this will increase the refresh time by 2 microseconds.

There is a need to modify the LPI receive state diagram. Add a transition out of RX_WAKE, conditional on !signal_ok to label "B"

CI 49 SC Fig 49-13 P L # 92
Pillai, Velu Broadcom

Comment Type TR Comment Status D

CI49 BER monitor state diagram (Fig 49-13): When in EEE mode, block_lock is latched in CI49 Rx lpi fsm. During transitions in and out of Quiet mode, PCS gets some garbage data which will trigger hi_ber. When hi_ber is set, 10G-R link is dropped. To avoid this freeze the BER fsm during low power mode. The proposal is shown in page 6 of pillai_01_0409.

SuggestedRemedy

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

See #154

CI 49 SC Fig 49-15 P 153 L # 89
Pillai, Velu Broadcom

Comment Type TR Comment Status D

The arc that loops back for RX_LI is qualified by "!signal_ok + R_TYPE(rx_coded) = LI". When the transmitter starts the refresh or wake sequence the signal_ok becomes valid, but R_TYPE may not be LI. Which means the state machine will arc towards RX_E. This will assert an error in the RS layer.

SuggestedRemedy

It should be ""rx_lpi_active" to be consistent with 10GBASE-T state diagram. This state diagram should keep asserting /LI/ towards the RS layer, until the RX LPI State diagram comes out of LPI mode. Please refer to pillai_01_0409

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

See #149, 150

CI 49 SC Fig 49-15 P 153 L # 80
Pillai, Velu Broadcom

Comment Type TR Comment Status D

Transition to RX_INIT should be reset+ r_test_mode + hi_ber + !rx_block_lock

SuggestedRemedy

Proposed Response Response Status W

PROPOSED ACCEPT.

CI 49 SC Fig 49-15 P 153 L # 87
Pillai, Velu Broadcom

Comment Type TR Comment Status D

This state machine does not handle LI code words appearing during normal mode. pillai_01_0409 page 3 shows the necessary changes.

SuggestedRemedy

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

See #151

CI 49 SC Fig 49-15 P 153 L # 88
Pillai, Velu Broadcom

Comment Type TR Comment Status D

State RX_LI has rx_raw . DECODE(rx_coded)

SuggestedRemedy

It should be rx_raw <= LI

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

See #149

CI 49 SC Fig 49-17 P 155 L # 91
Pillai, Velu Broadcom

Comment Type TR Comment Status D

This state diagram needs changes to handle the proposal on pillai_01_0309. rx_lpi_active is needed to handle the PCS receive state diagram arc. R_TYPE(rx_coded)=LI should be R_TYPE(rx_coded) /=LI for the transition from RX_WAKE and RX_WTF. Also some of the transitions need changes as shown in page 5 of pillai_01_0409.

SuggestedRemedy

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

See #153

Cl 49 SC Fig 49-17 P 155 L # 83
Pillai, Velu Broadcom

Comment Type TR Comment Status D

RX_DEACT state is missing. Please refer to the state diagram shown in page 5 of pillai_01_0409

SuggestedRemedy

Proposed Response Response Status W

PROPOSED REJECT.

Comment #89 in the previous draft argued (successfully) that this state is not required.

Cl 51 SC 51 P 159 L 1 # 158
Barrass, Hugh Cisco

Comment Type E Comment Status D

It's not necessary to have this boilerplate text for every clause.

SuggestedRemedy

Delete all the boilerplate text up to the Clause heading.

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 51 SC 51 P 159 L 26 # 39
Booth, Brad AMCC

Comment Type T Comment Status D

The PMA service interface also has a physical instantiation known as XSBI. There are no changes to XSBI to permit the exchange of the energy_detect variable across the physical interface.

SuggestedRemedy

Provide a means to pass the energy_detect information across XSBI.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Edit 51.4.1

Add energy_detect, rx_quiet, tx_quiet into Fig 51-3

Add definitions in 51.4.2

energy_detect: If the optional Energy Efficient Ethernet function is supported (see Clause 78) then the XSBI interface includes energy_detect as described in 51.8a.

rx_quiet: If the optional Energy Efficient Ethernet function is supported (see Clause 78) then the XSBI interface may rx_quiet as described in 51.8a.

tx_quiet: If the optional Energy Efficient Ethernet function is supported (see Clause 78) then the XSBI interface may tx_quiet as described in 51.8a.

Cl 51 SC 51.10 P 160 L 4 # 157
Barrass, Hugh Cisco

Comment Type E Comment Status D

Editor's note is no longer needed.

SuggestedRemedy

Delete the editor's note

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 51 SC 51.8a.1 P 159 L 41 # 38
Booth, Brad AMCC

Comment Type T Comment Status D

The PMA sublayer mentions a PMD signal called energy_detect, but there is no energy_detect in any of the supporting PMD sublayers.

The PCS also references this signal.

Could this signal be an extra state of the signal_detect from the PMD? The SIGNAL_OK could be expanded to be OK, FAIL and ENERGY_DETECTED.

SuggestedRemedy

Either add energy_detect to the PMD sublayers or add a new state for the signal_detect variable from the PMD.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Change definition for signal_detect in Clause 72 to fulfill energy_detect function (similarly to other PMDs).

"For Energy Efficient Ethernet, the SIGNAL_DETECT parameter shall be set to OK within 2µs after activation of a compliant transmitter and shall be set to FAIL within 2µs after deactivation of a compliant transmitter."

Change to:

"For Energy Efficient Ethernet, the SIGNAL_DETECT parameter can take on one of two values: OK or FAIL, indicating whether the PMD is detecting electrical energy at the receiver (OK) or not (FAIL). When SIGNAL_DETECT = FAIL, PMD_UNITDATA.indication(rx_bit) is undefined."

Also, change the definition of energy_detect in 51.8a.1:

"A boolean variable sent from the PMD that is set to TRUE when signal energy is detected at the receiver and is set to FALSE otherwise. This variable is derived directly from the PMD signal_detect parameter. When PMD signal_detect is OK, energy_detect is TRUE; when PMD signal_detect is FAIL, energy_detect is FALSE."

Cl 55 SC 55 P 161 L 1 # 160
Barrass, Hugh Cisco

Comment Type E Comment Status D

It's not necessary to have this boilerplate text for every clause.

SuggestedRemedy

Delete all the boilerplate text up to the Clause heading.

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 55 SC 55.3.2.2.21 P 170 L 21 # 210
Parnaby, Gavin Solarflare Communica

Comment Type E Comment Status D

PHY should be PHYs

SuggestedRemedy

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Replace PHY with PHYs.

Cl 55 SC 55.3.2.3 P 171 L 2 # 181
Grimwood, Michael Broadcom

Comment Type T Comment Status D

Clarify that the LDPC syndrome and CRC8 errors are not monitored during LPI. This clarification is needed for consistency with Figure 55-16 since otherwise undesired transitions to RX_INIT could occur during LPI.

SuggestedRemedy

In 802.3an-2006, page 92, add the following sentence after the fourth paragraph (ending with ".on the XGMII."):

"LDPC frame errors are not monitored during low-power operation."

Proposed Response Response Status W

PROPOSED ACCEPT.

We will need to make a change to the state diagram for this change.

I propose changing the transition from LFER_TEST_LF to LFER_BAD_LF from !lf_valid to !lf_valid * !rx_lpi_active

Cl 55 SC 55.3.4a.1 P 172 L 31 # 159
Barrass, Hugh Cisco

Comment Type E Comment Status D
Editor's note says convert to a active reference.

SuggestedRemedy

do it, then delete the editor's note.

Proposed Response Response Status W
PROPOSED ACCEPT IN PRINCIPLE.

The reference cannot be converted to an active reference in this draft because the referred to subclause is not in the draft.

The editor will delete this note.

Cl 55 SC 55.3.5.4 P 178 L 6 # 182
Grimwood, Michael Broadcom

Comment Type T Comment Status D
Clarify that LFER Monitor function is not performed during LPI. This clarification is needed for consistency with Figure 55-16 since otherwise undesired transitions to RX_INIT could occur during LPI.

SuggestedRemedy

In 802.3an-2006, page 98, in section 55.3.5.4 change the last paragraph from:

"The PCS shall perform the functions of LFER Monitor, Transmit, and Receive as specified in these state machines."

To:

"The PCS shall perform the functions of LFER Monitor, Transmit, and Receive as specified in these state machines. The PCS shall not perform the LFER Monitor function during low-power operation from the time that the PCS 64B/65B Receiver detects a sleep block until the state RX_W is exited."

Proposed Response Response Status W
PROPOSED ACCEPT IN PRINCIPLE.

See also comment 181

Cl 55 SC 55.4.2.2 P 185 L 13 # 211
Parnaby, Gavin Solarflare Communica

Comment Type E Comment Status D
Change 'is able to generate the alert signal ' to 'generates the alert alert signal as'

SuggestedRemedy

Proposed Response Response Status W
PROPOSED ACCEPT.

Cl 55 SC 55.4.2.2 P 185 L 4 # 183
Grimwood, Michael Broadcom

Comment Type T Comment Status D
Specify that the PMA transmit function continuously sources TX_TCLK to explicitly require that jitter and clock drift specifications be met during low-power operation.

SuggestedRemedy

In section 55.4.2.2 1st sentence, 2nd paragraph change:

When the PMA_CONFIG.indication parameter config is MASTER, the PMA Transmit function shall source TX_TCLK from a local clock source while meeting the transmit jitter requirements of 55.5.3.3.

To:

When the PMA_CONFIG.indication parameter config is MASTER, for both normal and lower-power operation, the PMA Transmit function shall continuously source TX_TCLK from a local clock source while meeting the transmit jitter requirements of 55.5.3.3.

Proposed Response Response Status W
PROPOSED ACCEPT.

Cl 69 SC 69 P 198 L 1 # 161
Barrass, Hugh Cisco

Comment Type E Comment Status D
It's not necessary to have this boilerplate text for every clause.

SuggestedRemedy

Delete all the boilerplate text up to the Clause heading.

Proposed Response Response Status W
PROPOSED ACCEPT.

Cl 70 **SC 70** **P 200** **L 1** # **162**
 Barrass, Hugh Cisco

Comment Type **E** **Comment Status** **D**

It's not necessary to have this boilerplate text for every clause.

SuggestedRemedy
 Delete all the boilerplate text up to the Clause heading.

Proposed Response **Response Status** **W**
 PROPOSED ACCEPT.

Cl 71 **SC 71** **P 208** **L 1** # **163**
 Barrass, Hugh Cisco

Comment Type **E** **Comment Status** **D**

It's not necessary to have this boilerplate text for every clause.

SuggestedRemedy
 Delete all the boilerplate text up to the Clause heading.

Proposed Response **Response Status** **W**
 PROPOSED ACCEPT.

Cl 71 **SC 71.1** **P 208** **L 45** # **48**
 Dietz, Bryan Alcatel-Lucent

Comment Type **E** **Comment Status** **D**

Consistent terminology

SuggestedRemedy
 Change "inter-frame" to "inter-frame idle"

Proposed Response **Response Status** **W**
 PROPOSED ACCEPT.

Cl 71 **SC 71.6.12** **P 210** **L 29** # **49**
 Dietz, Bryan Alcatel-Lucent

Comment Type **E** **Comment Status** **D**

Change /LPI/ to /LI/ to be consistent with rest of document. Also make the same change in page 220, line 18.

SuggestedRemedy
 Change /LPI/ to /LI/ to be consistent with rest of document. Also make the same change in page 220, line 18.

Proposed Response **Response Status** **W**
 PROPOSED ACCEPT.

Cl 72 **SC** **P** **L** # **77**
 Bennett, Michael LBNL

Comment Type **TR** **Comment Status** **D**

Subclause references and value/comment fields are incomplete on lines 43 and 45 and Subclause references on lines 48, 50 and line 3 on page 228 are incomplete. Subclauses refer to 72.6.11.x

For example on p 227, the feature is "LPI Transmit state diagram" and the subclause is 72.6.11.x, the value/comment is Meets requirement of Figure72-x, but the LPI Transmit state diagram is shown in figure 49-16 on page 154

SuggestedRemedy
 Change references to point to the relevant PCS clauses.

Proposed Response **Response Status** **W**
 PROPOSED ACCEPT IN PRINCIPLE.
 Will remove deleted requirements and fix references.

Cl 72 **SC 72** **P 217** **L 1** # **164**
 Barrass, Hugh Cisco

Comment Type **E** **Comment Status** **D**

It's not necessary to have this boilerplate text for every clause.

SuggestedRemedy
 Delete all the boilerplate text up to the Clause heading.

Proposed Response **Response Status** **W**
 PROPOSED ACCEPT.

Cl 72 **SC 72.1** **P 218** **L 18** # **50**
 Dietz, Bryan Alcatel-Lucent

Comment Type **E** **Comment Status** **D**
 Change "inter-frame" to "inter-frame idle" to be consistent with the rest of the document.

SuggestedRemedy
 Change "inter-frame" to "inter-frame idle" to be consistent with the rest of the document.

Proposed Response **Response Status** **W**
 PROPOSED ACCEPT.

Cl 72 **SC 72.6.11** **P 220** **L 14** # **78**
 Bennett, Michael LBNL

Comment Type **TR** **Comment Status** **D**
 On line 14:

 Energy Efficient Ethernet capabilities and parameters will be advertised during the Backplane Auto-negotiation, as described in Clause 45

 Should be clause 73

SuggestedRemedy
 change to refer to clause 73

Proposed Response **Response Status** **W**
 PROPOSED ACCEPT.

Cl 72 **SC 72.8** **P 224** **L 5** # **74**
 Bennett, Michael LBNL

Comment Type **ER** **Comment Status** **D**
 It appears that the subclause reference in the editor's change instructions are off by 1 on lines 5, 40 and 44.

SuggestedRemedy
 on line 5, change 72.7.3 to 72.8.3
 on line 40, change 72.7.3 to 72.8.3
 on line 44, change 72.7.3 to 72.8.3

Proposed Response **Response Status** **W**
 PROPOSED ACCEPT.

Need add some major headers and fix a couple of mis-number ones.

Cl 72 **SC 72.8** **P 225** **L 28** # **76**
 Bennett, Michael LBNL

Comment Type **ER** **Comment Status** **D**
 line 28 has:

 FS12 Low Power Idle function 72.6.11 Enters LowPower_st when requested
 LPI:M Yes [] N/A

 there are no brackets after the N/A

SuggestedRemedy
 add brackets after N/A

Proposed Response **Response Status** **W**
 PROPOSED ACCEPT.

Cl 72 **SC 72.8.3** **P 224** **L 23** # **75**
 Bennett, Michael LBNL

Comment Type **ER** **Comment Status** **D**
 Table 72.8.3 states that FEC is optional, however the support choice is "Yes"
 There should be a choice of "No"

This existed before we opened the clause, so I want to discuss whether or not we fix it or submit a maintenance request, but this is low priority

SuggestedRemedy
 If we are going to fix it, add a "No[]" choice

Proposed Response **Response Status** **W**
 PROPOSED ACCEPT IN PRINCIPLE.
 I'll add the "No []" choice.

Cl 72 **SC Table 72.9** **P 223** **L** # **82**
 Pillai, Velu Broadcom

Comment Type **TR** **Comment Status** **D**
 Subclause reference is wrong for Tsd and Tsa

SuggestedRemedy
 Correct subclause is 72.6.4

Proposed Response **Response Status** **W**
 PROPOSED ACCEPT.

Cl 72 **SC Table 72-6** **P 222** **L** # **81**
 Pillai, Velu Broadcom

Comment Type **TR** **Comment Status** **D**
 Subclause reference is wrong for Vtw, Vtd, and Vta

SuggestedRemedy
 Correct subclause reference is 72.6.5

Proposed Response **Response Status** **W**
 PROPOSED ACCEPT.

Cl 73 **SC 78.1.1** **P 237** **L 30** # **217**
 Parnaby, Gavin Solarflare Communica

Comment Type **E** **Comment Status** **D**
 EEE also specifies means

SuggestedRemedy
 should be

EEE also specifies a means

Proposed Response **Response Status** **W**
 PROPOSED ACCEPT.

Cl 73 **SC Annex73** **P 258** **L** # **193**
 Pillai, Velu Broadcom

Comment Type **TR** **Comment Status** **D**
 Annex 73A says EEE technology messages will follow the transmission of this page with at least two unformatted next pages that contain information defined in 45.2.7.13a which amounts to 144 bits sent when there are only 6 bits of information defined.

The 6 bits of information can be transferred as part of the message page and thus only require 48 bits of transmission

SuggestedRemedy
 Either Add table like in Annex 28C for clarity or put more text to explain the MP10 bit information. pillai_01_0409 that will be posted during the May interim will also address the remedy.

Proposed Response **Response Status** **W**
 PROPOSED ACCEPT IN PRINCIPLE.

Only 1 unformatted next page is required - change text to read "at least one unformatted next page"

Table 73A-1 is identical in form and function to Table 28C-1.

73.7.7.1 defines the unformatted next page format.

Cl 73A **SC 73A** **P 258** **L 8** # **165**
 Barrass, Hugh Cisco

Comment Type **E** **Comment Status** **D**
 Editor's note is no longer needed.

SuggestedRemedy
 Delete the editor's note box.

Proposed Response **Response Status** **W**
 PROPOSED ACCEPT.

Cl 74 SC P L # 85
Pillai, Velu Broadcom

Comment Type TR Comment Status D
FEC Counters may show false errors during transitions in and out of Quiet mode.

SuggestedRemedy

Proposed Response Response Status W
PROPOSED ACCEPT.

Add text to bypass FEC counter during LPI mode

Cl 74 SC P L # 84
Pillai, Velu Broadcom

Comment Type TR Comment Status D
What is the effect of link being on low power state on the FEC Lock state diagram is not clear from the current clause 74 in the IEEE802.3az specification ? It is not clear if the fec_block_lock must go to false when the transmission on the link has stopped i.e. when link is in low power state.

SuggestedRemedy

The state diagram (figure 74-8 of the IEEE 802.3 spec) could be updated to clarify the effect of energy_detect = false.

Proposed Response Response Status W
PROPOSED ACCEPT.

Cl 74 SC 74 P 229 L 1 # 166
Barrass, Hugh Cisco

Comment Type E Comment Status D
It's not necessary to have this boilerplate text for every clause.

SuggestedRemedy

Delete all the boilerplate text up to the Clause heading.

Proposed Response Response Status W
PROPOSED ACCEPT IN PRINCIPLE.

Cl 74 SC 74.7.4.7 P 231 L 4 # 51
Dietz, Bryan Alcatel-Lucent

Comment Type E Comment Status D
Typo

SuggestedRemedy

Remove period before "FEC"

Proposed Response Response Status W
PROPOSED ACCEPT.

Cl 74 SC Annex 74A P L # 86
Pillai, Velu Broadcom

Comment Type TR Comment Status D
Table B1 and Table C1 sequences has errors. Need corrections.

SuggestedRemedy

Proposed Response Response Status W
PROPOSED ACCEPT IN PRINCIPLE.

Cl 78 SC 78 P 237 L 3 # 167
Barrass, Hugh Cisco

Comment Type E Comment Status D
Editor's note is no longer needed.

SuggestedRemedy

Delete the editor's note box.

Proposed Response Response Status W
PROPOSED ACCEPT.

Cl 78 SC 78.1.1 P 237 L 24 # 218
Parnaby, Gavin Solarflare Communica

Comment Type E Comment Status D
...EEE defines 10 Mb/s PHY ...

SuggestedRemedy

should be EEE defines a 10 Mb/s PHY ...

Proposed Response Response Status W
PROPOSED ACCEPT.

Cl 78 SC 78.1.1 P 237 L 27 # 70
 Dietz, Bryan Alcatel-Lucent
 Comment Type E Comment Status D
 Editorial suggestion
 SuggestedRemedy
 Change "Definition of 10BASE-Te allows power consumption saving." to "The definition of 10Base-Te allows reduced power consumption."
 Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 78 SC 78.1.2 P 237 L 33 # 212
 Parnaby, Gavin Solarflare Communica
 Comment Type T Comment Status D
 Why are objectives included?
 SuggestedRemedy
 Delete objectives
 Proposed Response Response Status W
 PROPOSED REJECT.
 Editor does not understand commenter's concern and motivation to remove objectives from the 78.1.2

Cl 78 SC 78.1.3.1 P 238 L 26 # 185
 Grimwood, Michael Broadcom
 Comment Type E Comment Status D
 Make diagram label match acronym "PLS".
 SuggestedRemedy
 In diagram, change "Physical Signaling" to "Physical Layer Signaling".
 Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 78 SC 78.1.3.2 P 238 L 51 # 223
 Parnaby, Gavin Solarflare Communica
 Comment Type E Comment Status D
 decided should be decide
 SuggestedRemedy
 change to decide
 Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 78 SC 78.1.4 P 238 L 3 # 220
 Parnaby, Gavin Solarflare Communica
 Comment Type E Comment Status D
 font is incorrect
 SuggestedRemedy
 use the same font as elsewhere
 Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 78 SC 78.1.4 P 239 L 3 # 71
 Dietz, Bryan Alcatel-Lucent
 Comment Type E Comment Status D
 Parts of this clause use smaller than normal typeface.
 SuggestedRemedy
 Update type faces to match.
 Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 78 SC 78.1.4 P 239 L 4 # 184
 Grimwood, Michael Broadcom
 Comment Type E Comment Status D
 Smaller font was used for the following:
 "These services are described in."
 SuggestedRemedy
 Make font size consistent.
 Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 78 SC 78.1.4 P 239 L 5 # 72
 Dietz, Bryan Alcatel-Lucent
 Comment Type E Comment Status D
 Word "primatives" is misspelled
 SuggestedRemedy
 Change to "primitives"
 Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 78 SC 78.1.4 P 239 L 6 # 219
 Parnaby, Gavin Solarflare Communica
 Comment Type E Comment Status D
 prmiavtes
 SuggestedRemedy
 primitives
 Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 78 SC 78.1.4 P 239 L 6 # 186
 Grimwood, Michael Broadcom
 Comment Type E Comment Status D
 Typo.
 SuggestedRemedy
 "prmiavtes" should be "primitives"
 Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 78 SC 78.1.4.1.2 P 239 L 26 # 187
 Grimwood, Michael Broadcom
 Comment Type E Comment Status D
 Consistent spelling of signaling vs. signalling
 SuggestedRemedy
 In Clause 78, change all four occurrences of "signalling" to "signaling".
 Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 78 SC 78.1.4.2.2 P 239 L 50 # 221
 Parnaby, Gavin Solarflare Communica
 Comment Type E Comment Status D
 signaling/signalling are both used
 SuggestedRemedy
 signaling is the american spelling
 Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 78 SC 78.1.5 P 240 L 13 # 194
 Parnaby, Gavin Solarflare Communica
 Comment Type E Comment Status D
 dependant should be dependent
 SuggestedRemedy
 as comment
 Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 78 SC 78.1.5 P 240 L 13 # 190
 Grimwood, Michael Broadcom
 Comment Type E Comment Status D
 Typo.
 SuggestedRemedy
 Change "dependant" to "dependent".
 Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 78 SC 78.1.5 P 240 L 42 # 222
 Parnaby, Gavin Solarflare Communica
 Comment Type E Comment Status D
 and should be an
 SuggestedRemedy
 as comment
 Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 78 SC 78.1.5.1 P 240 L 53 # 195
 Parnaby, Gavin Solarflare Communica
 Comment Type E Comment Status D
 capitalise 'the' to 'The'
 SuggestedRemedy
 as comment
 Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 78 SC 78.1.5.1 P 240 L 53 # 73
 Dietz, Bryan Alcatel-Lucent
 Comment Type E Comment Status D
 Typo
 SuggestedRemedy
 Capitalize "the" at the start of the last sentence in the paragraph.
 Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 78 SC 78.1.5.1 P 241 L 12 # 191
 Grimwood, Michael Broadcom
 Comment Type E Comment Status D
 Typo, punctuation.
 SuggestedRemedy
 Change "PHY dependant" to "PHY-dependent"
 Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 78 SC 78.1.5.1 P 241 L 410 # 52
 Dietz, Bryan Alcatel-Lucent
 Comment Type E Comment Status D
 Clarify text. Edit the "de-assert" description to match the style and format of the "assert" description by combining two short paragraphs.
 SuggestedRemedy
 Change the three paragraphs starting at page 240 line 51 to read:
 "When the Low Power Idle request is deasserted, indicated by the LPI_REQUEST parameter set to DEASSERT in the LP_IDLE.request primitive of the LPI Client interface, the LPI assert function starts to transmit the 'normal inter-frame' encoding on the xMII. After a delay the LPI assert function sets the CARRIER_STATUS parameter to CARRIER_OFF in the PLS_CARRIER.indication primitive of the PLS service interface, allowing the MAC to start transmitting again.
 The delay on deassert is provided to allow the link partner to prepare for normal operation.
 The delay has a PHY dependant default value but this value can be adjusted using the Data Link Layer capabilities defined in 78.4.
 Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 78 SC 78.1.5.1 P 241 L 6 # 196
Parnaby, Gavin Solarflare Communica

Comment Type E Comment Status D
font appears to be incorrect

also happens on line 20 same page, line 51 same page and line 28 next page

SuggestedRemedy

use the same font as elsewhere

Proposed Response Response Status W
PROPOSED ACCEPT.

Cl 78 SC 78.1.5.2 P 241 L 20 # 188
Grimwood, Michael Broadcom

Comment Type E Comment Status D
Inconsistent font used for the text, "normal interframe".

SuggestedRemedy

Make font consistent. Exact same issue in 78.1.5.3.1, p 241, line 51 and 78.1.5.3.2, p 242, line 28.

Proposed Response Response Status W
PROPOSED ACCEPT.

Cl 78 SC 78.1.5.3 P 241 L 31 # 197
Parnaby, Gavin Solarflare Communica

Comment Type E Comment Status D
and should be an

SuggestedRemedy

Proposed Response Response Status W
PROPOSED ACCEPT.

Cl 78 SC 78.1.5.3.1 P 241 L 36 # 213
Parnaby, Gavin Solarflare Communica

Comment Type T Comment Status D
100BASE-T should be 100BASE-TX.

There are descriptions of 100BASE-TX, 1000BASE-T and 10GBASE-T EEE modes but nothing about backplane operation.

SuggestedRemedy

Correct 100BASE-T.

Add description of operation of the backplane EEE modes here (KX/KR/KX4)

Proposed Response Response Status W
PROPOSED ACCEPT IN PRINCIPLE.

100BASE-T will be replaced by 100BASE-TX.

Editor will add description of backplane EEE operation

Cl 78 SC 78.1.5.3.1 P 241 L 39 # 66
Dietz, Bryan Alcatel-Lucent

Comment Type E Comment Status D
100Base-T should be 100Base-TX.

SuggestedRemedy

Change 100Base-T to 100Base-TX

Proposed Response Response Status W
PROPOSED ACCEPT.

Cl 78 SC 78.1.5.3.2 P 242 L 22 # 198
Parnaby, Gavin Solarflare Communica

Comment Type E Comment Status D
delete 'some of the'

SuggestedRemedy

Proposed Response Response Status W
PROPOSED REJECT.

Cl 78 **SC 78.1.6** **P 242** **L 33** # **199**
Parnaby, Gavin Solarflare Communica

Comment Type **E** **Comment Status** **D**
EEE defines Low Power Idle mode ...

SuggestedRemedy
should be

EEE defines a Low Power Idle mode...

Proposed Response **Response Status** **W**
PROPOSED ACCEPT.

Cl 78 **SC 78.2.1** **P 243** **L 5** # **214**
Parnaby, Gavin Solarflare Communica

Comment Type **T** **Comment Status** **D**
Does it make sense to define states without any state diagram or normative requirements?

Do we need to define these states? They overlap with states defined in individual clauses. In my opinion this text confuses things rather than making this clearer.

SuggestedRemedy
Delete these state descriptions.

Proposed Response **Response Status** **W**
PROPOSED REJECT.

The definitions are useful for the descriptive text of EEE modes in this clause.

It is not clear why this text causes any confusion and this text is intended to be consistent with the definitions in the PHY clauses. If there is any inconsistency, please identify it.

Cl 78 **SC 78.2.2** **P 243** **L 27** # **53**
Dietz, Bryan Alcatel-Lucent

Comment Type **E** **Comment Status** **D**
Change "Low Power Mode" to "Low Power Idle Mode" to match other definitions on this page.

SuggestedRemedy
Change "Low Power Mode" to "Low Power Idle Mode" to match other definitions on this page.

Proposed Response **Response Status** **W**
PROPOSED ACCEPT.

Cl 78 **SC 78.2.3** **P 243** **L 42** # **215**
Parnaby, Gavin Solarflare Communica

Comment Type **T** **Comment Status** **D**
The propagation delay of a start of shell delimiter

(lines 42 and 43)

SuggestedRemedy
Replace with 'The propagation delay between the xxMII and the MDI'

Proposed Response **Response Status** **W**
PROPOSED ACCEPT.

Cl 78 **SC 78.2.3** **P 243** **L 42** # **67**
Dietz, Bryan Alcatel-Lucent

Comment Type **E** **Comment Status** **D**
Please add "(SSD)" after "start of shell delimiter". This would clarify references in other parts of the text.

SuggestedRemedy
Please add "(SSD)" after "start of shell delimiter". This would clarify references in other parts of the text.

Proposed Response **Response Status** **W**
PROPOSED ACCEPT.

Cl 78 **SC 78.2.3** **P 243** **L 44** # **200**
Parnaby, Gavin Solarflare Communica

Comment Type **E** **Comment Status** **D**
add 'the' between 'between' and 'two'

same for line 49

SuggestedRemedy

Proposed Response **Response Status** **W**
PROPOSED ACCEPT.

Cl 78 **SC 78.2.3** **P 244** **L 2** # **201**
Parnaby, Gavin Solarflare Communica

Comment Type **E** **Comment Status** **D**
add 'the' before 'reception of an IDLE signal' and add 'the' before 'first data codewords'

SuggestedRemedy

Proposed Response *Response Status* **W**
PROPOSED ACCEPT.

Cl 78 **SC 78.2.3** **P 244** **L 29** # **33**
Traeber, Mario Infineon Technologies

Comment Type **ER** **Comment Status** **D**
100BASE-TX timing parameters contain inconsistent values (MAX=MIN and not fitting to clause 24)

SuggestedRemedy
Insert Timing Values which are consistent to Table 24-2

Proposed Response *Response Status* **W**
PROPOSED ACCEPT IN PRINCIPLE.

Last row of the Table 78-2 (one that describes 100BASE-TX parameters) will be updated with following values:

Ts min: 200us
Ts max: 220us
Tq min: 20,000us
Tq max: 22,000us
Tr min: 200us
Tr max: 220us

Cl 78 **SC 78.2.3** **P 244** **L 9** # **202**
Parnaby, Gavin Solarflare Communica

Comment Type **E** **Comment Status** **D**
can does not seem to be the right word here

SuggestedRemedy
should or must would be better words.

Proposed Response *Response Status* **W**
PROPOSED ACCEPT IN PRINCIPLE.

See response to comment #189

Cl 78 **SC 78.2.3** **P 244** **L 9** # **189**
Grimwood, Michael Broadcom

Comment Type **E** **Comment Status** **D**
Word usage.

SuggestedRemedy
Change "can be" to "is".

Proposed Response *Response Status* **W**
PROPOSED ACCEPT.

Cl 78 **SC 78.3** **P 244** **L 37** # **216**
Parnaby, Gavin Solarflare Communica

Comment Type **T** **Comment Status** **D**
the text says that Auto-Negotiation is performed upon detection of a PHY error.

This is misleading. Auto-Negotiation is performed when the link drops.

SuggestedRemedy
Reeplace PHY error with link failure.

Proposed Response *Response Status* **W**
PROPOSED ACCEPT IN PRINCIPLE.

"upon detection of a PHY error" will be replaced by "due to link failure"

Cl 78 SC 78.3 P 244 L 41 # 192
Grimwood, Michael Broadcom

Comment Type T Comment Status D

Impose a minimum time between completing link-up and when the LPI Client can initially assert LPI in order to ensure a high-quality, stable link exists prior to entering LPI.

SuggestedRemedy

If EEE is supported by both link partners for the negotiated PHY type then the EEE function may be used independently in either direction.

To:

If EEE is supported by both link partners for the negotiated PHY type then the EEE function may be used independently in either direction with the constraint that the Low Power Idle Client shall not set the LPI_REQUEST parameter to ASSERT until at least 5 msec after link_status=OK.

Proposed Response Response Status W
PROPOSED ACCEPT IN PRINCIPLE.

Should be discussed by the group.
Editor supports this change.

Cl 78 SC 78.3 P 244 L 43 # 54
Dietz, Bryan Alcatel-Lucent

Comment Type E Comment Status D

Change "using frames" to "using L2 protocol frames".

SuggestedRemedy

Change "using frames" to "using L2 protocol frames".

Proposed Response Response Status W
PROPOSED ACCEPT.

Cl 78 SC 78.4 P L # 248
Diab, Wael Broadcom

Comment Type TR Comment Status D

Pls make the changes to support fallback mode

SuggestedRemedy

See presentation diab_vetteth_01_0409.pdf

Proposed Response Response Status W
PROPOSED ACCEPT IN PRINCIPLE.

There was unanimous consensus to proceed forward with this idea in the L2 Ad-Hoc. Review detailed proposal in TF per guidance from L2 Ad-Hoc and adopt if changes to the draft are complete.

Cl 78 SC 78.4 P 245 L 12 # 168
Barrass, Hugh Cisco

Comment Type E Comment Status D

Editor's note is no longer needed.

SuggestedRemedy

Delete the editor's note box.

Proposed Response Response Status W
PROPOSED ACCEPT IN PRINCIPLE.

Delete last two sentence. Add the following sentence "Material related to 802.3bc to be converted to editorial instructions against Clause 79 when 802.3bc is stable".

If decision is to do that in D1.3, no need for additional section and modified Editor's note to go into C79 edits.

Cl 78 SC 78.4 P 245 L 18 # 56
Dietz, Bryan Alcatel-Lucent

Comment Type E Comment Status D

Use plural form

SuggestedRemedy

Change "Implementation" to "Implementations".

Proposed Response Response Status W
PROPOSED ACCEPT.

Cl 78 SC 78.4 P 245 L 26 # 169
Barrass, Hugh Cisco

Comment Type ER Comment Status D

Editor's note indicates that cross reference table will be added.

SuggestedRemedy

Add the cross reference table, delete the editor's note box.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Intent of editor's note is to remind the reader that missing C30 refs will be added when C30 is ready. Clarify note accordingly.

Cl 78 SC 78.4 P 245 L 5 # 55
Dietz, Bryan Alcatel-Lucent

Comment Type T Comment Status D

Minor editorial clarification.

SuggestedRemedy

Change "Devices that require additional sleep times" to "Devices that require longer wake up times".

Proposed Response Response Status W

PROPOSED ACCEPT.

Good catch, we specify wake up and not sleep times. Changed type to technical in the Comment Type field.

Cl 78 SC 78.4.1 P 245 L 35 # 170
Barrass, Hugh Cisco

Comment Type ER Comment Status D

Editor's note indicates that this section will be moved to Clause 79.

SuggestedRemedy

Add Clause 79 into this document.

Move the TLV definition from 78.4.1 to 79.6a, change 78.4.1 to resemble 33.6.1 from .3at.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Agreed. Timing of move to be discussed in Task Force after proposed work plan is presented in the L2 ad-hoc report. Goal is to do the move when 802.3bc is stable.

Cl 78 SC 78.4.1.2 P 246 L 37 # 58
Dietz, Bryan Alcatel-Lucent

Comment Type E Comment Status D

Clarification

SuggestedRemedy

Consider swapping sections 78.4.1.1 and 78.4.1.2. The meaning of Tw is more clear if the Receive Tw is described before Transmit Tw.

Proposed Response Response Status W

PROPOSED REJECT.

Both sections reference the "other side" of the link (i.e. TX to RX and vice-versa) hence clarification by swapping maybe marginal and an argument for keeping as is may be made for clarification as well.

Cl 78 SC 78.4.1.2 P 246 L 38 # 203
Parnaby, Gavin Solarflare Communica

Comment Type E Comment Status D

Font is incorrect

SuggestedRemedy

Correct font

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 78 SC 78.4.1.2 P 246 L 3940 # 57
Dietz, Bryan Alcatel-Lucent

Comment Type E Comment Status D

First sentence in paragraph is duplicated.

SuggestedRemedy

Remove duplicated first sentence in this paragraph. Remove duplicated first sentence in this paragraph.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Agreed. Commenter has also duplicated his suggested remedy!

Cl 78 **SC 78.4.1.3** **P 246** **L 49** # **204**
Parnaby, Gavin Solarflare Communica

Comment Type **E** **Comment Status** **D**
partner should be device

SuggestedRemedy
replace partner with device on lines 50, 51 and 52

Proposed Response **Response Status** **W**
PROPOSED ACCEPT IN PRINCIPLE.

The correct term is "link partner". Agreed that shorthand of "partner" maybe confusing. Use "remote link partner" throughout

Cl 78 **SC 78.4.3** **P 247** **L 22** # **65**
Dietz, Bryan Alcatel-Lucent

Comment Type **T** **Comment Status** **D**
The times listed in paragraph 1 and paragraph 2 should be consistent.

SuggestedRemedy
Insert "Under normal operation," in front of first sentence of paragraph.

Proposed Response **Response Status** **W**
PROPOSED ACCEPT IN PRINCIPLE.

"under normal operation" was carry over from .3at where there was legacy support issues for Type-1. There is no need for it here. Delete "under normal operation".

Cl 78 **SC 78.4.3** **P 247** **L 26** # **171**
Barrass, Hugh Cisco

Comment Type **ER** **Comment Status** **D**
The editor's note indicates some changes that might be made.

If the changes are made then the editor's note is no longer needed, if not it is moot.

SuggestedRemedy
In either case, delete the editor's note.

Proposed Response **Response Status** **W**
PROPOSED ACCEPT IN PRINCIPLE.

A change is required to support this. The note is inaccurate in that it rules out ways to achieve the requirement that do not require changes to the auto-neg. There was consensus in the L2 Ad-Hoc to present a solution to the TF at the April interim.

If a solution is adopted for D1.4, note to be deleted. If not, not to be clarified per above.

Cl 78 **SC 78.4.4.1** **P 247** **L 51** # **59**
Dietz, Bryan Alcatel-Lucent

Comment Type **E** **Comment Status** **D**
Typo

SuggestedRemedy
Add space before word "constants".

Proposed Response **Response Status** **W**
PROPOSED ACCEPT.

Cl 78 **SC 78.4.4.2** **P 248** **L 5** # **205**
Parnaby, Gavin Solarflare Communica

Comment Type **E** **Comment Status** **D**
than should be that

SuggestedRemedy

Proposed Response **Response Status** **W**
PROPOSED ACCEPT.

Cl 78 **SC 78.4.4.3** **P 249** **L 7** # **60**
Dietz, Bryan Alcatel-Lucent

Comment Type **E** **Comment Status** **D**
Clarify meaning of variable.

SuggestedRemedy
Insert "Data Link Layer ready" before "This variable indicates." The term "dll" has other software meanings that are confusing in this case.

Proposed Response **Response Status** **W**
PROPOSED ACCEPT IN PRINCIPLE.

In addition to requested change see if there is an abbreviation for DLL anywhere in 802.3-2008 or P802.3at. If not, consider adding one.

Cl 78 **SC 78.4.4.5** **P 250** **L 3** # **172**
 Barrass, Hugh Cisco

Comment Type E **Comment Status D**
 Editor's note is no longer needed.

SuggestedRemedy
 Delete the editor's note box.

Proposed Response **Response Status W**
 PROPOSED ACCEPT.

Cl 78 **SC 78.4.4.5** **P 250** **L 9** # **61**
 Dietz, Bryan Alcatel-Lucent

Comment Type E **Comment Status D**
 EEE is defined only for point-to-point full duplex links. Delete "a set of" or replace with "two".

SuggestedRemedy
 EEE is defined only for point-to-point full duplex links. Delete "a set of" or replace with "two".

Proposed Response **Response Status W**
 PROPOSED ACCEPT IN PRINCIPLE.

Intent is to mean an RX and TX link partners not an RX and TX on an individual port.

With that clarification, commenter is encouraged to submit alternate text if he feels a clarification is still needed

Cl 78 **SC 78.4.4.5** **P 251** **L 28** # **68**
 Dietz, Bryan Alcatel-Lucent

Comment Type TR **Comment Status D**
 The state diagram transition condition between TX UPDATE and SYSTEM REALLOCATION contains an "OR" that should be an "AND".

This comment was discussed in the L2 ad-hoc, and should be fixed in part of the ad-hoc report.

SuggestedRemedy
 Change condition to "AND".

Proposed Response **Response Status W**
 PROPOSED ACCEPT.

Cl 78 **SC 78.4.4.5** **P 252** **L 16** # **69**
 Dietz, Bryan Alcatel-Lucent

Comment Type T **Comment Status D**
 The state diagram transition condition between RUNNING and CHANGE depends upon a condition RemTxSystemValue CHANGED. The meaning of CHANGED is not specified - CHANGED since what or since when.

See also page 251 line 15.

This comment was discussed in the L2 ad-hoc and the fix should be part of the ad-hoc report.

SuggestedRemedy
 There are two potential changes: add a note to explain CHANGED or define a variable that can be compared against RemTxSystemValue.

Proposed Response **Response Status W**
 PROPOSED ACCEPT IN PRINCIPLE.

Later suggested remedy (variable) as this is consistent with P802.3at.

Cl 78 **SC 78.4.4.5** **P 252** **L 24** # **63**
 Dietz, Bryan Alcatel-Lucent

Comment Type E **Comment Status D**
 Variable "New_RX_VALUE" in left exit condition from CHANGE should be "NEW_RX_VALUE".

SuggestedRemedy
 Variable "New_RX_VALUE" in left exit condition from CHANGE should be "NEW_RX_VALUE".

Proposed Response **Response Status W**
 PROPOSED ACCEPT.

Cl 78 SC 78.4.5.1 P 253 L 49 # 62
Dietz, Bryan Alcatel-Lucent

Comment Type E Comment Status D
Simplify text describing state diagram operation.

SuggestedRemedy

Simplify text by replacing:

"Irrespective of whether the transmitting link partner enters the SYSTEM REALLOCATION state from the TX UPDATE state; it ultimately returns to the RUNNING state through the UPDATE MIRROR state where it updates the echo for the Receive Tw_sys."

with

"The transmitting link partner enters MIRROR UPDATE state either from SYSTEM REALLOCATION or directly from TX UPDATE state. UPDATE MIRROR state then updates the echo for the Receive Tw_sys and returns to the RUNNING state."

Proposed Response Response Status W
PROPOSED ACCEPT.

Cl 78 SC 78.4.5.2 P 254 L 12 # 64
Dietz, Bryan Alcatel-Lucent

Comment Type E Comment Status D
Clarify explanation of state diagram operation.

SuggestedRemedy

Clarify text by replacing:

"Irrespective of whether the receiving link partner enters the SYSTEM REALLOCATION state, it ultimately gets to the RX UPDATE state."

with

"The receiving link partner ultimately enters RX UPDATE state, either from SYSTEM REALLOCATION state or directly from CHANGE state."

Proposed Response Response Status W
PROPOSED ACCEPT.

Cl 78 SC 78.5 P 254 L 30 # 206
Parnaby, Gavin Solarflare Communica

Comment Type E Comment Status D
Remove a .

SuggestedRemedy

Proposed Response Response Status W
PROPOSED ACCEPT.

Cl 78 SC 78.5 P 254 L 35 # 207
Parnaby, Gavin Solarflare Communica

Comment Type E Comment Status D
typo 'paraneters'; also add 'the' before systems designer, replace while with 'when', change PHY's to PHYs (also on line 38 and 39)

SuggestedRemedy

Proposed Response Response Status W
PROPOSED ACCEPT.

Cl 78 SC 78.5 P 255 L 9 # 173
Barrass, Hugh Cisco

Comment Type T Comment Status D
As far as this commenter understands, the conclusion of the wake time shrinkage concluded that the Tw_sys_rx for backplane PHYs should be the same as similar BASE-T PHYs.

SuggestedRemedy

Change the backplane TBD rows as follows:

1000BASE-KX: 12.76, 11, 0, 11, 1.76
10GBASE-KX4: 11.88, 9, 0, 9, 2.88
10GBASE-KR: 14.88, 12, 0, 12, 2.88

Add a new line for 10GBASE-KR (with scrambler_reset_enable = TRUE - use a footnote)

10GBASE-KR: 16.88, 14, 0, 14, 2.88

Proposed Response Response Status W
PROPOSED ACCEPT IN PRINCIPLE.

Wait till report of Wake time shrinkage adhoc call scheduled for 4/22/09

Cl **99** SC P7 L 16 # 249
Diab, Wael Broadcom

Comment Type **E** Comment Status **D**

Suggest that all clause editors and other TF officers are listed

SuggestedRemedy

Per comment

Proposed Response Response Status **W**

PROPOSED ACCEPT.