

IEEE P802.3bq - 40GBASE-T 1st Task Force review comments

Cl **00** SC **0** P L # **21**
McClellan, Brett Marvell

Comment Type **E** Comment Status **D** Editorial - references

subclause headers don't match 802.3-2012
for example 45.2.1.66 in draft 1.0 is register 1.129 but in 802.3-2012 it is reg 1.134. 45.2.3.12
in draft 1.0 is 3.10.20 in 802.3-2012 it is 3.25.
Are the headers in the draft supposed to reference 802.3-2012? or to a later amendment?

SuggestedRemedy

check that headers are correct

Proposed Response Response Status **W**

PROPOSED ACCEPT IN PRINCIPLE - EDITORIAL TEAM TO CHECK HEADERS AND IMPLEMENT

Cl **28** SC **28.5.4.8** P **8** L **26** # **60**
Zimmerman, George CME Consulting, Inc.

Comment Type **TR** Comment Status **D** Autoneg

Autoneg requires additional changes:
Link fail inhibit timer is defined for 10/100/1000 (SD11) & separately for 10G (SD11a)

SuggestedRemedy

Extend definition of SD11a in 28.5.4.8 to include M: 40G (mandatory for 40G)

Proposed Response Response Status **W**

PROPOSED ACCEPT IN PRINCIPLE. - committee to discuss

Cl **28B** SC **28B.3** P **9** L **1** # **61**
Zimmerman, George CME Consulting, Inc.

Comment Type **TR** Comment Status **D** Autoneg

Add 40GBASE-T to autoneg priority resolution

SuggestedRemedy

Add edit to normative Annex 28B, clause 28B.3 to insert 40GBASE-T above 10GBASE-T on the priority resolution list and renumber list accordingly

Proposed Response Response Status **W**

PROPOSED ACCEPT.

Cl **28C** SC **28C.11** P **9** L **2** # **62**
Zimmerman, George CME Consulting, Inc.

Comment Type **E** Comment Status **D** Autoneg

name of message code in 28C.11 doesn't include 10GBASE-T
also listed as code 9 in Table 28C-1 doesn't include 10GBASE-T

SuggestedRemedy

Change message code 9 name from: "10GBASE-T/1000BASE-T Technology message code (Extended Next Page)" to:
"Gigabit BASE-T Technology message code (Extended Next Page)"

Include 40GBASE-T (Clause 98) in the list of referenced clauses in 28C.11

Make appropriate changes to Clauses, 40, 55, and 98 to reflect the name change (see comment on 98.6.2)

Proposed Response Response Status **W**

PROPOSED ACCEPT IN PRINCIPLE.
DISCUSS - see comments 101 & 102

Cl **28D** SC **28D.6** P **9** L **1** # **63**
Zimmerman, George CME Consulting, Inc.

Comment Type **TR** Comment Status **D** Autoneg

Annex 28D.6, changes for 10GBASE-T needs to also include 40GBASE-T

SuggestedRemedy

Insert section 28D.7 with same text as 28D.6 and change references to reflect 40GBASE-T and Clause 98, including variable 40GigT

Proposed Response Response Status **W**

PROPOSED ACCEPT IN PRINCIPLE.
DISCUSS

IEEE P802.3bq - 40GBASE-T 1st Task Force review comments

Cl 30 SC 30.2.5 P 9 L 1 # 64
Zimmerman, George CME Consulting, Inc.

Comment Type T Comment Status D Management

Clause 30, requires minor changes:

1. extending 10G operating margin package to 40G (Table 30-1e "10GBASE-T operating margin package")
2. include 40GBASE-T Clause 98 in 30.3.2.1.2aPhyType and 30.3.2.1.3 aPhyTypeList
3. Edit 10GBASE-T SNR margin and fast retrain counts to include 40GBASE-T as well
4. Add 40GBASE-T to 30.6.1.1.5 aAutoNegLocalTechnologyAbility

SuggestedRemedy

1. Change label of column in Table 30-1e to "10G/40GBASE-T operating margin package (conditional)"
2. Add 40GBASE-T Clause 98 in 30.3.2.1.2aPhyType and 30.3.2.1.3 aPhyTypeList
3. Edit 30.5.1.1.19 through 30.5.1.1.22, and 30.5.1.1.24 & 25 to include 40GBASE-T with 10GBASE-T
4. Add 40GBASE-T to 30.6.1.1.5 aAutoNegLocalTechnologyAbility list

Proposed Response Response Status W
PROPOSED ACCEPT.

Cl 31B SC 31B.3.7 P 9 L 2 # 65
Zimmerman, George CME Consulting, Inc.

Comment Type T Comment Status D

Consider whether 40GBASE-T needs special treatment for PAUSE operation, as 10GBASE-T did relative to other 10G PHYs.

SuggestedRemedy

Discuss - no specific remedy

Proposed Response Response Status W
PROPOSED REJECT. - no specific remedy

Cl 45 SC 45.2.1 P 10 L 20 # 67
Zimmerman, George CME Consulting, Inc.

Comment Type ER Comment Status D Editorial
Missing "/"

SuggestedRemedy

Change to 10GBASE-T/40GBASE-T

Proposed Response Response Status W
PROPOSED ACCEPT.

Cl 45 SC 45.2.1.66 P 13 L 3 # 66
Zimmerman, George CME Consulting, Inc.

Comment Type E Comment Status D Control/Status bits

subclause appears to relate only to register 1.129, although title is amended to add "and 1.130"

SuggestedRemedy

Delete "and 1.130" from title

Proposed Response Response Status W
PROPOSED ACCEPT.

Cl 45 SC 45.2.1.66.2 P 13 L 13 # 68
Zimmerman, George CME Consulting, Inc.

Comment Type T Comment Status D Control/Status bits

No need for both a 10GBASE-T LP information valid bit and a 40GBASE-T LP information valid bit. This also includes Table 45-54

If the new bit for 40GBASE-T is to be kept, paragraph references the wrong (10GBASE-T) bit on line 17.

SuggestedRemedy

Delete inserted paragraph, and edit paragraph 45.2.1.66.1 10GBASE-T LP information valid (1.129.0) to be "40/10GBASE-T LP information valid"

IF the paragraph is not deleted, correct the reference on line 17 to bit 1.129.0 which should be 1.129.1

Proposed Response Response Status W
PROPOSED ACCEPT IN PRINCIPLE.
Delete inserted paragraph, and edit paragraph 45.2.1.66.1 10GBASE-T LP information valid (1.129.0) to be "40/10GBASE-T LP information valid"

Cl 45 SC 45.2.1.66.2 P 22 L 13 # 22
McClellan, Brett Marvell

Comment Type T Comment Status D Control/Status bits

45.2.1.66.2 40GBASE-T LP information valid (1.129.1)

Adding a new bit for 40G seems unnecessary, can we reuse the 10GBASE-T bit, 1.129.0? Otherwise we need to search and replace instances of 1.129.0 and replace with 1.129.1. See page 23 line 8.

SuggestedRemedy

delete bit 1.129.1 and rename 1.129.0 10/40GBASE-T LP information valid

Proposed Response Response Status W
PROPOSED ACCEPT.

IEEE P802.3bq - 40GBASE-T 1st Task Force review comments

Cl 45 **SC 45.2.1.68.1** **P 23** **L 8** # **123**
 Lusted, Kent Intel

Comment Type **ER** **Comment Status** **D** **Control/Status bits**

The last sentence references the LP information valid bit 1.129.0 and the TX power backoff bits. backoff bits are now defined for 10GbT and 40GbT. however, the 1.129.0 bit is now the 10GBASE-T LP information valid bit. Another bit is defined for 40GBASE-T (1.129.1).

SuggestedRemedy
 Add reference to 1.129.1, which is the 40GBASE-T LP information valid bit.

Proposed Response **Response Status** **W**
 PROPOSED REJECT. No change needed if comment #22 is accepted.

Cl 45 **SC 45.2.3.1.2** **P 25** **L 10** # **124**
 Lusted, Kent Intel

Comment Type **ER** **Comment Status** **D** **Editorial - references**

Link to 98.3.6.3 is to wrong section. Loopback is 98.3.7.3.

Note that the sentence immediately preceeding it for 10GBASE-T incorrectly references 55.3.6.3. The correct 10GBASE-T reference is 55.3.7.3.

SuggestedRemedy
 Point to 98.3.7.3

Proposed Response **Response Status** **W**
 PROPOSED ACCEPT.
 Recommend Commenter submit maintenance request on 10GBASE-T reference

Cl 45 **SC 45.2.3.12** **P 17** **L 28** # **69**
 Zimmerman, George CME Consulting, Inc.

Comment Type **TR** **Comment Status** **D** **Control/Status bits**

40GBASE-T EEE deep sleep is not supported in clause 98

SuggestedRemedy
 Delete section 45.2.3.12

Proposed Response **Response Status** **W**
 PROPOSED ACCEPT IN PRINCIPLE.
 - RESOLVED BY COMMENT 23

Cl 45 **SC 45.2.3.12** **P 26** **L 29** # **23**
 McClellan, Brett Marvell

Comment Type **E** **Comment Status** **D** **Control/Status bits**

"45.2.3.12 40GBASE-T EEE deep sleep supported (3.20.10)" doesn't match other EEE capability bit names.

SuggestedRemedy
 change to:
 "45.2.3.12 40GBASE-T EEE supported (3.20.10)"

Proposed Response **Response Status** **W**
 PROPOSED ACCEPT.
 - SEE COMMENT 69

Cl 45 **SC 45.2.3.17** **P 17** **L 40** # **70**
 Zimmerman, George CME Consulting, Inc.

Comment Type **ER** **Comment Status** **D** **Editorial - technical**

Description says that a device that does not implement BASE-R, 10GBASE-T, AND (emphasis added) 40GBASE_T ...

(FYI - same error is in the existing 802.3-2012)

while the bit is for BASE-R and 10GBASE-T currently, it isn't meant to mean that a device must implement ALL of the above, as an AND would indicate.

SuggestedRemedy
 change "and 40GBASE-T" to "or 40GBASE-T"

Proposed Response **Response Status** **W**
 PROPOSED ACCEPT IN PRINCIPLE.
 DISCUSS

Cl 45 **SC 45.2.3.17.4** **P 27** **L 40** # **125**
 Lusted, Kent Intel

Comment Type **ER** **Comment Status** **D** **Editorial - references**

Link to 98.3.6.1 is to wrong section. Variables is 98.3.6.2.2, or least in section 98.3.6.2. The variable hi_lfer is not in 98.3.6.1.

Note that the sentence immediately preceeding it for 10GBASE-T incorrectly references 55.3.6.1. The correct 10GBASE-T reference is 55.3.6.2.

SuggestedRemedy
 Point to 98.3.6.2.2 or 98.3.6.2

Proposed Response **Response Status** **W**
 PROPOSED ACCEPT.

IEEE P802.3bq - 40GBASE-T 1st Task Force review comments

CI 45 SC 45.2.3.17.5 P 27 L 52 # 126
Lusted, Kent Intel

Comment Type ER Comment Status D Editorial - references

Link to 98.3.2.3 is to wrong section. Variable definitions is 98.3.6.2.2, or least in section 98.3.6.2. The variable block_lock is not in 98.3.2.3.

Note that the sentence immediately preceding it for 10GBASE-T incorrectly references 55.3.2.3. The correct 10GBASE-T reference is 55.3.6.2.

SuggestedRemedy

Point to correct section.

Proposed Response Response Status W

PROPOSED ACCEPT.

Recommend Commenter submit maintenance request on 10GBASE-T reference

CI 45 SC 45.2.7.10 P 20 L 39 # 71
Zimmerman, George CME Consulting, Inc.

Comment Type E Comment Status D Editorial

subject (assignment of bits) and verb (are) should agree - subject is (still) singular. (no need to change "is" to "are")

SuggestedRemedy

reverse proposed deletion of "is" to replace with "are"

Proposed Response Response Status W

PROPOSED ACCEPT.

CI 45 SC 45.2.7.10.6 P 30 L 28 # 24
McClellan, Brett Marvell

Comment Type T Comment Status D Fast Retrain

Task force should consider making fast retrain mandatory.

SuggestedRemedy

If made mandatory, delete subclauses
45.2.7.10.6 40GBASE-T Fast retrain ability (7.32.3)
45.2.7.11.10 40GBASE-T Fast retrain ability (7.33.0)
modify tables accordingly
delete references to fast retrain "option" in Clause 98

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

- DISCUSS WITH COMMENT 52

CI 45 SC 45.2.7.11.1 P 31 L 29 # 127
Lusted, Kent Intel

Comment Type ER Comment Status D Editorial

Added sentences uses "10GBASE-T" but should be "40GBASE-T".

SuggestedRemedy

Change to "40GBASE-T"

Proposed Response Response Status W

PROPOSED ACCEPT.

CI 45 SC Table 45-7 P 20 L 21 # 121
Lusted, Kent Intel

Comment Type E Comment Status D Editorial

Description adds "40GBASE-T PMA" but the correct type selection should be "40GBASE-T PMA/PMD".

Listing PMA/PMD makes it consistent with 10GBASE-T, 1000BASE-T, 100BASE-TX, and other listings in Table 45-7

SuggestedRemedy

Change to "40GBASE-T PMA/PMD".

Proposed Response Response Status W

PROPOSED ACCEPT.

CI 78 SC 78 P 73 L 5 # 72
Zimmerman, George CME Consulting, Inc.

Comment Type ER Comment Status D Editorial

Clause 78 has template text throughout, which needs to be cleaned out

SuggestedRemedy

Clean out template text showing formates for paragraphs,etc.

Proposed Response Response Status W

PROPOSED ACCEPT.

IEEE P802.3bq - 40GBASE-T 1st Task Force review comments

Cl 78 SC 78.1 P 73 L 14 # 47
 Zimmerman, George CME Consulting, Inc.
 Comment Type ER Comment Status D EEE
 While phy implementations may or may not support EEE, in the standard, EEE as a protocol supports the phys.
 SuggestedRemedy
 reverse edit to read "EEE supports the 100BASE-TX PHY, ..., and the 40GBASE-T PHY".
 Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 78 SC 78.3 P 38 L 1 # 25
 McClellan, Brett Marvell
 Comment Type E Comment Status D Editorial - references
 "Table 78-2—Clauses associated with each interface type" title is incorrect
 SuggestedRemedy
 change to:
 "Table 78-2—Summary of the key EEE parameters for supported PHY"
 Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 78 SC 78.3 P 74 L 1 # 48
 Zimmerman, George CME Consulting, Inc.
 Comment Type ER Comment Status D Editorial
 Table 78-2 seems to have gotten the title of 78-1. In 802.3-2012, it is "Summary of the key EEE parameters for supported PHY"
 SuggestedRemedy
 Replace title of Table 78-2 with "Summary of the key EEE parameters for supported PHY"
 Proposed Response Response Status W
 PROPOSED ACCEPT.
 See Comment 25

Cl 78 SC 78.4 P 38 L 33 # 26
 McClellan, Brett Marvell
 Comment Type E Comment Status D Editorial
 pages 38 to 41 have unrelated editorial notes
 SuggestedRemedy
 remove this section
 Proposed Response Response Status W
 PROPOSED ACCEPT.
 (see comment 72)

Cl 98 SC 98.1 P 12 L 28 # 49
 Zimmerman, George CME Consulting, Inc.
 Comment Type T Comment Status D Cabling references
 Reference to media in ISO/IEC 11801:2002 is inappropriate - should be to Ed 3 draft
 SuggestedRemedy
 Replace reference with reference to ISO/IEC 11801 Edition 3 and ANSI/TIA-568-C.2-1-201x Addendum 1: Specifications for 100ohm Category 8 Cabling
 Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 98 SC 98.1.1 P 28 L 34 # 50
 Zimmerman, George CME Consulting, Inc.
 Comment Type ER Comment Status D Editorial - Discuss
 Remove editors notes in section
 SuggestedRemedy
 Remove editors notes under objectives
 Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.

IEEE P802.3bq - 40GBASE-T 1st Task Force review comments

CI **98** SC **98.1.3** P **30** L **24** # **52**
 Zimmerman, George CME Consulting, Inc.
 Comment Type **T** Comment Status **D** Fast Retrain
 There have been no contributions to remove fast retrain
 SuggestedRemedy
 Delete editors note
 Proposed Response Response Status **W**
 PROPOSED ACCEPT IN PRINCIPLE.
 - see comment 27 & 83

CI **98** SC **98.1.3** P **30** L **9** # **51**
 Zimmerman, George CME Consulting, Inc.
 Comment Type **T** Comment Status **D** Loop timing
 There are no known instances of 10GBASE-T implementing the alternate non-loop timed version. there has been no discussion that non-loop timed 40GBASE-T is technically feasible.
 SuggestedRemedy
 Remove references to optional loop timing in paragraph. (replace "may include" with "includes", delete "If loop timing is implemented,", delete sentence beginning with "If loop timing is not implemented"
 Proposed Response Response Status **W**
 PROPOSED ACCEPT IN PRINCIPLE.
 DISCUSS with comment 27 & 83

CI **98** SC **98.1.3** P **47** L **10** # **27**
 McClellan, Brett Marvell
 Comment Type **T** Comment Status **D** Loop timing
 "The MASTER-SLAVE relationship may include loop timing. If loop timing is implemented, the SLAVE PHY recovers the clock"
 Loop timing is required if EEE is supported. Task force should consider making loop timing required for 40GBASE-T to eliminate an option that likely will never be used (as in 10GBASE-T).
 SuggestedRemedy
 If made mandatory, change text to:
 "The MASTER-SLAVE relationship requires. The SLAVE PHY recovers the clock"
 modify other references in Clause 98 as required.
 Proposed Response Response Status **W**
 PROPOSED ACCEPT IN PRINCIPLE.
 - see comment 51 for other references

CI **98** SC **98.1.3** P **47** L **4** # **28**
 McClellan, Brett Marvell
 Comment Type **E** Comment Status **D** PMA General
 symbol period is 312.5ps not 325ps
 SuggestedRemedy
 change "325" to "312.5"
 Proposed Response Response Status **W**
 PROPOSED ACCEPT.

CI **98** SC **98.1.3.1** P **33** L **9** # **53**
 Zimmerman, George CME Consulting, Inc.
 Comment Type **E** Comment Status **D** Editorial - Discuss
 Editors note flagging the clause has done its job
 SuggestedRemedy
 Delete editors note
 Proposed Response Response Status **W**
 PROPOSED ACCEPT IN PRINCIPLE.

CI **98** SC **98.1.3.1** P **50** L **22** # **122**
 Lusted, Kent Intel
 Comment Type **E** Comment Status **D** Editorial
 The term "RS(140, 136, 2¹¹) code" is used without defining what RS is. The 802.3-2012 base standard abbreviation list says RS is Reconciliation Sublayer. That doesn't make sense in this section where the text uses "RS-coded bits". RS must mean Reed Solomon.
 SuggestedRemedy
 Please define the use of RS in this section as Reed Solomon, if necessary.
 Proposed Response Response Status **W**
 PROPOSED ACCEPT IN PRINCIPLE.
 - Edit first usage in line 49 to read:
 "comprising 3 RS-encoded (Reed-Solomon-encoded) bits and 4 LDPC-encoded"...

IEEE P802.3bq - 40GBASE-T 1st Task Force review comments

CI 98 SC 98.1.4 P 35 L 34 # 54
 Zimmerman, George CME Consulting, Inc.
 Comment Type **TR** Comment Status **D** Editorial-technical
 bit width of TXD, TXC, RXD, RXC are incorrect for XLGMII
 SuggestedRemedy
 Replace TXD<31:0> with TXD<63:0>, RXD<31:0> with RXD<63:0>, TXC<3:0> with TXC<7:0>, and RXC<3:0> with RXD<7:0>
 Proposed Response Response Status **W**
 PROPOSED ACCEPT.

CI 98 SC 98.12.7 P 146 L 15 # 9
 Larsen, Wayne CommScope
 Comment Type **E** Comment Status **D** PICS
 To align with the terminology used in clause 98.7.
 SuggestedRemedy
 in table entries LKS6, LKS7, and LKS15, change "FEXT" to "ACRF"
 Proposed Response Response Status **W**
 PROPOSED ACCEPT.

CI 98 SC 98.12.7 P 146 L 24 # 10
 Larsen, Wayne CommScope
 Comment Type **T** Comment Status **D** PICS
 To align the contents of this table with clause 98.7. The items listed are not included in clause 98.7.
 SuggestedRemedy
 Delete table entries LKS12, LKS13, LKS14, LKS16, LKS17, LKS18, and LKS19.
 Proposed Response Response Status **W**
 PROPOSED ACCEPT IN PRINCIPLE.
 - PICS to be scrubbed to align with revisions in clause 98 relative to clause 55 (these are some of them)

CI 98 SC 98.3.1 P 45 L 46 # 55
 Zimmerman, George CME Consulting, Inc.
 Comment Type **ER** Comment Status **D** Editorial - references
 cross reference to clause 45 for XLGMII is incorrect
 SuggestedRemedy
 Should point to Clause 81 for XLGMII
 Proposed Response Response Status **W**
 PROPOSED ACCEPT.

CI 98 SC 98.3.2.2 P 47 L 20 # 56
 Zimmerman, George CME Consulting, Inc.
 Comment Type **ER** Comment Status **D** Editorial
 extra "an"
 SuggestedRemedy
 delete "an" to rean "into two sets."
 Proposed Response Response Status **W**
 PROPOSED ACCEPT. (see comment 29)

CI 98 SC 98.3.2.2 P 64 L 20 # 29
 McClellan, Brett Marvell
 Comment Type **E** Comment Status **D** Editorial
 typo "and split the bits into an two sets"
 SuggestedRemedy
 change "and split the bits into an two sets"
 to
 "and split the bits into two sets"
 Proposed Response Response Status **W**
 PROPOSED ACCEPT.

IEEE P802.3bq - 40GBASE-T 1st Task Force review comments

Cl 98 SC 98.3.2.2 P 64 L 29 # 30
 McClellan, Brett Marvell
 Comment Type E Comment Status D PMA General
 "symbol period, T, is 1.25 ns."
 needs to be updated
 SuggestedRemedy
 change "symbol period, T, is 1.25 ns."
 to
 "symbol period, T, is 312.5 ps."
 Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 98 SC 98.3.2.2.16 P 56 L 4 # 74
 Zimmerman, George CME Consulting, Inc.
 Comment Type E Comment Status D Editorial
 65-bit block has extra spacing
 SuggestedRemedy
 clean up spacing on lines 4 & 34
 Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 98 SC 98.3.2.2.16 P 73 L 3 # 31
 McClellan, Brett Marvell
 Comment Type E Comment Status D Editorial
 typo "The transcoder construct"
 and "65-bit"
 SuggestedRemedy
 change to
 "The transcoder constructs"
 and
 "65-bit"
 Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 98 SC 98.3.2.2.17 P 58 L 3 # 75
 Zimmerman, George CME Consulting, Inc.
 Comment Type ER Comment Status D Editorial
 typo on "concatenated"
 SuggestedRemedy
 replace with concatenated
 Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 98 SC 98.3.2.2.19 P 75 L 30 # 32
 McClellan, Brett Marvell
 Comment Type T Comment Status D PCS
 auxiliary bit should be randomized
 SuggestedRemedy
 add text:
 "It is highly recommended that the auxiliary bit be randomized."
 Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.
 - DISCUSS

Cl 98 SC 98.3.2.2.2 P 48 L 10 # 57
 Zimmerman, George CME Consulting, Inc.
 Comment Type E Comment Status D PCS
 encoding of 64/65b in 40GBASE-T (and 10GBASE-T) did not provide for clock recovery or
 relate to LDPC frame errors.
 SuggestedRemedy
 Delete sentences "The encoding defined...., and "The encoding also...", as shown in strikeout,
 and delete editors note.
 Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.
 -discuss

IEEE P802.3bq - 40GBASE-T 1st Task Force review comments

Cl 98 SC 98.3.2.2.20 P 59 L 32 # 114
Wu, Peter Marvell

Comment Type T Comment Status D PCS
Text marked as pending approval

SuggestedRemedy

Request to accept the text with some changes in the presentation of "RS code scheme to protect "un-coded" bits at 40GBASE-T"

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.
- discuss with presentation

Cl 98 SC 98.3.2.2.20 P 59 L 35 # 76
Zimmerman, George CME Consulting, Inc.

Comment Type ER Comment Status D Editorial
extra "["

SuggestedRemedy

delete hanging "["

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 98 SC 98.3.2.2.20 P 60 L 50 # 77
Zimmerman, George CME Consulting, Inc.

Comment Type E Comment Status D PCS
Don't need extra annex, editors note has served its purpose

SuggestedRemedy

delete editors note asking question

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Cl 98 SC 98.3.2.2.20 P 77 L 36 # 33
McClellan, Brett Marvell

Comment Type E Comment Status D Editorial
figure 98-13, there is a line covering the text "p2"

SuggestedRemedy

remove line

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 98 SC 98.3.2.2.24 P 80 L 45 # 34
McClellan, Brett Marvell

Comment Type T Comment Status D EEE
1.2 us should be 1.12us

SuggestedRemedy

change 1.2 to 1.12

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 98 SC 98.3.2.2.4 P 48 L 49 # 58
Zimmerman, George CME Consulting, Inc.

Comment Type TR Comment Status D PCS
Figure 98-9 needs to be redrawn with corrections - replace references to uncoded bits with references to RS coded bits, colors need to be letter or number coded

SuggestedRemedy

Correct figure 98-9 as discussed above and delete editors note

Proposed Response Response Status W

PROPOSED ACCEPT.

IEEE P802.3bq - 40GBASE-T 1st Task Force review comments

Cl 98 SC 98.3.2.2.7 P 53 L 5 # 59
 Zimmerman, George CME Consulting, Inc.
 Comment Type ER Comment Status D Editorial - references
 reference to 10 Gigabit Ethernet and Clause 46 should be 40 Gigabit Ethernet and Clause 81,
 and 81.3.4
 SuggestedRemedy
 Replace references as above
 Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 98 SC 98.3.2.2.9 P 54 L 42 # 73
 Zimmerman, George CME Consulting, Inc.
 Comment Type T Comment Status D PCS
 Notes in Table 98-1 and column on 8B/10B are specific for 10Gbps Ethernet
 SuggestedRemedy
 Remove notes a & c, and replace note b with appropriate 40G reference
 Delete column referring to 8B/10B code
 Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.
 DISCUSS

Cl 98 SC 98.3.2.3 P 64 L 14 # 78
 Zimmerman, George CME Consulting, Inc.
 Comment Type TR Comment Status D Editorial
 Only uncorrectable RS errors should cause hi_lfer
 SuggestedRemedy
 change "RS error" to "uncorrectable RS error"
 Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 98 SC 98.3.4 P 66 L 13 # 79
 Zimmerman, George CME Consulting, Inc.
 Comment Type ER Comment Status D Editorial
 figure 98-15 is missing
 SuggestedRemedy
 Insert figure 98-15 from clause 55. (unchanged)
 Proposed Response Response Status W
 PROPOSED ACCEPT. - see comment 35

Cl 98 SC 98.3.4 P 83 L 13 # 35
 McClellan, Brett Marvell
 Comment Type E Comment Status D Editorial
 Figure 98-15 is missing/blank
 SuggestedRemedy
 fix the figure
 Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 98 SC 98.3.5.3 P 70 L 20 # 128
 Graba, Jim Broadcom
 Comment Type TR Comment Status D EEE
 This EEE feature, to allow a PHY to request the link partner to leave LPI mode, has not been
 approved by the TF.
 SuggestedRemedy
 Discuss and vote on the inclusion of this feature.
 Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.
 - discuss with comment 36
 reference graba_3bq_01_0714.pdf slides 5&6

IEEE P802.3bq - 40GBASE-T 1st Task Force review comments

Cl 98 SC 98.3.5.3 P 87 L 20 # 36
 McClellan, Brett Marvell
 Comment Type E Comment Status D
 the proposal lacks the details needed for a specification
 SuggestedRemedy
 remove until we have a full baseline or change to editorial note
 Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.
 - discuss with comment 128

Cl 98 SC 98.3.6.2.1 P 71 L 6 # 80
 Zimmerman, George CME Consulting, Inc.
 Comment Type TR Comment Status D Fast Retrain
 Cross reference is to 10G, Need to add Link Interruption ordered_set to XLGMII
 SuggestedRemedy
 Add Link Interruption Ordered_set to XLGMII in Clause 81 similar to 46.3.4 and change reference
 Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 98 SC 98.3.6.2.2 P 71 L 19 # 81
 Zimmerman, George CME Consulting, Inc.
 Comment Type T Comment Status D PCS
 4x change changes bit error rate for hi_lfer_cnt, since 125usec now includes 4x the number of bits
 SuggestedRemedy
 Change hi_lfer definition to "exceeds 64"
 alternatively, define in terms of a new term, N_sym, and make it a constant * N_sym so that for 40G it comes to 64
 Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.
 DISCUSS - with comment 37

Cl 98 SC 98.3.6.2.2 P 71 L 43 # 82
 Zimmerman, George CME Consulting, Inc.
 Comment Type TR Comment Status D Editorial
 Text refers to 32 bit XGMII words, and needs to be updated to reflect XLGMII
 SuggestedRemedy
 change references reflect 64 bit XLGMII word.
 Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 98 SC 98.3.6.2.2 P 88 L 38 # 38
 McClellan, Brett Marvell
 Comment Type T Comment Status D PCS
 "b. CRC8 check is satisfied"
 The CRC check was removed.
 SuggestedRemedy
 replace with
 "b. the RS did not have an uncorrectable error"
 Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 98 SC 98.3.6.2.3 P 90 L 18 # 37
 McClellan, Brett Marvell
 Comment Type T Comment Status D PCS
 The 125 us timer should be changed to 125/4 or the effective error rate should be changed from 4E-4 to 1E-4.
 SuggestedRemedy
 change timer to 31us,
 similarly change 125us to 31us in other locations
 Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.
 DISCUSS - with comment 81

IEEE P802.3bq - 40GBASE-T 1st Task Force review comments

Cl 98 SC 98.3.6.2.5 P 92 L 33 # 39
 McClellan, Brett Marvell
 Comment Type T Comment Status D EEE
 line 33 and line 38
 lpi_qr_time x 4
 should be
 lpi_qr_time x 6
 SuggestedRemedy
 change to lpi_qr_time x 6
 Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 98 SC 98.4.2.2 P 85 L 37 # 83
 Zimmerman, George CME Consulting, Inc.
 Comment Type T Comment Status D Loop timing
 remove option on loop timing - make it mandatory
 SuggestedRemedy
 Change "may include" to "includes", replace "If loop timing is implemented and the PMA_CONFIG..." with "If the PMA_CONFIG...", delete sentence beginning with "If loop timing is not implemented..."
 Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.
 DISCUSS - See comments 27 & 51

Cl 98 SC 98.4.2.4 P 105 L 41 # 40
 McClellan, Brett Marvell
 Comment Type T Comment Status D PMA Receiver
 "The receiver shall correct for differential delay variations of up to 50 ns across the wire-pairs."
 50ns is excessive for a 30 meter channel.
 SuggestedRemedy
 change to 15ns
 Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.
 - see comment 84
 Needs to be consistent with 98.7.2.6
 Change to 17 ns

Cl 98 SC 98.4.2.4 P 88 L 40 # 84
 Zimmerman, George CME Consulting, Inc.
 Comment Type TR Comment Status D PMA Receiver
 Receiver correction for differential delay (50ns) is still the 100m value, inconsistent with delay skew spec in 98.7.2.6 (17ns)
 SuggestedRemedy
 Change receiver differential delay variation spec (50ns) to be consistent with 98.7.2.6 - preferably by reference to 98.7.2.6
 Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.
 DISCUSS - with comment 40

Cl 98 SC 98.4.2.5.14 P 111 L 39 # 41
 McClellan, Brett Marvell
 Comment Type T Comment Status D PBO Startup
 "PBO=4 (corresponding to a power backoff of 8 dB). "
 needs to be updated for new PBO table
 SuggestedRemedy
 change to TBD until the PBO is selected for initial training
 Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.
 DISCUSS - with comment 87

Cl 98 SC 98.4.2.5.14 P 112 L 11 # 42
 McClellan, Brett Marvell
 Comment Type T Comment Status D PBO Startup
 "the SLAVE shall request a desired PBO level that is within two levels (within 4 dB)"
 4dB difference between devices is too large.
 Task force should consider reducing the difference or the master selects PBO for both, or both use the smaller backoff setting.
 SuggestedRemedy
 both devices use the smaller backoff setting
 Proposed Response Response Status W
 PROPOSED ACCEPT.

IEEE P802.3bq - 40GBASE-T 1st Task Force review comments

CI 98 SC 98.4.2.5.14 P 112 L 18 # 43
McClellan, Brett Marvell

Comment Type T Comment Status D Startup

"10ms" and "1ms"
absolute times should be reduced by 4 corresponding to the 4x clock rate
Task force should consider reducing initial count settings.

SuggestedRemedy

change 10ms to 2.5ms
change 1ms to 250us

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.
- see comment 90
Change times as commenter suggests

Committee to discuss count settings

CI 98 SC 98.4.2.5.14 P 94 L 48 # 87
Zimmerman, George CME Consulting, Inc.

Comment Type T Comment Status D PBO Startup

Editors note has done its job - PAM 2 Infocfield margin is greater than it was for 10GBASE-T at 100m.

SuggestedRemedy

Delete editors note

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.
DISCUSS - with comment 41

CI 98 SC 98.4.2.5.14 P 95 L 17 # 90
Zimmerman, George CME Consulting, Inc.

Comment Type TR Comment Status D Startup

relation of time to transition counter is incorrect because of 4x symbol rate. Conversion to allow longer time would require rework of infocfield format to allow longer transition counter

SuggestedRemedy

delete reference to time (10ms, line 17) and (1ms, line 18)
also, page 102, lines 28 & 29,

DISCUSS - this may have implications relative to prior decision on startup time.

Proposed Response Response Status W

PROPOSED ACCEPT.
- see comment 43

CI 98 SC 98.4.2.5.14 P 96 L 34 # 91
Zimmerman, George CME Consulting, Inc.

Comment Type T Comment Status D Startup

Table 98-10 - we may want to revisit Recommended times, especially average times.

SuggestedRemedy

Propose Chair charter an ad hoc to come back with proposals before the next meeting.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

CI 98 SC 98.4.2.5.15 P 97 L 3 # 85
Zimmerman, George CME Consulting, Inc.

Comment Type E Comment Status D Editorial

Editors note has done its job

SuggestedRemedy

Delete editors note

Proposed Response Response Status W

PROPOSED ACCEPT.

CI 98 SC 98.4.2.5.7 P 109 L 53 # 46
McClellan, Brett Marvell

Comment Type TR Comment Status D Startup

"frame error ratio of less than 3.2 X 10⁻⁹"
this doesn't match other occurrences of frame error ratio of 9.6 X 10⁻⁹page 134 line 2, line 28
page 135 line 14

SuggestedRemedy

change to:"frame error ratio of less than 9.6 X 10⁻⁹"
also need to change page 158 line 11

Proposed Response Response Status W

PROPOSED ACCEPT.
- also recommend commenter submit maintenance request on same section in Clause 55

IEEE P802.3bq - 40GBASE-T 1st Task Force review comments

Cl 98 SC 98.4.2.7 P 115 L 9 # 44
McClellan, Brett Marvell

Comment Type T Comment Status D EEE

"50 complete quiet-refresh cycles (nominally equal to 512 us)"
should be $8.192/4 = 2.048\text{ms}$

SuggestedRemedy
change 512us to 2.048ms

Proposed Response Response Status W
PROPOSED ACCEPT.

Cl 98 SC 98.4.3.1 P 116 L 1 # 45
McClellan, Brett Marvell

Comment Type T Comment Status D Startup - PBO

"power backoff (up to 14 dB)"
14dB is excessive, consider change the max PBO to 6dB

SuggestedRemedy
change 14dB to 6dB

Proposed Response Response Status W
PROPOSED ACCEPT IN PRINCIPLE.
Change 14dB to 8dB

see zimmerman_3bq_3_0714.pdf, PBO up to 8dB can be of use managing receiver dynamic
rate, and would also eliminate any need to change startup.

Cl 98 SC 98.4.3.1 P 99 L 14 # 89
Zimmerman, George CME Consulting, Inc.

Comment Type ER Comment Status D Editorial

reference to "scaled insertion loss equation" is incorrect. There is no longer a scaled insertion
loss equation in 98.7, and the explanatory remark is not relevant.

SuggestedRemedy
Delete "and have been computed using the scaled insertion loss equation in 98.7"

Proposed Response Response Status W
PROPOSED ACCEPT.

Cl 98 SC 98.4.3.1 P 99 L 3 # 88
Zimmerman, George CME Consulting, Inc.

Comment Type TR Comment Status D Editorial

power backoff set size is incorrect (left over from prior version)

SuggestedRemedy
Change "approximately 6 dB steps" to "approximately 2 dB steps"

Proposed Response Response Status W
PROPOSED ACCEPT.

Cl 98 SC 98.4.5.2 P 104 L 13 # 92
Zimmerman, George CME Consulting, Inc.

Comment Type TR Comment Status D EEE

time associated with 50 complete quiet refresh signal periods is incorrect

SuggestedRemedy
Change to 512usec, or, better, define a term, N_sym (proportional # symbols/sec) so that for
40G it is 512usec.

Proposed Response Response Status W
PROPOSED REJECT.

Cl 98 SC 98.4.6.3 P 108 L 24 # 93
Zimmerman, George CME Consulting, Inc.

Comment Type TR Comment Status D Editorial

References in note 2 point to 10GigT link status variables

SuggestedRemedy
replace with _40GigT variables

Proposed Response Response Status W
PROPOSED ACCEPT.

IEEE P802.3bq - 40GBASE-T 1st Task Force review comments

Cl 98 **SC 98.5.3.2** **P 114** **L 51** # **94**
 Zimmerman, George CME Consulting, Inc.

Comment Type T **Comment Status D** **PMA Transmitter**

Scale transmitter linearity for frequency

SuggestedRemedy

Discuss. Nominally this was related to distortion of the far-end signal and for safety should be > 33 dB (10dB better than threshold SNR) across the band to Nyquist. But, this is definitely an overkill safety margin and may be too high? (52 dB out to 200 MHz, then rolling off)

Scale frequency (25 becomes 100MHz), and put a "TBD" next to it, unless there is convergence on an alternate proposal.

Proposed Response **Response Status W**

PROPOSED ACCEPT IN PRINCIPLE.
 -Discuss

Cl 98 **SC 98.5.3.4** **P 116** **L 17** # **95**
 Zimmerman, George CME Consulting, Inc.

Comment Type ER **Comment Status D** **Editorial**

Figure 98-39 has mirrored y-axis label, and title still says "(update)"

SuggestedRemedy

fix y-axis on Figure 98-39 Transmit PSD, and delete the word "(update)" from title

Proposed Response **Response Status W**

PROPOSED ACCEPT.

Cl 98 **SC 98.5.4.1** **P 117** **L 1** # **96**
 Zimmerman, George CME Consulting, Inc.

Comment Type TR **Comment Status D** **PMA Receiver**

BER is after LDPC and RS decoding which is in the PCS this isn't mentioned

SuggestedRemedy

insert ", after LDPC and RS decoding, " between 10⁻¹² and "and sent to the XLGMII"

Proposed Response **Response Status W**

PROPOSED ACCEPT.

Cl 98 **SC 98.5.4.4** **P 118** **L 4** # **97**
 Zimmerman, George CME Consulting, Inc.

Comment Type T **Comment Status D** **PMA Receiver**

5 meters is probably not the right shortening to account for 2.5dB insertion loss at 40GBASE-T frequencies. Also, desire to be independent of both the test equipment and the transmission rate suggests the "helpful commentary" is less than helpful.

SuggestedRemedy

Delete "by approximately 5m"

Proposed Response **Response Status W**

PROPOSED ACCEPT IN PRINCIPLE.
 DISCUSS

Cl 98 **SC 98.5.4.5.1** **P 118** **L 21** # **98**
 Zimmerman, George CME Consulting, Inc.

Comment Type T **Comment Status D** **Short Reach**

TIA has defined a direct attach cord channel, reflected in the draft, unaccepted text

SuggestedRemedy

Accept the text inserted or alternate text referencing the TIA Category 8 direct attach channel.
 Delete the editors note.

Proposed Response **Response Status W**

PROPOSED ACCEPT IN PRINCIPLE.
 DISCUSS - with comment 2

IEEE P802.3bq - 40GBASE-T 1st Task Force review comments

CI 98 SC 98.5.4.5.1 P 118 L 28 # 115
Belopolsky, Yakov Bel Stewart

Comment Type TR Comment Status D Cabling references

IEC/ISO TR 11801-99-01 Guidance for balanced cabling in support of at least 40 Gbit/s data transmission recognizes Classes I and II ,and correspondingly components of categories 8.1 or 8.2 can be utilized for a Short Reach Test Channel.

SuggestedRemedy

Replace "Category 8.1" with "Category I or Category II component

Proposed Response Response Status W

PROPOSED REJECT.

- Short reach test channel text is to be "deleted or replaced" per Ed Note: "Need to delete or replace text below with an appropriate short reach channel, ideally referencing TIA or ISO specs". See contribution diminico_3bq_01_1114.pdf for short reach test channel replacement text.

-Also, even in the existing text, ISO nomenclature is Category 8.1 or Category 8.2 for components. The nomenclature of "Class" refers to channel requirements, not the components referenced in the clause.

CI 98 SC 98.5.4.5.1 P 135 L 22 # 2
DiMinico, Christopher MC Communications

Comment Type T Comment Status D Short Reach

98.5.4.5.1 Short reach test channel text provided in contribution per Ed note to delete or replace text with an appropriate short reach channel....

SuggestedRemedy

see contribution diminico_3bq_01_1114.pdf

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

DISCUSS - with comment 98
see contribution diminico_3bq_01_1114.pdf

CI 98 SC 98.6.1.1 P 119 L 8 # 99
Zimmerman, George CME Consulting, Inc.

Comment Type ER Comment Status D Editorial

Editors note has served its purpose, accept text in section.

SuggestedRemedy

Delete editors note and accept text.

Proposed Response Response Status W

PROPOSED ACCEPT.

CI 98 SC 98.6.1.2 P 119 L 48 # 100
Zimmerman, George CME Consulting, Inc.

Comment Type ER Comment Status D Editorial

Editors note has served its purpose

SuggestedRemedy

Delete editors note

Proposed Response Response Status W

PROPOSED ACCEPT.

CI 98 SC 98.6.2 P 122 L 2 # 101
Zimmerman, George CME Consulting, Inc.

Comment Type E Comment Status D Autoneg

Technology message code name is specific to 10G/1000BASE-T. need a new name that can apply also to 40GBASE-T. See comment on 28C.11

SuggestedRemedy

Change name to "Gigabit BASE-T Technology message code (Extended Next Page)"

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

DISCUSS - with comments 62 & 102
(also need to change references in Clause 55.6.2 and in Clause 40)

CI 98 SC 98.6.2 P 123 L 24 # 103
Zimmerman, George CME Consulting, Inc.

Comment Type T Comment Status D Loop timing

optional loop timing - make it mandatory

SuggestedRemedy

fix references on lines 24, delete sentence beginning with "In the situation where one link partner supports..." through the sentence ending with "was not resolved."

Proposed Response Response Status W

PROPOSED ACCEPT.

- see comments

IEEE P802.3bq - 40GBASE-T 1st Task Force review comments

Cl 98 SC 98.6.2 P 123 L 9 # 102
 Zimmerman, George CME Consulting, Inc.
 Comment Type ER Comment Status D Autoneg
 Editors note has served its purpose
 SuggestedRemedy
 Delete editors note
 Proposed Response Response Status W
 PROPOSED ACCEPT.
 - (outcome depends on discussion of comments 62&101)

Cl 98 SC 98.7 P 124 L 3 # 104
 Zimmerman, George CME Consulting, Inc.
 Comment Type T Comment Status D Cabling references
 Reference to "additional requirements specified in this subclause" is dated to 10GBASE-T running on cat 6. any link segment meeting the "requirements specified in this subclause" should work.
 SuggestedRemedy
 replace "Class I 4-pair balanced cabling that meets the additional requirements specified in this subclause" with "Class I or other 4-pair balanced cabling that meets the requirements specified in this subclause".
 Proposed Response Response Status W
 PROPOSED REJECT.
 The basis for the link segment specification is not for all "4-pair balanced cabling"; Class I is used.
 Page 141, L18 provide language to "support" other cabling that meets the requirements of 98.7.

Cl 98 SC 98.7 P 124 L 39 # 116
 Belopolsky, Yakov Bel Stewart
 Comment Type TR Comment Status D Cabling references
 40GBASE-T is intended to operate over the cabling that meets the requirements of the ISO/IEC 111801 standard that specially supports 40G, that standard includes Class I and Class II channels and, in fact, recognizes that components of category 6a and 7a or better can support such transmission. The statement that 40GBase is designed to operate over Class I cabling is incorrect
 SuggestedRemedy
 remove the " Class I" or replace with Class I or Class II

Proposed Response Response Status W
 PROPOSED REJECT.
 The language used in 98.7 allows for other classes to be supported if the link segment meets the requirements of 98.7. Reference to Class II is given in Table 98–18.
 98.7.1 Cabling system characteristics
 The cabling system used to support 40GBASE-T requires 4 pairs of ISO/IEC 111801 Class I balanced cabling with a nominal impedance of 100 ohm. Operation on other classes of cabling may be supported if the link segment meets the requirements of 98.7.

Cl 98 SC 98.7.1 P 124 L 2324 # 117
 Belopolsky, Yakov Bel Stewart
 Comment Type TR Comment Status D Cabling references
 40GBASE-T is intended to operate over the cabling that meets the requirements of the ISO/IEC 111801 standard that specially supports 40G, that standard include Class I and Class II channels and in fact recognizes that components of categories 6a and 7a or better can support such transmission. The statement t that 40GBase is designed to operate over Class I cabling is incorrect
 SuggestedRemedy
 remove the " Class I" or replace with "at least Class I"
 Proposed Response Response Status W
 PROPOSED REJECT.
 See response to comment#104 and comment#117

IEEE P802.3bq - 40GBASE-T 1st Task Force review comments

Cl 98 **SC 98.7.1** **P 124** **L 24** # **105**
 Zimmerman, George CME Consulting, Inc.

Comment Type **T** **Comment Status** **D**

"additional requirements" relative to class I? I don't think we have any

SuggestedRemedy
 delete "additional" - scrub document for other instances

Proposed Response **Response Status** **W**
 PROPOSED REJECT.
 See
 98.7.2.2 Differential characteristic impedance.
 In addition, like to keep the "additional" until we reach closure on link segment specifications.

Cl 98 **SC 98.7.2** **P 124** **L 28** # **129**
 Cibula, Peter Intel Corporation

Comment Type **T** **Comment Status** **D**

Consider whether Subclause 98.7.2 should include link segment transmission parameters appropriate for shielded cabling system characteristics.

SuggestedRemedy
 Discuss adding coupling attenuation and/or other characteristics as a transmission parameter(s) for shielded link segments.

Clause 98.7 states that 40GBASE-T is designed to operate over ISO/IEC 11801 Class I 4-pair balanced cabling, and defines a link segment based upon copper media specified by ISO/IEC JTC1/SC25/WG3 and TIA TR42.7. The corresponding draft specifications, PN-568-C.2-1, Draft 2.0c (to be published as ANSI/TIA-568-C.2-1) and ISO/IEC JTC 1/SC 25 DTR 11801-99-1 both include transmission requirements related to shielded implementations. The 40GBASE-T link segment should reflect those requirements and, of course, identify them as applying to shielded link segments.

Proposed Response **Response Status** **W**
 PROPOSED REJECT.
 Coupling attenuation measurements (laboratory) are used to characterize cabling electromagnetic immunity and not directly related to transmission parameters (i.e., the link segment transmission parameters) and transmission performance (SNR). The link segment alien crosstalk specifications indirectly characterizes cabling electromagnetic immunity as well as providing basis for transmission performance (SNR). In addition, 802.3bq references both ISO/IEC Class I and TIA Category 8 in which cabling characteristics related to the shielding performance are specified as well as other specifications not directly related to system performance (SNR). 802.3bq does not specify to characterize the link segment transmission performance.

Cl 98 **SC 98.7.2** **P 124** **L 3042** # **118**
 Belopolsky, Yakov Bel Stewart

Comment Type **TR** **Comment Status** **D** **Cabling references**

40GBASE-T is intended to operate over the cabling that meets the requirements of the ISO/IEC 111801 standard that specially supports 40G, that standard include Class I and Class II channels and in fact recognizes that components of categories 6a and 7a or better can support such transmission. The statement that 40GBase is designed to operate over Class I cabling is incorrect
 Table 98.18 is incorrect

SuggestedRemedy
 line 30 remove the " Class I" or replace with "at least Class I"
 Line 42 Table 98.18 remove Category 8 replace with ISO/IEC Classes I or II

Proposed Response **Response Status** **W**
 PROPOSED REJECT. See response to comment#104 and comment#117

Cl 98 **SC 98.7.2.1** **P 124** **L 48** # **12**
 Larsen, Wayne CommScope

Comment Type **T** **Comment Status** **D**

The IEEE IL formula can be more onerous than the ISO formula by up to 0.01 dB in the frequency range of about 1-50 MHz. Not sure anything needs to be done about this.

SuggestedRemedy

Proposed Response **Response Status** **W**
 PROPOSED REJECT. Commenter has not characterized problem to address or suggested remedy.

Cl 98 **SC 98.7.2.3** **P 125** **L 21** # **86**
 Zimmerman, George CME Consulting, Inc.

Comment Type **ER** **Comment Status** **D** **Editorial**

Equation 98-14 says "log" without showing it is a base-10 logarithm

SuggestedRemedy
 Change "log f" to "log₁₀ f" in equation 98-14 consistent with IEEE style

Proposed Response **Response Status** **W**
 PROPOSED ACCEPT.

IEEE P802.3bq - 40GBASE-T 1st Task Force review comments

Cl 98 SC 98.7.2.3 P 125 L 21 # 14
Larsen, Wayne CommScope
Comment Type E Comment Status D
Combine lines 4 and 5 of equation 98-14 into one line.
SuggestedRemedy
Proposed Response Response Status W
PROPOSED ACCEPT.
See response comment#1

Cl 98 SC 98.7.2.3 P 142 L 25 # 1
DiMinico, Christopher MC Communications
Comment Type ER Comment Status D Editorial
EQ 98-14 redundant frequency range
SuggestedRemedy
delete line in brackets {8 1600<f<=2000}
change {8 1600<f<=2000} to {8 1000<f<=2000}
Proposed Response Response Status W
PROPOSED ACCEPT.

Cl 98 SC 98.7.2.4.1 P 125 L 45 # 13
Larsen, Wayne CommScope
Comment Type T Comment Status D
We should fill in something to replace the TBD for (pair-to-pair) NEXT. The equations should be chosen to support both the TIA and ISO equations.
SuggestedRemedy
Use the TIA equation for 1-1486 MHz, and the ISO equation from 1486-2000 MHz. These equations will be provided in a contribution (They are also available from the drafts).
Proposed Response Response Status W
PROPOSED ACCEPT IN PRINCIPLE.
For committee review of commenter's presentation.

Cl 98 SC 98.7.2.4.1 P 125 L 46 # 106
Zimmerman, George CME Consulting, Inc.
Comment Type TR Comment Status D
pair-to-pair NEXT loss is unspecified (equation 98-15)
SuggestedRemedy
Specify pair-to-pair next loss consistent with MDNEXT loss in 98.7.2.4.2
Proposed Response Response Status W
PROPOSED ACCEPT IN PRINCIPLE.
See comment#13

Cl 98 SC 98.7.2.4.2 P 126 L 1 # 16
Larsen, Wayne CommScope
Comment Type T Comment Status D
There is no reason to have both terms "MDNEXT" and "PSNEXT". The text as it is written does not explicitly say that those are the same. Clause .2, titled MDNEXT, seems to give the requirement, and clause .3, titled PSNEXT, seems to give an explanation of how to calculate it from measured data. Other SDOs use the term "PSNEXT" but they do not use the term "MDNEXT".
SuggestedRemedy
Change the title of 98.7.2.4.2 to "Multiple disturber power-sum near-end crosstalk (PSNEXT) loss (same as the present title of .3). Delete the present clause heading of 98.7.2.4.3, so that the material therein becomes part of .2. Renumber sub-sequent clauses.

Proposed Response Response Status W
PROPOSED ACCEPT IN PRINCIPLE.
The use of multiple disturber crosstalk used here is consistent BASE-T and twinaxial PHYs (802.3ba, 802.3bj). Multiple disturber is related to the signalling topology (e.g., number of pairs) and provides the basis for understanding the need to combine crosstalk between duplex channels provided in the text.
Text is explicit:
"To ensure the total NEXT coupled into a duplex channel is limited, multiple disturber NEXT loss is specified as the power sum of individual NEXT losses."
Power summation is a calculation used here and in other SDO's to sum the individual NEXT losses also given in the text.

IEEE P802.3bq - 40GBASE-T 1st Task Force review comments

Cl 98 **SC 98.7.2.4.2** **P 126** **L 14** # **107**
 Zimmerman, George CME Consulting, Inc.
Comment Type ER **Comment Status D** *Editorial*
 equations 98-16, 98-17, 98-18 say "lg" rather than "log"
SuggestedRemedy
 change equation to read "log_10" consistent with IEEE style
Proposed Response **Response Status W**
 PROPOSED ACCEPT.

Cl 98 **SC 98.7.2.4.2** **P 126** **L 33** # **15**
 Larsen, Wayne CommScope
Comment Type T **Comment Status D**
 The IEEE PSNEXT (MDNEXT) requirement is more onerous than the ISO spec by up to 0.02 dB in the frequency range from 1078 MHz to 1100 MHz. Not sure how serious this is, but a remedy is proposed that will overcome it.
SuggestedRemedy
 Change the value 1100 to 1078 in two places. Lines 33 and 45.
Proposed Response **Response Status W**
 PROPOSED REJECT. Motion to approve equations refers to zimmerman_3bq_03a_0914.pdf illustrating differences and noting negligible effect. Motion #6: Move that 802.3bq accept the equations for PSNEXT and PSACRF on slides 5 & 6 of zimmerman_3bq_03a_0914.pdf as baseline text for the link segment PSNEXT and PSACRF requirements, with editorial license to make the equations consistent with 802.3 draft
 M: George Zimmerman S: Chris Diminico
 Technical (> 75%)
 Y: 18 N: 1 A: 3
 MOTION PASSES
 Commenter has not provided additional information pointing out a problem.

Cl 98 **SC 98.7.2.4.4** **P 127** **L 47** # **17**
 Larsen, Wayne CommScope
Comment Type T **Comment Status D**
 We need to fill in something for the TBD for ACRF. The TIA is more onerous than the ISO by 0.008 dB at every frequency point, based on my calculations. Doesn't make much difference, but suggest using the TIA equation for this reason.
SuggestedRemedy
 replace the TBD on line 47 with the TIA ACRF requirement. It will be provided in a contribution or can be obtained from the draft.
Proposed Response **Response Status W**
 PROPOSED ACCEPT IN PRINCIPLE.
 For committee review of referenced contribution.

Cl 98 **SC 98.7.2.4.5** **P 128** **L 14** # **19**
 Larsen, Wayne CommScope
Comment Type T **Comment Status D**
 There is no reason to have both terms "MDACRF" and "PSACRF". The text as it is written does not explicitly say that those are the same. Clause .5, titled MDACRF, seems to give the requirement, and clause .6, titled PS ACRF, seems to give an explanation of how to calculate it from measured data. Other SDOs use the term "PSARCF" but they do not use the term "MDACRF".
SuggestedRemedy
 Change the title of 98.7.2.4.5 to "Multiple disturber power-sum equal level far-end crosstalk (PSACRF) loss (same as the present title of .6). Delete the present clause heading of 98.7.2.4.6, so that the material therein becomes part of .2. Renummer sub-sequent clauses.
Proposed Response **Response Status W**
 PROPOSED REJECT.
 See response comment #16

Cl 98 **SC 98.7.2.4.5** **P 128** **L 23** # **18**
 Larsen, Wayne CommScope
Comment Type T **Comment Status D**
 The equaiton used was the pair-to-pair ACRF equaiton, not the power sum, in error.
SuggestedRemedy
 In equation 98-24, change 39 to 36, and change 43.1 to 40.1.
Proposed Response **Response Status W**
 PROPOSED ACCEPT.

IEEE P802.3bq - 40GBASE-T 1st Task Force review comments

CI **98** SC **98.7.2.5** P **128** L **53** # **20**
Larsen, Wayne CommScope

Comment Type **T** Comment Status **D**

The cabling channel will comply with 176 ns at 2000 MHz, but it has an increasing delay as the frequency becomes lower. We need to use an equation. Also, the requirement needs to apply starting at 1 MHz, not starting at 2.

Alternatively, we could specify less than 187 ns at all f from 1-2000 MHz or less than 179 ns from 10-2000 ns.

SuggestedRemedy

Use the TIA equation for this. It will be provided in a contribution or can be obtained from the draft.

Proposed Response Response Status **W**

PROPOSED ACCEPT IN PRINCIPLE.
Link segment delay starting frequency of 2MHz is consistent with BASE-T PHYs.
We need to carefully consider increasing delay requirements.

Options for delay limits:

- > leave limits as specified and cabling standards to align
- > align with cabling standards

To align with TIA as commenter suggests

Change: The propagation delay of a link segment shall not exceed 176 ns at all frequencies between 2 MHz and 2000 MHz.

To: The propagation delay of a link segment shall not exceed 185 ns at all frequencies between 2 MHz and 2000 MHz

For committee discussion.

CI **98** SC **98.7.2.6** P **129** L **4** # **3**
Larsen, Wayne CommScope

Comment Type **T** Comment Status **D**

The range should be from 1-2000 MHz, not 2-500 MHz.

SuggestedRemedy

Change the range to 1 MHz to 2000 MHz.

Proposed Response Response Status **W**

PROPOSED ACCEPT IN PRINCIPLE.
Link segment delay starting frequency 2 MHz consistent with BASE-T PHYs.
Change: 2 MHz to 500 MHz
to: 2 MHz to 2000 MHz

CI **98** SC **98.8.1** P **131** L **38** # **4**
Larsen, Wayne CommScope

Comment Type **T** Comment Status **D** MDI

The specification of the MDI was not updated correctly based on motion 7 from the September meeting.

SuggestedRemedy

Change from

IEC 60603-7-4 (unscreened) or IEC 60603.7-5 (screened)

change to

IEC 60603-7-51 (published) with the improved characteristics and frequency extensions specified in 60603-7-81 (currently CDV draft)

Proposed Response Response Status **W**

PROPOSED ACCEPT.

CI **98** SC **98.8.1** P **131** L **39** # **108**
Zimmerman, George CME Consulting, Inc.

Comment Type **ER** Comment Status **D** MDI

section does not implement resolution of motion 12 at September interim: "Move that 802.3bq include the RJ-45 as reflected in IEC 60603-7-51 (published) with the improved characteristics and frequency extensions specified in 60603-7-81 (currently CDV draft) as an MDI interface"

(apologies of the editor - I made this edit and it must have gotten lost in a crash...)

SuggestedRemedy

Replace first sentence ("Eight pin...") with: "Eight-pin connectors meeting the requirements of IEC 60603-7-51 with improved characteristics and frequency extensions specified in IEC 60603-7-81 (currently in CDV draft) shall be used as the mechanical interface to the balanced cabling.

Proposed Response Response Status **W**

PROPOSED ACCEPT IN PRINCIPLE.
- see comment 4

IEEE P802.3bq - 40GBASE-T 1st Task Force review comments

CI 98 SC 98.8.1 P 131,132 L # 119
Belopolsky, Yakov Bel Stewart

Comment Type TR Comment Status D MDI

40GBASE-T is intended to operate over the cabling that meets the requirements of the ISO/IEC 111801 standard that specially supports 40G, that standard include Class I and Class II channels and in fact recognizes that components of categories 6a and 7a or better can support such transmission .
The reference to IEC 60603-7-4 (unscreened) and IEC 606-7-5 (screened) is not correct
The use of unscreened connectors in the 2000MHz transmission is not supported by technical evidence known to the commenter.
The informational pictures 98-41 and 98-42 are misleading. The information on the recognized connectors is contained in the IEC/ISO TR 11801-99-01

(An animal with four legs is not always a horse)

SuggestedRemedy

remove pictures 98-41 and 98-42
Line 39 remove " IEC 60603-7-4 (unscreened) and IEC 606-7-5 (screened)" replace with "connectors recognized by IEC/ISO TR 11801-99-01"
preferred text : "connectors categories 8.1 or 8.2 recognized by IEC/ISO 11801

Line 41 remove the sentence starting with "These connectors are depicted..."

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.
Resolve with comment 4

In accordance with Motion#12 during 40GBASE-T Task Force
September 9-10, 2014. Revise 98.8.1 to include IEC references.
From: Eight-pin connectors meeting the requirements of IEC 60603-7-4 (unscreened) or IEC 60603-7-5 (screened) shall be used as the mechanical interface to the balanced cabling.
To: Eight-pin connectors meeting the requirements of IEC 60603-7-51 (published) with the improved characteristics and frequency extensions specified in IEC 60603-7-81 shall be used as the mechanical interface to the balanced cabling.
Update figures if necessary to represent the referenced connectors.

Motion #12 (Motion #7 reconsidered):
Move that 802.3bq include the RJ-45 as reflected in IEC 60603-7-51 (published) with the improved characteristics and frequency extensions specified in 60603-7-81 (currently in CDV draft) as an MDI interface
M: Jerry Chiang S: Peter Wu
Technical (> 75%)
Y: 16 N: 5 A: 2
MOTION PASSES

CI 98 SC 98.8.2.1 P 132 L 46 # 5
Larsen, Wayne CommScope

Comment Type T Comment Status D MDI

The requiements need to be extended to 2000 MHz. The 6 dB level as a flat plateau might be fine.

This editor's note would be accurt, if it applies to the connector by itself, free of magnitics and PCB mounting. This product is normally produced as an integrated module containing the conntor and the magnetic isolation coils. For this assembly, the return loss values in equation 98-31 are about right.

SuggestedRemedy

Delete the editor's note.

Add a new line, speciuifying RL of 6 dB, flat plateau, from 500 MHz to 2000 MHz.

Proposed Response Response Status W

PROPOSED ACCEPT.

CI 98 SC 98.8.2.2 P 133 L 15 # 11
Larsen, Wayne CommScope

Comment Type T Comment Status D MDI

To extend the MDI impedance balance requiement to 2000 MHz.

It seems this change was supposed to be implimented in the last cycle but was not implimented for some reason.

SuggestedRemedy

Change 500 to 2000 in equation 98-32.

Proposed Response Response Status W

PROPOSED ACCEPT.

CI 98 SC 98.8.2.2 P 134 L 1 # 6
Larsen, Wayne CommScope

Comment Type T Comment Status D MDI

The test procedures on this page can be improved.

Specific comments on how to improve them have been provided in the past.

SuggestedRemedy

Proposed Response Response Status W

PROPOSED REJECT.
Committer has not provided sufficient information to implement changes in draft

IEEE P802.3bq - 40GBASE-T 1st Task Force review comments

CI 98 SC 98.8.2.3 P 134 L 45 # 7
Larsen, Wayne CommScope

Comment Type T Comment Status D MDI

Thinking this is intended to prevent damage to the PHY itself and other electronic elements, not so much the MDI.

Since it is not really an MDI requirement, consider moving it to another place in the standard. The editor's note on line 53 alludes to this.

SuggestedRemedy

from:
each wire pair of the MDI shall, under all operation conditions, withstand without damage the application of short circuits of any wire to any other wire within the connected 4-pair cable to:
The electronic equipment containing a 40GBASE-T PHY shall, under all operation conditions, withstand without damage the application of short circuits of any wire to any other wire within the connected 4-pair cable

Proposed Response Response Status W

PROPOSED REJECT.
- Editor's note referred to the second paragraph ("A 40GBASE-T PHY...") Proposed resolution refers to the requirement on the MDI in the first paragraph of the subclause

See also comments 8 & 109

CI 98 SC 98.8.2.3 P 134 L 50 # 109
Zimmerman, George CME Consulting, Inc.

Comment Type E Comment Status D MDI

The requirement "A 40GBASE-T PHY shall be able to sustain" relates to the PHY not just the MDI - as such it is misplaced.

SuggestedRemedy

Move lines 50 - 54 on page 134 and 1-3 on page 135 to 98.5.1 Isolation requirements, or, optionally, add a new clause after 98.5.1 to speak to this requirement.
delete editors note

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.
DISCUSS - see also comments 7 & 8

CI 98 SC 98.8.2.3 P 135 L 1 # 8
Larsen, Wayne CommScope

Comment Type T Comment Status D MDI

Agree with the editor's note at the end of page 134. The wording of this sentence can be improved, and a suggestion is made below. Also agree this requirement should be moved to the isolation section.

SuggestedRemedy

From:
each wire pair shall withstand without damage a 1000 V common-mode impulse of either polarity.
To:
The electronic equipment containing a 40GBASE-T PHY shall withstand without damage a 1000 V common-mode impulse applied to any wire pair, of either polarity.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.
- see comment 109
See also comment 7

CI 99 SC P L 28 # 120
Lusted, Kent Intel

Comment Type E Comment Status D Editorial

IEEE Std 802.3bj-2014 now exists. Add a reference

SuggestedRemedy

Add 802.3bj and the relevant supporting text.

Proposed Response Response Status W

PROPOSED ACCEPT.

CI 99 SC P L 3 # 113
Zimmerman, George CME Consulting, Inc.

Comment Type E Comment Status D Editorial

Amendment should be : bq, not X

SuggestedRemedy

Substitute in at appropriate phase of editing

Proposed Response Response Status W

PROPOSED ACCEPT.

IEEE P802.3bq - 40GBASE-T 1st Task Force review comments

<i>Cl</i> 99	<i>SC</i>	<i>P</i> 2	<i>L</i> 1	# 112
Zimmerman, George		CME Consulting, Inc.		
<i>Comment Type</i>	ER	<i>Comment Status</i>	D	<i>Editorial</i>
Table of Contents is a placeholder				
<i>SuggestedRemedy</i>				
Fix production of book so Table of Contents is generated correctly				
<i>Proposed Response</i>	<i>Response Status</i>		W	
PROPOSED ACCEPT.				

<i>Cl</i> 99	<i>SC</i>	<i>P</i> 3	<i>L</i> 36	# 110
Zimmerman, George		CME Consulting, Inc.		
<i>Comment Type</i>	E	<i>Comment Status</i>	D	<i>Editorial</i>
Draft needs to add letters of amendment. (802.3bq)				
<i>SuggestedRemedy</i>				
Substitute 802.3bq for 802.3xx (global)				
<i>Proposed Response</i>	<i>Response Status</i>		W	
PROPOSED ACCEPT IN PRINCIPLE.				
Substitution will happen at appropriate phase of editing.				

<i>Cl</i> 99	<i>SC</i>	<i>P</i> 4	<i>L</i> 26	# 111
Zimmerman, George		CME Consulting, Inc.		
<i>Comment Type</i>	E	<i>Comment Status</i>	D	<i>Editorial</i>
List of amendments appears incomplete, 802.3bj, possibly others missing				
<i>SuggestedRemedy</i>				
Check amendments listed and include all relevant ones				
<i>Proposed Response</i>	<i>Response Status</i>		W	
PROPOSED ACCEPT. - see comment 120				