

IEEE P802.3bq - 40GBASE-T 1st Task Force review comments

CI 98 SC 98.7.2.3 P 142 L 25 # 1

DiMinico, Christopher

MC Communications

Comment Type ER Comment Status X

EQ 98-14 redundant frequency range

SuggestedRemedy

delete line in brackets {8 1600<f<=2000}
change {8 1600<f<=2000} to {8 1000<f<=2000}

Proposed Response

Response Status O

CI 98 SC 98.5.4.5.1 P 135 L 22 # 2

DiMinico, Christopher

MC Communications

Comment Type T Comment Status X

98.5.4.5.1 Short reach test channel text provided in contribution
per Ed note to delete or replace text with an appropriate short reach channel....

SuggestedRemedy

see contribution diminico_3bq_01_1114.pdf

Proposed Response

Response Status O

CI 98 SC 98.7.2.6 P 129 L 4 # 3

Larsen, Wayne

CommScope

Comment Type T Comment Status X

The range should be from 1-2000 MHz, not 2-500 MHz.

SuggestedRemedy

Change the range to 1 MHz to 2000 MHz.

Proposed Response

Response Status O

CI 98 SC 98.8.1 P 131 L 38 # 4

Larsen, Wayne

CommScope

Comment Type T Comment Status X

The specification of the MDI was not updated correctly based on motion 7 from the September meeting.

SuggestedRemedy

Change from

IEC 60603-7-4 (unscreened) or IEC 60603.7-5 (screened)

change to

IEC 60603-7-51 (published) with the improved characteristics and frequency extensions
sepcified in 60603-7-81 (currently CDV draft)

Proposed Response

Response Status O

CI 98 SC 98.8.2.1 P 132 L 46 # 5

Larsen, Wayne

CommScope

Comment Type T Comment Status X

The requiriements need to be extended to 2000 MHz. The 6 dB level as a flat plateau might be fine.

This editor's note would be accurte, if it applies to the connector by itself, free of magnitics and PCB mounting. This product is normally produced as an integrated module containing the conntor and the magnetic isolation coils. For this assembly, the return loss values in equation 98-31 are about right.

SuggestedRemedy

Delete the editor's note.

Add a new line, speciuifying RL of 6 dB, flat plateau, from 500 MHz to 2000 MHz.

Proposed Response

Response Status O

IEEE P802.3bq - 40GBASE-T 1st Task Force review comments

CI 98 SC 98.8.2.2 P 134 L 1 # 6
Larsen, Wayne CommScope

Comment Type T Comment Status X

The test procedures on this page can be improved.

Specific comments on how to improve them have been provided in the past.

SuggestedRemedy

Proposed Response Response Status O

CI 98 SC 98.8.2.3 P 134 L 45 # 7
Larsen, Wayne CommScope

Comment Type T Comment Status X

Thinking this is intended to prevent damage to the PHY itself and other electronic elements, not so much the MDI.

Since it is not really an MDI requirement, consider moving it to another place in the standard. The editor's note on line 53 alludes to this.

SuggestedRemedy

from:
each wire pair of the MDI shall, under all operation conditions, withstand without damage the application of short circuits of any wire to any other wire within the connected 4-pair cable to:
The electronic equipment containing a 40GBASE-T PHY shall, under all operation conditions, withstand without damage the application of short circuits of any wire to any other wire within the connected 4-pair cable

Proposed Response Response Status O

CI 98 SC 98.8.2.3 P 135 L 1 # 8
Larsen, Wayne CommScope

Comment Type T Comment Status X

Agree with the editor's note at the end of page 134. The wording of this sentence can be improved, and a suggestion is made below. Also agree this requirement should be moved to the isolation section.

SuggestedRemedy

From:
each wire pair shall withstand without damage a 1000 V common-mode impulse of either polarity.
To:
The electronic equipment containing a 40GBASE-T PHY shall withstand without damage a 1000 V common-mode impulse applied to any wire pair, of either polarity.

Proposed Response Response Status O

CI 98 SC 98.12.7 P 146 L 15 # 9
Larsen, Wayne CommScope

Comment Type E Comment Status X

To align with the terminology used in clause 98.7.

SuggestedRemedy

in table entries LKS6, LKS7, and LKS15, change "FEXT" to "ACRF"

Proposed Response Response Status O

CI 98 SC 98.12.7 P 146 L 24 # 10
Larsen, Wayne CommScope

Comment Type T Comment Status X

To align the contents of this table with clause 98.7. The items listed are not included in clause 98.7.

SuggestedRemedy

Delete table entries LKS12, LKS13, LKS14, LKS16, LKS17, LKS18, and LKS19.

Proposed Response Response Status O

IEEE P802.3bq - 40GBASE-T 1st Task Force review comments

CI 98 SC 98.8.2.2 P 133 L 15 # 11
Larsen, Wayne CommScope

Comment Type T Comment Status X

To extend the MDI impedance balance requirement to 2000 MHz.

It seems this change was supposed to be implemented in the last cycle but was not implemented for some reason.

SuggestedRemedy

Change 500 to 2000 in equation 98-32.

Proposed Response Response Status O

CI 98 SC 98.7.2.1 P 124 L 48 # 12
Larsen, Wayne CommScope

Comment Type T Comment Status X

The IEEE IL formula can be more onerous than the ISO formula by up to 0.01 dB in the frequency range of about 1-50 MHz. Not sure anything needs to be done about this.

SuggestedRemedy

Proposed Response Response Status O

CI 98 SC 98.7.2.4.1 P 125 L 45 # 13
Larsen, Wayne CommScope

Comment Type T Comment Status X

We should fill in something to replace the TBD for (pair-to-pair) NEXT. The equations should be chosen to support both the TIA and ISO equations.

SuggestedRemedy

Use the TIA equation for 1-1486 MHz, and the ISO equation from 1486-2000 MHz. These equations will be provided in a contribution (They are also available from the drafts).

Proposed Response Response Status O

CI 98 SC 98.7.2.3 P 125 L 21 # 14
Larsen, Wayne CommScope

Comment Type E Comment Status X

Combine lines 4 and 5 of equation 98-14 into one line.

SuggestedRemedy

Proposed Response Response Status O

CI 98 SC 98.7.2.4.2 P 126 L 33 # 15
Larsen, Wayne CommScope

Comment Type T Comment Status X

The IEEE PSNEXT (MDNEXT) requirement is more onerous than the ISO spec by up to 0.02 dB in the frequency range from 1078 MHz to 1100 MHz. Not sure how serious this is, but a remedy is proposed that will overcome it.

SuggestedRemedy

Change the value 1100 to 1078 in two places. Lines 33 and 45.

Proposed Response Response Status O

CI 98 SC 98.7.2.4.2 P 126 L 1 # 16
Larsen, Wayne CommScope

Comment Type T Comment Status X

There is no reason to have both terms "MDNEXT" and "PSNEXT". The text as it is written does not explicitly say that those are the same. Clause .2, titled MDNEXT, seems to give the requirement, and clause .3, titled PSNEXT, seems to give an explanation of how to calculate it from measured data. Other SDOs use the term "PSNEXT" but they do not use the term "MDNEXT".

SuggestedRemedy

Change the title of 98.7.2.4.2 to "Multiple disturber power-sum near-end crosstalk (PSNEXT) loss (same as the present title of .3). Delete the present clause heading of 98.7.2.4.3, so that the material therein becomes part of .2. Renumber sub-sequent clauses.

Proposed Response Response Status O

IEEE P802.3bq - 40GBASE-T 1st Task Force review comments

CI 98 SC 98.7.2.4.4 P 127 L 47 # 17
Larsen, Wayne CommScope

Comment Type T Comment Status X

We need to fill in something for the TBD for ACRF. The TIA is more onerous than the ISO by 0.008 dB at every frequency point, based on my calculations. Doesn't make much difference, but suggest using the TIA equation for this reason.

SuggestedRemedy

replace the TBD on line 47 with the TIA ACRF requirement. It will be provided in a contribution or can be obtained from the draft.

Proposed Response Response Status O

CI 98 SC 98.7.2.4.5 P 128 L 23 # 18
Larsen, Wayne CommScope

Comment Type T Comment Status X

The equaiton used was the pair-to-pair ACRF equaiton, not the power sum, in error.

SuggestedRemedy

In equation 98-24, change 39 to 36, and change 43.1 to 40.1.

Proposed Response Response Status O

CI 98 SC 98.7.2.4.5 P 128 L 14 # 19
Larsen, Wayne CommScope

Comment Type T Comment Status X

There is no reason to have both terms "MDACRF" and "PSACRF". The text as it is written does not explicitly say that those are the same. Clause .5, titled MDACRF, seems to give the requirement, and clause .6, titled PS ACRF, seems to give an explanation of how to calculate it from measured data. Other SDOs use the term "PSARCF" but they do not use the term "MDACRF".

SuggestedRemedy

Change the title of 98.7.2.4.5 to "Multiple disturber power-sum equal level far-end crosstalk (PSACRF) loss (same as the present title of .6). Delete the present clause heading of 98.7.2.4.6, so that the material therein becomes part of .2. Renumber sub-sequent clauses.

Proposed Response Response Status O

CI 98 SC 98.7.2.5 P 128 L 53 # 20
Larsen, Wayne CommScope

Comment Type T Comment Status X

The cabling channel will comply with 176 ns at 2000 MHz, but it has an increasing delay as the frequency becomes lower. We need to use an equation. Also, the requirement needs to apply starting at 1 MHz, not starting at 2.

Alternatively, we could specify less than 187 ns at all f from 1-2000 MHz or less than 179 ns from 10-2000 ns.

SuggestedRemedy

Use the TIA equation for this. It will be provided in a contribution or can be obtained from the draft.

Proposed Response Response Status O

CI 00 SC 0 P L # 21
McClellan, Brett Marvell

Comment Type E Comment Status X

subclause headers don't match 802.3-2012
for example 45.2.1.66 in draft 1.0 is register 1.129 but in 802.3-2012 it is reg 1.134. 45.2.3.12 in draft 1.0 is 3.10.20 in 802.3-2012 it is 3.25.
Are the headers in the draft supposed to reference 802.3-2012? or to a later amendment?

SuggestedRemedy

check that headers are correct

Proposed Response Response Status O

CI 45 SC 45.2.1.66.2 P 22 L 13 # 22
McClellan, Brett Marvell

Comment Type T Comment Status X

45.2.1.66.2 40GBASE-T LP information valid (1.129.1)
Adding a new bit for 40G seems unnecessary, can we reuse the 10GBASE-T bit, 1.129.0?
Otherwise we need to search and replace instances of 1.129.0 and replace with 1.129.1. See page 23 line 8.

SuggestedRemedy

delete bit 1.129.1 and rename 1.129.0 10/40GBASE-T LP information valid

Proposed Response Response Status O

IEEE P802.3bq - 40GBASE-T 1st Task Force review comments

CI 45 SC 45.2.3.12 P 26 L 29 # 23
McClellan, Brett Marvell

Comment Type E Comment Status X

"45.2.3.12 40GBASE-T EEE deep sleep supported (3.20.10)" doesn't match other EEE capability bit names.

SuggestedRemedy

change to:
"45.2.3.12 40GBASE-T EEE supported (3.20.10)"

Proposed Response Response Status O

CI 45 SC 45.2.7.10.6 P 30 L 28 # 24
McClellan, Brett Marvell

Comment Type T Comment Status X

Task force should consider making fast retrain mandatory.

SuggestedRemedy

If made mandatory, delete subclauses
45.2.7.10.6 40GBASE-T Fast retrain ability (7.32.3)
45.2.7.11.10 40GBASE-T Fast retrain ability (7.33.0)
modify tables accordingly
delete references to fast retrain "option" in Clause 98

Proposed Response Response Status O

CI 78 SC 78.3 P 38 L 1 # 25
McClellan, Brett Marvell

Comment Type E Comment Status X

"Table 78–2—Clauses associated with each interface type"
title is incorrect

SuggestedRemedy

change to:
"Table 78–2—Summary of the key EEE parameters for supported PHY"

Proposed Response Response Status O

CI 78 SC 78.4 P 38 L 33 # 26
McClellan, Brett Marvell

Comment Type E Comment Status X

pages 38 to 41 have unrelated editorial notes

SuggestedRemedy

remove this section

Proposed Response Response Status O

CI 98 SC 98.1.3 P 47 L 10 # 27
McClellan, Brett Marvell

Comment Type T Comment Status X

"The MASTER-SLAVE relationship may include loop timing. If loop timing is implemented, the SLAVE PHY recovers the clock"
Loop timing is required if EEE is supported. Task force should consider making loop timing required for 40GBASE-T to eliminate an option that likely will never be used (as in 10GBASE-T).

SuggestedRemedy

If made mandatory, change text to:
"The MASTER-SLAVE relationship requires. The SLAVE PHY recovers the clock"
modify other references in Clause 98 as required.

Proposed Response Response Status O

CI 98 SC 98.1.3 P 47 L 4 # 28
McClellan, Brett Marvell

Comment Type E Comment Status X

symbol period is 312.5ps not 325ps

SuggestedRemedy

change "325" to "312.5"

Proposed Response Response Status O

IEEE P802.3bq - 40GBASE-T 1st Task Force review comments

CI 98 SC 98.3.2.2 P 64 L 20 # 29

McClellan, Brett

Marvell

Comment Type E Comment Status X

typo "and split the bits into an two sets"

SuggestedRemedy

change "and split the bits into an two sets"

to

"and split the bits into two sets"

Proposed Response

Response Status O

CI 98 SC 98.3.2.2 P 64 L 29 # 30

McClellan, Brett

Marvell

Comment Type E Comment Status X

"symbol period, T, is 1.25 ns."

needs to be updated

SuggestedRemedy

change "symbol period, T, is 1.25 ns."

to

"symbol period, T, is 312.5 ps."

Proposed Response

Response Status O

CI 98 SC 98.3.2.2.16 P 73 L 3 # 31

McClellan, Brett

Marvell

Comment Type E Comment Status X

typo "The transcoder construct"
and "65- bit"

SuggestedRemedy

change to

"The transcoder constructs"

and

"65-bit"

Proposed Response

Response Status O

CI 98 SC 98.3.2.2.19 P 75 L 30 # 32

McClellan, Brett

Marvell

Comment Type T Comment Status X

auxiliary bit should be randomized

SuggestedRemedy

add text:

"It is highly recommended that the auxiliary bit be randomized."

Proposed Response

Response Status O

CI 98 SC 98.3.2.2.20 P 77 L 36 # 33

McClellan, Brett

Marvell

Comment Type E Comment Status X

figure 98-13, there is a line covering the text "p2"

SuggestedRemedy

remove line

Proposed Response

Response Status O

CI 98 SC 98.3.2.2.24 P 80 L 45 # 34

McClellan, Brett

Marvell

Comment Type T Comment Status X

1.2 us should be 1.12us

SuggestedRemedy

change 1.2 to 1.12

Proposed Response

Response Status O

CI 98 SC 98.3.4 P 83 L 13 # 35

McClellan, Brett

Marvell

Comment Type E Comment Status X

Figure 98-15 is missing/blank

SuggestedRemedy

fix the figure

Proposed Response

Response Status O

IEEE P802.3bq - 40GBASE-T 1st Task Force review comments

CI 98 SC 98.3.5.3 P 87 L 20 # 36
McClellan, Brett Marvell

Comment Type E Comment Status X
the proposal lacks the details needed for a specification

SuggestedRemedy

remove until we have a full baseline or change to editorial note

Proposed Response Response Status O

CI 98 SC 98.3.6.2.3 P 90 L 18 # 37
McClellan, Brett Marvell

Comment Type T Comment Status X
The 125 us timer should be changed to 125/4 or the effective error rate should be changed from 4E-4 to 1E-4.

SuggestedRemedy

change timer to 31us,
similarly change 125us to 31us in other locations

Proposed Response Response Status O

CI 98 SC 98.3.6.2.2 P 88 L 38 # 38
McClellan, Brett Marvell

Comment Type T Comment Status X
"b. CRC8 check is satisfied"
The CRC check was removed.

SuggestedRemedy

replace with
"b. the RS did not have an uncorrectable error"

Proposed Response Response Status O

CI 98 SC 98.3.6.2.5 P 92 L 33 # 39
McClellan, Brett Marvell

Comment Type T Comment Status X
line 33 and line 38
lpi_qr_time x 4
should be
lpi_qr_time x 6

SuggestedRemedy

change to lpi_qr_time x 6

Proposed Response Response Status O

CI 98 SC 98.4.2.4 P 105 L 41 # 40
McClellan, Brett Marvell

Comment Type T Comment Status X
"The receiver shall correct for differential delay variations of up to 50 ns across the wire-pairs."
50ns is excessive for a 30 meter channel.

SuggestedRemedy

change to 15ns

Proposed Response Response Status O

CI 98 SC 98.4.2.5.14 P 111 L 39 # 41
McClellan, Brett Marvell

Comment Type T Comment Status X
"PBO=4 (corresponding to a power backoff of 8 dB). "
needs to be updated for new PBO table

SuggestedRemedy

change to TBD until the PBO is selected for initial training

Proposed Response Response Status O

IEEE P802.3bq - 40GBASE-T 1st Task Force review comments

CI 98 SC 98.4.2.5.14 P 112 L 11 # 42
McClellan, Brett Marvell

Comment Type T Comment Status X

"the SLAVE shall request a desired PBO level that is within two levels (within 4 dB)"
4dB difference between devices is too large.
Task force should consider reducing the difference or the master selects PBO for both, or both use the smaller backoff setting.

SuggestedRemedy

both devices use the smaller backoff setting

Proposed Response Response Status O

CI 98 SC 98.4.2.5.14 P 112 L 18 # 43
McClellan, Brett Marvell

Comment Type T Comment Status X

"10ms" and "1ms"
absolute times should to be reduced by 4 corresponding to the 4x clock rate
Task force should consider reducing initial count settings.

SuggestedRemedy

change 10ms to 2.5ms
change 1ms to 250us

Proposed Response Response Status O

CI 98 SC 98.4.2.7 P 115 L 9 # 44
McClellan, Brett Marvell

Comment Type T Comment Status X

"50 complete quiet-refresh cycles (nominally equal to 512 us)"
should be $8.192/4 = 2.048$ ms

SuggestedRemedy

change 512us to 2.048ms

Proposed Response Response Status O

CI 98 SC 98.4.3.1 P 116 L 1 # 45
McClellan, Brett Marvell

Comment Type T Comment Status X

"power backoff (up to 14 dB)"
14dB is excessive, consider change the max PBO to 6dB

SuggestedRemedy

change 14dB to 6dB

Proposed Response Response Status O

CI 98 SC 98.4.2.5.7 P 109 L 53 # 46
McClellan, Brett Marvell

Comment Type TR Comment Status X

"frame error ratio of less than 3.2×10^{-9} "
this doesn't match other occurrences of frame error ratio of 9.6×10^{-9} page 134 line 2, line 28
page 135 line 14

SuggestedRemedy

change to: "frame error ratio of less than 9.6×10^{-9} "
also need to change page 158 line 11

Proposed Response Response Status O

CI 78 SC 78.1 P 73 L 14 # 47
Zimmerman, George CME Consulting, Inc.

Comment Type ER Comment Status X

While phy implementations may or may not support EEE, in the standard, EEE as a protocol supports the phys.

SuggestedRemedy

reverse edit to read "EEE supports the 100BASE-TX PHY, ..., and the 40GBASE-T PHY".

Proposed Response Response Status O

IEEE P802.3bq - 40GBASE-T 1st Task Force review comments

CI 78 SC 78.3 P 74 L 1 # 48
 Zimmerman, George CME Consulting, Inc.

Comment Type ER Comment Status X

Table 78-2 seems to have gotten the title of 78-1. In 802.3-2012, it is "Summary of the key EEE parameters for supported PHY"

SuggestedRemedy

Replace title of Table 78-2 with "Summary of the key EEE parameters for supported PHY"

Proposed Response Response Status O

CI 98 SC 98.1 P 12 L 28 # 49
 Zimmerman, George CME Consulting, Inc.

Comment Type T Comment Status X

Reference to media in ISO/IEC 11801:2002 is inappropriate - should be to Ed 3 draft

SuggestedRemedy

Replace reference with reference to ISO/IEC 11801 Edition 3 and ANSI/TIA-568-C.2-1-201x Addendum 1: Specifications for 100ohm Category 8 Cabling

Proposed Response Response Status O

CI 98 SC 98.1.1 P 28 L 34 # 50
 Zimmerman, George CME Consulting, Inc.

Comment Type ER Comment Status X

Remove editors notes in section

SuggestedRemedy

Remove editors notes under objectives

Proposed Response Response Status O

CI 98 SC 98.1.3 P 30 L 9 # 51
 Zimmerman, George CME Consulting, Inc.

Comment Type T Comment Status X

There are no known instances of 10GBASE-T implementing the alternate non-loop timed version. there has been no discussion that non-loop timed 40GBASE-T is technically feasible.

SuggestedRemedy

Remove references to optional loop timing in paragraph. (replace "may include" with "includes", delete "If loop timing is implmeented,", delete sentence beginning with "If loop timing is not implemented"

Proposed Response Response Status O

CI 98 SC 98.1.3 P 30 L 24 # 52
 Zimmerman, George CME Consulting, Inc.

Comment Type T Comment Status X

There have been no contributions to remove fast retrain

SuggestedRemedy

Delete editors note

Proposed Response Response Status O

CI 98 SC 98.1.3.1 P 33 L 9 # 53
 Zimmerman, George CME Consulting, Inc.

Comment Type E Comment Status X

Editors note flagging the clause has done its job

SuggestedRemedy

Delete editors note

Proposed Response Response Status O

IEEE P802.3bq - 40GBASE-T 1st Task Force review comments

CI 98 SC 98.1.4 P 35 L 34 # 54

Zimmerman, George CME Consulting, Inc.

Comment Type TR Comment Status X

bit width of TXD, TXC, RXD, RXC are incorrect for XLGMII

SuggestedRemedy

Replace TXD<31:0> with TXD<63:0>, RXD<31:0> with RXD<63:0>, TXC<3:0> with TXC<7:0>, and RXC<3:0> with RXD<7:0>

Proposed Response Response Status O

CI 98 SC 98.3.1 P 45 L 46 # 55

Zimmerman, George CME Consulting, Inc.

Comment Type ER Comment Status X

cross reference to clause 45 for XLGMII is incorrect

SuggestedRemedy

Should point to Clause 81 for XLGMII

Proposed Response Response Status O

CI 98 SC 98.3.2.2 P 47 L 20 # 56

Zimmerman, George CME Consulting, Inc.

Comment Type ER Comment Status X

extra "an"

SuggestedRemedy

delete "an" to rean "into two sets."

Proposed Response Response Status O

CI 98 SC 98.3.2.2.2 P 48 L 10 # 57

Zimmerman, George CME Consulting, Inc.

Comment Type E Comment Status X

encoding of 64/65b in 40GBASE-T (and 10GBASE-T) did not provide for clock recovery or relate to LDPC frame errors.

SuggestedRemedy

Delete sentences "The encoding defined...., and "The encoding also...", as shown in strikeout, and delete editors note.

Proposed Response Response Status O

CI 98 SC 98.3.2.2.4 P 48 L 49 # 58

Zimmerman, George CME Consulting, Inc.

Comment Type TR Comment Status X

Figure 98-9 needs to be redrawn with corrections - replace references to uncoded bits with references to RS coded bits, colors need to be letter or number coded

SuggestedRemedy

Correct figure 98-9 as discussed above and delete editors note

Proposed Response Response Status O

CI 98 SC 98.3.2.2.7 P 53 L 5 # 59

Zimmerman, George CME Consulting, Inc.

Comment Type ER Comment Status X

reference to 10 Gigabit Ethernet and Clause 46 should be 40 Gigabit Ethernet and Clause 81, and 81.3.4

SuggestedRemedy

Replace references as above

Proposed Response Response Status O

IEEE P802.3bq - 40GBASE-T 1st Task Force review comments

CI 28 SC 28.5.4.8 P 8 L 26 # 60

Zimmerman, George CME Consulting, Inc.

Comment Type TR Comment Status X

Autoneg requires additional changes:

Link fail inhibit timer is defined for 10/100/1000 (SD11) & separately for 10G (SD11a)

SuggestedRemedy

Extend definition of SD11a in 28.5.4.8 to include M: 40G (mandatory for 40G)

Proposed Response Response Status O

CI 28B SC 28B.3 P 9 L 1 # 61

Zimmerman, George CME Consulting, Inc.

Comment Type TR Comment Status X

Add 40GBASE-T to autoneg priority resolution

SuggestedRemedy

Add edit to normative Annex 28B, clause 28B.3 to insert 40GBASE-T above 10GBASE-T on the priority resolution list and renumber list accordingly

Proposed Response Response Status O

CI 28C SC 28C.11 P 9 L 2 # 62

Zimmerman, George CME Consulting, Inc.

Comment Type E Comment Status X

name of message code in 28C.11 doesn't include 10GBASE-T
also listed as code 9 in Table 28C-1 doesn't include 10GBASE-T

SuggestedRemedy

Change message code 9 name from: "10GBASE-T/1000BASE-T Technology message code (Extended Next Page)" to:

"Gigabit BASE-T Technology message code (Extended Next Page)"

Include 40GBASE-T (Clause 98) in the list of referenced clauses in 28C.11

Make appropriate changes to Clauses, 40, 55, and 98 to reflect the name change (see comment on 98.6.2)

Proposed Response Response Status O

CI 28D SC 6 P 9 L 1 # 63

Zimmerman, George CME Consulting, Inc.

Comment Type TR Comment Status X

Annex 28D.6, changes for 10GBASE-T needs to also include 40GBASE-T

SuggestedRemedy

Insert section 28D.7 with same text as 28D.6 and change references to reflect 40GBASE-T and Clause 98, including variable 40GigT

Proposed Response Response Status O

CI 30 SC 30.2.5 P 9 L 1 # 64

Zimmerman, George CME Consulting, Inc.

Comment Type T Comment Status X

Clause 30, requires minor changes:

1. extending 10G operating margin package to 40G (Table 30-1e "10GBASE-T operating margin package")
2. include 40GBASE-T Clause 98 in 30.3.2.1.2aPhyType and 30.3.2.1.3 aPhyTypeList
3. Edit 10GBASE-T SNR margin and fast retrain counts to include 40GBASE-T as well
4. Add 40GBASE-T to 30.6.1.1.5 aAutoNegLocalTechnologyAbility

SuggestedRemedy

1. Change label of column in Table 30-1e to "10G/40GBASE-T operating margin package (conditional)"
2. Add 40GBASE-T Clause 98 in 30.3.2.1.2aPhyType and 30.3.2.1.3 aPhyTypeList
3. Edit 30.5.1.1.19 through 30.5.1.1.22, and 30.5.1.1.24 & 25 to include 40GBASE-T with 10GBASE-T
4. Add 40GBASE-T to 30.6.1.1.5 aAutoNegLocalTechnologyAbility list

Proposed Response Response Status O

CI 31B SC 3.7 P 9 L 2 # 65

Zimmerman, George CME Consulting, Inc.

Comment Type T Comment Status X

Consider whether 40GBASE-T needs special treatment for PAUSE operation, as 10GBASE-T did relative to other 10G PHYs.

SuggestedRemedy

Discuss - no specific remedy

Proposed Response Response Status O

IEEE P802.3bq - 40GBASE-T 1st Task Force review comments

CI 45 SC 45.2.1.66 P 13 L 3 # 66
Zimmerman, George CME Consulting, Inc.
Comment Type E Comment Status X
subclause appears to relate only to register 1.129, although title is amended to add "and 1.130"
SuggestedRemedy
Delete "and 1.130" from title
Proposed Response Response Status O

CI 45 SC 2.1 P 10 L 20 # 67
Zimmerman, George CME Consulting, Inc.
Comment Type ER Comment Status X
Missing "/"
SuggestedRemedy
Change to 10GBASE-T/40GBASE-T
Proposed Response Response Status O

CI 45 SC 45.2.1.66.2 P 13 L 13 # 68
Zimmerman, George CME Consulting, Inc.
Comment Type T Comment Status X
No need for both a 10GBASE-T LP information valid bit and a 40GBASE-T LP information valid bit. This also includes Table 45-54

If the new bit for 40GBASE-T is to be kept, paragraph references the wrong (10GBASE-T) bit on line 17.
SuggestedRemedy
Delete inserted paragraph, and edit paragraph 45.2.1.66.1 10GBASE-T LP information valid (1.129.0) to be "40/10GBASE-T LP information valid"

If the paragraph is not deleted, correct the reference on line 17 to bit 1.129.0 which should be 1.129.1

Proposed Response Response Status O

CI 45 SC 45.2.3.12 P 17 L 28 # 69
Zimmerman, George CME Consulting, Inc.
Comment Type TR Comment Status X
40GBASE-T EEE deep sleep is not supported in clause 98
SuggestedRemedy
Delete section 45.2.3.12
Proposed Response Response Status O

CI 45 SC 45.2.3.17 P 17 L 40 # 70
Zimmerman, George CME Consulting, Inc.
Comment Type ER Comment Status X
Description says that a device that does not implement BASE-R, 10GBASE-T, AND (emphasis added) 40GBASE_T ...

(FYI - same error is in the existing 802.3-2012)

while the bit is for BASE-R and 10GBASE-T currently, it isn't meant to mean that a device must implement ALL of the above, as an AND would indicate.
SuggestedRemedy
change "and 40GBASE-T" to "or 40GBASE-T"
Proposed Response Response Status O

CI 45 SC 45.2.7.10 P 20 L 39 # 71
Zimmerman, George CME Consulting, Inc.
Comment Type E Comment Status X
subject (assignment of bits) and verb (are) should agree - subject is (still) singular. (no need to change "is" to "are")
SuggestedRemedy
reverse proposed deletion of "is" to replace with "are"
Proposed Response Response Status O

IEEE P802.3bq - 40GBASE-T 1st Task Force review comments

CI 78 SC 78 P 73 L 5 # 72
 Zimmerman, George CME Consulting, Inc.
 Comment Type ER Comment Status X
 Clause 78 has template text throughout, which needs to be cleaned out
 SuggestedRemedy
 Clean out template text showing formates for paragraphs,etc.
 Proposed Response Response Status O

CI 98 SC 98.3.2.2.9 P 54 L 42 # 73
 Zimmerman, George CME Consulting, Inc.
 Comment Type T Comment Status X
 Notes in Table 98-1 and column on 8B/10B are specific for 10Gbps Ethernet
 SuggestedRemedy
 Remove notes a & c, and replace note b with appropriate 40G reference
 Delete column referring to 8B/10B code
 Proposed Response Response Status O

CI 98 SC 98.3.2.2.16 P 56 L 4 # 74
 Zimmerman, George CME Consulting, Inc.
 Comment Type E Comment Status X
 65-bit block has extra spacing
 SuggestedRemedy
 clean up spacing on lines 4 & 34
 Proposed Response Response Status O

CI 98 SC 98.3.2.2.17 P 58 L 3 # 75
 Zimmerman, George CME Consulting, Inc.
 Comment Type ER Comment Status X
 typo on "concatenated"
 SuggestedRemedy
 replace with concatenated
 Proposed Response Response Status O

CI 98 SC 98.3.2.2.20 P 59 L 35 # 76
 Zimmerman, George CME Consulting, Inc.
 Comment Type ER Comment Status X
 extra "["
 SuggestedRemedy
 delete hanging "["
 Proposed Response Response Status O

CI 98 SC 98.3.2.2.20 P 60 L 50 # 77
 Zimmerman, George CME Consulting, Inc.
 Comment Type E Comment Status X
 Don't need extra annex, editors note has served its purpose
 SuggestedRemedy
 delete editors note asking question
 Proposed Response Response Status O

CI 98 SC 98.3.2.3 P 64 L 14 # 78
 Zimmerman, George CME Consulting, Inc.
 Comment Type TR Comment Status X
 Only uncorrectable RS errors should cause hi_lfer
 SuggestedRemedy
 change "RS error" to "uncorrectable RS error"
 Proposed Response Response Status O

CI 98 SC 98.3.4 P 66 L 13 # 79
 Zimmerman, George CME Consulting, Inc.
 Comment Type ER Comment Status X
 figure 98-15 is missing
 SuggestedRemedy
 Insert figure 98-15 from clause 55. (unchanged)
 Proposed Response Response Status O

IEEE P802.3bq - 40GBASE-T 1st Task Force review comments

CI 98 SC 98.3.6.2.1 P 71 L 6 # 80
Zimmerman, George CME Consulting, Inc.

Comment Type TR Comment Status X

Cross reference is to 10G, Need to add Link Interruption ordered_set to XLGMII

SuggestedRemedy

Add Link Interruption Ordered_set to XLGMII in Clause 81 similar to 46.3.4 and change reference

Proposed Response Response Status O

CI 98 SC 98.3.6.2.2 P 71 L 19 # 81
Zimmerman, George CME Consulting, Inc.

Comment Type T Comment Status X

4x change changes bit error rate for hi_lfer_cnt, since 125usec now includes 4x the number of bits

SuggestedRemedy

Change hi_lfer definition to "exceeds 64"
alternatively, define in terms of a new term, N_sym, and make it a constant * N_sym so that for 40G it comes to 64

Proposed Response Response Status O

CI 98 SC 98.3.6.2.2 P 71 L 43 # 82
Zimmerman, George CME Consulting, Inc.

Comment Type TR Comment Status X

Text refers to 32 bit XGMII words, and needs to be updated to reflect XLGMII

SuggestedRemedy

change references reflect 64 bit XLGMII word.

Proposed Response Response Status O

CI 98 SC 98.4.2.2 P 85 L 37 # 83
Zimmerman, George CME Consulting, Inc.

Comment Type T Comment Status X

remove option on loop timing - make it mandatory

SuggestedRemedy

Change "may include" to "includes", replace "If loop timing is implemented and the PMA_CONFIG..." with "If the PMA_CONFIG...", delete sentence beginning with "If loop timing is not implemented..."

Proposed Response Response Status O

CI 98 SC 88 P 88 L 40 # 84
Zimmerman, George CME Consulting, Inc.

Comment Type TR Comment Status X

Receiver correction for differential delay (50ns) is still the 100m value, inconsistent with delay skew spec in 98.7.2.6 (17ns)

SuggestedRemedy

Change receiver differential delay variation spec (50ns) to be consistent with 98.7.2.6 - preferably by reference to 98.7.2.6

Proposed Response Response Status O

CI 98 SC 98.4.2.5.15 P 97 L 3 # 85
Zimmerman, George CME Consulting, Inc.

Comment Type E Comment Status X

Editors note has done its job

SuggestedRemedy

Delete editors note

Proposed Response Response Status O

IEEE P802.3bq - 40GBASE-T 1st Task Force review comments

CI 98 SC 98.7.2.3 P 125 L 21 # 86
 Zimmerman, George CME Consulting, Inc.
 Comment Type ER Comment Status X
 Equation 98-14 says "log" without showing it is a base-10 logarithm
 SuggestedRemedy
 Change "log f" to "log₁₀ f" in equation 98-14 consistent with IEEE style
 Proposed Response Response Status O

CI 98 SC 98.4.2.5.14 P 94 L 48 # 87
 Zimmerman, George CME Consulting, Inc.
 Comment Type T Comment Status X
 Editors note has done its job - PAM 2 Infocfield margin is greater than it was for 10GBASE-T at 100m.
 SuggestedRemedy
 Delete editors note
 Proposed Response Response Status O

CI 98 SC 98.4.3.1 P 99 L 3 # 88
 Zimmerman, George CME Consulting, Inc.
 Comment Type TR Comment Status X
 power backoff set size is incorrect (left over from prior version)
 SuggestedRemedy
 Change "approximately 6 dB steps" to "approximately 2 dB steps"
 Proposed Response Response Status O

CI 98 SC 98.4.3.1 P 99 L 14 # 89
 Zimmerman, George CME Consulting, Inc.
 Comment Type ER Comment Status X
 reference to "scaled insertion loss equation" is incorrect. There is no longer a scaled insertion loss equation in 98.7, and the explanatory remark is not relevant.
 SuggestedRemedy
 Delete "and have been computed using the scaled insertion loss equation in 98.7"
 Proposed Response Response Status O

CI 98 SC 98.4.2.5.14 P 95 L 17 # 90
 Zimmerman, George CME Consulting, Inc.
 Comment Type TR Comment Status X
 relation of time to transition counter is incorrect because of 4x symbol rate. Conversion to allow longer time would require rework of infocfield format to allow longer transition counter
 SuggestedRemedy
 delete reference to time (10ms, line 17) and (1ms, line 18)
 also, page 102, lines 28 & 29,
 DISCUSS - this may have implications relative to prior decision on startup time.
 Proposed Response Response Status O

CI 98 SC 98.4.2.5.14 P 96 L 34 # 91
 Zimmerman, George CME Consulting, Inc.
 Comment Type T Comment Status X
 Table 98-10 - we may want to revisit Recommended times, especially average times.
 SuggestedRemedy
 Propose Chair charter an ad hoc to come back with proposals before the next meeting.
 Proposed Response Response Status O

IEEE P802.3bq - 40GBASE-T 1st Task Force review comments

CI 98 SC 98.4.5.2 P 104 L 13 # 92
 Zimmerman, George CME Consulting, Inc.
 Comment Type TR Comment Status X
 time associated with 50 complete quiet refresh signal periods is incorrect
 SuggestedRemedy
 Change to 512usec, or, better, define a term, N_sym (proportional # symbols/sec) so that for 40G it is 512usec.
 Proposed Response Response Status O

CI 98 SC 98.4.6.3 P 108 L 24 # 93
 Zimmerman, George CME Consulting, Inc.
 Comment Type TR Comment Status X
 References in note 2 point to 10GigT link status variables
 SuggestedRemedy
 replace with _40GigT variables
 Proposed Response Response Status O

CI 98 SC 98.5.3.2 P 114 L 51 # 94
 Zimmerman, George CME Consulting, Inc.
 Comment Type T Comment Status X
 Scale transmitter linearity for frequency
 SuggestedRemedy
 Discuss. Nominally this was related to distortion of the far-end signal and for safety should be > 33 dB (10dB better than threshold SNR) across the band to Nyquist. But, this is definitely an overkill safety margin and may be too high? (52 dB out to 200 MHz, then rolling off)
 Scale frequency (25 becomes 100MHz), and put a "TBD" next to it, unless there is convergence on an alternate proposal.
 Proposed Response Response Status O

CI 98 SC 98.5.3.4 P 116 L 17 # 95
 Zimmerman, George CME Consulting, Inc.
 Comment Type ER Comment Status X
 Figure 98-39 has mirrored y-axis label, and title still says "(update)"
 SuggestedRemedy
 fix y-axis on Figure 98-39 Transmit PSD, and delete the word "(update)" from title
 Proposed Response Response Status O

CI 98 SC 98.5.4.1 P 117 L 1 # 96
 Zimmerman, George CME Consulting, Inc.
 Comment Type TR Comment Status X
 BER is after LDPC and RS decoding which is in the PCS this isn't mentioned
 SuggestedRemedy
 insert ", after LDPC and RS decoding, " between 10¹² and "and sent to the XLGMII"
 Proposed Response Response Status O

CI 98 SC 98.5.4.4 P 118 L 4 # 97
 Zimmerman, George CME Consulting, Inc.
 Comment Type T Comment Status X
 5 meters is probably not the right shortening to account for 2.5dB insertion loss at 40GBASE-T frequencies. Also, desire to be independent of both the test equipment and the transmission rate suggests the "helpful commentary" is less than helpful.
 SuggestedRemedy
 Delete "by approximately 5m"
 Proposed Response Response Status O

IEEE P802.3bq - 40GBASE-T 1st Task Force review comments

CI 98 SC 98.5.4.5.1 P 118 L 21 # 98
 Zimmerman, George CME Consulting, Inc.
 Comment Type T Comment Status X
 TIA has defined a direct attach cord channel, reflected in the draft, unaccepted text
 SuggestedRemedy
 Accept the text inserted or alternate text referencing the TIA Category 8 direct attach channel.
 Delete the editors note.
 Proposed Response Response Status O

CI 98 SC 98.6.1.1 P 119 L 8 # 99
 Zimmerman, George CME Consulting, Inc.
 Comment Type ER Comment Status X
 Editors note has served its purpose, accept text in section.
 SuggestedRemedy
 Delete editors note and accept text.
 Proposed Response Response Status O

CI 98 SC 98.6.1.2 P 119 L 48 # 100
 Zimmerman, George CME Consulting, Inc.
 Comment Type ER Comment Status X
 Editors note has served its purpose
 SuggestedRemedy
 Delete editors note
 Proposed Response Response Status O

CI 98 SC 98.6.2 P 122 L 2 # 101
 Zimmerman, George CME Consulting, Inc.
 Comment Type E Comment Status X
 Technology message code name is specific to 10G/1000BASE-T. need a new name that can apply also to 40GBASE-T. See comment on 28C.11
 SuggestedRemedy
 Change name to "Gigabit BASE-T Technology message code (Extended Next Page)"
 Proposed Response Response Status O

CI 98 SC 98.6.2 P 123 L 9 # 102
 Zimmerman, George CME Consulting, Inc.
 Comment Type ER Comment Status X
 Editors note has served its purpose
 SuggestedRemedy
 Delete editors note
 Proposed Response Response Status O

CI 98 SC 98.6.2 P 123 L 24 # 103
 Zimmerman, George CME Consulting, Inc.
 Comment Type T Comment Status X
 optional loop timing - make it mandatory
 SuggestedRemedy
 fix references on lines 24, delete sentence beginning with "In the situation where one link partner supports..." through the sentence ending with "was not resolved."
 Proposed Response Response Status O

IEEE P802.3bq - 40GBASE-T 1st Task Force review comments

CI 98 SC 98.7 P 124 L 3 # 104
Zimmerman, George CME Consulting, Inc.

Comment Type T Comment Status X

Reference to "additional requirements specified in this subclause" is dated to 10GBASE-T running on cat 6. any link segment meeting the "requirements specified in this subclause" should work.

SuggestedRemedy

replace "Class I 4-pair balanced cabling that meets the additional requirements specified in this subclause" with "Class I or other 4-pair balanced cabling that meets the requirements specified in this subclause".

Proposed Response Response Status O

CI 98 SC 98.7.1 P 124 L 24 # 105
Zimmerman, George CME Consulting, Inc.

Comment Type T Comment Status X

"additional requirements" relative to class I? I don't think we have any

SuggestedRemedy

delete "additional" - scrub document for other instances

Proposed Response Response Status O

CI 98 SC 98.7.2.4.1 P 125 L 46 # 106
Zimmerman, George CME Consulting, Inc.

Comment Type TR Comment Status X

pair-to-pair NEXT loss is unspecified (equation 98-15)

SuggestedRemedy

Specify pair-to-pair next loss consistent with MDNEXT loss in 98.7.2.4.2

Proposed Response Response Status O

CI 98 SC 98.7.2.4.2 P 126 L 14 # 107
Zimmerman, George CME Consulting, Inc.

Comment Type ER Comment Status X

equations 98-16, 98-17, 98-18 say "lg" rather than "log"

SuggestedRemedy

change equation to read "log_10" consistent with IEEE style

Proposed Response Response Status O

CI 98 SC 98.8.1 P 131 L 39 # 108
Zimmerman, George CME Consulting, Inc.

Comment Type ER Comment Status X

section does not implement resolution of motion 12 at September interim: "Move that 802.3bq include the RJ-45 as reflected in IEC 60603-7-51 (published) with the improved characteristics and frequency extensions specified in 60603-7-81 (currently CDV draft) as an MDI interface"

(apologies of the editor - I made this edit and it must have gotten lost in a crash...)

SuggestedRemedy

Replace first sentence ("Eight pin...") with: "Eight-pin connectors meeting the requirements of IEC 60603-7-51 with improved characteristics and frequency extensions specified in IEC 60603-7-81 (currently in CDV draft) shall be used as the mechanical interface to the balanced cabling.

Proposed Response Response Status O

CI 98 SC 98.8.2.3 P 134 L 50 # 109
Zimmerman, George CME Consulting, Inc.

Comment Type E Comment Status X

The requirement "A 40GBASE-T PHY shall be able to sustain" relates to the PHY not just the MDI - as such it is misplaced.

SuggestedRemedy

Move lines 50 - 54 on page 134 and 1-3 on page 135 to 98.5.1 Isolation requirements, or, optionally, add a new clause after 98.5.1 to speak to this requirement.
delete editors note

Proposed Response Response Status O

IEEE P802.3bq - 40GBASE-T 1st Task Force review comments

CI 99 SC P 3 L 36 # 110

Zimmerman, George CME Consulting, Inc.

Comment Type E Comment Status X

Draft needs to add letters of amendment. (802.3bq)

SuggestedRemedy

Substitute 802.3bq for 802.3xx (global)

Proposed Response Response Status O

CI 99 SC P 4 L 26 # 111

Zimmerman, George CME Consulting, Inc.

Comment Type E Comment Status X

List of amendments appears incomplete, 802.3bj, possibly others missing

SuggestedRemedy

Check amendments listed and include all relevant ones

Proposed Response Response Status O

CI 99 SC P 2 L 1 # 112

Zimmerman, George CME Consulting, Inc.

Comment Type ER Comment Status X

Table of Contents is a placeholder

SuggestedRemedy

Fix production of book so Table of Contents is generated correctly

Proposed Response Response Status O

CI 99 SC P L 3 # 113

Zimmerman, George CME Consulting, Inc.

Comment Type E Comment Status X

Amendment should be : bq, not X

SuggestedRemedy

Substitute in at appropriate phase of editing

Proposed Response Response Status O

CI 98 SC 98.3.2.2.20 P 59 L 32 # 114

Wu, Peter Marvell

Comment Type T Comment Status X

Text marked as pending approval

SuggestedRemedy

Request to accept the text with some changes in the presentation of "RS code scheme to protect "un-coded" bits at 40GBASE-T"

Proposed Response Response Status O

CI 98 SC 98.5.4.5.1 P 118 L 28 # 115

Belopolsky, Yakov Bel Stewart

Comment Type TR Comment Status X

IEC/ISO TR 11801-99-01 Guidance for balanced cabling in support of at least 40 Gbit/s data transmission recognizes Classes I and II, and correspondingly components of categories 8.1 or 8.2 can be utilized for a Short Reach Test Channel.

SuggestedRemedy

Replace "Category 8.1" with "Category I or Category II component

Proposed Response Response Status O

CI 98 SC 98.7 P 124 L 39 # 116

Belopolsky, Yakov Bel Stewart

Comment Type TR Comment Status X

40GBASE-T is intended to operate over the cabling that meets the requirements of the ISO/IEC 111801 standard that specially supports 40G, that standard includes Class I and Class II channels and, in fact, recognizes that components of category 6a and 7a or better can support such transmission. The statement that 40GBase is designed to operate over Class I cabling is incorrect

SuggestedRemedy

remove the " Class I" or replace with Class I or Class II

Proposed Response Response Status O

IEEE P802.3bq - 40GBASE-T 1st Task Force review comments

CI 98 SC 98.7.1 P 124 L 2324 # 117
Belopolsky, Yakov Bel Stewart

Comment Type TR Comment Status X

40GBASE-T is intended to operate over the cabling that meets the requirements of the ISO/IEC 111801 standard that specially supports 40G, that standard include Class I and Class II channels and in fact recognizes that components of categories 6a and 7a or better can support such transmission. The statement t that 40GBase is designed to operate over Class I cabling is incorrect

SuggestedRemedy

remove the " Class I" or replace with "at least Class I"

Proposed Response Response Status O

CI 98 SC 98.7.2 P 124 L 3042 # 118
Belopolsky, Yakov Bel Stewart

Comment Type TR Comment Status X

40GBASE-T is intended to operate over the cabling that meets the requirements of the ISO/IEC 111801 standard that specially supports 40G, that standard include Class I and Class II channels and in fact recognizes that components of categories 6a and 7a or better can support such transmission. The statement t that 40GBase is designed to operate over Class I cabling is incorrect
Table 98.18 is incorrect

SuggestedRemedy

line 30 remove the " Class I" or replace with "at least Class I"

Line 42 Table 98.18 remove Category 8 replace with ISO/IEC Classes I or II

Proposed Response Response Status O

CI 98 SC 98.8.1 P 131,132 L # 119
Belopolsky, Yakov Bel Stewart

Comment Type TR Comment Status X

40GBASE-T is intended to operate over the cabling that meets the requirements of the ISO/IEC 111801 standard that specially supports 40G, that standard include Class I and Class II channels and in fact recognizes that components of categories 6a and 7a or better can support such transmission.

The reference to IEC 60603-7-4 (unscreened) and IEC 606-7-5 (screened) is not correct

The use of unscreened connectors in the 2000MHz transmission is not supported by technical evidence known to the commenter.

The informational pictures 98-41 and 98-42 are misleading. The information on the recognized connectors is contained in the IEC/ISO TR 11801-99-01

(An animal with four legs is not always a horse)

SuggestedRemedy

remove pictures 98-41 and 98-42

Line 39 remove " IEC 60603-7-4 (unscreened) and IEC 606-7-5 (screened)" replace with "connectors recognized by IEC/ISO TR 11801-99-01"

preferred text : "connectors categories 8.1 or 8.2 recognized by IEC/ISO 11801

Line 41 remove the sentence starting with "These connectors are depicted...

Proposed Response Response Status O

CI 99 SC P L 28 # 120
Lusted, Kent Intel

Comment Type E Comment Status X

IEEE Std 802.3bj-2014 now exists. Add a reference

SuggestedRemedy

Add 802.3bj and the relevent supporting text.

Proposed Response Response Status O

IEEE P802.3bq - 40GBASE-T 1st Task Force review comments

CI 45 SC Table 45-7 P 20 L 21 # 121
Lusted, Kent Intel
Comment Type E Comment Status X
Description adds "40GBASE-T PMA" but the correct type selection should be "40GBASE-T PMA/PMD".
Listing PMA/PMD makes it consistent with 10GBASE-T, 1000BASE-T, 100BASE-TX, and other listings in Table 45-7
SuggestedRemedy
Change to "40GBASE-T PMA/PMD".
Proposed Response Response Status O

CI 98 SC 98.1.3.1 P 50 L 22 # 122
Lusted, Kent Intel
Comment Type E Comment Status X
The term "RS(140, 136, 2^M11) code" is used without defining what RS is. The 802.3-2012 base standard abbreviation list says RS is Reconciliation Sublayer. That doesn't make sense in this section where the text uses "RS-coded bits". RS must mean Reed Solomon.
SuggestedRemedy
Please define the use of RS in this section as Reed Solomon, if necessary.
Proposed Response Response Status O

CI 45 SC 45.2.1.68.1 P 23 L 8 # 123
Lusted, Kent Intel
Comment Type ER Comment Status X
The last sentence references the LP information valid bit 1.129.0 and the TX power backoff bits. backoff bits are now defined for 10GbT and 40GbT. however, the 1.129.0 bit is now the 10GBASE-T LP information valid bit. Another bit is defined for 40GBASE-T (1.129.1).
SuggestedRemedy
Add reference to 1.129.1, which is the 40GBASE-T LP information valid bit.
Proposed Response Response Status O

CI 45 SC 45.2.3.1.2 P 25 L 10 # 124
Lusted, Kent Intel
Comment Type ER Comment Status X
Link to 98.3.6.3 is to wrong section. Loopback is 98.3.7.3.
Note that the sentence immediately preceeding it for 10GBASE-T incorrectly references 55.3.6.3. The correct 10GBASE-T reference is 55.3.7.3.
SuggestedRemedy
Point to 98.3.7.3
Proposed Response Response Status O

CI 45 SC 45.2.3.17.4 P 27 L 40 # 125
Lusted, Kent Intel
Comment Type ER Comment Status X
Link to 98.3.6.1 is to wrong section. Variables is 98.3.6.2.2, or least in section 98.3.6.2. The variable hi_lfer is not in 98.3.6.1.
Note that the sentence immediately preceeding it for 10GBASE-T incorrectly references 55.3.6.1. The correct 10GBASE-T reference is 55.3.6.2.
SuggestedRemedy
Point to 98.3.6.2.2 or 98.3.6.2
Proposed Response Response Status O

CI 45 SC 45.2.3.17.5 P 27 L 52 # 126
Lusted, Kent Intel
Comment Type ER Comment Status X
Link to 98.3.2.3 is to wrong section. Variable definitions is 98.3.6.2.2, or least in section 98.3.6.2. The variable block_lock is not in 98.3.2.3.
Note that the sentence immediately preceeding it for 10GBASE-T incorrectly references 55.3.2.3. The correct 10GBASE-T reference is 55.3.6.2.
SuggestedRemedy
Point to correct section.
Proposed Response Response Status O

IEEE P802.3bq - 40GBASE-T 1st Task Force review comments

CI 45 **SC 45.2.7.11.1** **P 31** **L 29** # 127

Lusted, Kent Intel

Comment Type **ER** **Comment Status** **X**

Added sentences uses "10GBASE-T" but should be "40GBASE-T".

SuggestedRemedy

Change to "40GBASE-T"

Proposed Response **Response Status** **O**

CI 98 **SC 98.3.5.3** **P 70** **L 20** # 128

Graba, Jim Broadcom

Comment Type **TR** **Comment Status** **X**

This EEE feature, to allow a PHY to request the link partner to leave LPI mode, has not been approved by the TF.

SuggestedRemedy

Discuss and vote on the inclusion of this feature.

Proposed Response **Response Status** **O**

CI 98 **SC 98.7.2** **P 124** **L 28** # 129

Cibula, Peter Intel Corporation

Comment Type **T** **Comment Status** **X**

Consider whether Subclause 98.7.2 should include link segment transmission parameters appropriate for shielded cabling system characteristics.

SuggestedRemedy

Discuss adding coupling attenuation and/or other characteristics as a transmission parameter(s) for shielded link segments.

Clause 98.7 states that 40GBASE-T is designed to operate over ISO/IEC 11801 Class I 4-pair balanced cabling, and defines a link segment based upon copper media specified by ISO/IEC JTC1/SC25/WG3 and TIA TR42.7. The corresponding draft specifications, PN-568-C.2-1, Draft 2.0c (to be published as ANSI/TIA-568-C.2-1) and ISO/IEC JTC 1/SC 25 DTR 11801-99-1 both include transmission requirements related to shielded implementations. The 40GBASE-T link segment should reflect those requirements and, of course, identify them as applying to shielded link segments.

Proposed Response **Response Status** **O**