



# Power Budget Confirmation

**January, 2015**  
**Yazaki Corporation**  
**Takayuki Tajima**

## **Contributors:**

**M. Kagami (Toyota Central Labs.)**

**S. Hinata (Toyota Central Labs.)**

**O. Sugihara (Utsunomiya Univ.)**

**Y. Ishimori (OITDA)**

**N. Matsuda (AIST)**

**S. Takahashi (POF-P)**

**M. Mizuno (Denso)**

**Y. Hyakutake (Adamant)**

**S. Kobayashi (TE)**

**T. Kimura (TE)**

**H. Yuki (Sumitomo)**

**T. Saito (Furukawa)**

**N. Serizawa (Yazaki)**

**C. Yamagata (Yazaki)**



---

## ■ Agenda

---

1. Briefing
2. Definition of the power budget and test points
3. Measurement conditions
4. Test Result at TP2
5. Communication Test (15m with 4 inline connectors)
6. Communication Test (15m without inline connectors)
7. Communication Test (40m without inline connectors)
8. Inline Connector Loss Assumption
9. Wavelength at TP2
10. Summary



## ■ 1. Briefing

**O-GEAR performed the test to determine the target of power budget allocation.**

### **< Results >**

- **Launch Power at TP2: -2.6dBm (average)**
- **Gigabit Ethernet communication was confirmed to be successful at room temperature.**
- **Launch Power at TP3 as follows:**
  - 15m with 4 inline connectors: -13.1 to -13.8dBm**
  - 40m without inline connector : -11.6 to -12.2dBm**
- **Central Wavelength of LED: 649.3nm (average)**


### **< Next Step >**

**Confirm whether the communication is successful or not when testing with the change of ambient temperature.**

**\* O-GEAR: Optical Gigabit Ethernet for Automotive aRchitecture**



## 2. Definition of the power budget and test points



- Allocated multi-valued systems for optical communications and set the test points as described above .
- Tested the launch power for each TP2 and TP3 and also the communication in the entire system to see the feasibility of current multi-valued system for optical communications.

TP2: Launch Power with 1m POF (including coupling loss for Tx connector)


TP3: Launch Power with 15m POF with 4 inline connectors and 40m without inline connector (including coupling loss for Tx connector)



### 3. Measurement Conditions

#### Measuring Equipment:


- Test Board: Test Board PHY:KD-1012 (KDPOF)
- Optical Connector: X41281-P902 (YAZAKI)
- POF: GHAN – 4001 (Mitsubishi Rayon)
- Ethernet Tester: AccessOne FE/GbE L2 TESTER 1070A (NEC Networks & System Integration)
- Optical Power Meter: 205A (Photom)
- Attenuator: OVR-660-FC (Fujitok)
- Optical Spectrum Analyzer: AQ-6315A (ANDO)





#### 4. Test Result of TP2



### Test Setup





## 5. Communication Test (15m with 4 inline connectors)

### Test Setup





Communication : Good  
 TP3: -13.1 to -13.8 dBm  
 (n=4)



## Test Setup

### 6. Communication Test (15m without inline connectors)



Communication : Good  
 TP3: -6.9 to -7.6 dBm  
 (n=4)

<Predict the transmission loss of POF by the replacement method>

Since TP2 is -2.6 dBm, the POF attenuation will be 0.30 to 0.35 dB/m.


$$\{(-2.6) - (-7.6)\} / (15-1) = \mathbf{0.35 \text{ dB/m}}, \{(-2.6) - (-6.9)\} / (15-1) = \mathbf{0.30 \text{ dB/m}}$$





## 7. Communication Test (40m without inline connectors)

### Test Setup



Communication : Good  
 TP3: -11.6 to -12.2 dBm  
 (n=4)

<Predict the transmission loss of POF by the replacement method>



Since TP2 is -2.6 dBm, the POF attenuation will be 0.23 to 0.25 dB/m.

$$\{(-2.6) - (-11.6)\} / (40-1) = \mathbf{0.23 \text{ dB/m}}, \{(-2.6) - (-12.2)\} / (40-1) = \mathbf{0.25 \text{ dB/m}}$$



## 8. Inline Connector Measurement

### Test Setup



### <Procedure>

Measure the optical power by increasing the number of 3m POF cable up to 5 pieces

	SG #1			SG #2			Ave dB	$\Delta$ Average
	dBm	dBm	dBm	dBm	dBm	dBm	dB	dB
15m w/ 4 inlines	-14.3	-14.2	-14.3	-13.7	-13.8	-13.8	-14.0	2.1
12m w/ 3 inlines	-12.2	-12.1	-12.0	-11.8	-11.9	-11.8	-12.0	2.5
9m w/ 2 inlines	-9.4	-9.4	-9.4	-9.5	-9.5	-9.5	-9.5	2.4
6m w/ 1 inline	-7.0	-7.1	-7.1	-7.1	-7.0	-7.1	-7.1	2.6
3m w/o inline	-4.5	-4.4	-4.4	-	-	-	-4.4	


### <Predict inline connector loss>

The above  $\Delta$ Ave values indicate inline coupling loss with 3mPOF attenuation  
 Given that 1dB of POF transmission loss, the inline connector loss will be from **1.1dB to 1.6 dB**



## 9. Test Result of $\lambda$ at TP2

### Test Setup



	$\lambda_c$	$\Delta\lambda$
	Nm	nm
Test board 1	649.3	25.434
Test board 2	650.0	27.086
Test board 3	649.3	29.774
Test board 4	648.7	25.738
Ave	<b>649.3</b>	<b>27.0</b>



## 10. Summary

**The test results of communication show as follows:**

	TP2	TP3	Comm.
1m w/o inline conn.	-2.6dBm	-	-
15m w/o inline conn.	-	-6.9 to -7.6 dBm	Good
15m w/ 4 inline conn.	-	-13.1 to -13.8 dBm	Good
40m w/o inline conn.	-	-11.6 to -12.2 dBm	Good

**Transmission Loss: 0.30 to 0.35dB/m (at 15m)**  
**0.23 to 0.25dB/m (at 40m)**

**Inline Connector Loss: 1.37 to 1.75dB/pcs**

**Next Step:**

- **Confirm whether the communication is successful or not when testing with the change of ambient temperature.**



# Thank you