

Proposed Responses Specifications and Management Parameters for 25Gb/s, 50Gb/s, and 100Gb/s Passive Optical Networks 1:

Cl 1 SC 1.4 P20 L14 # 137  
 Hajduczenia, Marek Charter Communicatio  
 Comment Type T Comment Status D  
 Missing definition of EPON (as an architecture, to match EPON definitions we already have in Clause 1 in base standard), where we do not specify really ONU, but EPON  
 SuggestedRemedy  
 Rename all existing definitions of "ONU" in 1.4 with "EPON", e.g., 25/10G-ONU becomes 25/10G-EPON  
 Replace in all existing definitions of "ONU", "An EPON ONU" with "An EPON architecture"  
 Proposed Response Response Status W  
 PROPOSED ACCEPT.

Cl 1 SC 1.4 P20 L14 # 138  
 Hajduczenia, Marek Charter Communicatio  
 Comment Type T Comment Status D  
 Missing definition for all new PMDs (EPON speeds) we are adding  
 SuggestedRemedy  
 Add a new definition:  
 Clause 141 EPON: An EPON architecture operating at a number of different downstream and upstream speeds, i.e., 25G/10G, 25G/25G, 50G/10G, 50G/25G, or 50G/50G. This term collectively refers to 25/10G-EPON, 25/25G-EPON, 50/10G-EPON, 50/25G-EPON, and 50/50G-EPON architectures.  
 Replace all instances of 100G-EPON in Clause 141 with "Clause 141 EPON"  
 Proposed Response Response Status W  
 PROPOSED ACCEPT.

Cl 1 SC 1.4 P20 L25 # 136  
 Hajduczenia, Marek Charter Communicatio  
 Comment Type T Comment Status D  
 Missing 50/10G-ONU combination  
 SuggestedRemedy  
 Insert a new definition of 50/10G-ONU (before 50/25G-ONU): An EPON ONU supporting the maximum sustained throughput of 50 Gb/s in downstream direction and 10 Gb/s in upstream direction (asymmetric rate).  
 Proposed Response Response Status W  
 PROPOSED ACCEPT.

Cl 1 SC 1.4 P20 L36 # 152  
 Harstead, Ed Nokia  
 Comment Type TR Comment Status D 100G-EPON  
 100G ONUs out of scope  
 SuggestedRemedy  
 Delete 1.4.7a, .8a, .9a, .10a (100G ONU definitions)  
 Proposed Response Response Status W  
 PROPOSED ACCEPT.  
 Changed E to T

Cl 1 SC 1.4 P20 L36 # 158  
 Brown, Alan ADTRAN, Inc.  
 Comment Type T Comment Status D 100G-EPON  
 Motion #9 during Nov. 2017 TF meeting removed Objective for 100G.  
 SuggestedRemedy  
 Delete Definitions 1.4.7a, 1.4.8a, 1.4.9a, and 1.4.10a.  
 Proposed Response Response Status W  
 PROPOSED ACCEPT.  
 Changed type from E to T

Cl 1 SC 1.4 P20 L36 # 134  
 Hajduczenia, Marek Charter Communicatio  
 Comment Type T Comment Status D 100G-EPON  
 All 100G variants of the PMD need to be removed  
 SuggestedRemedy  
 Remove the following definitions: 100/25G-ONU, 100/50G-ONU, 100/100-ONU, 100G-ONU; from Table 2-1, remove three last lines covering 100G variations  
 Proposed Response Response Status W  
 PROPOSED ACCEPT.

Proposed Responses Specifications and Management Parameters for 25Gb/s, 50Gb/s, and 100Gb/s Passive Optical Networks 1:

Cl 1 SC 1.4 P21 L8 # 171  
 Kramer, Glen Broadcom

Comment Type T Comment Status D

Previous definition of grant was clear in that a grant resulted in an upstream burst from the ONU. Now, with .3ca combining multiple LLID transmissions into a single burst, the definition of a Grant became somewhat ambiguous. Under current definition, Grant causes transmission of one envelope, but we need a term that describes the entire ONU transmission (all envelopes that form one burst).

SuggestedRemedy

Adopt the following definitions:

1. Grant: The term Grant refers to a single transmission window allocated to an ONU. A grant includes one or more envelope allocations. The OLT conveys a grant to the ONU using one or multiple GATE MPCPDUs, all having the same StartTime values. There is one-to-one correspondence between the grants issued to an ONU and upstream bursts transmitted by that ONU, i.e., a grant issued to an ONU results in a single upstream burst transmitted by that ONU.
2. Envelope Allocation: a transmission window allocated to a single LLID (including GLID). A single GATE MPCPDU can carry up to seven envelope allocations
3. Envelope: an upstream transmission that corresponds to an envelope allocation received from the OLT. The order of envelopes in an upstream burst shall match order of envelope allocations received in corresponding GATE MPCPDU(s). An envelope carries data belonging to a specific LLID (excluding GLID), i.e., the data or idles sourced from a specific MAC. An envelope starts with an Envelope Start Header (ESH) and continues uninterrupted for the number of EQs represented by the EnvLength parameter.

Proposed Response Response Status W  
 PROPOSED ACCEPT.

Cl 1 SC 1.4.1a P20 L16 # 10  
 Remein, Duane Huawei Technologies

Comment Type E Comment Status D bucket

Section numbers incorrect.

SuggestedRemedy

Align to P8023\_D3p2\_SECTION1 numbering

Proposed Response Response Status W  
 PROPOSED ACCEPT.

Cl 1 SC 1.4.7a P20 L36 # 11  
 Remein, Duane Huawei Technologies

Comment Type T Comment Status D 100G-EPON

100G-EPON stuff. We are no longer planning 4 channel ONU or OLT.

SuggestedRemedy

Remove definitions for 100/x-ONUs (1.4.7a to 1.4.10a)

Proposed Response Response Status W  
 PROPOSED ACCEPT.

See comment #134

Cl 1 SC 1.4.12a P21 L3 # 12  
 Remein, Duane Huawei Technologies

Comment Type E Comment Status D bucket

missing article "at appropriate"

SuggestedRemedy

change to "at the appropriate"

Proposed Response Response Status W  
 PROPOSED ACCEPT.

Cl 1 SC 1.4.13a P21 L6 # 13  
 Remein, Duane Huawei Technologies

Comment Type E Comment Status D bucket

missing period

SuggestedRemedy

add after "(Envelope Continuation Header)"

Proposed Response Response Status W  
 PROPOSED ACCEPT.

Proposed Responses Specifications and Management Parameters for 25Gb/s, 50Gb/s, and 100Gb/s Passive Optical Networks 1:

Cl 1 SC 1.4.15a P21 L11 # 14  
 Remein, Duane Huawei Technologies

Comment Type T Comment Status D  
 Definition for LLID conflicts with 1.4.313 in revision

SuggestedRemedy

Show as update to 1.4.313 to read:  
 Logical Link Identifier (LLID): A numeric identifier assigned to a P2MP association between an OLT and ONU established through the Point-to-Point Emulation sublayer. Each P2MP association is assigned a unique LLID. The P2MP association is bound to an ONU DTE, where a MAC would observe a private association. In {100G-EPON} a collective term that refers to Physical Layer ID, Management Link ID, User Link ID, and Group Link ID.

Proposed Response Response Status W  
 PROPOSED ACCEPT IN PRINCIPLE.

Show as update to 1.4.313 to read:  
 Logical Link Identifier (LLID): A numeric identifier assigned to a P2MP association between an OLT and ONU established through the Point-to-Point Emulation sublayer. Each P2MP association is assigned a unique LLID. The P2MP association is bound to an ONU DTE, where a MAC would observe a private association. In {100G-EPON} a collective term that refers to Physical Layer ID (PLID), Management Link ID (MLID), User Link ID (ULID), and Group Link ID (GLID).

Cl 1 SC 1.4.17a P21 L18 # 15  
 Remein, Duane Huawei Technologies

Comment Type T Comment Status D Table 2-1  
 I'm not aware of any power budget tables in Section 1.4

SuggestedRemedy

Convert 25/10GBASE-PR, 25GBASE-PR, 50/25GBASE-PR, and 50GBASE-PR definitions to proper format of form:  
 IEEE 802.3 Physical Layer specifications for a xx Gb/s downstream yy Gb/s upstream point-to-multipoint link over one single-mode optical fiber. (See IEEE Std 802.3, Table 56-1, Clause 141, Clause 142, Clause 143, and Clause 144).

Proposed Response Response Status W  
 PROPOSED ACCEPT IN PRINCIPLE.

Per comment + remove Table 2-1.

Cl 1 SC 1.4.17a P21 L19 # 139  
 Hajduczenia, Marek Charter Communicatio

Comment Type T Comment Status D Table 2-1  
 Table 2-1 is missing entry for 50/10GBASE-PR

SuggestedRemedy

Add a new row before 50/25GBASE-PR with the following content:  
 50/10GBASE-PR | 2 | 1 (10 Gbs/)

Proposed Response Response Status W  
 PROPOSED ACCEPT IN PRINCIPLE.

See comment #15

Cl 1 SC 1.4.17a P21 L19 # 140  
 Hajduczenia, Marek Charter Communicatio

Comment Type T Comment Status D Table 2-1  
 Table 2-1 is missing entry for 50GBASE-PR

SuggestedRemedy

Add a new row after 50/25GBASE-PR with the following content:  
 50GBASE-PR | 2 | 2

Proposed Response Response Status W  
 PROPOSED ACCEPT IN PRINCIPLE.

See comment #15

Cl 1 SC 1.4.17a P21 L27 # 159  
 Brown, Alan ADTRAN, Inc.

Comment Type E Comment Status D Table 2-1, 100G-EPON  
 Motion #9 during Nov. 2017 TF meeting removed Objective for 100G.

SuggestedRemedy

Delete 100G rows from Table 2-1--Power Budgets.

Proposed Response Response Status W  
 PROPOSED ACCEPT IN PRINCIPLE.

See comment #15

Proposed Responses Specifications and Management Parameters for 25Gb/s, 50Gb/s, and 100Gb/s Passive Optical Networks 1:

Cl 1 SC 1.4.18a P21 L32 # 160  
 Brown, Alan ADTRAN, Inc.  
 Comment Type E Comment Status D bucket  
 This clause is empty.  
 SuggestedRemedy  
 Remove empty clause, unless it is to serve as a placeholder, in which case add an editorial comment to that effect indicating needed content. This should be done for all empty clauses, including the following:  
 Proposed Response Response Status W  
 PROPOSED ACCEPT.

Cl 1 SC 1.5 P21 L38 # 16  
 Remein, Duane Huawei Technologies  
 Comment Type E Comment Status D bucket  
 abbreviation for ABBR is not needed  
 SuggestedRemedy  
 remove.  
 Proposed Response Response Status W  
 PROPOSED ACCEPT.

Cl 1 SC 1.5 P21 L38 # 17  
 Remein, Duane Huawei Technologies  
 Comment Type E Comment Status D bucket  
 Abbreviations should be in alphabetical order  
 SuggestedRemedy  
 sort properly  
 Proposed Response Response Status W  
 PROPOSED ACCEPT.

Cl 1 SC 1.5 P21 L38 # 161  
 Brown, Alan ADTRAN, Inc.  
 Comment Type E Comment Status D bucket  
 "ABBR" and "expanded version" are not intended to be included in the draft. The document 802.3-2017 already includes an appropriate introduction.  
 SuggestedRemedy  
 Remove the line containing the quoted text.  
 Proposed Response Response Status W  
 PROPOSED ACCEPT.

Cl 1 SC 1.5 P21 L38 # 135  
 Hajduczenia, Marek Charter Communicatio  
 Comment Type E Comment Status D bucket  
 "ABBR expanded version" should be removed it is left over from template  
 SuggestedRemedy  
 Per comment  
 Proposed Response Response Status W  
 PROPOSED ACCEPT.

Cl 56 SC 56 P25 L1 # 19  
 Remein, Duane Huawei Technologies  
 Comment Type T Comment Status D  
 Open Table 56-1 and add entries for 25/10GBASE-PR, 25GBASE-PR, 50/25GBASE-PR, and 50GBASE-PR.  
 SuggestedRemedy  
 per comment  
 Proposed Response Response Status W  
 PROPOSED ACCEPT IN PRINCIPLE.  
 Per comment, but also include 50/10BASE-PR

Proposed Responses Specifications and Management Parameters for 25Gb/s, 50Gb/s, and 100Gb/s Passive Optical Networks 1:

CI 141 SC 141 P23 L2 # 118  
 Remein, Duane Huawei Technologies

Comment Type TR Comment Status D 100G-EPON  
 100G-EPON stuff. It does not appear we will be doing 100G-EPON just yet.

SuggestedRemedy

Remove all instances of 100G-EPON from the draft except in page headers. May be replaced by: nothing (as in this title), "25-EPON and 50G-EPON", or "25-EPON or 50G-EPON" as dictated by context.

Proposed Response Response Status W  
 PROPOSED ACCEPT IN PRINCIPLE.

A more generic designation covering all PHY variations under development is needed. I do not think we want to use "25-EPON and 50G-EPON", or "25-EPON or 50G-EPON" as dictated by context, since it is getting wordy to list all speed combinations quickly.

CI 141 SC 141 P25 L1 # 162  
 Brown, Alan ADTRAN, Inc.

Comment Type E Comment Status D 100G-EPON  
 Motion #9 during Nov. 2017 TF meeting removed Objective for 100G.

SuggestedRemedy

Rename clause: change "25G- EPON, 50G-EPON, and 100G-EPON" to "25G- EPON and 50G-EPON".

Proposed Response Response Status W  
 PROPOSED ACCEPT.

CI 141 SC 141 P25 L1 # 173  
 Harstead, Ed Nokia

Comment Type TR Comment Status D 100G-EPON  
 Section title refers to 100G EPON \*PMD\*

SuggestedRemedy

Remove text "100G-EPON"

Proposed Response Response Status W  
 PROPOSED ACCEPT IN PRINCIPLE.

See comment #27

Changed type from E to T

CI 141 SC 141.1 P25 L7 # 141  
 Hajduczenia, Marek Charter Communicatio

Comment Type T Comment Status D  
 Overview mentions 100G but not 10G

SuggestedRemedy

Change:  
 operating at the line rate of 25, 50, or 100 Gb/s, in either downstream or in both downstream and upstream directions.  
 To:  
 operating at the line rate of 25 or 50 Gb/s in the downstream direction and the line rate of 10, 25, or 50 Gb/s in the upstream direction.

Proposed Response Response Status W  
 PROPOSED ACCEPT.

CI 141 SC 141.1 P25 L7 # 20  
 Remein, Duane Huawei Technologies

Comment Type E Comment Status D bucket  
 Assuming you will want to use this abbreviation, add "(EPON)" after "Ethernet Passive Optical Networks".

SuggestedRemedy

per comment

Proposed Response Response Status W  
 PROPOSED ACCEPT.

CI 141 SC 141.1 P25 L8 # 163  
 Brown, Alan ADTRAN, Inc.

Comment Type T Comment Status D 100G-EPON  
 Motion #9 during Nov. 2017 TF meeting removed Objective for 100G.

SuggestedRemedy

Change "25, 50, or 100 Gb/s," to "25 or 50 Gb/s".

Proposed Response Response Status W  
 PROPOSED ACCEPT.

Changed E to T

Proposed Responses Specifications and Management Parameters for 25Gb/s, 50Gb/s, and 100Gb/s Passive Optical Networks 1:

Cl 141 SC 141.1.1 P25 L16 # 21  
 Remein, Duane Huawei Technologies  
 Comment Type E Comment Status D bucket  
 Per IEEE Style Guide italics font is reserved for variable names.  
 SuggestedRemedy  
 Use normal font for upstream and downstream  
 Proposed Response Response Status W  
 PROPOSED ACCEPT.

Cl 141 SC 141.1.3 P25 L33 # 23  
 Remein, Duane Huawei Technologies  
 Comment Type E Comment Status D bucket  
 "for PON" s/b plural (Also line 35)  
 SuggestedRemedy  
 "for PONs"  
 Proposed Response Response Status W  
 PROPOSED ACCEPT.

Cl 141 SC 141.1.2 P25 L22 # 144  
 Hajduczenia, Marek Charter Communicatio  
 Comment Type T Comment Status D  
 Definition of medium power budget is not consistent with the discussion at the last F2F meeting - 24dB Channel Insertion loss assumed distance of 20km, not 10km  
 SuggestedRemedy  
 Change:  
 with the split ratio of at least 1:16 and the distance of at least 20 km or a PON with the split ratio of at least 1:32 and the distance of at least 10 km.  
 To:  
 with the split ratio of at least 1:16 and the distance of at least 20 km.  
 Proposed Response Response Status W  
 PROPOSED ACCEPT.

Cl 141 SC 141.1.3 P25 L36 # 142  
 Hajduczenia, Marek Charter Communicatio  
 Comment Type T Comment Status D  
 Definition of PR-A power budget is open-ended  
 SuggestedRemedy  
 Change:  
 PR-A power budget describes asymmetric-rate PHY for PON operating at 25 Gb/s or 50 Gb/s in the downstream direction and 10 Gb/s and above in the upstream direction, over a single SMF  
 To:  
 PR-A power budget describes asymmetric-rate PHY for PON operating at 25 Gb/s in the downstream direction and 10 Gb/s in the upstream direction, or 50 Gb/s in the downstream direction, and 10 or 25 Gb/s in the upstream direction, over a single SMF  
 Proposed Response Response Status W  
 PROPOSED ACCEPT.

Cl 141 SC 141.1.2 P25 L22 # 22  
 Remein, Duane Huawei Technologies  
 Comment Type E Comment Status D bucket  
 Missing article "supports P2MP" (also in line 25).  
 SuggestedRemedy  
 "supports a P2MP"  
 Proposed Response Response Status W  
 PROPOSED ACCEPT.

Cl 141 SC 141.1.3 P26 L3 # 143  
 Hajduczenia, Marek Charter Communicatio  
 Comment Type T Comment Status D Table 141-1  
 Table 141-1 is missing basic information on individual power budgets and associated data rates  
 SuggestedRemedy  
 Use hajduczenia\_3ca\_4\_0518.pdf for table structure and data updates.  
 Proposed Response Response Status W  
 PROPOSED ACCEPT.

Proposed Responses Specifications and Management Parameters for 25Gb/s, 50Gb/s, and 100Gb/s Passive Optical Networks 1:

CI 141 SC 141.1.4 P26 L41 # 24  
 Remein, Duane Huawei Technologies

Comment Type TR Comment Status D

100G-EPON stuff. The TF needs to make a decision regarding support of 50/10Gb/s devices. Suggested solution assumes it is removed. If the TF decides to keep this variant then there are numerous places in the draft that list the PMD where 50/10GBASE-PR should be added.

SuggestedRemedy

Strike all instance of 50/10G\*:  
 pg. Line Phrase  
 3 3 "50/10 Gb/s,"  
 26 41 "50/10G-EPON" (move the and in list)  
 34 39 "50/10GBASE-PR20-D" (3 instances in draft)  
 35 45 "50/10GBASE-PR30-D" (3 instances in draft)

Proposed Response Response Status W  
 PROPOSED REJECT.

As discussed, 50/10G is within the scope and has not been removed in any way. Technically, there is nothing that prevents operation of 2 downstream 25G channels and a single 10G upstream channel.

CI 141 SC 141.2 P27 L1 # 145  
 Hajduczenia, Marek Charter Communicatio

Comment Type T Comment Status D

Figure 141-1 shows 4 x 25GMII, providing 100G connectivity. Per updated objectives, we support 50G only

SuggestedRemedy

Change Figure 141-1 per hajduczenia\_3ca\_5\_0518.pdf, were the number of supported PHY instances is shown to be 1 or 2. With the dashed line, it can be used pretty much for any number of PHY instances supported by the PMD and MPRS. Similar figure can be used in Clauses 142, 143, and 144 with proper shading to show specific sublayer(s) defined in the given Clause.

Proposed Response Response Status W  
 PROPOSED ACCEPT.

CI 141 SC 141.2 P28 L6 # 25  
 Remein, Duane Huawei Technologies

Comment Type E Comment Status D

"Such PMDs are further distinguished by appending a digit after the suffix D or U." Looks like two digits to me that indicate power budget as explained in 141.1.3 quite well. Could change "a digit" to "two digits" or just drop the whole para, seems a bit late to make this point in any case.

SuggestedRemedy

Strike para.

Proposed Response Response Status W  
 PROPOSED REJECT.

This is not an editorial change. The purpose of D and U designator is to differentiate between ONU and OLT PMDs. This should not be confused with 20/30 designators for power budget.

CI 141 SC 141.2.1.1 P28 L40 # 26  
 Remein, Duane Huawei Technologies

Comment Type T Comment Status D

Do we really need to list PMD names in section titles (e.g., {PMD\_X} & {(NG)-type)? I think not.

SuggestedRemedy

Strike "{PMD\_X}", "{(NG) type}", and "{PMD\_Y}" from the draft.

Proposed Response Response Status W  
 PROPOSED REJECT.

This list will be filled in at some time, just like we had it done in 10G-EPON. It does provide a reference list of all options expected to be supported.

CI 141 SC 141.3 P26 L3 # 153  
 Harstead, Ed Nokia

Comment Type TR Comment Status D Table 141-1  
 Nominal wavelengths missing in Table 141-1

SuggestedRemedy

UW0=1270 nm, UW1=1300 nm, UW2=1320 nm, DW0=1358 nm, DW1=1324 nm. Or, is this redundant with Table 141-5, -6?

Proposed Response Response Status W  
 PROPOSED ACCEPT IN PRINCIPLE.

See comment #143

Proposed Responses Specifications and Management Parameters for 25Gb/s, 50Gb/s, and 100Gb/s Passive Optical Networks 1:

CI 141 SC 141.3 P26 L3 # 154  
 Harstead, Ed Nokia  
 Comment Type **TR** Comment Status **D** Table 141-1  
 Wavelengths tolerances missing in Table 141-1  
 SuggestedRemedy  
 UW0=+/-10 nm, UW1=+/-10 nm, UW2=+/-2 nm, DW0=+/-2 nm, DW1=+/-2 nm. Or, is this redundant with Table 141-5, -6?  
 Proposed Response Response Status **W**  
 PROPOSED ACCEPT IN PRINCIPLE.  
 See comment #143

CI 141 SC 141.3 P29 L28 # 27  
 Remein, Duane Huawei Technologies  
 Comment Type **T** Comment Status **D** 100G-EPON  
 More placeholders "{NG-EPON type}"  
 SuggestedRemedy  
 Replace 8x with "25G-EPON and 50G-EPON"  
 Proposed Response Response Status **W**  
 PROPOSED ACCEPT IN PRINCIPLE.  
 Agree on replacement being needed, but we also need a global term to designate all PMDs defined in this project, and not rely on lists.

CI 141 SC 141.3 P30 L19 # 155  
 Harstead, Ed Nokia  
 Comment Type **ER** Comment Status **D** 100G-EPON  
 Multiple references to 100G-EPON PMD at this line and following  
 SuggestedRemedy  
 Replace with 25G- and 50G-EPON PMDs  
 Proposed Response Response Status **W**  
 PROPOSED ACCEPT IN PRINCIPLE.  
 See comment #27

CI 141 SC 141.3.1 P29 L41 # 28  
 Remein, Duane Huawei Technologies  
 Comment Type **TR** Comment Status **D** primitives  
 We should align text with the channelized PMD.  
 SuggestedRemedy  
 Given the single channelized PMD interfaces with multiple PMAs the PMD service interface naming should reflect this. Change "PMD\_UNITDATA." to "PMD\_UNITDATAch." and "PMD\_SIGNAL." to "PMD\_SIGNALch." and add the following to the end of para at pg. 29 line 40 "Where "ch" represents the PMA Channel; 1 for 2." Change "between the PMA and PMD entities" to "between the PMAch and PMD entities" at pg. 29 line 38. The 7 instances of "{TBD, depending on the structure of PMA}" in CI 141.3.x will be dealt with in a separate comments.

Proposed Response Response Status **W**  
 PROPOSED ACCEPT IN PRINCIPLE.  
 Agreed on the scope of suggested change. However, rather than add "ch" to the primitive name, other projects typically use "\_i" designator to imply channel number. For example, 123.2 for 16 channel 400GBASE-SR16 defines:  
 PMD:IS\_UNITDATA\_i.request  
 PMD:IS\_UNITDATA\_i.indication  
 PMD:IS\_SIGNAL.indication

CI 141 SC 141.3.1.2 P29 L52 # 29  
 Remein, Duane Huawei Technologies  
 Comment Type **T** Comment Status **D**  
 "Clause 201" s/b CI 142 (2 instances).  
 SuggestedRemedy  
 Change to: "Clause 142" with live link to clause.  
 Proposed Response Response Status **W**  
 PROPOSED ACCEPT.



Cl 141 SC 141.3.1.2 P30 L1 # 30  
 Remein, Duane Huawei Technologies

Comment Type T Comment Status D primitives

Replace "{TBD, depending on the structure of PMA}" with:

*SuggestedRemedy*

The semantics of the service primitive are PMD\_UNITDATAch.request(tx\_bit). The data conveyed by PMD\_UNITDATAch.request is a continuous stream of bits. The tx\_bit parameter can take one of two values: ONE or ZERO. The Clause 142 PMA continuously sends the appropriate stream of bits to the PMD for transmission on the medium, at a nominal signaling speed of 25.7812 GBd in the case of 25G-EPON or 50G-EPON OLT and ONU PMDs. The {Clause 77} PMA continuously sends the appropriate stream of bits to the PMD for transmission on the medium, at a nominal signaling speed of 10.3125 GBd in the case of 25/10G-EPON ONU PMDs. Upon the receipt of this primitive, the PMD converts the specified stream of bits into the appropriate signals at the MDI.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Agreed on the scope of suggested change. However, rather than add "ch" to the primitive name, other projects typically use "\_i" designator to imply channel number. For example, 123.2 for 16 channel 400GBASE-SR16 defines:

PMD:IS\_UNITDATA\_i.request  
 PMD:IS\_UNITDATA\_i.indication  
 PMD:IS\_SIGNAL.indication

Cl 141 SC 141.3.1.3 P30 L6 # 31  
 Remein, Duane Huawei Technologies

Comment Type T Comment Status D primitives

Replace "{TBD, depending on the structure of PMA}" with:

*SuggestedRemedy*

The semantics of the service primitive are PMD\_UNITDATAch.indication(rx\_bit). The data conveyed by PMD\_UNITDATA.indication is a continuous stream of bits. The rx\_bit parameter can take one of two values: ONE or ZERO. The PMD continuously sends a stream of bits to the Clause 142 PMA corresponding to the signals received from the MDI, at the nominal signaling speed of 25.7812 GBd in the case of 25G-EPON or 50G-EPON OLT and ONU PMDs or to the {Clause 77} PMA at the nominal signaling speed of 10.3125 GBd in the case of 10/1G-EPON OLT PMDs.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Agreed on the scope of suggested change. However, rather than add "ch" to the primitive name, other projects typically use "\_i" designator to imply channel number. For example, 123.2 for 16 channel 400GBASE-SR16 defines:

PMD:IS\_UNITDATA\_i.request  
 PMD:IS\_UNITDATA\_i.indication  
 PMD:IS\_SIGNAL.indication

Proposed Responses Specifications and Management Parameters for 25Gb/s, 50Gb/s, and 100Gb/s Passive Optical Networks 1:

Cl 141 SC 141.3.1.4 P30 L10 # 32  
 Remein, Duane Huawei Technologies

Comment Type T Comment Status D primitives

Replace "{TBD, depending on the structure of PMA}" with:

*SuggestedRemedy*

In the upstream direction, this primitive is generated by the Clause 142 PMA to turn on and off the transmitter according to the granted time. A signal for laser control is generated as described in 142.x.x.x for the Clause 142 PCS.

The semantics of the service primitive are PMD\_SIGNALch.request(tx\_enable). The tx\_enable parameter can take on one of two values: ENABLE or DISABLE, determining whether the PMD transmitter is on (enabled) or off (disabled). The Clause 142 PMA generates this primitive to indicate a change in the value of tx\_enable. Upon the receipt of this primitive, the PMD turns the transmitter on or off as appropriate.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Agreed on the scope of suggested change. However, rather than add "ch" to the primitive name, other projects typically use "\_j" designator to imply channel number. For example, 123.2 for 16 channel 400GBASE-SR16 defines:

PMD:IS\_UNITDATA\_i.request  
 PMD:IS\_UNITDATA\_i.indication  
 PMD:IS\_SIGNAL.indication

Cl 141 SC 141.3.1.5 P30 L14 # 33  
 Remein, Duane Huawei Technologies

Comment Type T Comment Status D primitives

Replace "{TBD, depending on the structure of PMA}" with:

*SuggestedRemedy*

This primitive is generated by the PMD to indicate the status of the signal being received from the MDI. The semantics of the service primitive are PMD\_SIGNALch.indication(SIGNAL\_DETECT). The SIGNAL\_DETECT parameter can take on one of two values: OK or FAIL, indicating whether the PMD is detecting light at the receiver (OK) or not (FAIL). When SIGNAL\_DETECT = FAIL, PMD\_UNITDATAch.indication(rx\_bit) is undefined. The PMD generates this primitive to indicate a change in the value of SIGNAL\_DETECT. If the MDIO interface is implemented, then PMD\_global\_signal\_detect shall be continuously set to the value of SIGNAL\_DETECT. NOTE—SIGNAL\_DETECT = OK does not guarantee that PMD\_UNITDATAch.indication(rx\_bit) is known good. It is possible for a poor quality link to provide sufficient light for a SIGNAL\_DETECT = OK indication and still not meet the specified bit error ratio. PMD\_SIGNALch.indication(SIGNAL\_DETECT) has different characteristics for upstream and downstream links, see 141.x.x.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Agreed on the scope of suggested change. However, rather than add "ch" to the primitive name, other projects typically use "\_j" designator to imply channel number. For example, 123.2 for 16 channel 400GBASE-SR16 defines:

PMD:IS\_UNITDATA\_i.request  
 PMD:IS\_UNITDATA\_i.indication  
 PMD:IS\_SIGNAL.indication

Cl 141 SC 141.3.2 P30 L19 # 164  
 Brown, Alan ADTRAN, Inc.

Comment Type E Comment Status D 100G-EPON

Motion #9 during Nov. 2017 TF meeting removed Objective for 100G.

*SuggestedRemedy*

Change "100G-EPON PMDs" to "25G-EPON PMDs and 50G-EPON PMDs".

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

See comment #27.

Proposed Responses Specifications and Management Parameters for 25Gb/s, 50Gb/s, and 100Gb/s Passive Optical Networks 1:

Cl 141 SC 141.3.3 P30 L37 # 34  
 Remein, Duane Huawei Technologies

Comment Type T Comment Status D primitives

Replace "{TBD, depending on the structure of PMA}" with:

SuggestedRemedy

The PMD Transmit function shall convey the bits requested by the PMD service interface message PMD\_UNITDATAch.request(tx\_bit) to the MDI according to the optical specifications in Clause 141. In the upstream direction, the flow of bits is interrupted according to PMD\_SIGNAL.request(tx\_enable). This implies three optical levels, 1, 0, and dark, the latter corresponding to the transmitter being in the OFF state. The higher optical power level shall correspond to tx\_bit = ONE.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Agreed on the scope of suggested change. However, rather than add "ch" to the primitive name, other projects typically use "\_i" designator to imply channel number. For example, 123.2 for 16 channel 400GBASE-SR16 defines:

PMD:IS\_UNITDATA\_i.request  
 PMD:IS\_UNITDATA\_i.indication  
 PMD:IS\_SIGNAL.indication

Cl 141 SC 141.3.4 P30 L41 # 35  
 Remein, Duane Huawei Technologies

Comment Type T Comment Status D primitives

Replace "{TBD, depending on the structure of PMA}" with:

SuggestedRemedy

The PMD Receive function shall convey the bits received from the MDI according to the optical specifications in Clause 141 to the PMD service interface using the message PMD\_UNITDATAch.indication(rx\_bit). The higher optical power level shall correspond to rx\_bit = ONE.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Agreed on the scope of suggested change. However, rather than add "ch" to the primitive name, other projects typically use "\_i" designator to imply channel number. For example, 123.2 for 16 channel 400GBASE-SR16 defines:

PMD:IS\_UNITDATA\_i.request  
 PMD:IS\_UNITDATA\_i.indication  
 PMD:IS\_SIGNAL.indication

Cl 141 SC 141.3.5.1 P30 L47 # 36  
 Remein, Duane Huawei Technologies

Comment Type T Comment Status D primitives

Replace "{TBD, depending on the structure of PMA}" with:

SuggestedRemedy

The PMD Signal Detect function for the continuous mode downstream signal shall report to the PMD service interface, using the message PMD\_SIGNALch.indication(SIGNAL\_DETECT), which is signaled continuously. PMD\_SIGNALch.indication is intended to be an indicator of the presence of the optical signal. The value of the SIGNAL\_DETECT parameter shall be generated according to the conditions defined in Table 141-4 for 25G-EPON and 50G-EPON PMDs. The ONU PMD receiver is not required to verify whether a compliant 25G-EPON or 50G-EPON signal is being received.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Agreed on the scope of suggested change. However, rather than add "ch" to the primitive name, other projects typically use "\_i" designator to imply channel number. For example, 123.2 for 16 channel 400GBASE-SR16 defines:

PMD:IS\_UNITDATA\_i.request  
 PMD:IS\_UNITDATA\_i.indication  
 PMD:IS\_SIGNAL.indication

Cl 141 SC 141.3.5.2 P31 L1 # 146  
 Hajduczenia, Marek Charter Communicatio

Comment Type T Comment Status D Figure 141-2

Figure 141-2 has reference to 10G-EPON in the title

SuggestedRemedy

Change title of Figure 141-2 to read "Clause 141 EPON block diagram"

Proposed Response Response Status W

PROPOSED ACCEPT.

Proposed Responses Specifications and Management Parameters for 25Gb/s, 50Gb/s, and 100Gb/s Passive Optical Networks 1:

CI 141 SC 141.3.5.2 P31 L31 # 37  
 Remein, Duane Huawei Technologies  
 Comment Type T Comment Status D Figure 141-2  
 We can at least fix the figure title  
 SuggestedRemedy  
 Change "10GBASE-PR and 10/1GBASE-PRX block diagram" to "25-EPON and 50G-EPON block diagram"  
 Proposed Response Response Status W  
 PROPOSED ACCEPT IN PRINCIPLE.  
 See comment #146

CI 141 SC 141.3.5.2 P31 L37 # 38  
 Remein, Duane Huawei Technologies  
 Comment Type T Comment Status D 100G-EPON  
 100G-EPON stuff. If only we were doing a 100G-EPON.  
 SuggestedRemedy  
 Change "100G-EPON" to "25G-EPON or 50G-EPON" in 2 places in this para.  
 Proposed Response Response Status W  
 PROPOSED ACCEPT IN PRINCIPLE.  
 Agreed on need to change, but we need new global designator for all PMDs we are doing in the project

CI 141 SC 141.3.5.3 P31 L49 # 165  
 Brown, Alan ADTRAN, Inc.  
 Comment Type E Comment Status D 100G-EPON  
 Motion #9 during Nov. 2017 TF meeting removed Objective for 100G.  
 SuggestedRemedy  
 Change "100G-EPON PMD" to "25G-EPON PMD" over "50G-EPON PMD", stacked in column.  
 Proposed Response Response Status W  
 PROPOSED ACCEPT IN PRINCIPLE.  
 See comment #27

CI 141 SC 141.5.1 P34 L52 # 157  
 Harstead, Ed Nokia  
 Comment Type TR Comment Status D  
 Value for Average launch power, each channel (min) is in wrong field (max)  
 SuggestedRemedy  
 Move "4.8" to Average launch power, each channel (min)  
 Proposed Response Response Status W  
 PROPOSED ACCEPT.  
 Comment is on page 33 likely

CI 141 SC 141.5.2 P34 L40 # 156  
 Harstead, Ed Nokia  
 Comment Type TR Comment Status D  
 Missing channel wavelength ranges in Table 141-9. Same for Table 141-10, -11, -12, -13  
 SuggestedRemedy  
 Add as above. Or remove (redundant with Table 141-5, -6).  
 Proposed Response Response Status W  
 PROPOSED REJECT.  
 "Add as above." is unclear.

CI 141 SC 141.6 P36 L47 # 39  
 Remein, Duane Huawei Technologies  
 Comment Type T Comment Status D 100G-EPON  
 More placeholders.  
 SuggestedRemedy  
 Change first "{XXX}" to "medium" and second to "25-EPON or 50G-EPON"  
 Proposed Response Response Status W  
 PROPOSED ACCEPT IN PRINCIPLE.  
 Agreed on need to change, but we need new global designator for all PMDs we are doing in the project

Proposed Responses Specifications and Management Parameters for 25Gb/s, 50Gb/s, and 100Gb/s Passive Optical Networks 1:

**Cl 141**    **SC 141.6.2**    **P39**    **L3**    # **40**  
 Remein, Duane    Huawei Technologies

**Comment Type T**    **Comment Status D**    **100G-EPON**  
 Even more placeholders.

**SuggestedRemedy**  
 Change {PMD-types} to "25-EPON or 50G-EPON"

**Proposed Response**    **Response Status W**  
 PROPOSED ACCEPT IN PRINCIPLE.

Agreed on need to change, but we need new global designator for all PMDs we are doing in the project

**Cl 141**    **SC 141.7.1.**    **P40**    **L49**    # **147**  
 Hajduczenia, Marek    Charter Communicatio

**Comment Type T**    **Comment Status D**  
 Wavelengths for insertion loss measurement are now defined

**SuggestedRemedy**  
 Change:  
 Insertion loss for SMF fiber optic cabling (channel) is defined at {TBD, NG-EPON wavelengths},  
 To:  
 Insertion loss for SMF fiber optic cabling (channel) is defined at 1270 nm, 1300 nm, 1320 nm, 1342 nm, or 1358 nm,

**Proposed Response**    **Response Status W**  
 PROPOSED ACCEPT.

**Cl 141**    **SC 141.7.2**    **P41**    **L3**    # **148**  
 Hajduczenia, Marek    Charter Communicatio

**Comment Type T**    **Comment Status D**  
 Section on allocation for penalties is TBD right now

**SuggestedRemedy**  
 Use the following text derived from 75.7.2:  
 All the receiver types specified in Clause 141 are required to tolerate a path penalty not exceeding 1 dB to account for total degradations due to reflections, intersymbol interference, mode partition noise, laser chirp and detuning of the central wavelength, including chromatic dispersion penalty. All the transmitter types specified in Clause 141 introduce less than 1 dB of optical path penalty over the channel. The path penalty is a component of transmitter and dispersion penalty (TDP), which is specified in Table 141-7, Table 141-8, Tale 141-11, and Table 141-12 and described in 52.9.10, with the measurement procedure defined in 114.7.5.1, 114.7.5.3, and 114.7.5.4.

**Proposed Response**    **Response Status W**  
 PROPOSED ACCEPT.

**Cl 141**    **SC 141.7.3**    **P41**    **L7**    # **149**  
 Hajduczenia, Marek    Charter Communicatio

**Comment Type T**    **Comment Status D**  
 Section on test patterns is TBD right now

**SuggestedRemedy**  
 The test patterns used in this clause shall be the same as those used for 100GBASE-SR4, as described in 95.8.1 and shown in Table 95-9, with the exception that pattern 5, the scrambled idle test pattern defined in 82.2.11, is encoded by Clause 108 RS-FEC for 25GBASE-LR and 25GBASE-ER. The multi-lane testing considerations described in 95.8.1.1 do not apply. Table 114-9 shows the test patterns to be used in each measurement, unless otherwise specified, and also lists references to the subclauses in which each parameter is defined.

Effectively, the text from 25GBASE-R is proposed to be reused as the baseline.

**Proposed Response**    **Response Status W**  
 PROPOSED ACCEPT.

Proposed Responses Specifications and Management Parameters for 25Gb/s, 50Gb/s, and 100Gb/s Passive Optical Networks 1:

CI 141 SC 141.7.15.1 P42 L37 # 41  
 Remein, Duane Huawei Technologies

Comment Type E Comment Status D

Slightly confusing "Treceiver\_settling is denoted as the time beginning from the time that the optical power in the receiver at TP7 reaches the conditions specified in 141.7.12 and ending at the time that ..."

SuggestedRemedy

Precede the first time with "elapsed" and change 2nd & 3rd time to moment so the phrase reads "Treceiver\_settling is denoted as the elapsed time beginning from the moment that the optical power in the receiver at TP7 reaches the conditions specified in 141.7.12 and ending at the moment that ..."

Proposed Response Response Status W

PROPOSED REJECT.

Current definition has been used in 1G-EPON and 10G-EPON and has never been found "confusing". If there is an actual technical issue, or we need to redefine it for multi-wavelength system, please offer actual technical description of the problem.

CI 141 SC 141.7.15.1 P43 L49 # 42  
 Remein, Duane Huawei Technologies

Comment Type T Comment Status D

While I realize that the following sentence is directly taken from the standard in CI 75 it should be removed, or at least converted into a complete sentence. Can anyone even tell me what it is intended to mean and what value it adds to the standard?  
 "A non-rigorous way to describe this test setup would be (using a transmitter with a known Ton)."

SuggestedRemedy

Strike.

Proposed Response Response Status W

PROPOSED ACCEPT.

CI 141 SC 141.7.15.1 P43 L53 # 43  
 Remein, Duane Huawei Technologies

Comment Type E Comment Status D

Use of "reassuring" isn't very comforting (a synonym).

SuggestedRemedy

Change to confirming

Proposed Response Response Status W

PROPOSED REJECT.

Personal preference of the commenter

CI 141 SC 141.8.2 P44 L9 # 166  
 Brown, Alan ADTRAN, Inc.

Comment Type E Comment Status D 100G-EPON

Motion #9 during Nov. 2017 TF meeting removed Objective for 100G.

SuggestedRemedy

Change "100G-EPON" to "25G-EPON and 50G-EPON" in these locations (page/line):  
 44/9, 44/28, 44/36

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

See comment #27

Proposed Responses Specifications and Management Parameters for 25Gb/s, 50Gb/s, and 100Gb/s Passive Optical Networks 1:

CI 141 SC 141.8.5 P44 L39 # 44  
 Remein, Duane Huawei Technologies

Comment Type T Comment Status D  
 Replace "{list NG-EPON PMDs}" with

SuggestedRemedy  
 25/10GBASE-PR20-D  
 25GBASE-PR20-D  
 50/25GBASE-PR20-D  
 50GBASE-PR20-D  
 25/10GBASE-PR30-D  
 25GBASE-PR30-D  
 50/25GBASE-PR30-D  
 50GBASE-PR30-D

Proposed Response Response Status W  
 PROPOSED ACCEPT IN PRINCIPLE.

Per comment + 50/10G-BASE-PR20-D + 50/10G-BASE-PR30-D + all counterparts with "-  
 U" designator

CI 141 SC 141.9.1 P45 L2 # 45  
 Remein, Duane Huawei Technologies

Comment Type T Comment Status D  
 Why the reference to CI 75?

SuggestedRemedy  
 Change "Table 75B-1 and Table 75B-2" to "TBD"

Proposed Response Response Status W  
 PROPOSED ACCEPT.

CI 141 SC 141.9.3 P45 L18 # 150  
 Hajduczenia, Marek Charter Communicatio

Comment Type T Comment Status D  
 Nominal wavelengths are missing in Table 141-15

SuggestedRemedy  
 Add nominal wavelengths: 1270 nm, 1300 nm, 1320 nm, 1342 nm, 1358 nm and add  
 columns are needed

Proposed Response Response Status W  
 PROPOSED ACCEPT.

CI 141 SC 141.9.3 P45 L41 # 167  
 Brown, Alan ADTRAN, Inc.

Comment Type E Comment Status D  
 Motion #9 during Nov. 2017 TF meeting removed Objective for 100G.

SuggestedRemedy  
 Change "100G-EPON" to "25G-EPON or 50G-EPON" in these locations (page/line):  
 45/41

Proposed Response Response Status W  
 PROPOSED ACCEPT IN PRINCIPLE.

See comment #27

CI 142 SC 142.1 P49 L7 # 46  
 Remein, Duane Huawei Technologies

Comment Type E Comment Status D  
 bucket  
 Abbreviations are to be properly introduced.

SuggestedRemedy  
 Change "FEC" to "forward error correction (FEC)". On line 41 change "forward error  
 correction (FEC)" to "FEC"

Proposed Response Response Status W  
 PROPOSED ACCEPT.

CI 142 SC 142.2.1 P49 L31 # 47  
 Remein, Duane Huawei Technologies

Comment Type E Comment Status D  
 bucket  
 Why define an abbreviation if you don't use it?

SuggestedRemedy  
 Change "physical coding sublayers" to "PCS" and on line 32 change "point-to-multipoint  
 physical" to P2MP".

Proposed Response Response Status W  
 PROPOSED ACCEPT.

Proposed Responses Specifications and Management Parameters for 25Gb/s, 50Gb/s, and 100Gb/s Passive Optical Networks 1:

CI 142 SC 142.2.1 P49 L46 # 48  
 Remein, Duane Huawei Technologies  
 Comment Type T Comment Status D  
 Update to Figure 142-1.  
 SuggestedRemedy  
 See remain\_3ca\_1\_0518.pdf (also available in visio).  
 Proposed Response Response Status W  
 PROPOSED ACCEPT IN PRINCIPLE.  
 Change "PMA\_SIGNAL.request" to "PMA\_SIGNAL\_i.request" and "PMD\_SIGNAL.request" to "PMD\_SIGNAL\_i.request" to indicate that it is per channel signal.

CI 142 SC 142.2.2.1 P53 L5 # 133  
 Hajduczenia, Marek Charter Communicatio  
 Comment Type T Comment Status D  
 Content of 142.2.2.1 is missing  
 SuggestedRemedy  
 Use hajduczenia\_3ca\_3\_0518.pdf for text and drawing of the upstream burst structure  
 Proposed Response Response Status W  
 PROPOSED ACCEPT.

CI 142 SC 142.2.2.5.1 P53 L38 # 128  
 Laubach, Mark Broadcom Inc.  
 Comment Type TR Comment Status D  
 Motion #6 from the March 2018 Rosemont, IL Task Force meeting, adopted slide 6 of kramer\_3ca\_1\_0318.pdf as part of the improved alignment motion. However, the adopted updated parity matrix, puncturing, information word and parity word sizes were sized for the "New Code" option on slide 9, which is slightly different than slide 6. These changes adjust the information word size and shortening to match slide 6. Note that the actual parity code matrix is the same, no changes. For the May TF meeting, laubach\_3ca\_1\_0518.pdf summarizes performance impact of these small adjustments.

SuggestedRemedy  
 Page 53:  
 Line 38: change "14328" to "14392"  
 Line 39: change "264" to "200"  
 Line 44: change "16888" to "16952"  
 Line 47: change "0.8484" to "0.849"  
 Page 56:  
 Line 52: change "264" to "200"  
 Line 53: change "0.8484" to "0.849"

Proposed Response Response Status W  
 PROPOSED ACCEPT.

CI 142 SC 142.2.2.5.1 P54 L8 # 131  
 Laubach, Mark Broadcom Inc.  
 Comment Type TR Comment Status D  
 In Figure 142-3, the circled "+" should be a mux symbol to combine "M+P-bit LDPC parity" with "M-bit parity" and "K-bit user", not to serially add them. Also need to correct a box label in the figure and formula in the text to be clear on use of de-interleaved info as input to the encoder.  
 SuggestedRemedy  
 1) Change "circle-+" symbol to a mux symbol (see original submitted draft word file). For clarity, label the bottom arrow (that comes from the far left) with "K-bit information" aligned under "M-bit parity"  
 2) Change the box text "Information Bit Interleaver" to "Information Bit De-interleaver"  
 Corresponding text change Page 57, Line 19:  
 3) Change "<pi>" symbol to "<pi>-1" where the "-1" is a superscript.  
 Proposed Response Response Status W  
 PROPOSED ACCEPT.



Proposed Responses Specifications and Management Parameters for 25Gb/s, 50Gb/s, and 100Gb/s Passive Optical Networks 1:

CI 142 SC 142.2.2.5.2 P54 L49 # 129  
 Laubach, Mark Broadcom Inc.  
 Comment Type TR Comment Status D  
 In Table 142-1, a few of the values have errors from the source material. (Verified from both the original .docx (pdf) file and the .txt file.)  
 SuggestedRemedy  
 Page 54: Line 49, Col C7: change "204" to "104"  
 Page 54: Line 51, Col C5: change "01" to "-1"  
 Page 56, Line 23, Col C5: change "235" to "135"  
 Page 56, Line 32, Col C7: change "259" to "159"  
 Proposed Response Response Status W  
 PROPOSED ACCEPT.

CI 142 SC 142.2.2.5.3 P57 L27 # 132  
 Laubach, Mark Broadcom Inc.  
 Comment Type TR Comment Status D  
 Following motion #6 from the November 2017 Orlando meeting, the Omega256 interleaver text needs to be added to the draft. The text has been submitted in "han\_3ca\_1\_0518.pdf". The submitted file "han\_3ca\_2\_0518.txt" contains the binary seed code values suitable for making available (similar to the LDPC parity code matrix) via download from an IEEE web site.  
 SuggestedRemedy  
 Add the draft text from "han\_3ca\_1\_0518.pdf" beginning with new subclause 142.2.2.5.4.  
 Proposed Response Response Status W  
 PROPOSED ACCEPT.

CI 142 SC 142.2.2.5.2 P57 L6 # 49  
 Remein, Duane Huawei Technologies  
 Comment Type E Comment Status D  
 There is no reference to Figure 142-2  
 SuggestedRemedy  
 Add reference in text.  
 Proposed Response Response Status W  
 PROPOSED ACCEPT IN PRINCIPLE.  
 Likely Figure 142-4 is the subject of this comment. Add the following statement on page 56, line 53 (at the end): "The Codeword Information/Parity Location assignment is shown in Figure 142-4" (make the link live)

CI 142 SC 142.2.3 P57 L34 # 50  
 Remein, Duane Huawei Technologies  
 Comment Type E Comment Status D bucket  
 Why define an abbreviation if you don't use it?  
 SuggestedRemedy  
 Change "physical coding sublayers" to "PCS"  
 Proposed Response Response Status W  
 PROPOSED ACCEPT.

CI 142 SC 142.2.2.5.3 P57 L22 # 130  
 Laubach, Mark Broadcom Inc.  
 Comment Type TR Comment Status D  
 Should be "parity" and not "info".  
 SuggestedRemedy  
 Change subscript "info" to "parity"  
 Proposed Response Response Status W  
 PROPOSED ACCEPT.

CI 142 SC 142.3.1 P61 L41 # 168  
 Powell, Bill Nokia  
 Comment Type TR Comment Status D  
 Ambiguity in differential encoder figure 142-7 (register input/output vs. Control)  
 SuggestedRemedy  
 Proposed change to Figure 142-7 in Red on Slide 3, Section A, of powell\_3ca\_1\_0518  
 Proposed Response Response Status W  
 PROPOSED ACCEPT.

Proposed Responses Specifications and Management Parameters for 25Gb/s, 50Gb/s, and 100Gb/s Passive Optical Networks 1:

Cl 142 SC 142.3.2 P61 L3 # 169  
 Powell, Bill Nokia  
 Comment Type TR Comment Status D  
 Ambiguity in differential decoder figure 142-8 (register output vs. Control)  
 SuggestedRemedy  
 Proposed change to Figure 142-8 in Red on Slide 3, Section B, of powell\_3ca\_1\_0518  
 Proposed Response Response Status W  
 PROPOSED ACCEPT.

Cl 143 SC 143.1 P65 L12 # 51  
 Remein, Duane Huawei Technologies  
 Comment Type T Comment Status D  
 Is this really true? "It is acceptable for only one MAC to be connected to this MPRS"  
 Now that we have PLID, MLID and ULIDs it would seem to me that the minimum number of  
 MACs is 3.  
 SuggestedRemedy  
 Strike the sentence.  
 Proposed Response Response Status W  
 PROPOSED ACCEPT.

Cl 143 SC 143.1 P65 L15 # 52  
 Remein, Duane Huawei Technologies  
 Comment Type TR Comment Status D  
 100G-EPON stuff. We have decided not to pursue 100G-EPON using 4x25G. The draft  
 still reflects our earlier thinking that we would support 4x25G as is illustrated here "This  
 concept is expanded in this clause to allow multiple MACs to interface with up to four PHYs  
 requiring up to four 25 Gigabit Media Independent Interfaces (25GMIIs)." The longer we  
 put off fixing this the more difficult it will be to get it correct. I suggest we for the most part  
 adopt a slightly ambiguous wording to the maximum number of 25GMII/PHYS we support  
 in this standard.

SuggestedRemedy  
 Change from:  
 "This concept is expanded in this clause to allow multiple MACs to interface with up to four  
 PHYs requiring up to four 25 Gigabit Media Independent Interfaces (25GMIIs)." to  
 This concept is expanded in this clause to allow multiple MACs to interface with multiple  
 PHYs requiring multiple 25 Gigabit Media Independent Interfaces (25GMIIs)."  
 pg. 65 Line 46 change from:  
 "b) The MPRS converts between the MAC serial data stream and the parallel data paths of  
 up to four 25GMII servicing separate PHYs." to:  
 "b) The MPRS converts between the MAC serial data stream and the parallel data paths to  
 multiple 25GMII servicing separate PHYs."  
 pg. 68 line 2 Change from:  
 "The 100G-EPON MPRS is defined as a set of four parallel MPRS channels in each  
 direction." to:  
 "The 100G-EPON MPRS is defined as a multiple set of parallel MPRS channels in each  
 direction."  
 pg. 68 line 8 Change from:  
 "Compliant implementations are not required to support all four MPRS channels." To:  
 "Compliant implementations are not required to support multiple MPRS channels."  
 pg. 68 line 10 strike the sentence that reads:  
 "An implementation containing all four channels supports 25 Gb/s, 50 Gb/s, and 100 Gb/s  
 MAC data rates."  
 pg. 68 line 39 change:  
 "(N = {1,2,3,4})" to:  
 "(N = {1,2})"  
 pg. 70 line 53 strike the sentence that reads:  
 "Some ONUs may support all four MPRS channels in each direction."  
 pg. 71 line 37 Change from:  
 "Thus, a 100G-EPON system with four MPRS channels of 25 Gb/s each can achieve an  
 instantaneous transmission rate of 25, 50, 75, or 100 Gb/s by varying, ..." To:  
 "Thus, a 100G-EPON system with two MPRS channels of 25 Gb/s each can achieve an  
 instantaneous transmission rate of 25, or 50 Gb/s by varying, ..."  
 pg. 74 line 50 Change from:  
 "In addition to the multiple PLS service interfaces (one per MAC) and up to four 25GMII"  
 To:  
 "In addition to the multiple PLS service interfaces (one per MAC) and multiple 25GMII"  
 pg. 75 line 51 Change from:

Proposed Responses Specifications and Management Parameters for 25Gb/s, 50Gb/s, and 100Gb/s Passive Optical Networks 1:

"However, for other 100G-EPON systems there may be one, two or four PLS service interfaces active at any given time." To:  
 "However, for other 100G-EPON systems there may be one, or two PLS service interfaces active at any given time."  
 pg. 85 line 3 strike "(four columns)"

Proposed Response Response Status **W**  
 PROPOSED ACCEPT IN PRINCIPLE.

All changes as proposed, with one difference: "rate of 25, or 50 Gb/s" should be "rate of 25 or 50 Gb/s" (no need for serial comma).

Cl 143 SC 143.1 P65 L18 # 53  
 Remein, Duane Huawei Technologies  
 Comment Type **E** Comment Status **D** bucket

It appears the abbreviation "PCS" gets defined later in the para.

SuggestedRemedy

Change "PCS" on line 18 to read "Physical Coding Sublayer (PCS)" and on line 20 change "Physical Coding Sublayers (PCS)" to read "PCSs".

Proposed Response Response Status **W**  
 PROPOSED ACCEPT.

Cl 143 SC 143.1 P65 L20 # 54  
 Remein, Duane Huawei Technologies  
 Comment Type **T** Comment Status **D**

"The 100G-EPON Physical Coding Sublayers (PCS) are specified to the 25GMII, ..."?  
 Needs to be rephrased.

SuggestedRemedy

Change to read "The 100G-EPON PCSs are specified to interface with the 25GMII, ..."

Proposed Response Response Status **W**  
 PROPOSED ACCEPT.

Cl 143 SC 143.2.1 P67 L12 # 55  
 Remein, Duane Huawei Technologies  
 Comment Type **E** Comment Status **D** bucket

Missing article "below MAC"

SuggestedRemedy

Change to "below the MAC"

Proposed Response Response Status **W**  
 PROPOSED ACCEPT.

Cl 143 SC 143.2.2.1 P68 L20 # 56  
 Remein, Duane Huawei Technologies

Comment Type **T** Comment Status **D**  
 100G-EPON stuff. Table 143-1 should be pruned to two channels.

SuggestedRemedy

Remove rows DS2, DC3, UC2, and UC3.

Proposed Response Response Status **W**  
 PROPOSED ACCEPT.

Cl 143 SC 143.2.3.3 P69 L46 # 57  
 Remein, Duane Huawei Technologies

Comment Type **T** Comment Status **D**  
 "the ESH is discarded ..." well there's certainly more to it that a simple discard.

SuggestedRemedy

Change to "the ESH is processed by the MPRS and then discarded..."

Proposed Response Response Status **W**  
 PROPOSED ACCEPT.

Cl 143 SC 143.2.4.2 P72 L1 # 58  
 Remein, Duane Huawei Technologies

Comment Type **T** Comment Status **D**  
 100G-EPON stuff. Figure 143-6, 143-7, 143-8, 143-9, 143-10, 143-11, 143-12, 143-15 need updating to show only two channels.

SuggestedRemedy

per comment

Proposed Response Response Status **W**  
 PROPOSED REJECT.

Given the complexity, the Editor will need replacement figures with specific changes to demonstrate needed changes. Alternatively, we can mark these as concept examples, using 4 channels.

Proposed Responses Specifications and Management Parameters for 25Gb/s, 50Gb/s, and 100Gb/s Passive Optical Networks 1:

CI 143 SC 143.2.4.3 P73 L6 # 59  
 Remein, Duane Huawei Technologies

Comment Type TR Comment Status D

In referring to the ENV\_Tx/Rx buffers is this statement; "The number of rows is set to 32,"  
 But in Table 143-4 and on pg. 82 line 16 EnvPam is defined as 6 bits. These should agree,  
 if the ONU uses 6 bits and the OLT only 5 well there's a problem brewing.

SuggestedRemedy

Change to "The number of rows is set to 64," align Fig 143-8 to 64 (may also reduce  
 number of columns due to separate comment).

Proposed Response Response Status W

PROPOSED REJECT.

There is no issue with the EH having the field larger than actually needed (64 possible, 32  
 used). As long as 32 is the setting on both ONU and OLT, no interop problems are  
 expected.

CI 143 SC 143.2.4.3 P73 L28 # 60  
 Remein, Duane Huawei Technologies

Comment Type TR Comment Status D

We are inconsistent in our reference to the TX\_CLK. Fig 143-10 names it TX\_CLK25 and  
 shows one per 25GMII. Table 143-2 uses TX\_CLK and includes a footnote that all  
 25GMII's share a common clock. Section 143.4.1.3 on pg. 78 ln. 39 clearly states that "only  
 one TX\_CLK is required". TX\_CLK[c] is defined on pg. 82 ln. 46 and implies there is one  
 TX\_CLK per channel; "of the TX\_CLK signal for channel c".

SuggestedRemedy

In Fig 143-10 pull TX\_CLK25 out of the 25GMII grouping to indicate it is a common signal.  
 When TX\_CLK refers to that common signal use TX\_CLK25 {(pg., ln.), (73,28), (76,50),  
 (78,39), (82,30), (82,49), (85,5), (88,38), (88,39), and ex in Table 143-2}.

On pg. 82 line 48 remove "for channel c" so the definition reads; "Each TX\_CLK[c] clear on  
 read variable is set to True on each edge, positive and negative, of the TX\_CLK25 signal."

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Per comment, excluding changes to Fig 143-10 - please submit a suggestion on what  
 changes need to be really made: "pull TX\_CLK25 out of the 25GMII grouping to indicate it  
 is a common signal" is not really clear in the current context.

CI 143 SC 143.2.4.4 P73 L37 # 61  
 Remein, Duane Huawei Technologies

Comment Type T Comment Status D

Clarification.

SuggestedRemedy

Change:  
 "the EPAM field is extracted and its value is used as the write pointer (row index) ..."

to read:

"the EPAM field is extracted and its value is used to update the write pointer (row index) ..."

Proposed Response Response Status W

PROPOSED ACCEPT.

CI 143 SC 143.3.3.2 P101 L44 # 98  
 Remein, Duane Huawei Technologies

Comment Type E Comment Status D bucket

links dead (3x 144.2.2.3 on this page, and several on pg. 102, 112, 113 and possibly  
 elsewhere)

SuggestedRemedy

make live

Proposed Response Response Status W

PROPOSED ACCEPT.

CI 143 SC 143.4.1.1.1 P77 L3 # 62  
 Remein, Duane Huawei Technologies

Comment Type TR Comment Status D

100G-EPON stuff. Table 143-2 and 143-3 should be pruned to two channels.

SuggestedRemedy

Remove row for 100G-EPON

Proposed Response Response Status W

PROPOSED ACCEPT.

Proposed Responses Specifications and Management Parameters for 25Gb/s, 50Gb/s, and 100Gb/s Passive Optical Networks 1:

CI 143 SC 143.4.1.2 P78 L4 # 63  
 Remein, Duane Huawei Technologies  
 Comment Type T Comment Status D  
 Incorrect references to Tables 143-3 & 4.  
 SuggestedRemedy  
 Add new table per remain\_3ca\_2\_0518.pdf and reference new table.  
 Proposed Response Response Status W  
 PROPOSED ACCEPT IN PRINCIPLE.  
 Per comment, but rather than "[ch]", use "\_j"

CI 143 SC 143.4.1.2.1 P78 L11 # 64  
 Remein, Duane Huawei Technologies  
 Comment Type E Comment Status D  
 epam should be in italics  
 More generally we need to decide if we want to follow this guideline, that variable names appear in italics. As a past editor that did adopt this guideline I found it a royal pain and would not object to not following it (I notice in the standard that few amendments do).  
 SuggestedRemedy  
 Italicize "epam"  
 Proposed Response Response Status W  
 PROPOSED REJECT.  
 In this case, "epam" is a value, and not a variable. Following the style guide, it should not be italicized.

CI 143 SC 143.4.1.2.2 P78 L21 # 65  
 Remein, Duane Huawei Technologies  
 Comment Type TR Comment Status D  
 The MPCP does not need to wait "for the start of next FEC codeword (for envelopes that are expected to be in a separate transmission burst)." the MPCP can start a new envelope at it's discretion.  
 SuggestedRemedy  
 Change to "for envelopes that are expected to be in a separate transmission bursts."  
 Proposed Response Response Status W  
 PROPOSED ACCEPT.

CI 143 SC 143.4.1.3 P78 L37 # 66  
 Remein, Duane Huawei Technologies  
 Comment Type E Comment Status D bucket  
 It would be easier on the reader if we just reference the tables rather than the section.  
 SuggestedRemedy  
 Change: "143.4.1.1" to "Table 143-2 and Table 143-3"  
 Proposed Response Response Status W  
 PROPOSED ACCEPT.

CI 143 SC 143.4.2 P79 L15 # 67  
 Remein, Duane Huawei Technologies  
 Comment Type E Comment Status D  
 In Fig 143-11 Octet 0 seems to have two extra bits before bit 8 and after bit 15. Also we seem to have lost the EPAM label (TXD-Lane0 in 2nd transfer).  
 SuggestedRemedy  
 Trim the line immediately before the 8 and after the 15 so they are short and don't extent top to bottom. Add EPAM label (if using the original visio file it may be hiding behind the white box representing bits 0-5).  
 Proposed Response Response Status W  
 PROPOSED ACCEPT IN PRINCIPLE.  
 Trim the line immediately before the 8 and after the 15 so they are short and don't extent top to bottom.  
 Not clear where the EPAM label should be placed.

CI 143 SC 143.4.2 P79 L35 # 68  
 Remein, Duane Huawei Technologies  
 Comment Type E Comment Status D  
 Wording: "transmission of ... the transmitting MPRS"  
 SuggestedRemedy  
 Change to "transmission of the envelope from the sending MPRS"  
 Proposed Response Response Status W  
 PROPOSED ACCEPT IN PRINCIPLE.  
 Change to "transmission of the envelope from the source MPRS"

Proposed Responses Specifications and Management Parameters for 25Gb/s, 50Gb/s, and 100Gb/s Passive Optical Networks 1:

CI 143 SC 143.4.3 P80 L21 # 69  
 Remein, Duane Huawei Technologies  
 Comment Type T Comment Status D  
 Clarification on what CRC covers in normative table.  
 SuggestedRemedy  
 Change "CRC8" to "CRC8 covering bit 0-63"  
 Proposed Response Response Status W  
 PROPOSED ACCEPT.  
 Changes from E to T

CI 143 SC 143.4.3 P80 L44 # 70  
 Remein, Duane Huawei Technologies  
 Comment Type TR Comment Status D  
 This cannot be true as wRow is a 1-bit variable. "(Number of bits matches the size of wRow)". This confusion exists because we use rRow and wRow in both the transmit and receive SDs to mean two different variable sets. In the transmit SD we only need a 1-bit variable while in the receive SD we need a 6-bit variable.  
 SuggestedRemedy  
 Align variable name to SD in which it is used so that:  
 In section 143.4.3 change wRow to iRow (for input row) and rRow to tRow (for transmit row) in text and figures.  
 In section 143.4.4 change wRow to rRow (for receive row) and rRow to oRow (for output row) in text and figures.  
 at pg. 80 line 44 Change to "(Number of bits matches the size of rRow)"  
 Proposed Response Response Status W  
 PROPOSED REJECT.  
 Page 80, like 44 does not have the referenced text.

CI 143 SC 143.4.3.2 P81 L9 # 71  
 Remein, Duane Huawei Technologies  
 Comment Type E Comment Status D  
 I don't believe we have any timers in this section.  
 SuggestedRemedy  
 Remove the blurb about time start and stop.  
 Proposed Response Response Status W  
 PROPOSED ACCEPT IN PRINCIPLE.  
 Remove text page 81, lines 9-12

CI 143 SC 143.4.3.3 P81 L14 # 72  
 Remein, Duane Huawei Technologies  
 Comment Type E Comment Status D bucket  
 Does this notation only apply to counters as indicated or does it also apply to other variables?  
 "The notation ++ after a counter indicates",  
 "The notation -- after a counter indicates",  
 "The notation -= after a counter indicates", and  
 "The notation += after a counter indicates"  
 SuggestedRemedy  
 Change to "counter" to "variable" in each instance. (may want to apply this globally)

Proposed Response Response Status W  
 PROPOSED ACCEPT.  
 CI 143 SC 143.4.3.4 P81 L53 # 73  
 Remein, Duane Huawei Technologies  
 Comment Type T Comment Status D  
 100G-EPON stuff. We no longer have 4 channels  
 SuggestedRemedy  
 change to 1-bit integer.  
 Proposed Response Response Status W  
 PROPOSED REJECT.  
 No harm in keeping it at 2 bits

CI 143 SC 143.4.3.4 P82 L23 # 8  
 Heaven, Bo Huawei  
 Comment Type TR Comment Status D  
 Need exact components of GRANT\_MARGIN and its default value or maximum value  
 SuggestedRemedy  
 Add "The value includes LaserOnTime, syncTime, and Burst Delimiter that precede the first packet in the burst."  
 Proposed Response Response Status W  
 PROPOSED REJECT.  
 Better text will be needed, likely tied to the SP1/2/3 durations as announced using SYNC\_PATTERN MPCPDU

Proposed Responses Specifications and Management Parameters for 25Gb/s, 50Gb/s, and 100Gb/s Passive Optical Networks 1:

CI 143 SC 143.4.3.4 P82 L36 # 75  
 Remein, Duane Huawei Technologies  
 Comment Type E Comment Status D bucket  
 TYPE mis-aligned  
 SuggestedRemedy  
 Indent  
 Proposed Response Response Status W  
 PROPOSED ACCEPT.

CI 143 SC 143.4.3.4 P82 L36 # 74  
 Remein, Duane Huawei Technologies  
 Comment Type T Comment Status D  
 "LinkID[c]" s/b "LinkId[c]" (or alternatively the other way around, now we have both forms).  
 SuggestedRemedy  
 Change all instances of "LinkID" to "LinkId"  
 Proposed Response Response Status W  
 PROPOSED ACCEPT.

CI 143 SC 143.4.3.4 P83 L2 # 76  
 Remein, Duane Huawei Technologies  
 Comment Type TR Comment Status D  
 100G-EPON stuff "For 100 Gb/s devices N = 4, for 50 Gb/s devices N = 2, and for 25 Gb/s devices N = 1."  
 SuggestedRemedy  
 Change to: "For 50 Gb/s devices N = 2 and for 25 Gb/s devices N = 1."  
 Proposed Response Response Status W  
 PROPOSED ACCEPT.

CI 143 SC 143.4.3.4 P83 L7 # 77  
 Remein, Duane Huawei Technologies  
 Comment Type TR Comment Status D  
 100G-EPON stuff. For wCol change type to 1-bit integer  
 SuggestedRemedy  
 per comment  
 Proposed Response Response Status W  
 PROPOSED REJECT.

No harm in keeping it at 2 bits' wide.  
 CI 143 SC 143.4.3.5 P83 L44 # 78  
 Remein, Duane Huawei Technologies  
 Comment Type TR Comment Status D  
 100G-EPON stuff. EnvStartHeader() section should be updated to reflect only 2 channels  
 SuggestedRemedy  
 Change:  
 if( EnvLeft[col+1] == GRANT\_MARGIN &&  
 EnvLeft[col+2] == GRANT\_MARGIN &&  
 EnvLeft[col+3] == GRANT\_MARGIN ) EnvPam = epam;  
 To:  
 if( EnvLeft[col+1] == GRANT\_MARGIN ) EnvPam = epam;  
 Proposed Response Response Status W  
 PROPOSED ACCEPT.

CI 143 SC 143.4.3.6.1 P85 L2 # 79  
 Remein, Duane Huawei Technologies  
 Comment Type E Comment Status D bucket  
 What is a "start envelope header"  
 SuggestedRemedy  
 Change to "envelope start header"  
 Proposed Response Response Status W  
 PROPOSED ACCEPT.

Proposed Responses Specifications and Management Parameters for 25Gb/s, 50Gb/s, and 100Gb/s Passive Optical Networks 1:

Cl 143 SC 143.4.3.6.1 P85 L4 # 80  
 Remein, Duane Huawei Technologies  
 Comment Type **TR** Comment Status **D**  
 100G-EPON stuff. "(four columns)"  
 SuggestedRemedy  
 Strike.  
 Proposed Response Response Status **W**  
 PROPOSED ACCEPT.

Cl 143 SC 143.4.4 P87 L38 # 83  
 Remein, Duane Huawei Technologies  
 Comment Type **ER** Comment Status **D**  
 Errant ref to 143.4.3.6.1  
 SuggestedRemedy  
 Change to 143.4.4.5.1  
 Proposed Response Response Status **W**  
 PROPOSED ACCEPT.

Cl 143 SC 143.4.3.6.1 P85 L7 # 81  
 Remein, Duane Huawei Technologies  
 Comment Type **T** Comment Status **D**  
 Clarification; "The process adjusts the MAC rate to account for FEC parity insertion in the PCS."  
 SuggestedRemedy  
 Change to read: "The process adjusts the MAC rate by inserting PARITY\_PLACEHLDR EQs to account for FEC parity insertion in the PCS."  
 Proposed Response Response Status **W**  
 PROPOSED ACCEPT.

Cl 143 SC 143.4.4.3 P88 L46 # 84  
 Remein, Duane Huawei Technologies  
 Comment Type **TR** Comment Status **D**  
 100G-EPON stuff. The TYPE for rCol should reflect 2 columns not 4  
 SuggestedRemedy  
 change to 1-bit integer.  
 Proposed Response Response Status **W**  
 PROPOSED REJECT.  
 No harm in keeping it at 2 bits' wide.

Cl 143 SC 143.4.3.6.1 P86 L48 # 82  
 Remein, Duane Huawei Technologies  
 Comment Type **E** Comment Status **D** bucket  
 Extraneous line extending up into WRITE\_EQ\_TO\_ENV\_TX state.  
 SuggestedRemedy  
 In the words of the famous Pete Trowbridge "nudge the line" down so it does not interfere with the state box.  
 Proposed Response Response Status **W**  
 PROPOSED ACCEPT.

Cl 143 SC 143.4.4.3 P89 L13 # 85  
 Remein, Duane Huawei Technologies  
 Comment Type **TR** Comment Status **D**  
 100G-EPON stuff. "For 100 Gb/s devices N = 4, for 50 Gb/s devices N = 2, and for 25 Gb/s devices N = 1."  
 SuggestedRemedy  
 Change to: "For 50 Gb/s devices N = 2 and for 25 Gb/s devices N = 1."  
 Proposed Response Response Status **W**  
 PROPOSED ACCEPT.



Proposed Responses Specifications and Management Parameters for 25Gb/s, 50Gb/s, and 100Gb/s Passive Optical Networks 1:

Cl 143 SC 143.4.4.4 P89 L32 # 86  
 Remein, Duane Huawei Technologies  
 Comment Type E Comment Status D bucket  
 This editorial note has served its purpose; "EDITOR NOTE: the IsHeader() function was originally defined ..."  
 SuggestedRemedy  
 Strike note  
 Proposed Response Response Status W  
 PROPOSED ACCEPT.

Cl 143 SC 143.4.4.4 P89 L34 # 87  
 Remein, Duane Huawei Technologies  
 Comment Type TR Comment Status D  
 IsMisaligned is written for an ordered set header  
 SuggestedRemedy  
 Replace function definition with:  

```
bool IsMisaligned(EQ eq )
{
    return(( eq<39:36> == 0xF AND // Mis-aligned INTER_ENV_IDLE
           eq<71:40> == 08080808 ) // ... s.b. INTER_ENV_IDLE
           OR
           ( eq<39:36> == 0x8 AND // Misaligned Env. Header
           eq<47:40> == 0xFB )); // ... s.b. Start Control Code
}
```

 Proposed Response Response Status W  
 PROPOSED ACCEPT IN PRINCIPLE.

Replace function definition with:  

```
bool IsMisaligned(EQ eq )
{
    return(( eq<39:36> == 0xF AND // Mis-aligned INTER_ENV_IDLE
           eq<71:40> == 0x08080808 ) // ... s.b. INTER_ENV_IDLE
           OR
           ( eq<39:36> == 0x8 AND // Misaligned Env. Header
           eq<47:40> == 0xFB )); // ... s.b. Start Control Code
}
```

Cl 143 SC 143.4.4.4 P90 L17 # 88  
 Remein, Duane Huawei Technologies  
 Comment Type TR Comment Status D  
 The function, SetMacOctet is not defined.  
 SuggestedRemedy  
 Add in 143.3.3:  
 SetMacOctet( link\_id, rx\_data, data\_valid )  
 This function shifts the eight bits in rx\_data to the MAC using the PLS\_DATA.indication, along with the data\_valid Boolean using the PLD\_DATA\_VALID.indication to the MAC associated with link\_id.  
 Proposed Response Response Status W  
 PROPOSED ACCEPT.

Cl 143 SC 143.4.4.4 P90 L27 # 89  
 Remein, Duane Huawei Technologies  
 Comment Type E Comment Status D bucket  
 This phrase does not make sense. "due to different ONUs and transport skew,"  
 SuggestedRemedy  
 Change to "due to different delay and transport skew for each ONU,"  
 Proposed Response Response Status W  
 PROPOSED ACCEPT.

Cl 143 SC 143.4.4.5.2 P91 L39 # 90  
 Remein, Duane Huawei Technologies  
 Comment Type T Comment Status D  
 Clarification to "no subsequent frames are lost due to the error"  
 SuggestedRemedy  
 Change to read: "no subsequent frames are lost due to the error since the next envelope continuation header will resynchronize the process for the following frame."  
 Proposed Response Response Status W  
 PROPOSED ACCEPT IN PRINCIPLE.

Change to read: "no subsequent frames are lost due to the error since the next envelope continuation header resynchronizes the process for the following frame."

Proposed Responses Specifications and Management Parameters for 25Gb/s, 50Gb/s, and 100Gb/s Passive Optical Networks 1:

Cl 143 SC 143.4.4.5.2 P92 L33 # 91  
Remein, Duane Huawei Technologies

Comment Type T Comment Status D

What is magical about OutEQ<16> = 1?

SuggestedRemedy

It represents an Envelope Start Header.  
Replace OutEQ<16> = 1 with OutEQ<16> = ES\_HEADER  
Add definition to constants:  
ES\_HEADER  
TYPE: integer  
Value: 1  
The value of the envelope Start Flag indicating the header is an envelope start header.

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 144 SC 144.3.3.2 P102 L3 # 99  
Remein, Duane Huawei Technologies

Comment Type E Comment Status D bucket

"who"? ONUs are not people.

SuggestedRemedy

Change "who may then retry" to "which may then retry"

Proposed Response Response Status W

PROPOSED ACCEPT.

Wrong clause (is 143 and should be 144)

Cl 144 SC 144.1.6 P97 L18 # 92  
Remein, Duane Huawei Technologies

Comment Type ER Comment Status D

In 10G these were included in the variable definitions. This would be better imho than in conventions.

SuggestedRemedy

Move MACI & MADI definitions to the variable definitions section.

Proposed Response Response Status W

PROPOSED REJECT.

These have nothing to do with variables, and are just part of conventions used in the SDs in this clause.

Cl 144 SC 144.3.3 P98 L4 # 93  
Remein, Duane Huawei Technologies

Comment Type E Comment Status D bucket

We have a mix of Discovery Window(s) and discovery window(s), we should be consistent.

SuggestedRemedy

Use lower case consistently.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Use "Discovery Window" consistently

Wrong clause (is 143 and should be 144)

Cl 144 SC 144.3.3 P98 L6 # 94  
Remein, Duane Huawei Technologies

Comment Type T Comment Status D

More likely the end user (SP) "The periodicity of these windows is unspecified and left up to the implementer"

SuggestedRemedy

Strike "and left up to the implementer"

Proposed Response Response Status W

PROPOSED REJECT.

A system may or may not expose periodicity parameters to the end user. Current statement is correct.

Wrong clause (is 143 and should be 144)

Proposed Responses Specifications and Management Parameters for 25Gb/s, 50Gb/s, and 100Gb/s Passive Optical Networks 1:

Cl 144 SC 144.3.3 P98 L30 # 95  
 Remein, Duane Huawei Technologies

Comment Type T Comment Status D

We are using EQ to mean both a number of bits (72, 4 control and 64 data) and a time period (2.56ns). Using as a time is ambiguous as it depends on the rate (2.56 ns is only correct at 25GMII which is 36-bits wide) It would be a good idea to explicitly distinguish these two uses.

SuggestedRemedy

Where EQ is referring to a time change to EQt and add to definitions to mean 2.56 ns.

Proposed Response Response Status W

PROPOSED REJECT.

Please suggest a specific change - it is not really clear what the source of the issue is: 1EQ is defined at 25GMII level (see 143.2.3.1) and it is clear how much time it takes using 25GMII data rate and number of bits covered by 1EQ.

Wrong clause (is 143 and should be 144)

Cl 144 SC 144.3.3 P98 L33 # 2  
 Heaven, Bo Huawei

Comment Type T Comment Status D

LLID looks a not that accurate.

SuggestedRemedy

Change "LLID" to "PLID and MLID"

Proposed Response Response Status W

PROPOSED ACCEPT.

Type changed from E to T

Cl 144 SC 144.3.3 P98 L35 # 97  
 Remein, Duane Huawei Technologies

Comment Type T Comment Status D

We now using more than one LLID; "which contains the ONU's LLID"

SuggestedRemedy

Change "LLID" to "LLIDs"

Proposed Response Response Status W

PROPOSED ACCEPT.

Wrong clause (is 143 and should be 144)

Cl 144 SC 144.3.3 P98 L36 # 3  
 Heaven, Bo Huawei

Comment Type E Comment Status D

as same as above

SuggestedRemedy

Proposed Response Response Status W

PROPOSED REJECT.

Context is missing

Cl 144 SC 144.3.3.2 P102 L13 # 100  
 Remein, Duane Huawei Technologies

Comment Type T Comment Status D

The PMD is not turned on and off, the laser in the PMD is.

SuggestedRemedy

Change:  
 "turning off the PMD" to "turning off the laser" and  
 "turning on the PMD" to "turning on the laser" (line 20)

Proposed Response Response Status W

PROPOSED ACCEPT.

Wrong clause (is 143 and should be 144)

Cl 144 SC 144.3.3.5 P103 L24 # 101  
 Remein, Duane Huawei Technologies

Comment Type TR Comment Status D

I find neither MAC:MADI nor MAC:MADI in 2.3.2. Same issue pg. 113 and 117.

SuggestedRemedy

spell out the alias so that the definition can be found in the referenced section.

Proposed Response Response Status W

PROPOSED REJECT.

MADI and MACR are defined in 2.3.2 - see 144.1.6 for definitions of what these stand for.

Proposed Responses Specifications and Management Parameters for 25Gb/s, 50Gb/s, and 100Gb/s Passive Optical Networks 1:

Cl 144 SC 144.3.3.5 P103 L35 # 102  
 Remein, Duane Huawei Technologies

Comment Type TR Comment Status D

We're using new opcodes for our messages.

SuggestedRemedy

Change names for all Opcodes used (suggest xxx25, so DISCOVERY25). Open 31A and add new opcodes to Table 31A-1.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

These opcodes are specific to Clause 144. If any changes in definitions are needed, they would go into Annex 31A.

Add Annex 31A to the draft, and insert new entries into Table 31A-1, covering new opcodes defined in Clause 144 with appropriate cross references. Update the 00-07 through 01-00 entry to match the range remaining after allocation of new Opcodes for Clause 144 MPCPDUs.

Cl 144 SC 144.3.3.5 P106 L44 # 103  
 Remein, Duane Huawei Technologies

Comment Type T Comment Status D

OpcodespecificFunction does not seem to be used anywhere but it is defined twice; here and on pg. 114.

SuggestedRemedy

Remove both definitions.

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 144 SC 144.3.3.6 P107 L5 # 4  
 Heaven, Bo Huawei

Comment Type TR Comment Status D

The broadcast LLID of 25G should be defined for distinguishing from 10G's in the case of coexistence with 10GEPON

SuggestedRemedy

Change "0x7FFE" to "0x7FFD"

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 144 SC 144.3.3.6 P110 L15 # 5  
 Heaven, Bo Huawei

Comment Type TR Comment Status D

Cannot find the definition of GuardThresholdOLT

SuggestedRemedy

The value of 8EQs for the purpose of promoting the accuracy of upstream will be good to carry realtime service in upstream

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

guardThresholdOLT  
 This constant holds the maximal amount of drift allowed for a timestamp received at the OLT. This value is measured in units of 1 EQ.  
 TYPE: integer  
 VALUE: 8

Cl 144 SC 144.3.4.6 P115 L11 # 104  
 Remein, Duane Huawei Technologies

Comment Type TR Comment Status D

Is there precedence for using a for loop within a state in a SD?

SuggestedRemedy

I could not find any. If it exists I may withdraw this comment.  
 I suggest splitting the states that use the construct into two. One state would set the variables that don't need the looping and another to set those variable that do need the looping.

Proposed Response Response Status W

PROPOSED REJECT.

There is absolutely no need to further complicate the SD by "looping" in graphical form. "for" loop is commonly used in all types of languages and concetp behind it - well understood.

Cl 144 SC 144.3.4.6 P115 L47 # 105  
 Remein, Duane Huawei Technologies

Comment Type T Comment Status D

"MCI:NADR" s/b "MCI:MADR"

SuggestedRemedy

per comment

Proposed Response Response Status W

PROPOSED ACCEPT.

Proposed Responses Specifications and Management Parameters for 25Gb/s, 50Gb/s, and 100Gb/s Passive Optical Networks 1:

Cl 144 SC 144.3.5 P116 L3 # 106  
Remein, Duane Huawei Technologies  
Comment Type T Comment Status D  
We now have multiple transmitters "...arbitrate a single transmitter ..."  
SuggestedRemedy  
Change to "... arbitrate specific transmitters ..."  
Proposed Response Response Status W  
PROPOSED ACCEPT.

Cl 144 SC 144.3.5 P116 L13 # 107  
Remein, Duane Huawei Technologies  
Comment Type T Comment Status D  
Should we also concern ourselves with the minimum maximum and maybe median maximums? "The OLT shall not issue more than the maximum supported maximum outstanding grants as advertised by the ONU during registration (see pending grants in 77.3.6.3)."  
SuggestedRemedy  
Change to: ""The OLT shall not issue to an ONU more outstanding grants than the pending grants parameter advertised during registration (see pending grants in 77.3.6.3)."  
Proposed Response Response Status W  
PROPOSED ACCEPT IN PRINCIPLE.  
Changed type from E to T  
Change "maximum supported maximum outstanding grants" to "maximum supported outstanding grants"

Cl 144 SC 144.3.5 P116 L17 # 108  
Remein, Duane Huawei Technologies  
Comment Type T Comment Status D  
"In order to maintain the watchdog timer at the ONU, grants are periodically generated." Can they be any grants to any ONU?  
SuggestedRemedy  
Add to the sentence so it reads: "In order to maintain the watchdog timer at the ONU, grants are periodically generated for that ONU."  
Proposed Response Response Status W  
PROPOSED REJECT.  
The following sentence clarifies what is used and how it is used.

Cl 144 SC 144.3.5.5 P118 L14 # 110  
Remein, Duane Huawei Technologies  
Comment Type T Comment Status D  
MCC:MACR() missing DA  
SuggestedRemedy  
Add DA to message.  
Proposed Response Response Status W  
PROPOSED ACCEPT.

Cl 144 SC 144.3.5.5 P118 L14 # 111  
Remein, Duane Huawei Technologies  
Comment Type TR Comment Status D  
The definition of MCC:MACR(DA, GATE ...) in 144.36.3.5 states for LLID[7] "Only elements j with non-zero value in associated Length[j] field of the array are used." Similar statements are made for Length, Fragment, etc. However, in the normative SD there is no accommodation for omitting zero length fields.  
Same issue in Fig 144-5 ONU GATE Reception Process state diagram pg. 119 and possibly Fig 144-11 (pg. 115), and Fig 144-12 (pg. 115).  
SuggestedRemedy  
In the SD change the "[7]" for LLID, Length, Fragment and ForceReport to "[n]". In SEND GATE state change for "(i=0;i<7;i++)" to "for (i=0;i<n;i++)".  
Add a definition for "n" as the integer number of non-zero value Length(j) fields.  
Proposed Response Response Status W  
PROPOSED ACCEPT IN PRINCIPLE.  
In the SD change the "[7]" for LLID, Length, Fragment and ForceReport to "[n]". In SEND GATE state change for "(i=0;i<7;i++)" to "for (i=0;i<n;i++)".  
It is not clear where the said definition of "n" would be added.

Proposed Responses Specifications and Management Parameters for 25Gb/s, 50Gb/s, and 100Gb/s Passive Optical Networks 1:

CI 144 SC 144.3.5.6 P117 L31 # 109  
 Remein, Duane Huawei Technologies  
 Comment Type T Comment Status D  
 MA\_CONTROL.request(DA, GATE, ChMap, StartTime, LLID[7], Length[7], Fragment[7], ForceReport[7]) is not defined in 144.3.3.5. Perhaps MCC:MACR(DA, GATE, ChMap, StartTime, LLID[7], Length[7], Fragment[7], ForceReport[7]) is being referred to.  
 SuggestedRemedy  
 Change to: MCC:MACR(DA, GATE, ChMap, StartTime, LLID[7], Length[7], Fragment[7], ForceReport[7])  
 Proposed Response Response Status W  
 PROPOSED ACCEPT.

CI 144 SC 144.3.7 P122 L2 # 112  
 Remein, Duane Huawei Technologies  
 Comment Type TR Comment Status D  
 We use normative language here for the generic MPCPDU but informative language when describing details of the specific MPCPDUs (except for LLID type and a few other parameters). It would be more precise to use informative language here and normative language with the specifics. This will also make PICs easier as there will only need to be one PICS statement per MPCPDU type rather than multiple requirements (see MP6-16 in CI 64).  
 SuggestedRemedy  
 Change:  
 "The MPCPDU structure shall be as shown in Figure 144–17, and is further defined as follows:" to read  
 "The MPCPDU structure is shown in Figure 144–17, with details defined as follows:"  
 In the opening paras for each MPCPDU type change from:  
 "The mpcpdu\_type MPCPDU is an instantiation of the Generic MPCPDU, and is further defined as follows:" to  
 "The mpcpdu\_type MPCPDU is an instantiation of the Generic MPCPDU and shall be as shown in Figure 144-xx with details defined as follows:"  
 where mpcpdu\_type is one of DISCOVERY GATE, REGISTER\_REQ, REGISTER, REGISTER\_ACK, GATE, or REPORT and xx is replace with the appropriate figure ref.  
 Where there is additional normative language in the description change it to be informative. For example sentences such as:  
 "The mpcpdu\_type MPCPDU shall be generated by a MAC Control instance ..."  
 Change to:  
 "The mpcpdu\_type MPCPDU is generated by a MAC Control instance ..."  
 Proposed Response Response Status W  
 PROPOSED REJECT.  
 The very same definition style was used in 1G-EPON and 10G-EPON and never caused concerns about the "language".

Proposed Responses Specifications and Management Parameters for 25Gb/s, 50Gb/s, and 100Gb/s Passive Optical Networks 1:

Cl 144 SC 144.3.7 P122 L4 # 113  
 Remein, Duane Huawei Technologies

Comment Type TR Comment Status D

We now have a specific LLID for MPCP traffic; the PLID. Shouldn't this be reflected in DA and SA?

SuggestedRemedy

Change "port" to "PLID" so this reads:

- a) Destination Address (DA). The DA in MPCPDU is the MAC Control Multicast address as specified in the annexes to Clause 31, or the individual MAC address associated with the PLID to which the MPCPDU is destined.
- b) Source Address (SA). The SA in MPCPDU is the individual MAC address associated with the PLID through which the MPCPDU is transmitted. For MPCPDUs originating at the OLT end, this can be the address any of the individual MACs. These MACs may all share a single unicast address, as explained in 144.1.2.

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 144 SC 144.3.7 P122 L40 # 114  
 Remein, Duane Huawei Technologies

Comment Type TR Comment Status D

We've lost all reference to the order in which bits within a field are transmitted.

SuggestedRemedy

In all MPCPDU message figures add the following note: "Octets within the frame are transmitted from top to bottom. Bits within a field or word are transmitted left to right with the leftmost bit within a field being the lsb." The arrow/note to the right of the octet numbering can then be removed.  
 Note that the label "Octets" should be kept and placed above the rightmost column of numbers.

Proposed Response Response Status W

PROPOSED REJECT.

This information was dropped from figures per comment #83 on D0.7, since it was considered superfluous and confusing.

Cl 144 SC 144.3.7.1 P122 L43 # 115  
 Remein, Duane Huawei Technologies

Comment Type E Comment Status D

The order in which we describe MPCPDUs does not follow any logical order. We should first describe discovery & registration then proceed to Gates & Reports. In 1G & 10G Gates included discovery so there was some logic to the order.

SuggestedRemedy

Put MPCPDU descriptions in the following order; DISCOVERY, REGISTER\_REQ, REGISTER, REGISTER\_ACK, GATE, and REPORT.

Proposed Response Response Status W

PROPOSED REJECT.

The order of definition does not help in any way to understand the use cases - MPCPDUs are referenced throughout the text, and not just here.

Cl 144 SC 144.3.7.1 P122 L45 # 170  
 Kramer, Glen Broadcom

Comment Type TR Comment Status D

Description of GATE message is wrong. Grants with zero length are valid and are used to request a report for a specific LLID without granting that LLID.

Reports are not sent in the associated grants. They are sent in PLID grant.

Transmission overhead components are not included in granted length.

SuggestedRemedy

Replace the text of this subclause with the text provided in the attached file kramer\_3ca\_3\_0518.pdf.

Proposed Response Response Status W

PROPOSED ACCEPT.

Proposed Responses Specifications and Management Parameters for 25Gb/s, 50Gb/s, and 100Gb/s Passive Optical Networks 1:

Cl 144 SC 144.3.7.1 P124 L22 # 6  
 Heaven, Bo Huawei

Comment Type ER Comment Status D

Should define a value for invalid LLID used for GATE with less then 7 grants

SuggestedRemedy

Add description such as "The value of invalid LLID is 0"

Proposed Response Response Status W

PROPOSED REJECT.

LLID values (valid and invalid) should be defined in Clause 143, where LLIDs are created.

Cl 144 SC 144.3.7.1 P124 L24 # 116  
 Remein, Duane Huawei Technologies

Comment Type TR Comment Status D

"All transmission overhead components (see TBD) are included in and thus consume part of the granted transmission slot." This was reasonable when there was a one-to-one start time and length per grant in a GATE but is it reasonable when there is one start time and multiple grant lengths? Where does the sync pattern time come from, the first grant or the last one or is it equally deducted from each?

SuggestedRemedy

Change to : "Burst transmission overhead components (Start of Burst and End of Burst) are not included in the grant length parameters whereas parity overhead is."

Proposed Response Response Status W

PROPOSED REJECT.

This is not just markers that should be excluded. It would be best to descrieb these in PCS (?) and reference from MPCP, rather than redefine them in MPCP for no reason.

Cl 144 SC 144.3.7.1 P124 L26 # 7  
 Heaven, Bo Huawei

Comment Type TR Comment Status D

We can learn that each ENV length of grant does not include FEC overhead and burst overhead from Figure 143-13

SuggestedRemedy

"All transmission overhead components (see TBD) are included in and thus consume part of the granted transmission slot." should be removed

Proposed Response Response Status W

PROPOSED REJECT.

Clarification is actually handy, since it is not mentioned anywhere else at this time explicitly. A reader will have to figure it out on their own.

Cl 144 SC 144.3.7.1 P124 L27 # 117  
 Remein, Duane Huawei Technologies

Comment Type TR Comment Status D

Text for Fragmentation flag.

SuggestedRemedy

When this flag is set to 0 the ONU shall not fragment a frame; when set to a 1 fragmentation is allowed within the respective grant.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

See comment #170

Cl 144 SC 144.3.7.1 P124 L29 # 118  
 Remein, Duane Huawei Technologies

Comment Type TR Comment Status D

FR is normative.

SuggestedRemedy

change:

"no action is required from the ONU" to "the ONU may issue a gratuitous REPORT"

"the ONU should issue a REPORT" to "the ONU shall issue a mandatory REPORT"

At the end of the para add "An ONU must transmit mandatory REPORTs prior to gratuitous REPORTs."

Proposed Response Response Status W

PROPOSED REJECT.

This is a major change in the ONU behavior from what is expected from the ONU today.



Proposed Responses Specifications and Management Parameters for 25Gb/s, 50Gb/s, and 100Gb/s Passive Optical Networks 1:

Cl 144 SC 144.3.7.1 P124 L32 # 119  
 Remein, Duane Huawei Technologies  
 Comment Type E Comment Status D bucket  
 Oxymoronic statements have no place in a standard; "This is an empty field that is transmitted as zeroes" If the field has zeroes in it , it cannot be empty.  
 Same issue at pg. 124 ln. 48, pg. 126 ln. 49, pg. 128 ln. 15, and 129 ln. 20.  
 SuggestedRemedy  
 Change to: "This field is transmitted as zeroes"  
 Proposed Response Response Status W  
 PROPOSED ACCEPT.  
 See also comment #170 for text alignment

Cl 144 SC 144.3.7.1 P124 L46 # 121  
 Remein, Duane Huawei Technologies  
 Comment Type T Comment Status D  
 100G-EPON stuff. Table 144-1 Channel Assignment flags bits 2 & 3 should be reserved.  
 SuggestedRemedy  
 per comment  
 Proposed Response Response Status W  
 PROPOSED ACCEPT.

Cl 144 SC 144.3.7.2 P124 L39 # 120  
 Remein, Duane Huawei Technologies  
 Comment Type E Comment Status D bucket  
 missing article  
 SuggestedRemedy  
 Change "- Time stamp" to "- the time stamp"  
 Proposed Response Response Status W  
 PROPOSED ACCEPT.

Cl 144 SC 144.3.7.2 P124 L46 # 122  
 Remein, Duane Huawei Technologies  
 Comment Type TR Comment Status D  
 Text for b)  
 SuggestedRemedy  
 The number of LLIDs in the ONU with non-empty queues.  
 Proposed Response Response Status W  
 PROPOSED ACCEPT.

Cl 144 SC 144.3.7.2 P124 L47 # 123  
 Remein, Duane Huawei Technologies  
 Comment Type TR Comment Status D  
 Text for c)  
 SuggestedRemedy  
 The local time, in units of EQ, at which the REPORT information was collected in the ONU.  
 Proposed Response Response Status W  
 PROPOSED ACCEPT IN PRINCIPLE.  
 The local time, in units of 1 EQ, at which the REPORT information was collected in the ONU.

Cl 144 SC 144.3.7.2 P125 L53 # 124  
 Remein, Duane Huawei Technologies  
 Comment Type TR Comment Status D  
 Shouldn't this be the PLID?  
 SuggestedRemedy  
 Change "a unicast type of LLID (see TBD)." to "the PLID of the originating ONU."  
 Proposed Response Response Status W  
 PROPOSED ACCEPT.

Proposed Responses Specifications and Management Parameters for 25Gb/s, 50Gb/s, and 100Gb/s Passive Optical Networks 1:

CI 144 SC 144.3.7.3 P126 L8 # 125  
 Remein, Duane Huawei Technologies

Comment Type ER Comment Status D

The presentation order of tables and figures seems backwards (low level details are presented before high-level details) and is opposite to that in previous sections.

SuggestedRemedy

Reorder section so Figure 144-20 comes before Table 144-2 & 3. Add reference to Figure 144-20 in the opening para. Edit sections 144.3.7.4, 144.3.7.5, and 144.3.7.6 similarly.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Table and figure placement depends largely on the page flow.

CI 144 SC 144.3.7.3 P126 L22 # 126  
 Remein, Duane Huawei Technologies

Comment Type T Comment Status D

Exactly where is Pending Grants configured (which imho implies provisioning).

SuggestedRemedy

Change "configured to buffer" to "capable of buffering"

Proposed Response Response Status W

PROPOSED ACCEPT.

CI 144 SC 144.3.7.6 P130 L3 # 127  
 Remein, Duane Huawei Technologies

Comment Type E Comment Status D bucket

Errant reference to Table 144-1 s/b 144-6

SuggestedRemedy

per comment

Proposed Response Response Status W

PROPOSED ACCEPT.

CI 144 SC 144.3.7.6 P130 L8 # 172  
 Kramer, Glen Broadcom

Comment Type T Comment Status D

Both normal GATEs and discovery GATEs are scheduled by the same scheduler. Since normal GATEs have grant length limited to 22 bits, we should apply the same limit to the discovery grant length. This will allow the entire scheduler operate on 22-bit numbers.

SuggestedRemedy

Replace the text "Discovery Grant Length: This 24-bit unsigned field represents the length of the discovery grant, expressed in the units of 1 EQ."

with text "Discovery Grant Length: This 22-bit unsigned field represents the length of the discovery grant, expressed in the units of 1 EQ."

In Figure 14-23, show the two most-significant bits of grant length as reserved.

Proposed Response Response Status W

PROPOSED ACCEPT.

CI 144 SC 144.3.7.6 P130 L40 # 9  
 Dekun, Liu Huawei

Comment Type TR Comment Status D

page 7 and 8 is basically the same, the only difference is that all ONUs calculate the RSSI thresholds thx based on ONUs' typical launch power in page 7, while every ONU calculate the RSSI thresholds thx based on its transmitter TSSI in page 8. Considering that, if the ONU calculates the RSSI thresholds based on its typical launch power or TSSI is only an ONU's inner implementation issue, ONU can decide it by itself. So the current Table 144-6 can cover both the ways in page 7 and page 8. Only some illustration on how ONUs calculates RSSI thresholds is newly needed.

SuggestedRemedy

Add the following text below Table 144-6:

th0, th1, th2 are ONU RSSI thresholds, they can be calculated by ONU based on the following equations:

$$th0 = TH0 - (ONU\_Tx - OLT\_Tx)$$

$$th1 = TH1 - (ONU\_Tx - OLT\_Tx)$$

$$th2 = TH2 - (ONU\_Tx - OLT\_Tx)$$

TH0, TH1 and TH2 are OLT receiver thresholds which are announced by OLT, the unit is in dBm.

OLT\_Tx is the OLT transmitter launch power which are announced by OLT, ONU\_Tx is the ONU transmitter launch power, the unit of (ONU\_Tx - OLT\_Tx) is in dB.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Insert proposed text as footnote to Values for bits 7-9

Proposed Responses Specifications and Management Parameters for 25Gb/s, 50Gb/s, and 100Gb/s Passive Optical Networks 1:

Cl 144 SC 144.3.7 P131 L1 # 151  
Hajduczenia, Marek Charter Communicatio

Comment Type TR Comment Status D

New SYNC\_PATTERN MPCPDU is needed to address the need for dynamic configuration of Sync Pattern zones (value and/or duration)

SuggestedRemedy

See hajduczenia\_3ca\_1\_0518.pdf for motivation and hajduczenia\_3ca\_2\_0518.pdf for all changes in Clause 144 needed to accommodate the new mechanism, including new MPCPDU, changes to existing MPCPDUs, state diagrams, and associated text. All changes to the original D1.0 MPCP Clause are marked in red, including strike-throughs where appropriate.

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 144 SC 1443.3.3 P98 L32 # 96  
Remein, Duane Huawei Technologies

Comment Type T Comment Status D

We should be specific on which types of LLIDs are allocated. "the OLT registers the ONU, allocating and assigning a new port identity (LLID), and bonding a corresponding MAC to the LLID."

SuggestedRemedy

Change to: "the OLT registers the ONU, allocating and assigning a new ONU (PLID) and management (MLID) port identities, and bonding a corresponding MACs to the LLIDs."

Proposed Response Response Status W

PROPOSED ACCEPT.

Wrong clause (is 143 and should be 144)

Cl Abstract SC Abstract P3 L4 # 1  
Heaven, Bo Huawei

Comment Type T Comment Status D

Does 50G/10G include case of 2x25G downstream and 1x10G upstream.

SuggestedRemedy

How about add option of 2x25G downstream and 2 x 10G upstream(50G/20G)

Proposed Response Response Status W

PROPOSED REJECT.

No specific change proposed at this time.