

Approved Responses

IEEE P802.3ca D1.4 25/50G-EPON Task Force 5th Task Force review comments

Cl 1 SC 1.4.128d P20 L11 # 392
 Kramer, Glen Broadcom
 Comment Type E Comment Status A bucket
 50/50-EPON - Missing "G"
 SuggestedRemedy
 Change to 50/50G-EPON
 Response Response Status C
 ACCEPT.

Cl 1 SC 1.4.129a P20 L15 # 330
 Powell, William Nokia
 Comment Type E Comment Status R bucket
 speeds
 SuggestedRemedy
 throughputs
 Response Response Status C
 REJECT.
 The change would imply MAC level throughput, which is not what the speed designator is for.

Cl 1 SC 1.4.245a P20 L33 # 391
 Kramer, Glen Broadcom
 Comment Type TR Comment Status A
 We provide definition for EQ and also list the "EQ" under the abbreviations, showing the expanded name as "envelope quantum". But there is no definition for the "envelope quantum". Additionally, the definition of EQ is incorrect. EQ is not always 72 bits. In MPCP and above, EQ is 64 bits. In PCS, after 64B/66B encoding, an EQ is 66 bits.
 SuggestedRemedy
 Use the following definition of EQ:
 1.4.245a Envelope Quantum: The unit of measurement of volume of information. Each envelope quantum represents 64 bits of data plus the layer-specific encoding. Thus, at the MAC sublayer and above, an envelope quantum is equal to 64 bits. Within the MCRS, an envelope quantum contains 72 bits (i.e., 64 bits of data and 8 bits of control). Within PCS, after the 64B/66B encoding, an envelope quantum contains 66 bits.
 Response Response Status C
 ACCEPT.

Cl 1 SC 1.4.278 P19 L26 # 409
 Kramer, Glen Broadcom
 Comment Type T Comment Status A
 The definition of Grant provides specific details for C144, but is silent on similar details in C64 and C77
 SuggestedRemedy
 Change the definition to the following:

"1.4.278 Grant: Within P2MP protocols, a permission to transmit at a specific time, for a specific duration. Grants are issued by the OLT (master) to ONUs (slaves) by means of GATE messages. <u>In Clause 64 and Clause 77, a GATE MPCPDU contain one or multiple grants issued to a single LLID. Each grant results in one or multiple upstream bursts transmitted by the ONU. In Clause 144, a grant includes envelope allocations for multiple LLIDs. The OLT conveys a grant to the ONU using one or multiple GATE MPCPDUs, all having the same StartTime values. There is a one-to-one correspondence between the grants issued to an ONU and upstream bursts transmitted by that ONU, i.e., a grant issued to an ONU results in a single upstream burst transmitted by that ONU.</u>"

<u>...</u> - underline

Response Response Status C
 ACCEPT IN PRINCIPLE.

"1.4.278 Grant: Within P2MP protocols, a permission to transmit at a specific time, for a specific duration. Grants are issued by the OLT (master) to ONUs (slaves) by means of GATE messages. <u>In Clause 64 and Clause 77, a GATE MPCPDU contains one or multiple grants issued to a single LLID. Each grant results in one or multiple upstream bursts transmitted by the ONU. In Clause 144, a grant includes envelope allocations for multiple LLIDs. The OLT conveys a grant to the ONU using one or multiple GATE MPCPDUs, all having the same StartTime values. There is a one-to-one correspondence between the grants issued to an ONU and upstream bursts transmitted by that ONU, i.e., a grant issued to an ONU results in a single upstream burst transmitted by that ONU.</u>"

Approved Responses

IEEE P802.3ca D1.4 25/50G-EPON Task Force 5th Task Force review comments

Cl 30 SC 30 P31 L1 # 322
 Laubach, Mark Broadcom
 Comment Type TR Comment Status A
 Clause 30 changes to add to the draft
 SuggestedRemedy
 Insert new Clause 30 changes as per laubach_3ca_5_0119.pdf
 Response Response Status C
 ACCEPT IN PRINCIPLE.
 Insert new Clause 30 changes as per laubach_3ca_5_0119.pdf, with the following changes:
 - replace "Clause 142 PCS" with "Clause 142" globally

Cl 31A SC 31A P22 L16 # 331
 Powell, William Nokia
 Comment Type ER Comment Status A bucket
 recipient stop
 SuggestedRemedy
 recipient stops
 Response Response Status C
 ACCEPT.
 Use appropriate markup, since this is base standard text

Cl 31A SC 31A P22 L20 # 332
 Powell, William Nokia
 Comment Type ER Comment Status A bucket
 recipient allow
 SuggestedRemedy
 recipient allows
 Response Response Status C
 ACCEPT.
 Use appropriate markup, since this is base standard text

Cl 31A SC 31A P22 L41 # 333
 Powell, William Nokia
 Comment Type ER Comment Status A bucket
 recipient allow
 SuggestedRemedy
 recipient allows
 Response Response Status C
 ACCEPT.

Cl 31A SC 31A P23 L12 # 334
 Powell, William Nokia
 Comment Type ER Comment Status A bucket
 Request that recipients to attempt
 SuggestedRemedy
 Request that recipients attempt
 Response Response Status C
 ACCEPT.

Cl 31A SC 31A P23 L15 # 335
 Powell, William Nokia
 Comment Type E Comment Status A SYNC_PATTERN_def
 Used by OLT to announce elements of the FEC-unprotected area (SP) to all ONUs on the given PON
 SuggestedRemedy
 Sync pattern used by the OLT to indicate the start of elements of the sync area to all ONUs on the given PON.
 Response Response Status C
 ACCEPT IN PRINCIPLE.
 See comment #402

Approved Responses

IEEE P802.3ca D1.4 25/50G-EPON Task Force 5th Task Force review comments

Cl 31A **SC 31A** **P23** **L15** # **402**
 Kramer, Glen Broadcom

Comment Type **T** **Comment Status** **A** *SYNC_PATTERN_def*

Description of SYNC_PATTERN in Table 31A-1 is inaccurate. SYNC_PATTERN cannot be sent to *all* ONUs on the given PON. It can be sent to all unregistered ONUs, or all registered ONUs, or several registered ONUs, or individual registered ONUs. Also, it does not announce all the elements of FEC-unprotected area (i.e., EBD).

SuggestedRemedy
 Use the following description:

"Announces burst synchronization patterns to all unregistered ONUs, multiple/all registered ONUs, or individual registered ONUs."

Response **Response Status** **C**
 ACCEPT.

Cl 31A **SC 31A** **P23** **L18** # **295**
 Lyskey, Eric Broadcom

Comment Type **T** **Comment Status** **A**

CCP frames not listed in Table 31A-1.

SuggestedRemedy
 Change reserved to be 00-19 through 00-1f. Add row for 00-20, CC_REQUEST, 144.4.2.1, Query or change the state of ONU channel(s), No. Add row for 00-21, CC_RESPONSE, 144.4.2.2, Report current channel(s) state and action result code, No. Add row for reserved 00-22 through 01-00.

Response **Response Status** **C**
 ACCEPT IN PRINCIPLE.

Change reserved to be 00-19 through 00-1f.

Add row for | 00-20 | CC_REQUEST | 144.4.2.1 | Query or change the state of ONU channel(s) | No |

Add row for | 00-21 | CC_RESPONSE | 144.4.2.2 | Report current channel(s) state and action result code | No |

Add row for reserved 00-22 through 01-00.

Cl 31A **SC 31A** **P23** **L19** # **363**
 Powell, William Nokia

Comment Type **ER** **Comment Status** **A** *bucket*

Requests that the recipient stop transmissions in

SuggestedRemedy
 Request that the recipient stops transmission in

Response **Response Status** **C**
 ACCEPT.

Use appropriate markup, since this is base standard text

Cl 31A **SC 31A** **P23** **L26** # **364**
 Powell, William Nokia

Comment Type **E** **Comment Status** **R** *bucket*

This frame is used ...

SuggestedRemedy
 Request that the MAC Control generates ...

Response **Response Status** **C**
 REJECT.

Current text is correct as is.

Cl 45 **SC 45.2.1** **P24** **L5** # **418**
 Remein, Duane Huawei

Comment Type **TR** **Comment Status** **A** *post-deadline*

Proposed material for Clause 45 PCS registers.

SuggestedRemedy
 See remain_3ca_2_1901.pdf (to be included in the draft) and remain_3ca_3_1901.pdf

Response **Response Status** **C**
 ACCEPT IN PRINCIPLE.

Use remain_3ca_2b_0119.pdf

Approved Responses

IEEE P802.3ca D1.4 25/50G-EPON Task Force 5th Task Force review comments

Cl 45 SC 45.2.1 P24 L5 # 417
 Remein, Duane Huawei
 Comment Type TR Comment Status A C45
 Proposed material for Clause 45 PMA/PMD registers.
 SuggestedRemedy
 See remain_3ca_1_1901.pdf
 Response Response Status C
 ACCEPT.
 Per comment + insert editorial note in 142.4.1 for Bill P to provide register definition in Clause 45 for differential encoder control register.

Cl 45 SC 45.2.1.93a P24 L32 # 365
 Powell, William Nokia
 Comment Type ER Comment Status A C45
 writes ignored
 SuggestedRemedy
 write operations are ignored
 Response Response Status C
 ACCEPT IN PRINCIPLE.
 See comment #417

Cl 45 SC 45.2.1.93a P24 L39 # 366
 Powell, William Nokia
 Comment Type ER Comment Status A C45
 Read only
 SuggestedRemedy
 Read-Only
 Response Response Status C
 ACCEPT IN PRINCIPLE.
 See comment #417

Cl 56 SC 56.1.2 P27 L1 # 367
 Powell, William Nokia
 Comment Type ER Comment Status A bucket
 at 25.78125
 SuggestedRemedy
 at a 25.78125
 Response Response Status C
 ACCEPT.

Cl 56 SC 56.1.2 P27 L2 # 368
 Powell, William Nokia
 Comment Type ER Comment Status A bucket
 and 25.87125 GBd or 10.3125 GBd
 SuggestedRemedy
 and a 25.87125 GBd or a 10.3125 GBd
 Response Response Status C
 ACCEPT.

Cl 56 SC 56.1.2.1 P27 L15 # 369
 Powell, William Nokia
 Comment Type E Comment Status R bucket
 in 77.4.
 SuggestedRemedy
 in Clause 77.4.
 Response Response Status C
 REJECT.
 References to subclauses do not need "Clause" statement.

Approved Responses

IEEE P802.3ca D1.4 25/50G-EPON Task Force 5th Task Force review comments

Cl 56 SC 56.1.2.1 P27 L17 # 370
 Powell, William Nokia
 Comment Type ER Comment Status A bucket
 plus one or more
 SuggestedRemedy
 and one or more
 Response Response Status C
 ACCEPT.

Cl 56 SC 56.1.3 P29 L19 # 371
 Powell, William Nokia
 Comment Type ER Comment Status A bucket
 For ... signaling systems transmit rate
 SuggestedRemedy
 For ... signaling systems the transmit rate
 Response Response Status C
 ACCEPT.

Cl 56 SC 56.1.3 P29 L26 # 373
 Powell, William Nokia
 Comment Type ER Comment Status A bucket
 all of these
 SuggestedRemedy
 all these
 Response Response Status C
 ACCEPT.

Cl 56 SC 56.1.3 P29 L26 # 372
 Powell, William Nokia
 Comment Type ER Comment Status A bucket
 sentence segment: mandatory FEC capability; in particular in Clause 56.1.2, the term "mandatory FEC function" is used.
 SuggestedRemedy
 mandatory FEC function
 Response Response Status C
 ACCEPT.

Cl 56 SC 56.1.3 P29 L29 # 374
 Powell, William Nokia
 Comment Type ER Comment Status A bucket
 a new table 56-4 and Changeing existing
 SuggestedRemedy
 a new Table 56-4 and changing the existing
 Response Response Status C
 ACCEPT.

Cl 141 SC 141.1.1 P34 L19 # 375
 Powell, William Nokia
 Comment Type ER Comment Status A bucket
 OLT to the ONU
 SuggestedRemedy
 OLT to the ONUs OR OLT to an ONU
 Response Response Status C
 ACCEPT IN PRINCIPLE.
 Use "OLT to ONUs"

Cl 141 SC 141.3.1.1 P40 L48 # 416
 Remein, Duane Huawei
 Comment Type TR Comment Status A
 Delay constraints. Comment 434 against Draft 1.2 suggested a mecahnism to allocate delay constrints for Nx25G-EPON but there were objections to that proposal. This item has not been addressed yet and needs to be resolved in order for the draft to be technically complete and proceed to WG Ballot.
 SuggestedRemedy
 Work out a solution during the March meeting.
 Response Response Status C
 ACCEPT IN PRINCIPLE.
 Insert editorial note in all delay-related subclauses for Glen and Duane to work out a solution for delay definition for EPON.

Approved Responses

IEEE P802.3ca D1.4 25/50G-EPON Task Force 5th Task Force review comments

Cl 141 SC 141.3.1.5 P41 L48 # 284
 Hajduczenia, Marek Charter Communicatio
 Comment Type E Comment Status A bucket
 Missing link in red
 SuggestedRemedy
 Use "141.3.5" + make link live
 Response Response Status C
 ACCEPT.

Cl 141 SC 141.4 P44 L1 # 325
 Johnson, John Broadcom
 Comment Type T Comment Status A
 The column headings on Tables 141-11 and 141-12 are inconsistent.
 SuggestedRemedy
 Change the heading on the first column of Table 141-11 to "Wavelength Name".
 Response Response Status C
 ACCEPT.

Cl 141 SC 141.5.1 P45 L16 # 296
 Lynskey, Eric Broadcom
 Comment Type T Comment Status A
 Table 141-13 does not list the total average launch power for the single channel case. This is different than Table 141-14. Both tables should be consistent with each other.
 SuggestedRemedy
 Remove the 7.8 dBm total average launch power from Table 141-14.
 Response Response Status C
 ACCEPT IN PRINCIPLE.
 In Table 141-14, change "7.8" to "-"

Cl 141 SC 141.5.2 P47 L30 # 326
 Johnson, John Broadcom
 Comment Type T Comment Status A
 The line "Conditions of stressed receiver sensitivity test:" in Tables 141-15 and 16 is a section heading and has no associated parameter values. See example format in Table 141-19.
 SuggestedRemedy
 Remove TBD placeholders on this line in Tables 141-15 and 16 and merge the cells in the row on Table 141-16. Use formatting similar to Table 141-19.
 Response Response Status C
 ACCEPT.

Cl 141 SC 141.5.2 P48 L27 # 297
 Lynskey, Eric Broadcom
 Comment Type T Comment Status A
 Table 141-16 references Table 75-7 for parameters related to 10G upstream. However, in the 2018 revision of IEEE 802.3, Table 75-7 refers to 10/1 power receive characteristics.
 SuggestedRemedy
 Replace reference with Table 75-6.
 Response Response Status C
 ACCEPT.

Cl 141 SC 141.5.2 P52 L26 # 324
 Johnson, John Broadcom
 Comment Type T Comment Status A
 The same type of receiver technology will be used for Nx25G-EPON as for 10G-EPON (APD in TO-can). The same value of receiver reflectance (max) should be used.
 SuggestedRemedy
 Replace TBD values for Receiver reflectance (max) in Tables 141-19 and 141-20 with a value of -12 dB.
 Response Response Status C
 ACCEPT.

Approved Responses

IEEE P802.3ca D1.4 25/50G-EPON Task Force 5th Task Force review comments

Cl 141 SC 141.7.4 P54 L32 # 304
 Lynskey, Eric Broadcom

Comment Type T Comment Status A
 Some tests call for "any valid encoded 256B/257B data stream". Some call for "valid Nx25G-EPON signal". Pick one and be consistent.

SuggestedRemedy
 Replace 256B/257B data stream with valid Nx25G-EPON signal.

Response Response Status C
 ACCEPT.

Cl 141 SC 141.7.5 P54 L37 # 303
 Lynskey, Eric Broadcom

Comment Type T Comment Status A
 It seems like the I2 reference is a copy paste from 10G/1G EPON.

SuggestedRemedy
 Remove "repeating pattern /I2/ ordered set (see 36.2.4.12) or".

Response Response Status C
 ACCEPT.

Cl 141 SC 141.7.9 P55 L1 # 327
 Johnson, John Broadcom

Comment Type T Comment Status A
 Section 141.7.9 is incomplete and requires additional text.

SuggestedRemedy
 Use the text in johnson_3ca_1_0191.doc for section 141.7.9.

Response Response Status C
 ACCEPT IN PRINCIPLE.

Use the text in johnson_3ca_1_0119.pdf for section 141.7.9, and change "the lane under test" to "the lane (wavelength) under test"

Cl 141 SC 141.7.13 P55 L25 # 301
 Lynskey, Eric Broadcom

Comment Type T Comment Status A laser_time
 Max Ton value from Table 141-17 is 512ns, since it is inherited from Table 75-8.

SuggestedRemedy
 Change 128ns to 512ns.

Response Response Status C
 ACCEPT IN PRINCIPLE.

Table 141-17 shows value of 128ns for new PMDs. In Table 141-17, rows for Ton and Toff times will be expanded across all PMDs (overriding settings for last column), similar to what is done for Table 141-18.

Cl 141 SC 141.7.13 P55 L33 # 302
 Lynskey, Eric Broadcom

Comment Type T Comment Status A laser_time
 Max Toff value from Table 141-17 is 512ns, since it is inherited from Table 75-8.

SuggestedRemedy
 Change 128ns to 512ns.

Response Response Status C
 ACCEPT IN PRINCIPLE.

See comment #301

Cl 141 SC 141.7.13.2 P56 L25 # 419
 Remein, Duane Huawei

Comment Type E Comment Status A post-deadline bucket
 We have 19 instances of "synchronization pattern", 2 of "Synchronization Pattern", and 17 of "Sync Pattern". Some consistency should be invoked.

SuggestedRemedy
 Use "synchronization pattern".

Response Response Status C
 ACCEPT.

Approved Responses

IEEE P802.3ca D1.4 25/50G-EPON Task Force 5th Task Force review comments

Cl 141 SC 141.8.5 P59 L36 # 388
 Kramer, Glen Broadcom
 Comment Type T Comment Status A
 There is no need to repeat a long list of all defined PMDs. All supported PMDs are already listed in Table 141-7 on page 38.
 SuggestedRemedy
 Replace the text "Defined PMDs are as follows: <list of PMDs>" with the following text:
 "The list of all supported PMDs is shown in Table 141-7."
 Response Response Status C
 ACCEPT.

Cl 141 SC 141.9.1 P60 L41 # 413
 Ferretti, Vince Corning
 Comment Type ER Comment Status A bucket
 Insertion loss is not specified in Table 141.21
 SuggestedRemedy
 Change to "specified in Tables 141.1 through 141.5"
 Response Response Status C
 ACCEPT IN PRINCIPLE.
 Change to "specified in Table 141-1 through Table 141-5". Make links live.

Cl 141 SC 141.9.3 P61 L1 # 328
 Johnson, John Broadcom
 Comment Type T Comment Status A
 The downstream wavelength names in Table 141-21 are inconsistent with the definitions in Table 141-11.
 SuggestedRemedy
 Change the wavelength names in Table 141-21 to agree with Table 141-11. Change DW2 to DW0 and change the column order so that DW0 is to the left of DW1.
 Response Response Status C
 ACCEPT.

Cl 141 SC 141.9.3 P61 L19 # 414
 Ferretti, Vince Corning
 Comment Type ER Comment Status A bucket
 Insertion loss is not specified in Table 141.21
 SuggestedRemedy
 Change to "specified in Tables 141.1 through 141.5"
 Response Response Status C
 ACCEPT IN PRINCIPLE.
 Change to "specified in Table 141-1 through Table 141-5". Make links live

Cl 142 SC 142.1 P64 L9 # 376
 Powell, William Nokia
 Comment Type ER Comment Status A bucket
 The term "passive optical multipoint networks (PONs)" is introduced here. It seems more logical to use the "regular" term. The previous sentence already points out that this is a point-to-multipoint (P2MP) network.
 SuggestedRemedy
 remove "multipoint" to obtain: passive optical networks (PONs)
 Response Response Status C
 ACCEPT.

Approved Responses

IEEE P802.3ca D1.4 25/50G-EPON Task Force 5th Task Force review comments

Cl 142 SC 142.1.1 P64 L26 # 412
 Kramer, Glen Broadcom

Comment Type T Comment Status A conventions

We repeat the Conventions section in every clause (C142, C143, C144). There is a lot of duplicated material, but also some differences in how requirements are stated.

SuggestedRemedy

Use one Convention section in C142 and reference it from C143 and C144. Expand the convention section to cover timers, vector notations, and FIFO operations. Specific changes:

- 1) Replace subclause 142.1.1 with the material shown in kramer_3ca_6_0119.pdf
- 2) In 142.2.5.3, delete definitions of FIFO.Append(v), FIFO.Fill(v), FIFO.GetHead(), and FIFO.IsEmpty()
- 3) Add this text to the last sentence of InputFifo definition: "and supports operations `<i>Append()`, `<i>IsEmpty()`, and `<i>GetHead()` (see 142.1.1.5)."
- 4) Add this sentence of TxFifo definition: "The TxFifo[] supports operations `<i>Append()`, `<i>Fill()`, and `<i>GetHead()` (see 142.1.1.5)."
- 5) Change title of 143.3.3.1 from "State diagram conventions" to "Conventions". Replace subclause text with "See 142.1.1."
- 6) Replace subclause 143.3.4.1 text with "See 142.1.1."
- 7) Change title of 144.1.6 from "State diagram conventions" to "Conventions". Replace subclause text with "See 142.1.1."
- 8) In 144.3.6.3, change definition of EnvList as follows:
 - 8.a) Remove the sentence "Each EnvList[ch] list has several associated functions:".
 - 8.b) Remove the list of functions
 - 8.c) Insert text: "Each `<i>EnvList[ch]</i>` list supports operations `<i>Append()`, `<i>Clear()`, `<i>IsEmpty()`, `<i>GetHead()`, and `<i>PeekHead()` (see 142.1.1.5)."
- 9) In Figure 144-22, replace "RemoveHead()" with "GetHead()" (2 places)

Response Response Status C

ACCEPT IN PRINCIPLE.

Use one Convention section in C142 and reference it from C143 and C144. Expand the convention section to cover timers, vector notations, and FIFO operations. Specific changes:

- 1) Replace subclause 142.1.1 with the material shown in kramer_3ca_6b_0119.pdf

2) In 142.2.5.3, delete definitions of FIFO.Append(v), FIFO.Fill(v), FIFO.GetHead(), and FIFO.IsEmpty()

3) Add this text to the last sentence of InputFifo definition: "and supports FIFO access operations as defined in 142.1.1.5."

4) Add this sentence of TxFifo definition: "The TxFifo[] supports FIFO access operations as defined in 142.1.1.5."

5) Change title of 143.3.3.1 from "State diagram conventions" to "Conventions". Replace subclause text with "See 142.1.1."

6) Replace subclause 143.3.4.1 text with "See 142.1.1."

7) Change title of 144.1.6 from "State diagram conventions" to "Conventions". Replace subclause text with "See 142.1.1."

8) In 144.3.6.3, change definition of EnvList as follows:

8.a) Remove the sentence "Each EnvList[ch] list has several associated functions:".

8.b) Remove the list of functions

8.c) Insert text: "Each `<i>EnvList[ch]</i>` list supports FIFO access operations as defined in 142.1.1.5."

9) In Figure 144-22, replace "RemoveHead()" with "GetHead()" (2 places)

Cl 142 SC 142.1.1 P64 L28 # 377
 Powell, William Nokia

Comment Type ER Comment Status A conventions

It seems useful to start with the remark that code examples adhere to the C programming language. The subsequent notation ++, --, += and -= does not need to be explained.

SuggestedRemedy

The notation used in the state diagrams in this clause follows the conventions in Clause 21.5. Code examples provided in this clause adhere to the style of the "C" programming language. In particular, if the notation ++ or -- is used directly after a variable name representing an integer value, this integer value is incremented by 1 or decremented by 1, respectively. Similarly, if the notation += and -= are used after a variable, the corresponding value is to be incremented or decremented by the following value, respectively.

Response Response Status C

ACCEPT IN PRINCIPLE.

See comment #412

Cl 142 SC 142.1.3 P64 L43 # 378
Powell, William Nokia

Comment Type ER Comment Status A

The term "FEC-unprotected" is not common.

SuggestedRemedy

Suggest to rewrite this, e.g., An ONU burst transmission comprises two or three distinct synchronization pattern (SP) zones, followed by one or more FEC codewords, and ending with an end-of-burst (EBD) delimiter.

Response Response Status C

ACCEPT IN PRINCIPLE.

Change "FEC protected" to "FEC-protected" and "FEC unprotected" to "FEC-unprotected" globally.

Change "FEC-unprotected and the FEC-protected portions" to "FEC-unprotected and the FEC-protected areas"

Cl 142 SC 142.1.3 P66 L4 # 379
Powell, William Nokia

Comment Type T Comment Status A

TXD[i]<31:0>, TXC[i]<3:0>, TXC, RXD[i]<31:0>, RXC<3:0>, RXC[i] in Figure 142-2 is first specified in Clause 143.3.1.1.

SuggestedRemedy

Propose to either introduce this notation in the text when describing Fig. 142-2, or to refer to Clause 143.3.1.1. BTW, should "TXC" be "TXC[i]"?

Response Response Status C

ACCEPT IN PRINCIPLE.

Transmit direction operates on a single clock signal TX_CLK shared by all channels, so that is correct.

Add the following statement on page 64, line 25: "See 143.3.1.1 for definition of TXD, TXC, TX_CLK, RXD, RXD, and RX_CLK. In figure 142-2, replace TCX (standalone) with TX_CLK. Same for RXC standalone to RX_CLK - it seems like an error.

Cl 142 SC 142.1.3 P66 L52 # 380
Powell, William Nokia

Comment Type TR Comment Status A

sentence fragment: where the last codeword may be shortened to minimize the unused LDPC codeword payload ... This statement is inaccurate. First, the LDPC code used has wordlength 17,664, with a 14,592-bit payload and a 3,072-bit parity check segment. A transmitted codeword that comprises a maximum-size payload portion consists of 56 257-bit encoded and scrambled data blocks, i.e., a total of 14,392 bits, followed by 10 257-bit parity blocks carrying interleaved parity information and a codeword delimiter. As such, there is a 200-bit reduction in payload to allow for an integer-number of 256B257B blocks, and the last 512 parity check bits have been punctured to increase the code rate. Given that at this point, the LDPC encoder has not been introduced yet, and can also consider making a more general statement, that, depending on the number of bits to be transmitted during the burst transmission, one or several codewords will be formed, and that all codewords, except the last one, will be of full length.

SuggestedRemedy

Suggested change: The LDPC code used has wordlength 17,664, with a 14,592-bit payload and a 3,072-bit parity check segment. A transmitted codeword that comprises a maximum-size payload portion consists of 56 257-bit encoded and scrambled data blocks, i.e., a total of 14,392 bits, followed by 10 257-bit parity blocks carrying interleaved parity information and a codeword delimiter. As such, there is a 200-bit reduction in payload to allow for an integer-number of 256B257B blocks, and the last 512 parity check bits have been punctured to increase the code rate. The number of bits that are to be placed in the last transmitted codeword of a burst may be shorter than the maximum-size payload. In this case, only the information-carrying part of the payload is transmitted, followed by the entire 10 257-bit parity blocks.

Response Response Status C

ACCEPT IN PRINCIPLE.

Change "shortened to minimize the unused LDPC codeword payload at the end of the burst" to "shortened to minimize the unused LDPC codeword payload at the end of the burst (see 142.2.4)"

Approved Responses

IEEE P802.3ca D1.4 25/50G-EPON Task Force 5th Task Force review comments

Cl 142 SC 142.1.3 P67 L2 # 381
Powell, William Nokia

Comment Type T Comment Status R

segment: ... data blocks and 10 of 257-bit blocks carrying LDPC parity and codeword delimiter. At this point, the LDPC encoder has not been introduced yet. Consider making a more general statement, that, depending on the number of bits to be transmitted, one or several codewords will be formed, and that all codewords, except the last one, will be of full length.

SuggestedRemedy

Alternative option: In normal operation, the SBD is followed by a number of FEC codewords, where the payload of all codewords, except for the last codeword, comprises 56 257-bit 256B/257B encoded and scrambled data blocks. The last data part of a burst is sent, followed by the full-length parity segment.

Response Response Status C

REJECT.

Text reads correctly as is.

Cl 142 SC 142.1.3 P67 L19 # 382
Powell, William Nokia

Comment Type TR Comment Status R

Figure 142-3 - the parameter N is used in the figure to denote the number of codewords in the burst. This may lead to confusion, given that the codeword length is also denoted by N.

SuggestedRemedy

Suggest to replace N by, e.g., B.

Response Response Status C

REJECT.

"N" is used clearly as number of FEC codewords within the same figure.

Cl 142 SC 142.1.3 P67 L20 # 393
Kramer, Glen Broadcom

Comment Type T Comment Status A

"TP Length" is shown in figures 142-3 and 142-4, but is not explained in text and is not used anywhere else.

SuggestedRemedy

Remove "TP Length" and the associated dimension arrows from both figures.

Response Response Status C

ACCEPT.

Cl 142 SC 142.1.3 P67 L20 # 403
Kramer, Glen Broadcom

Comment Type T Comment Status A

"The default number of Sync Pattern zones is two" But yet the diagram for 3 zones is shown immediately below and text after the figure only describes two zones.

SuggestedRemedy

Swap order of figures 142-3 and 142-4.

Response Response Status C

ACCEPT.

Cl 142 SC 142.2.2 P70 L20 # 394
Kramer, Glen Broadcom

Comment Type T Comment Status A

"Prior to being transcoded into 257-bit blocks the Nx25G PCS scrambles four aggregated 66-bit blocks."

This sentence states that PCS itself is being transcoded.

SuggestedRemedy

Change to "The Nx25G PCS scrambles the payload of each 66-bit block. It then accumulates 66-bits blocks into groups of four and transcodes each group into a single 257-bit block"

Response Response Status C

ACCEPT.

Approved Responses

IEEE P802.3ca D1.4 25/50G-EPON Task Force 5th Task Force review comments

Cl 142 SC 142.2.4 P70 L32 # 383
 Powell, William Nokia

Comment Type TR Comment Status A

Original text: The Nx25G-EPON PCS shall encode the transmitted data stream using LDPC(16952,14392) FEC, defined in 142.2.4. Annex 142A gives an example of LDPC(16952,14392) FEC encoding and interleaving. The notation LDPC(16952,14392) FEC is not a common notation for an LDPC code, and it does not fully specify the code, unlike, e.g., a Reed Solomon code. It is suggested to provide a more general statement and refer to subsequent Clauses for further details.

SuggestedRemedy

The Nx25G-EPON PCS shall perform the FEC encoding operation using a quasi-cyclic low-density parity-check (QC-LDPC) code with blockwise interleaving as defined in Clause 142.2.4. Annex 142A provides examples of the blockwise interleaving and LDPC encoding operations.

Response Response Status C

ACCEPT IN PRINCIPLE.

Use laubach_3ca_6a_0119.pdf for replacement of 142.2.4

Cl 142 SC 142.2.4 P70 L33 # 384
 Powell, William Nokia

Comment Type T Comment Status A

Suggest to provide the details of the LDPC code in an Annex. The main advantage is that one can then first specify the full-length quasi-cyclic low-density parity-check code, using an mxn matrix that specifies the amount of cyclic rotation of a diagonal zxz sub-matrix.

SuggestedRemedy

Migrate portions of Clause 142.2.4 to an Annex.

Response Response Status C

ACCEPT IN PRINCIPLE.

See comment #383

Cl 142 SC 142.2.4 P70 L34 # 385
 Powell, William Nokia

Comment Type T Comment Status A

Annex 142A has not been included yet.

SuggestedRemedy

Suggest to include examples as soon as possible. These may be modified/improved later on.

Response Response Status C

ACCEPT IN PRINCIPLE.

See comment #383

Cl 142 SC 142.2.4.1 P70 L37 # 386
 Powell, William Nokia

Comment Type T Comment Status A

The bit sequence input for a given code block to the FEC Encoder ...

SuggestedRemedy

It may be best to state that during a burst transmission, an ONU is allocated sufficient time to transmit K_B bits. The number of codewords equals $B = \text{ceil}(K_B/K_{\text{max}})$.

Response Response Status C

ACCEPT IN PRINCIPLE.

See comment #383

Cl 142 SC 142.2.4.1 P70 L38 # 336
Powell, William Nokia

Comment Type T Comment Status A

The current text is convoluted; it would make most sense to write that a quasi-cyclic LDPC code was selected, specified by an $m \times n$ shift-matrix and a lifting factor $Z = 256$. This specifies the maximum word length: $N^* = nZ$ and the number of parity-check bits $M^* = mZ$. It is typically also useful to specify $k = n-m$, and $K^* = N-M$, the maximum number of systematic bits. After the definition of the code and its parameters, one can state that one uses K information bits, where $K \leq K_{\max} \leq K^*$, and that the remaining K^*-K bits are assumed to be zero, and not transmitted - this way, one also does not need a "zero-padding" module in the encoder. The first $M = M^* - 512$ parity-check bits are transmitted; this implies that the remaining parity-check bits do not have to be computed (one does not need a puncturing module in the encoder). Using this outline, one does not need the parameters P and S .

SuggestedRemedy

Proposal: specify the full-length LDPC code in 142.2.4.1. Avoid any discussion about puncturing and shortening here. Move this to 142.2.4.3. The description on p. 75, lines 5-18 is generally better than on p. 71, lines 3-25.

Response Response Status C

ACCEPT IN PRINCIPLE.

See comment #383

Cl 142 SC 142.2.4.1 P70 L38 # 387
Powell, William Nokia

Comment Type T Comment Status A

sentence: ... The parity check bit sequence produced by FEC Encoder ...

SuggestedRemedy

rewrite: ... Prior to encoding, the input bit sequence is grouped into K/z z-bit segments $u_i^{(j)}$

Response Response Status C

ACCEPT IN PRINCIPLE.

See comment #383

Cl 142 SC 142.2.4.1 P70 L40 # 337
Powell, William Nokia

Comment Type TR Comment Status A

sentence: ... where M is the number of parity check bits.

SuggestedRemedy

... where M is the number of transmitted interleaved parity-check bits.

Response Response Status C

ACCEPT IN PRINCIPLE.

See comment #383

Cl 142 SC 142.2.4.1 P70 L41 # 338
Powell, William Nokia

Comment Type ER Comment Status A

sentence: ... where $N = K + M$ is the length of the encoder output sequence ... Issue: in Fig. 142-6, the FEC encoder only produces parity-bit segments.

SuggestedRemedy

rewrite this sentence to: ... where $N = K+M$ is the length of the transmitted codeword.

Response Response Status C

ACCEPT IN PRINCIPLE.

See comment #383

Cl 142 SC 142.2.4.1 P70 L46 # 339
Powell, William Nokia

Comment Type T Comment Status A

sentence: the LDPC parity check matrix is a 12-by-69 quasi-cyclic matrix - this is confusing. The matrix that specifies the H-matrix is a 12x69 matrix, but the matrix itself is 12Z x 69Z. It is suggested to move all text that defines a QC-LDPC code to 142.2.4.1 and the encoding details to 142.2.4.2.

SuggestedRemedy

the LDPC parity check matrix is specified by a 12 x 69 matrix H_c OR, move the paragraphs starting on p. 71, lines 29 up to p. 74, line 30 to the beginning of Clause 142.2.4.1. The Encoder-related material in 142.2.4.1 can then move to Clause 142.2.4.2.

Response Response Status C

ACCEPT IN PRINCIPLE.

See comment #383

Approved Responses

IEEE P802.3ca D1.4 25/50G-EPON Task Force 5th Task Force review comments

Cl 142 SC 142.2.4.1 P70 L51 # 404
 Kramer, Glen Broadcom

Comment Type T Comment Status A
 "— the number of shortened information bits, S (Smin = 200); "

We never use Smin anywhere else in text. And it is not clear that Smin is only used when we have Kmax information bits. It would be more informative to illustrate how value S is obtained.

SuggestedRemedy
 Replace "(Smin = 200)" with
 "(S = 14592 - K)"

Response Response Status C
 ACCEPT IN PRINCIPLE.

See comment #383

Cl 142 SC 142.2.4.1 P70 L53 # 340
 Powell, William Nokia

Comment Type TR Comment Status A
 sentence: ... where M is the number of parity-check bits after puncturing

SuggestedRemedy
 rewrite: ... where M is the number of transmitted parity-check bits.

Response Response Status C
 ACCEPT IN PRINCIPLE.

See comment #383

Cl 142 SC 142.2.4.1 P70 L54 # 341
 Powell, William Nokia

Comment Type ER Comment Status A
 sentence: ... the number of parity-check bits after puncturing, M (M = 3072 - 512 = 2560);

SuggestedRemedy
 please note that M has already been defined on p. 70, line 5; it may not be necessary to redefine it here. Alternatively, rewrite: ... the number of transmitted interleaved parity-check bits, M (M = 2560).

Response Response Status C
 ACCEPT IN PRINCIPLE.

See comment #383

Cl 142 SC 142.2.4.1 P71 L1 # 343
 Powell, William Nokia

Comment Type TR Comment Status A
 a maximum number of information bits is specified, but can this be any number, or is it a multiple of 8, 16, ...? Should one also specify a minimum number of information bits? On p. 67, lines 1-4, it seems that the data granularity is 256 bits.

SuggestedRemedy
 Add information on the minimum payload length and the granularity. If there are no restrictions, then indicate that K can take any possible value, as long as $K \leq K_{max}$.

Response Response Status C
 ACCEPT IN PRINCIPLE.

See comment #383

Cl 142 SC 142.2.4.1 P71 L1 # 342
 Powell, William Nokia

Comment Type T Comment Status A
 sentence: the number of output bits ... it would be less ambiguous to refer to this as the transmitted sequence?

SuggestedRemedy
 the number of transmitted bits

Response Response Status C
 ACCEPT IN PRINCIPLE.

See comment #383

Cl 142 SC 142.2.4.1 P71 L1 # 344
 Powell, William Nokia

Comment Type E Comment Status A
 sentence: ... on the burst length pattern to determine shortening length ... This sentence is ambiguous. The notion of "burst length" is mentioned in 141.3.5.2, p. 43, line 23. There is no notion of a burst length pattern prior to p. 71.

SuggestedRemedy
 Suggest to more specifically formulate the number of bits to be transmitted during a burst, in terms of information bits, and possibly introduce extra variables: the number of data bits, the number of input bits to the FEC encoder (256B/257B redundancy), ...

Response Response Status C
 ACCEPT IN PRINCIPLE.

See comment #383

Approved Responses

IEEE P802.3ca D1.4 25/50G-EPON Task Force 5th Task Force review comments

Cl 142 SC 142.2.4.1 P71 L3 # 345
Powell, William Nokia

Comment Type TR Comment Status A

sentence: the code rate, $R = K/N$, defined as the code rate after puncturing and after shortening. Propose to use the standard definition.

SuggestedRemedy

Rewrite: the code rate, $R = K/N$, defined as the ratio between the number of information bits (K) and the number of transmitted bits (N).

Response Response Status C

ACCEPT IN PRINCIPLE.

See comment #383

Cl 142 SC 142.2.4.1 P71 L5 # 346
Powell, William Nokia

Comment Type TR Comment Status A

sentence: The encoder supports highest code rate $R_{max} = K_{max}/N_{max} = 0.849$.

SuggestedRemedy

Rewrite: The FEC Encoder supports an FEC code rate up to $R_{max} = K_{max}/N_{max} = 14392/16952 = 0.849$.

Response Response Status C

ACCEPT IN PRINCIPLE.

See comment #383

Cl 142 SC 142.2.4.1 P71 L8 # 320
Laubach, Mark Broadcom

Comment Type TR Comment Status A

After producing and verifying the test vector addition to Annex 142A, these figures were updated to improved clarity, fix process flow, create symmetry and align with other PCS figures and state diagrams.

SuggestedRemedy

Replace both Figure 142-6 and 142-15 (page 87, line 34) with the respective figures in laubach_3ca_3_0119.pdf

Response Response Status C

ACCEPT IN PRINCIPLE.

Use laubach_3ca_3a_0119.pdf

Cl 142 SC 142.2.4.1 P74 L23 # 348
Powell, William Nokia

Comment Type T Comment Status A

Fig. 142-7 - the labeling in this figure is ambiguous. If the systematic part of this "codeword" represents the input to the encoder, then the label "transmitted user bits" is inaccurate, as the encoder operates on an "bit-interleaved" sequence. The label "Transmitted Parity Bits" is also ambiguous, as the Parity Bits are interleaved prior to transmission. At the same time, this is also not a depiction of the transmitted sequence.

SuggestedRemedy

It is proposed to modify at least the labels, and possibly to introduce a second/third figure, or a combined figure. One could then show: block of K information bits; implicit zero-extension; 256-bit blockwise interleaving; encoding, i.e., determination of the first 10 256-bit parity-check segments; (de)interleaving of the parity segments; transmission of the K user bits, followed by 2560 interleaved parity-check bits.

Response Response Status C

ACCEPT IN PRINCIPLE.

See comment #383

Cl 142 SC 142.2.4.2 P71 L47 # 347
Powell, William Nokia

Comment Type T Comment Status A

right column shifts

SuggestedRemedy

propose to introduce a shift-by-one $Z \times Z$ matrix B, or using a cyclic permutation. The matrix probably works best. The HC matrix would then specify the exponent of B (repeated shifts).

Response Response Status C

ACCEPT IN PRINCIPLE.

See comment #383

Approved Responses

IEEE P802.3ca D1.4 25/50G-EPON Task Force 5th Task Force review comments

Cl 142 SC 142.2.4.3 P74 L43 # 349
 Powell, William Nokia
 Comment Type TR Comment Status A
 Sentence: ... which is then interleaved ... To be consistent with other parts of the text, the term de-interleaved should be used; a better option seems to be to write that a reverse omega network is used.
 SuggestedRemedy
 Propose to write: the first 10 256-bit segments of computed parity bits $p^{(1)}$ $p^{(10)}$ are interleaved using an 8-stage reverse Omega network with seed value $s(i)$.
 Response Response Status C
 ACCEPT IN PRINCIPLE.
 See comment #383

Cl 142 SC 142.2.4.4 P75 L1 # 319
 Laubach, Mark Broadcom
 Comment Type TR Comment Status A 142.2.4.4
 After producing and verifying the test vector addition to Annex 142A, the interleaver text was reviewed. This update removes ambiguities, improves clarity, and reduces wording. Also provided is laubach_3ca_2_0119.pdf, a framemaker compare with the Draft 1.4 text.
 SuggestedRemedy
 Replace 142.2.4.4 with contents of laubach_3ca_1_0119.pdf.
 Response Response Status C
 ACCEPT.

Cl 142 SC 142.2.4.4 P75 L1 # 350
 Powell, William Nokia
 Comment Type TR Comment Status A 142.2.4.4
 sub-clause title is confusing; the information part is transmitted in regular order (non-interleaved)
 SuggestedRemedy
 Proposed change: Interleaving operation of parity-bit segment
 Response Response Status C
 ACCEPT IN PRINCIPLE.
 See comment #319 + change "142.2.4.4 Transmit Interleaving" to "142.2.4.4 Interleaver"

Cl 142 SC 142.2.4.4 P75 L1 # 420
 Laubach, Mark Broadcom
 Comment Type TR Comment Status A post-deadline
 Reviewing the test vector addition to Annex 142A and the updates to the 142.2.4.4 interleaver text, reviewing additional comments and proposed responses, then suggested reviewing all encoder text. This update removes ambiguities, improves clarity, reduces wording, fixes typos, and attempts to address some of the proposed comments. Doing these as many individual comments could lead to error, so bulk replacement text is provided. Also provided is laubach_3ca_7_0119.pdf, a framemaker compare with the Draft 1.4 text.
 SuggestedRemedy
 Replace 142.2.4 intro text, 142.2.4.1, 142.2.4.2, 142.2.4.3 with the respective contents of laubach_3ca_6_0119.pdf.
 Response Response Status C
 ACCEPT IN PRINCIPLE.
 See comment #383

Cl 142 SC 142.2.4.4 P75 L3 # 351
 Powell, William Nokia
 Comment Type TR Comment Status A 142.2.4.4
 For the purposes here: ... it is hard to parse this sentence. The recommendation is to remove this paragraph.
 SuggestedRemedy
 Proposed change: remove this paragraph.
 Response Response Status C
 ACCEPT IN PRINCIPLE.
 See comment #319

Approved Responses

IEEE P802.3ca D1.4 25/50G-EPON Task Force 5th Task Force review comments

Cl 142 SC 142.2.4.4 P75 L7 # 353
 Powell, William Nokia
 Comment Type T Comment Status A 142.2.4.4
 Sentence: ... reverse-omega networks. The term omega network is not all that common. It may be a better idea to introduce the omega network and the reverse network first, as for the LDPC code, and then describe the encoder and decoder operation.
 SuggestedRemedy
 Proposal: change the order of discussion - first the full-length LDPC code, the omega network and the reverse omega network, and then the FEC Encoder (and optionally, the FEC Decoder).
 Response Response Status C
 ACCEPT IN PRINCIPLE.
 See comment #319

Cl 142 SC 142.2.4.4 P75 L7 # 352
 Powell, William Nokia
 Comment Type TR Comment Status A 142.2.4.4
 The term interleaving is generally used to describe the process of transforming a sequence that is in regular order into a sequence that is interleaved. Rather than turning this definition upside-down, it is proposed to discuss the 8-stage 256-input omega network and the 8-stage 256-input reverse omega network. One can then simply state that for the interleaver in the encoder, an 8-stage 256-input reverse omega network is used, and that, consequently, the decoder uses the 8-stage 256-bit omega network.
 SuggestedRemedy
 The FEC Encoder uses an 8-stage 256 x 256 reverse omega network.
 Response Response Status C
 ACCEPT IN PRINCIPLE.
 See comment #319

Cl 142 SC 142.2.4.4 P75 L15 # 354
 Powell, William Nokia
 Comment Type T Comment Status A 142.2.4.4
 The proposed de-interleaver/interleaver is a module that has 256 data inputs, 256 data outputs, a 128-bit seed, and a "fixed/pre-defined" cyclic rotation of this seed (shift factor: 17). Fig. 142-8 seems to imply that a massively parallel structure is needed with 57 * 256 inputs.
 SuggestedRemedy
 It seems more straightforward to present one de-interleaver unit and then associate the seeds with the segment indices.
 Response Response Status C
 ACCEPT IN PRINCIPLE.
 See comment #319

Cl 142 SC 142.2.4.4 P75 L28 # 356
 Powell, William Nokia
 Comment Type TR Comment Status A 142.2.4.4
 Sentence: The parity bit interleaver ... given that Fig. 142-8 show the information bit de-interleaver, it seems to make sense to first discuss the parity-check bit interleaver
 SuggestedRemedy
 Sentence: The parity-check bit de-interleaver ...
 Response Response Status C
 ACCEPT IN PRINCIPLE.
 See comment #319

Cl 142 SC 142.2.4.4 P75 L28 # 355
 Powell, William Nokia
 Comment Type TR Comment Status A 142.2.4.4
 Sentence: The first ten ... These local interleavers are realized by 12 independent omega networks.
 SuggestedRemedy
 Proposed change: Change first "de-interleaved" to "interleaved"
 Response Response Status C
 ACCEPT IN PRINCIPLE.
 See comment #319

Approved Responses

IEEE P802.3ca D1.4 25/50G-EPON Task Force 5th Task Force review comments

Cl 142 SC 142.2.4.4 P75 L30 # 357
Powell, William Nokia

Comment Type TR Comment Status A 142.2.4.4

Sentence: ... consists of 12 local interleavers ... not sure what local refers to; it seems to make more sense to state that the first 10 256-bit parity-check bit segments are de-interleaved using an 8-stage 256x256 reversed omega network, where each segment has its own seed.

SuggestedRemedy

Proposed: The first 10 256-bit parity-check bit segments are de-interleaved using an 8-stage 256x256 reversed omega network, where each segment has its own seed.

Response Response Status C

ACCEPT IN PRINCIPLE.

See comment #319

Cl 142 SC 142.2.4.4 P75 L36 # 358
Powell, William Nokia

Comment Type TR Comment Status A 142.2.4.4

The figure caption is misleading, as this is the Parity-Check Bit interleaver.

SuggestedRemedy

Revised caption: Parity-Check Bit interleaver.

Response Response Status C

ACCEPT IN PRINCIPLE.

See comment #319

Cl 142 SC 142.2.4.5 P76 L31 # 359
Powell, William Nokia

Comment Type T Comment Status R

Sentence: ... and i - 0, ..., 127 - the regular numbering thus far starts at 1. In the context of the permutation, an index starting at 0 can be useful, but it is not difficult to let this index also start at 1.

SuggestedRemedy

Rewrite: ... and i = 0, ..., 127.

Response Response Status C

REJECT.

Text is correct as is.

Cl 142 SC 142.2.5.1 P80 L26 # 298
Lynskey, Eric Broadcom

Comment Type T Comment Status A

The lower 257-bits are no longer TBD, per 142.3.5.1. Also, it shouldn't be necessary to specify the 258-bit value here and 257-bit value elsewhere.

SuggestedRemedy

Value: {MSB = 0, EBD} as specified in 142.3.5.1}

Response Response Status C

ACCEPT IN PRINCIPLE.

Value: EBD257 (see 142.3.5.1) with a bit having value 0 appended as MSB

Cl 142 SC 142.2.5.2 P81 L25 # 278
Hajduczenia, Marek Charter Communicatio

Comment Type TR Comment Status D

ClkOut and ClkXfr are defined in 142.2.5.2 and have the very same definition: "The clear on read variable ClkOut is set to true once for each 257-bits of data output by the PMD." - since the event happens at the specific moment of time (when 257 bits are transferred by the PMD), we could
- combine definition into just one
- rewrite it to set to true on bit 257 and false otherwise - this is sufficient to trigger transition in target SDs

SuggestedRemedy

Remove ClkXfr
Change definition of ClkOut to read "The variable ClkOut is set to true once every 257-bits of data output by the PMD and set to false otherwise."
Change the name of ClkOut to ClkOut257b. Update SDs (142-12, 142-13, and 142-14 accordingly)
Change all instances of ClkXfr to ClkOut257b. Update SDs (142-12, 142-13, and 142-14 accordingly)

Proposed Response Response Status Z

REJECT.

This comment was WITHDRAWN by the commenter.

Approved Responses

IEEE P802.3ca D1.4 25/50G-EPON Task Force 5th Task Force review comments

Cl 142 SC 142.2.5.3 P83 L11 # 360
 Powell, William Nokia
 Comment Type T Comment Status R
 FecParity() - would it make sense to provide a counter as argument?
 SuggestedRemedy
 FecParity(i)
 Response Response Status C
 REJECT.
 Current definition and the use case for this function does not require any external counters to be passed into it.

Cl 142 SC 142.2.5.3 P83 L15 # 323
 Laubach, Mark Broadcom
 Comment Type E Comment Status A bucket
 Appears to be a pre-mature line return after "return"
 SuggestedRemedy
 Fix if possible.
 Response Response Status C
 ACCEPT.

Cl 142 SC 142.2.5.3 P83 L20 # 361
 Powell, William Nokia
 Comment Type ER Comment Status A bucket
 Sentence: This function adds the block v to the input of FIFO buffer.
 SuggestedRemedy
 Rewrite: This function adds block v to the input of the FIFO buffer.
 Response Response Status C
 ACCEPT.

Cl 142 SC 142.2.5.3 P83 L23 # 362
 Powell, William Nokia
 Comment Type ER Comment Status A bucket
 Sentence: This function writes block v, to each element of FIFO buffer. Suggest to remove the comma, and to insert "the".
 SuggestedRemedy
 Rewrite: This function writes block v to each element of the FIFO buffer.
 Response Response Status C
 ACCEPT.

Cl 142 SC 142.2.5.3 P83 L40 # 292
 Hajduczenia, Marek Charter Communicatio
 Comment Type E Comment Status A bucket
 Dead reference to Figure 143-2
 SuggestedRemedy
 Make link live, it is correct reference
 Response Response Status C
 ACCEPT.

Cl 142 SC 142.2.6.2 P81 L38 # 390
 Kramer, Glen Broadcom
 Comment Type T Comment Status A
 When we define a variable with "[]" at the end, we always specify the type as "array of <units>". We create such array definitions only if we need to access individual elements using an index. The ParityStagingBuffer definition has "[]", but the type is defined as "block of 2570 bits".
 This is inconsistent. We either need to define it as "array of 270 bits" or remove the brackets. In text or in the state diagrams, we never access individual elements of ParityStagingBuffer. We only use "<m:n>" notation as we do for blocks (vectors).
 SuggestedRemedy
 1) Make the type "2570-bit block"
 2) Remove "[]" from the definition.
 Response Response Status C
 ACCEPT.

Approved Responses

IEEE P802.3ca D1.4 25/50G-EPON Task Force 5th Task Force review comments

Cl 142 SC 142.3 P84 L50 # 285
 Hajduczenia, Marek Charter Communicatio
 Comment Type E Comment Status A bucket
 Missing link in red
 SuggestedRemedy
 Use "142.3.1.1" + make link live
 Response Response Status C
 ACCEPT.

Cl 142 SC 142.3.1 P85 L48 # 286
 Hajduczenia, Marek Charter Communicatio
 Comment Type T Comment Status A
 Remove current text from the subclause and insert red TBD
 SuggestedRemedy
 Per comment
 Response Response Status C
 ACCEPT IN PRINCIPLE.
 Remove "Note to Editor: text and figures extracted from 142.2.2.5. 142.3.1.1 LDPC Decoder" (yes, remove subclause heading)

Cl 142 SC 142.3.5 P88 L15 # 411
 Kramer, Glen Broadcom
 Comment Type TR Comment Status A
 There are multiple issues with the PCS receive data path state diagrams:
 1) OLT and ONU synchronizers don't pass any aligned data to the rest of PCS receive path
 2) Receive state diagram attempts to find perfect match for EBD and SBD values, which with input BER of 0.01 will happen only in 0.6% of bursts.
 3) PMAUDI is a primitive. But it is used in the PCS receive state diagram as if it is a variable or a buffer.
 4) In PCS Output SD, the variable OutEqCtr is used without being initialized
 5) Non-mutually exclusive transitions from state NEXT_VECTOR
 SuggestedRemedy
 Replace subclause 142.3.5 with the material in kramer_3ca_2_0119.pdf.
 Response Response Status C
 ACCEPT IN PRINCIPLE.

Replace subclause 142.3.5 with the material in kramer_3ca_2a_0119.pdf, with the following changes:
 - change "The OutputFifo supports operations IsEmpty() and GetHead() (see 142.1.1.5)." to "The OutputFifo supports FIFO access operations as defined in 142.1.1.5."
 - change "The RxCwBuf supports operations Append(), Clear(), IsEmpty(), and IsFull() (see 142.1.1.5)." to "The RxCwBuf supports FIFO access operations as defined in 142.1.1.5."

Cl 142 SC 142.3.5.1 P89 L6 # 398
 Kramer, Glen Broadcom
 Comment Type T Comment Status A
 "parity delimiter" term is undefined. We use the term "FEC codeword delimiter"
 SuggestedRemedy
 Replace "parity delimitet" with "FEC codeword delimiter" in two places:
 page 89, line 6
 page 89, line 37
 Response Response Status C
 ACCEPT IN PRINCIPLE.
 See comment #411.

Approved Responses

IEEE P802.3ca D1.4 25/50G-EPON Task Force 5th Task Force review comments

Cl 142 SC 142.3.5.2 P90 L12 # 415
 Remein, Duane Huawei
 Comment Type T Comment Status A
 PMAUDI[i] Alias for PMA_UNITDATA[i]<256:0>.indication needs refinement
 SuggestedRemedy
 Change to: PMAUDI[i]
 Alias for PMA_UNITDATA[i](rx_code_group<256:0>)
 Response Response Status C
 ACCEPT IN PRINCIPLE.
 See comment #411

Cl 142 SC 142.3.5.2 P90 L32 # 287
 Hajduczenia, Marek Charter Communicatio
 Comment Type E Comment Status A bucket
 Missing link in red
 SuggestedRemedy
 Use "142.1.3" + make link live
 Response Response Status C
 ACCEPT.

Cl 142 SC 142.3.5.3 P90 L48 # 288
 Hajduczenia, Marek Charter Communicatio
 Comment Type E Comment Status A bucket
 Missing link in red
 SuggestedRemedy
 Use "142.2.5.3" + make link live
 Response Response Status C
 ACCEPT.

Cl 142A SC 142A P97 L37 # 321
 Laubach, Mark Broadcom
 Comment Type TR Comment Status A
 Insert informational test vector text. Note: the five test vector files are also provided to the Editor in a zip file.
 SuggestedRemedy
 Insert new text after 142A.1 as per laubach_3ca_4_0119.pdf
 Response Response Status C
 ACCEPT IN PRINCIPLE.
 Insert new text after 142A.1 as per laubach_3ca_4a_0119.pdf

Cl 143 SC 143.2.4.2 P100 L29 # 405
 Kramer, Glen Broadcom
 Comment Type T Comment Status A
 Figure 143-3 may be confusing to readers, since it doesn't show the envelope headers at the beginning of each frame, as Figure 143-4 does. Probably just leaving Figure 143-4 is enough.
 SuggestedRemedy
 Delete Figure 143-3 and its referemce in text.
 Response Response Status C
 ACCEPT.

Cl 143 SC 143.2.4.3 P101 L18 # 299
 Lynskey, Eric Broadcom
 Comment Type E Comment Status A bucket
 Text says LLID is N, figure says LLID is L.
 SuggestedRemedy
 Replace LLID N with LLID L.
 Response Response Status C
 ACCEPT.

Approved Responses

IEEE P802.3ca D1.4 25/50G-EPON Task Force 5th Task Force review comments

Cl 143 SC 143.2.6 P106 L23 # 401
 Kramer, Glen Broadcom
 Comment Type T Comment Status A
 Section 143.2.6 "MCRS Time synchronization" is located in the generic part of MCRS clause, but it talks about EPON-specific concepts, such as OLT, ONU, LocalTime. At the same time, there is an empty section 143.4.2 "MCRS and MPCP clock synchronization" in the EPON-specific part of the clause.
 SuggestedRemedy
 Move the subclause 143.2.6 into 143.4.2. Use the title "MCRS Time synchronization"
 Response Response Status C
 ACCEPT.

Cl 143 SC 143.3.3.2 P115 L51 # 289
 Hajduczenia, Marek Charter Communicatio
 Comment Type E Comment Status A bucket
 Missing link in red
 SuggestedRemedy
 Link is correct, just make it live
 Response Response Status C
 ACCEPT.

Cl 143 SC 143.3.4.4 P125 L22 # 400
 Kramer, Glen Broadcom
 Comment Type TR Comment Status A
 Definition of IsMisaligned function is wrong. The function is supposed to return true is the first xGMII transfer contains the second part of IBI EQ and the second transfer contains the first half of an envelope header.
 SuggestedRemedy
 Replace the definition of IsMisaligned() function with the one shown in kramer_3ca_5_0119.pdf. Note the italics and indentation.
 Response Response Status C
 ACCEPT.
 Comment line was fixed (was 12, should be 22)

Cl 143 SC 143.4.1 P128 L34 # 395
 Kramer, Glen Broadcom
 Comment Type E Comment Status A bucket
 "These are passive optical multipoint networks (PONs)"
 We use terms "passive optical networks (PON)" and "point-to-multipoint (P2MP)", but we never define "passive optical multipoint networks" (POMN?)
 Also, not clear what "these" refers to.
 SuggestedRemedy
 Replace "These" with "P2MP networks". Strike "multipoint".
 Response Response Status C
 ACCEPT.

Cl 144 SC 144.1 P135 L19 # 300
 Lynskey, Eric Broadcom
 Comment Type E Comment Status A bucket
 Missing descriptions for bandwidth allocation, authentication, provisioning, and more.
 SuggestedRemedy
 "This clause does not address..."
 Response Response Status C
 ACCEPT.

Cl 144 SC 144.1.1 P135 L38 # 305
 Lynskey, Eric Broadcom
 Comment Type E Comment Status A bucket
 Reference to clause instead of figure.
 SuggestedRemedy
 Replace Clause 144-1 with Figure 144-1.
 Response Response Status C
 ACCEPT.

Approved Responses

IEEE P802.3ca D1.4 25/50G-EPON Task Force 5th Task Force review comments

Cl 144 SC 144.1.2 P138 L3 # 279
 Hajduczenia, Marek Charter Communicatio
Comment Type T Comment Status A
 Text missing in 144.1.2 "Position of Multipoint MAC Control within the IEEE 802.3 hierarchy"
SuggestedRemedy
 Use the text per hajduczenia_3ca_1_0119.pdf
Response Response Status C
 ACCEPT IN PRINCIPLE.
 Use the following text in 144.1.2
 "Figure 144–2 depicts the architectural positioning of the Multipoint MAC Control sublayer with respect to the MAC and the MAC Control client. The Multipoint MAC Control sublayer extends the MAC Control sublayer to support multiple clients and additional MAC control functionality."

Cl 144 SC 144.1.3 P138 L20 # 316
 Lynskey, Eric Broadcom
Comment Type T Comment Status A
 The CCP is missing from Figure 144-3.
SuggestedRemedy
 Add, similar to GATE generation process, to show that there are multiple instances.
Response Response Status C
 ACCEPT IN PRINCIPLE.
 Add editorial note under figure 144-3 and 144-4 indicating homework for Glen to come up with a new way to show MPCP and CCP on one figure for OLT and one figure for ONU. This will be submitted as comment against next version of a draft.

Cl 144 SC 144.2.1 P141 L31 # 280
 Hajduczenia, Marek Charter Communicatio
Comment Type E Comment Status A bucket
 I believe note in red can be removed, since botj Control Parser and Control Multiplexer are already shown in Figure 144-5/6, respectively.
SuggestedRemedy
 Strike the note in red.
Response Response Status C
 ACCEPT.

Cl 144 SC 144.3.1 P182 L48 # 294
 Lynskey, Eric Broadcom
Comment Type T Comment Status A
 INVALID_COMMAND is not defined.
SuggestedRemedy
 INVALID_COMMAND. This constant represents the value of ActionResultCode corresponding to "Invalid command", per Table 144-11. Value 0x4.
Response Response Status C
 ACCEPT IN PRINCIPLE.
 Per comment + insert "continued" tag into Table 144-11 caption.

Cl 144 SC 144.3.1.1 P144 L54 # 290
 Hajduczenia, Marek Charter Communicatio
Comment Type E Comment Status A bucket
 Red link: 143.2.6
SuggestedRemedy
 Link is correct, just make it live
Response Response Status C
 ACCEPT.

Cl 144 SC 144.3.1.1 P146 L2 # 282
 Hajduczenia, Marek Charter Communicatio
Comment Type E Comment Status A bucket
 Red link: 143.2.6
SuggestedRemedy
 Make link live, remove red highlight
Response Response Status C
 ACCEPT.

Approved Responses

IEEE P802.3ca D1.4 25/50G-EPON Task Force 5th Task Force review comments

Cl 144 SC 144.3.1.1 P146 L16 # 281
 Hajduczenia, Marek Charter Communicatio
 Comment Type E Comment Status A bucket
 Dead link: 143.2.6
 SuggestedRemedy
 Make link live
 Response Response Status C
 ACCEPT.

Cl 144 SC 144.3.2.2 P148 L6 # 293
 Lynskey, Eric Broadcom
 Comment Type T Comment Status A
 MLID is also used to carry CCPDUs.
 SuggestedRemedy
 Add "and CCPDUs (see 144.4)" to end of first sentence.
 Response Response Status C
 ACCEPT.

Cl 144 SC 144.3.3 P148 L53 # 283
 Hajduczenia, Marek Charter Communicatio
 Comment Type E Comment Status A bucket
 Table 144-1 is missing bottom cell line
 SuggestedRemedy
 Add the missing line at line 53
 Response Response Status C
 ACCEPT.

Cl 144 SC 144.3.4 P149 L28 # 410
 Kramer, Glen Broadcom
 Comment Type TR Comment Status A MPCPDU-rewrite
 Action item from Bangkok meeting to update the MPCPDU description section to reflect the new approach of operand list structure in state diagrams
 The main purpose of this update was to align field names and message structures with what we use in state diagrams and to ensure that all fields are defined only once in a single place.

SuggestedRemedy
 Replace the current subclause 144.3.4 with the text and figures provided in kramer_3ca_3_0119.pdf.
 In the new subclause, each MPCPDU has its operands grouped in a single structure called MsgName and every field can be accessed in any state diagram by using notation MsgName.FieldName. All state diagrams in C144 already use this notation.
 (By definition, the operand list in a MAC Control message comprises all the fields following the opcode, but excluding Pad and FCS).

Response Response Status C
 ACCEPT IN PRINCIPLE.
 Replace the current subclause 144.3.4 with the text and figures provided in kramer_3ca_3_0119.pdf. Update "x bit" to "x-bit" where used as compound adjective.
 Add Editorial Note in 144.4.2 with AI for Glen to rewrite the definitions of CCPDUs using template from MPCPDUs (see 144.3.4).

Cl 144 SC 144.3.4 P149 L44 # 313
 Lynskey, Eric Broadcom
 Comment Type E Comment Status A bucket
 There is no subclause 144.6.2.
 SuggestedRemedy
 Looking at previous EPON standards, it is likely supposed to be a reference to the empty 144.1.2.
 Response Response Status C
 ACCEPT.

Approved Responses

IEEE P802.3ca D1.4 25/50G-EPON Task Force 5th Task Force review comments

Cl 144 SC 144.3.4.1 P151 L39 # 306
 Lynskey, Eric Broadcom
 Comment Type T Comment Status A MPCPDU-rewrite
 The bit positions of FR and F in Figure 144-10 are not clear.
 SuggestedRemedy
 Add some bit positions on the figure to show that F corresponds to bit [23] and FR corresponds to bit [22] and EnvLength corresponds to bits [21:0]. This would be similar to Figure 144-15.
 Response Response Status C
 ACCEPT IN PRINCIPLE.
 See comment #410

Cl 144 SC 144.3.5 P161 L3 # 308
 Lynskey, Eric Broadcom
 Comment Type E Comment Status A bucket
 This is the only page in the draft that uses the term off-line ONU. The term, unregistered, is used more frequently.
 SuggestedRemedy
 Replace off-line with unregistered on lines 3, 4, and 27.
 Response Response Status C
 ACCEPT.

Cl 144 SC 144.3.5 P161 L15 # 307
 Lynskey, Eric Broadcom
 Comment Type T Comment Status A
 The statement about aborting the registration attempt should be from the point of view of receiving the new SYNC_PATTERN_MPCPDU.
 SuggestedRemedy
 If a SYNC_PATTERN_MPCPDU is received prior to the transmission of a REGISTER_REQ MPCPDU of an ONU responding to a previous discovery window...
 Response Response Status C
 ACCEPT IN PRINCIPLE.
 If a SYNC_PATTERN MPCPDU is received prior to the transmission of a REGISTER_REQ MPCPDU of an ONU responding to a previous discovery window...

Cl 144 SC 144.3.5 P161 L28 # 406
 Kramer, Glen Broadcom
 Comment Type T Comment Status A
 "Discovery windows are unique in that they are the only times when multiple ONUs can access the PON simultaneously, and transmission overlap can occur."
 This statement is not true in multi-channel PON.
 SuggestedRemedy
 Change the sentence to
 "Discovery windows are unique in that they are the only times when multiple ONUs can access the same upstream channel simultaneously, and transmission overlap can occur."
 Response Response Status C
 ACCEPT IN PRINCIPLE.

Change the sentence to
 "Discovery windows are unique in that they are the only times when multiple ONUs are allowed to access the same upstream channel simultaneously, and transmission overlap may occur."

Cl 144 SC 144.3.5 P161 L50 # 407
 Kramer, Glen Broadcom
 Comment Type E Comment Status A bucket
 "bonding" should be "binding" in the following sentences:
 "Upon receipt of a valid REGISTER_REQ MPCPDU, the OLT registers the ONU, allocating and assigning two new port identities (PLID and MLID), and bonding them to corresponding MACs in the OLT."
 "It is the responsibility of Layer Management to perform the MAC bonding, and start transmission from/to the newly registered ONU."
 SuggestedRemedy
 Replace "bonding" with "binding"
 Response Response Status C
 ACCEPT.

Approved Responses

IEEE P802.3ca D1.4 25/50G-EPON Task Force 5th Task Force review comments

Cl 144 SC 144.3.5 P161 L54 # 309
 Lynskey, Eric Broadcom

Comment Type T Comment Status A

The final sentence that carries over to the next page is incorrect. The OLT no longer sends laser on/off back to the ONU.

SuggestedRemedy

Delete the final sentence on page 161 beginning with, "The OLT also..."

Response Response Status C

ACCEPT.

Cl 144 SC 144.3.5 P162 L4 # 408
 Kramer, Glen Broadcom

Comment Type T Comment Status A

There are several problems with the following sentence:

"The OLT at that time has enough information to schedule the ONU for access to the PON and transmits a standard GATE MPCPDU allowing the ONU to transmit a REGISTER_ACK MPCPDU."

- 1) Not clear at what time the OLT has the information.
- 2) "transmits a standard GATE" implies that 802.3ca standard will also describe a non-standard GATE.

SuggestedRemedy

Change the sentence to

"After processing the REGISTER_REQ MPCPDU received from a given ONU, the OLT has enough information to schedule that ONU for access to the PON. The OLT transmits a GATE MPCPDU allowing the ONU to transmit a REGISTER_ACK MPCPDU."

Response Response Status C

ACCEPT.

Cl 144 SC 144.3.5.1 P164 L15 # 310
 Lynskey, Eric Broadcom

Comment Type T Comment Status A

Does a constant need a default value?

SuggestedRemedy

Remove "default value".

Response Response Status C

ACCEPT IN PRINCIPLE.

Change "default value" to "for ODN with 20 km reach"

Cl 144 SC 144.3.5.1 P164 L29 # 311
 Lynskey, Eric Broadcom

Comment Type T Comment Status A

A constant shouldn't have an unknown value.

SuggestedRemedy

Move GRANT_MARGIN to 144.3.5.3 Variables.

Response Response Status C

ACCEPT IN PRINCIPLE.

Per comment + change "constant" to "variable". Change name from GRANT_MARGIN to GrantMargin + update SDs

Cl 144 SC 144.3.6.3 P170 L54 # 291
 Hajduczenia, Marek Charter Communicatio

Comment Type E Comment Status A bucket

Missing link in red

SuggestedRemedy

Given that the only location where envelope descriptor is defined is the same subclause, see Env structure, te reference is not needed.

Change "(see 144.x.x.x)" to (see <i>Env</i> variable)"

Response Response Status C

ACCEPT.

Approved Responses

IEEE P802.3ca D1.4 25/50G-EPON Task Force 5th Task Force review comments

Cl 144 SC 144.3.6.8. P172 L39 # 396
 Kramer, Glen Broadcom
 Comment Type TR Comment Status A
 In Figure 144-22, "=" shall be "<=". The originally accepted state diagram had the correct symbol.
 SuggestedRemedy
 Replace "MsgGate.StartTime - LocalTime = MPCP_PROCESS_DLY"
 with
 "MsgGate.StartTime - LocalTime <= MPCP_PROCESS_DLY"
 Response Response Status C
 ACCEPT.

Cl 144 SC 144.4.1.1 P177 L9 # 314
 Lynskey, Eric Broadcom
 Comment Type T Comment Status A
 It doesn't seem quite right to have the ONU send a unicast CC_RESPONSE. In 144.4.2, it says the destination address of the CCPDU can have either the multicast address or a unicast address associated with a PLID. It seems that the ONU should be able to use the multicast DA here.
 SuggestedRemedy
 Remove "unicast" in all five instances of "sends a unicast CC_RESPONSE".
 Response Response Status C
 ACCEPT IN PRINCIPLE.

Per comment + in 144.4.2, change ", or the individual MAC address associated with the PLID to which the CCPDU is destined." to ".".
 Cl 144 SC 144.4.2 P178 L54 # 312
 Lynskey, Eric Broadcom
 Comment Type E Comment Status A bucket
 There is no subclause 144.6.2.
 SuggestedRemedy
 Looking at previous EPON standards, it is likely supposed to be a reference to the empty 144.1.2.
 Response Response Status C
 ACCEPT.

Cl 144 SC 144.4.3 P181 L35 # 389
 Kramer, Glen Broadcom
 Comment Type E Comment Status A bucket
 Missing "n" in "Chanel"
 SuggestedRemedy
 Change to "Channel"
 Response Response Status C
 ACCEPT.

Cl 144 SC 144.4.3.1 P182 L7 # 397
 Kramer, Glen Broadcom
 Comment Type T Comment Status A
 No units are needed for CCP_TIMEOUT, since this interval applies to a timer, not a counter. We do not specify time resolution units for timers.
 SuggestedRemedy
 Strike ",expressed in units of EQT."
 Response Response Status C
 ACCEPT.

Cl 144 SC 144.4.3.1 P182 L11 # 317
 Lynskey, Eric Broadcom
 Comment Type T Comment Status R delete_retry
 Setting a 100ms timeout and retry limit of 3 appears to be taking control away from the client. In the current draft, the client could immediately issue the same CCP message again after 300ms.
 SuggestedRemedy
 Delete these two constants.
 Response Response Status C
 REJECT.
 The purpose is to enforce a retry mechanism up to 3 times, with 100ms max wait time for ONU response.

Approved Responses

IEEE P802.3ca D1.4 25/50G-EPON Task Force 5th Task Force review comments

Cl 144 SC 144.4.3.3 P184 L7 # 399
 Kramer, Glen Broadcom
 Comment Type T Comment Status A
 No return value is needed in the definition of function UpdateChState(int chIndex, int NewState)
 SuggestedRemedy
 Delete "int4"
 Response Response Status C
 ACCEPT.

Cl 144 SC 144.4.3.6 P185 L1 # 318
 Lynskey, Eric Broadcom
 Comment Type T Comment Status R delete_retry
 In a different comment, I suggested removing the timeout and retry limits. If that is accepted, changes will also be needed in figure 144-29.
 SuggestedRemedy
 Remove all state transitions leaving FORWARD_REQUEST. Add a new UCT transition from FORWARD_REQUEST to WAIT_FOR_CCPDU. Also remove the CcpRetry action in WAIT_FOR_CCPDU.
 Response Response Status C
 REJECT.
 See comment #317

Cl 144 SC 144.4.3.6 P186 L8 # 315
 Lynskey, Eric Broadcom
 Comment Type T Comment Status R
 There is no enforced priority if the MCSR and MCII happen at the same time.
 SuggestedRemedy
 Change so that MCII(MsgChRequest) has priority when leaving WAIT_FOR_CCPDU and FORWARD_CC_REQUEST states.
 Response Response Status C
 REJECT.
 By state diagram definitions, these events are detected in zero time. There cannot be a collision where multiple events are detected at the same time. For example, see Figure 144-20—ONU Registration state diagram, exit from state REGISTERED on MCII and MCRS primitives.
 In practice, such conditions are prioritized arbitrarily.

Cl Abstrac SC Abstract P2 L1 # 329
 Powell, William Nokia
 Comment Type E Comment Status A bucket
 extends operation
 SuggestedRemedy
 extends the operation
 Response Response Status C
 ACCEPT.