

## IEEE P802.3cc D3.1 25 Gb/s Ethernet Over Single-Mode Fiber 1st Sponsor recirculation ballot comments

Cl 0 SC 0 P L # r01-11  
Perry, Lisa

Comment Type G Comment Status D

This draft meets all editorial requirements.

SuggestedRemedy

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 1 SC 1 P 1 L 1 # r01-8  
BUCANEG, DEMETRIO JR Hawaiian Electric Com

Comment Type G Comment Status D

Note: Details of the tabulated comments seemed to get lost during the downloading of Excel Spreadsheet but could be emailed if needed.

SuggestedRemedy

Proposed Response Response Status W

PROPOSED REJECT.

This is not a comment against P802.3cc D3.1.

Cl 30 SC 30.5.1.1.2 P 19 L 10 # r01-1  
BUCANEG, DEMETRIO JR Hawaiian Electric Com

Comment Type ER Comment Status D

Quote: Written as "30.5.1.1.2 aMAUType" and might have been a minor typo for that letter "a".

SuggestedRemedy

Rewrite as: "30.5.1.1.2a aMAUType"

Proposed Response Response Status W

PROPOSED REJECT.

"aMAUType" is specified to be name of the attribute of a managed object. "a" is not part of the clause number.

Cl 45 SC 45.2.1.8 P 21 L 9 # r01-2  
BUCANEG, DEMETRIO JR Hawaiian Electric Com

Comment Type ER Comment Status D

For consistency as was written in "Tables 45-9 and 45-10", row 1 in "Table 45-12" should be corrected as shown.

SuggestedRemedy

Rewrite row 1 under column "PMA/PMD" as "25GBASE-LR, and 25GBASE-ER"

Proposed Response Response Status W

PROPOSED REJECT.

The format for the entries in Tables 45-9, 45-10, and 45-12 are consistent with convention (see tables in 802.3-2015).

Cl 108 SC 108.7.3 P 27 L 13 # r01-3  
BUCANEG, DEMETRIO JR Hawaiian Electric Com

Comment Type ER Comment Status D

For completeness, include the "Subclause" references for "25GBASE-LR and 25GBASE-ER" respectively in table.

SuggestedRemedy

Add "Subclause" references for "\*LR & \*ER" in the table.

Proposed Response Response Status W

PROPOSED REJECT.

Leaving the reference blank is consistent with what was done for \*KR, \*CR, and \*SR in Clause 108.7.3, which was introduced by P802.3by.

## IEEE P802.3cc D3.1 25 Gb/s Ethernet Over Single-Mode Fiber 1st Sponsor recirculation ballot comment:

CI 114 SC 114.1 P 40 L 7 # r01-7  
BUCANEG, DEMETRIO JR Hawaiian Electric Com

Comment Type TR Comment Status D

In comparison, "Table 114-8, 25GBASE-ER, 30 km, Channel Insertion Loss (Max) = 15 dB" is different from "Table 114-11, 25GBASE-ER, 30 km, Channel Insertion Loss (Max) = 18 dB". If needs to match in value, suggest taking the higher magnitude where "Table 114-8" is revised as shown.

#### SuggestedRemedy

Coordinate consistent value of the "25GBASE-ER, 30 km, Channel Insertion Loss (Max) = 18 dB" between "Tables 114-11 and 114-8".

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Tables 114-8 and 114-11 should be consistent with Tables 87-9 and 87-14, which set the precedent for illustrative link power budget and fiber optical cabling characteristics, respectively, when there is a specification for minimum channel loss. The following changes to Tables 114-8 and 114-11 will make them consistent with Tables 87-9 and 87-14.

1. Delete "(max)" from the channel insertion loss parameter cell in Table 114-8.
2. Delete the entire row for channel insertion loss (min) in Table 114-8.
3. Combine the cells for channel insertion loss (max) in Table 114-11 for 25GBASE-ER at 30km and 40km.

CI 114 SC 114.6 P 33 L 4 # r01-10  
Lewis, David Lumentum

Comment Type TR Comment Status D

We need to include an allowance for MPI penalty in the link budget for 25GBASE-ER. According to [http://www.ieee802.org/3/cc/public/adhoc/170614/king\\_01\\_25gsmf\\_061417.pdf](http://www.ieee802.org/3/cc/public/adhoc/170614/king_01_25gsmf_061417.pdf), the penalty needs to be 0.7 dB for leacy cable plants used for 10GBASE-LR.

#### SuggestedRemedy

Table 114-6: change Transmitter reflectance (max) from -12 to -26 dB. Table 114-8: change Channel insertion loss (max) from 15 and 18 to 15 - value in Table yyy and 18 - value in Table yyy, change maximum discrete reflectance from -26 to "see Table yyy". Add a new Table yyy with combinations of -26 and -35 dB connectors and corresponding entries to be subtracted from Channel insertion loss (max) for MPI penalty. These changes will be detailed in a presentation at the Berlin task force meeting.

Proposed Response Response Status W

(Pending presentation and discussion)

CI 114 SC 114.6 P 33 L 4 # r01-9  
Lewis, David Lumentum

Comment Type TR Comment Status D

We need to include an allowance for MPI penalty in the link budget for 25GBASE-LR. According to [http://www.ieee802.org/3/cc/public/adhoc/170614/king\\_01\\_25gsmf\\_061417.pdf](http://www.ieee802.org/3/cc/public/adhoc/170614/king_01_25gsmf_061417.pdf), the penalty needs to be 0.7 dB for leacy cable plants used for 10GBASE-LR.

#### SuggestedRemedy

Table 114-6: change Transmitter reflectance (max) from -12 to -26 dB. Table 114-7: change Receiver sensitivity (OMA) (max) from -11.3 to -12 dBm and change Stressed receiver sentivity (OMA) (max) from -8.8 to -9.5 dBm. Table 114-8: change Power budget (for maximum TDP) from 9 to 9.7 dB, change maximum discrete reflectance from -26 to "see table xxx", and change Allocation for penalties (for maximum TDP) from 2.7 to 3.4 dB. Add a new table xxx with combinations of -26 and -35 dB connectors that are supported based on an MPI penalty of 0.7 dB. These changes will be detailed in a presentation at the Berlin task force meeting.

Proposed Response Response Status W

(Pending presentation and discussion)

CI 114 SC 114.6.1 P 33 L 40 # r01-4  
BUCANEG, DEMETRIO JR Hawaiian Electric Com

Comment Type TR Comment Status D

In "Table 114-6", "25GBASE-ER" has "Center Wavelength (Range)" of "1295 to 1310 nm". In comparison, "Table 114-7, 25GBASE-ER" has a different "Center Wavelength (Range)" of "1295 to 1325 nm". If needs to match in values, suggest taking the higher range where "Table 114-6" is revised as shown.

#### SuggestedRemedy

Revise as: "Table 114-6, 25GBASE-ER, Center Wavelength (Range) = 1295 to 1310 1325 nm".

Proposed Response Response Status W

PROPOSED REJECT.

Comments r01-4 and r01-5 are the same. The center wavelength range in Table 114-6 was made narrower to limit dispersion penalties for the 25GBASE-ER transmitter. The center wavelength range in Table 114-7, which specifies the 25GBASE-ER receiver, was matched to the range of 25GBASE-LR to allow interoperability between 25GBASE-LR and 25GBASE-ER.

## IEEE P802.3cc D3.1 25 Gb/s Ethernet Over Single-Mode Fiber 1st Sponsor recirculation ballot comments

CI 114 SC 114.6.2 P 35 L 13 # r01-5  
BUCANEG, DEMETRIO JR Hawaiian Electric Com

Comment Type **TR** Comment Status **X**

In "Table 114-6", "25GBASE-ER" has "Center Wavelength (Range)" of "1295 to 1310 nm".  
In comparison, "Table 114-7, 25GBASE-ER" has a different "Center Wavelength (Range)" of "1295 to 1325 nm". If needs to match in values, suggest taking the higher range where "Table 114-6" is revised as shown.

*SuggestedRemedy*

Coordinate consistent values of the "25GBASE-ER, Center Wavelength (Range) = 1295 to 1325 nm" between "Tables 114-7 and 114-6".

Proposed Response Response Status **W**

PROPOSED REJECT.

Comments r01-4 and r01-5 are the same. The center wavelength range in Table 114-6 was made narrower to limit dispersion penalties for the 25GBASE-ER transmitter. The center wavelength range in Table 114-7, which specifies the 25GBASE-ER receiver, was matched to the range of 25GBASE-LR to allow interoperation between 25GBASE-LR and 25GBASE-ER.

CI 114 SC 114.6.3 P 36 L 15 # r01-6  
BUCANEG, DEMETRIO JR Hawaiian Electric Com

Comment Type **TR** Comment Status **D**

In comparison, "Table 114-8, 25GBASE-ER, 30 km, Channel Insertion Loss (Max) = 15 dB" is different from "Table 114-11, 25GBASE-ER, 30 km, Channel Insertion Loss (Max) = 18 dB". If needs to match in value, suggest taking the higher magnitude where "Table 114-8" is revised as shown.

*SuggestedRemedy*

Revise as: "Table 114-8, 25GBASE-ER, 30 km, Channel Insertion Loss (Max) = 15 18 dB"

Proposed Response Response Status **W**

PROPOSED ACCEPT IN PRINCIPLE.

Channel insertion loss (max) in Table 114-11 is correct at 18 dB. "Channel insertion loss (max)" will be changed to "Channel insertion loss" in Table 114-8, which will remove the confusion.