

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

CI 98 SC 98C.5 P L # 289
 Graber, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status D AutoNeg

Next Page Information for 10BASE-T1L need to be added to Annex 98.C

SuggestedRemedy

Please add text shown in presentation "10BASE-T1L Auto-Negotiation.pdf", page 13.

Proposed Response Response Status W

PROPOSED ACCEPT.

CI 00 SC 0 P L # 313
 Huszák, Gergely Kone

Comment Type E Comment Status D Editorial

There are unnecessary and inconsistent repetitions the two names of the 5B symbols (e.g. "SYNC, SYNC, SYNC, SSD sequence (that is a J/J/J/K 5B sequence)" and "SYNC, SSD symbol sequence (that is a J/K sequence)").
 At the same time also fix the inconsistent use of the term "symbol"

SuggestedRemedy

Use only the names listed in column "Special function" of table 147-1

Remove unnecessary use of "symbol"

Example changes:

"SYNC, SYNC, SYNC, SSD sequence (that is a J/J/J/K 5B sequence)" -> "SYNC, SYNC, SYNC, SSD sequence"

"SYNC, SSD symbol sequence (that is a J/K sequence)" -> "SYNC, SSD sequence"

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Delete "(that is a ... sequence)" at:

Page 139 line 3 and Page 142 line 17)

CI 00 SC 0 P L # 311
 Huszák, Gergely Kone

Comment Type E Comment Status D Editorial

Usage of the term 10BASE-T1S is inconsistent ("10BASE-T1S" vs. "10BASE-T1S PHY" vs. "10BASE-T1S Ethernet PHY")

SuggestedRemedy

- "10BASE-T1S" should be used as an adjective

- "10BASE-T1S PHY" should be used as a noun

- "10BASE-T1S Ethernet PHY" should not be used

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Change "10BASE-T1S Ethernet PHY" to "10BASE-T1S PHY" on page 149 line 50

Change "10BASE-T1S PHY" on page 129 line 33 to "10BASE-T1S"

Note "10BASE-T1S" may be a noun or an adjective - sometimes it is the name of the protocol. Do not globally modify other instances of "10BASE-T1S" (these may be subject to later, detailed editorial comments on a case by case basis)

CI 00 SC 0 P L # 312
 Huszák, Gergely Kone

Comment Type E Comment Status D EZ

There are unnecessary and inconsistent repetitions of references to table 147-1 (e.g. "5B symbol as defined in Table 147-1")

SuggestedRemedy

Remove all but the first reference (in C147) to table 147-1

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Delete "(See Table 147-1)" at:

page 134 line 36;

page 135 lines 9, 11, 14, 16, 19, 21;

page 143 lines 10 and 19

*keep references to Table 147-1 in first reference, ENCODE and DECODE function definitions

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

Cl 98 SC 98C.6 P L # 290
 Graber, Steffen Pepperl+Fuchs GmbH
 Comment Type T Comment Status D AutoNeg
 Next Page Information for 10BASE-T1S need to be added to Annex 98.C
 SuggestedRemedy
 Please add text shown in presentation "10BASE-T1L Auto-Negotiation.pdf", page 14.
 Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 98 SC 98C.1 P L # 288
 Graber, Steffen Pepperl+Fuchs GmbH
 Comment Type T Comment Status D AutoNeg
 Next Page information for 10BASE-T1S need to be added to table 98C-1.
 SuggestedRemedy
 Add Message Code ID 8 (00000001000) with message code description for 10BASE-T1S Information (see presentation "10BASE-T1L Auto-Negotiation.pdf")
 Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 98 SC 98C.1 P L # 287
 Graber, Steffen Pepperl+Fuchs GmbH
 Comment Type T Comment Status D AutoNeg
 Next Page information for 10BASE-T1L need to be added to table 98C-1.
 SuggestedRemedy
 Add Message Code ID 7 (00000000111) with message code description for 10BASE-T1L Information (see presentation "10BASE-T1L Auto-Negotiation.pdf")
 Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 98 SC 98B.4 P L # 286
 Graber, Steffen Pepperl+Fuchs GmbH
 Comment Type T Comment Status D AutoNeg
 Priority resolution for 10BASE-T1S and 10BASE-T1L need no be added to IEEE802.3 standard.
 SuggestedRemedy
 Add 10BASE-T1S in the priority resolution list after 100BASE-T1 and then add 10BASE-T1L in the priority resolution list after 10BASE-T1S.
 Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 98 SC 98B.3 P L # 285
 Graber, Steffen Pepperl+Fuchs GmbH
 Comment Type T Comment Status D AutoNeg
 10BASE-T1S and 10BASE-T1L PHYs need to be added to table 98B-1 of IEEE802.3 standard.
 SuggestedRemedy
 Change bit A1 in table 98B-1 from RESERVED to 10BASE-T1S
 Proposed Response Response Status W
 PROPOSED ACCEPT.

Cl 00 SC 0 P 1 L 6 # 301
 Maguire, Valerie The Siemon Company
 Comment Type E Comment Status D EZ
 "Draft Standard for Ethernet-Amendment:" appears twice on the title page.
 SuggestedRemedy
 Delete "Draft Standard for Ethernet Amendment." on lines 12-15.
 Proposed Response Response Status W
 PROPOSED ACCEPT.
 Delete "Draft Standard for Ethernet Amendment." on lines 12-15.

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

Cl 00 SC 0 P 1 L 22 # 300

Maguire, Valerie

The Siemon Company

Comment Type E Comment Status D Editorial

Align media references with revised objectives.

SuggestedRemedy

Globally search and replace, "single balanced twisted-pair" with "single balanced pair" when the text appears before a media term (e.g. "cabling", "connector", "cable", "cord", etc.). The first occurrence of this change is in the title of the draft.

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 30 SC 30.3 P 29 L 20 # 461

Brandt, David

Rockwell Automation

Comment Type T Comment Status D Management

10BASE-T1S RS lacks PLCA management

SuggestedRemedy

Bring in new Figure 30-3 to draft, insert an additional object (box) between oMACEntity and oPHYEntity with one-to-one relationships. Box contains "oPLCA" and link to 30.3.9.

Add new clause to draft:

30.3.9 PLCA managed object class

This subclause formally defines the behaviours for the oPLCA managed object class attributes.

30.3.9.1 PLCA Attributes

30.3.9.1.1 aPLCAAdminState

ATTRIBUTE

APPROPRIATE SYNTAX:

An ENUMERATED VALUE that has the following entries:

disabled
enabled

BEHAVIOUR DEFINED AS:

A read-only value that indicates the mode of operation of the Reconciliation Sublayer for PLCA operation. A disabled PLCA utilizes Clause 22 reconciliation sublayer without modification. An enabled PLCA modifies the behavior of the reconciliation sublayer per Clause 148. By default, PLCA is disabled.;

30.3.9.2 PLCA device actions

30.3.2.2.1 acPLCAAdminControl

ACTION

APPROPRIATE SYNTAX:

Same as aPLCAAdminState

BEHAVIOUR DEFINED AS:

This action provides a means to alter aPLCAAdminState. Setting PLCA to the enabled state will result in alteration of the Reconciliation Sublayer behavior to follow Clause 148 provided the PHY implements and enables optional Clause 147 PLCA as indicated in MDIO interface register ability bit 3.2292.13 and enable bit 3.2291.13;

30.3.2.2.2 acPLCAReset

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

ACTION

APPROPRIATE SYNTAX:

An ENUMERATED VALUE that has the following entries:

reset
normal

BEHAVIOUR DEFINED AS:

This action provides a means to reset the PLCA state of a Reconciliation Sublayer. Setting acPLCAReset to reset will reset the PLCA portion of a Reconciliation Sublayer provided the PHY implements and enables optional Clause 147 PLCA as indicated in MDIO interface register ability bit 3.2292.13 and enable bit 3.2291.13. After reset is complete, acPLCAReset returns to normal. The default state of acPLCAReset is normal.;

Proposed Response Response Status **W**

PROPOSED ACCEPT.

Cl 30 SC 30.5.1.1.4 P 29 L 35 # 302
Maguire, Valerie The Siemon Company

Comment Type **E** Comment Status **D** EZ
1000BASE-RH was made the third sentence and 100BASE-T1 the fourth sentence in the draft 3.2 revision of 802.3cj.

SuggestedRemedy

Change "Change the third sentence" to "Change the fourth sentence" in the editing instruction on line 35.

Proposed Response Response Status **W**

PROPOSED ACCEPT.

Change "Change the third sentence" to "Change the fourth sentence" in the editing instruction on line 35.

Cl 30 SC 30.5.1.1.4 P 29 L 38 # 303
Maguire, Valerie The Siemon Company

Comment Type **E** Comment Status **D** EZ
Unchanged text should not be shown.

SuggestedRemedy

Delete, "All other states of link_status map to the enumeration "not available"." on line 38.

Proposed Response Response Status **W**

PROPOSED ACCEPT.

Delete, "All other states of link_status map to the enumeration "not available"." on line 38.

Cl 45 SC 45.2.1.174a P 32 L 36 # 291
Graber, Steffen Pepperl+Fuchs GmbH

Comment Type **T** Comment Status **D** AutoNeg

1 = Enable 1.0 Vpp operating mode, 0 = Enable 2.4 Vpp operating mode

SuggestedRemedy

1 = Enable 2.4 Vpp operating mode, 0 = Enable 1.0 Vpp operating mode (1.0 Vpp is intended to be the default behavior in the future, to support 1.8 V only supply voltages for a PHY IC) (See presentation "10BASE-T1L Auto-Negotiation". This bit can be independently set by the management entity, if auto-negotiation is disabled. If auto-negotiation is enabled, this bit has to be set by management entity according to the auto-negotiation rules defined in the next page mechanism.)

Proposed Response Response Status **W**

PROPOSED ACCEPT.

Change from,

1 = Enable 1.0 Vpp operating mode

0 = Enable 2.4 Vpp operating mode

to,

1 = Enable 2.4 Vpp operating mode

0 = Enable 1.0 Vpp operating mode

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

CI 45 SC 45.2.1.174a P 32 L 40 # 292
Graber, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status D EEE

Bit 1.2294.10 is reserved

SuggestedRemedy

Change bit 1.2294.10 functionality to: 1 = Enable EEE functionality, 0 = Disable EEE functionality (See presentation "10BASE-T1L Auto-Negotiation". This bit is set by independently the management entity, if auto-negotiation is disabled. If auto-negotiation is enabled, this bit has to be set by management entity according to the auto-negotiation rules defined in the next page mechanism.)

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.
Change reserved row bits from,
1.2294.10:0

to,
1.2294.9:0

Insert new bit after 1.2294.11
Bit(s): 1.2294.10
Name: EEE functionality
Description:
1 = Enable EEE functionality
0 = Disable EEE functionality
R/W: R/W

CI 45 SC 45.2.1.174a.4 P 33 L 25 # 293
Graber, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status D PMA

When bit 1.2294.12 is set to one, the 10BASE-T1L PMA shall transmit using the 1.0 Vpp operating mode according to 146.5.4.1. When bit 1.2294.12 is set to zero, the 10BASE-T1L PMA shall transmit using the 2.4 Vpp operating mode according to 146.5.4.1. The default value of bit 1.2294.12 is zero.

SuggestedRemedy

When bit 1.2294.12 is set to one, the 10BASE-T1L PMA shall transmit using the 2.4 Vpp operating mode according to 146.5.4.1. When bit 1.2294.12 is set to zero, the 10BASE-T1L PMA shall transmit using the 1.0 Vpp operating mode according to 146.5.4.1. The default value of bit 1.2294.12 is zero. (reverse signal amplitude levels and add Auto-Negotiation enable bit)

Proposed Response Response Status W

PROPOSED ACCEPT.

Change from,
When bit 1.2294.12 is set to one, the 10BASE-T1L PMA shall transmit using the 1.0 Vpp operating mode according to 146.5.4.1. When bit 1.2294.12 is set to zero, the 10BASE-T1L PMA shall transmit using the 2.4 Vpp operating mode according to 146.5.4.1.

to,
When bit 1.2294.12 is set to one, the 10BASE-T1L PMA shall transmit using the 2.4 Vpp operating mode according to 146.5.4.1. When bit 1.2294.12 is set to zero, the 10BASE-T1L PMA shall transmit using the 1.0 Vpp operating mode according to 146.5.4.1.

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

Cl 45 SC 45.2.1.174a.6 P 33 L 45 # 294
Graber, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status D EEE

Description for bit "Enable EEE functionality" needs to be added.

SuggestedRemedy

Add chapter "45.2.1.174a.6 EEE functionality (1.2294.10)". When bit 1.2294.10 is set to one, the 10BASE-T1L PHY shall enable EEE functionality. When bit 1.2294.10 is set to zero, the 10BASE-T1L PHY shall disable EEE functionality. The default value of bit 1.2294.10 is zero.

Proposed Response Response Status W

PROPOSED ACCEPT.
Insert new clause,

45.2.1.174a.6 EEE functionality (1.2294.10)

When bit 1.2294.10 is set to one, the 10BASE-T1L PHY shall enable EEE functionality.
When bit 1.2294.10 is set to zero, the 10BASE-T1L PHY shall disable EEE functionality.
The default value of bit 1.2294.10 is zero.

Cl 45 SC 45.2.1.174b P 34 L 13 # 295
Graber, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status D AutoNeg

1 = PHY has 1.0 Vpp operating mode ability, 0 = PHY does not have 1.0 Vpp operating mode ability

SuggestedRemedy

1 = PHY has 2.4 Vpp operating mode ability, 0 = PHY does not have 2.4 Vpp operating mode ability (default value is now 1.0 Vpp, optional mode is 2.4 Vpp, therefore 1.0 Vpp needs to be changed to 2.4 Vpp)

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE. This comment assumes that one of the transmitter voltages is optional.

Task group to consider: Is one operating mode optional? PICS tags one mode as optional. 146.5.4.1 shows both as mandatory. PICS may change.

If accepted, change from,
1 = PHY has 1.0 Vpp operating mode ability 0 = PHY does not have 1.0 Vpp operating mode ability

to,
1 = PHY has 2.4 Vpp operating mode ability, 0 = PHY does not have 2.4 Vpp operating mode ability

Cl 45 SC 45.2.1.174b.1 P 34 L 38 # 338
Graber, Steffen Pepperl+Fuchs GmbH

Comment Type E Comment Status D EZ

When read as one ...

SuggestedRemedy

When read as a one . (align with other text parts of Clause 45)

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Change from,
"When read as one"

to,
"When read as a one" on line 38

Change from,
"When read as zero"

to,
"When read as a zero" on line 39

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

Cl 45 SC 45.2.1.174b.2 P 34 L 40 # 296
 Graber, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status D AutoNeg

45.2.1.174b.2 1.0 Vpp operating mode ability (1.2295.12)
 When read as one, this bit indicates that the 10BASE-T1L PHY supports a transmit level of 1.0 Vpp. When read as a zero, this bit indicates that the 10BASE-T1L PHY does not support a transmit level of 1.0 Vpp.

SuggestedRemedy

45.2.1.174b.2 2.4 Vpp operating mode ability (1.2295.12)
 When read as one, this bit indicates that the 10BASE-T1L PHY supports a transmit level of 2.4 Vpp. When read as a zero, this bit indicates that the 10BASE-T1L PHY does not support a transmit level of 2.4 Vpp. (change 1.0 Vpp to 2.4 Vpp at three locations)

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Change from,
 45.2.1.174b.2 1.0 Vpp operating mode ability (1.2295.12)
 When read as a one, this bit indicates that the 10BASE-T1L PHY supports a transmit level of 1.0 Vpp. When read as a zero, this bit indicates that the 10BASE-T1L PHY does not support a transmit level of 1.0 Vpp.

to,
 45.2.1.174b.2 2.4 Vpp operating mode ability (1.2295.12)
 When read as one, this bit indicates that the 10BASE-T1L PHY supports a transmit level of 2.4 Vpp. When read as a zero, this bit indicates that the 10BASE-T1L PHY does not support a transmit level of 2.4 Vpp.

Cl 45 SC 45.2.1.174b.2 P 34 L 43 # 339
 Graber, Steffen Pepperl+Fuchs GmbH

Comment Type E Comment Status D EZ

When read as one ...

SuggestedRemedy

When read as a one . (align with other text parts of Clause 45)

Proposed Response Response Status W

PROPOSED ACCEPT.
 Change from,
 "When read as one"

to,
 "When read as a one" on line 43

Cl 45 SC 45.2.1.174b.5 P 35 L 11 # 340
 Graber, Steffen Pepperl+Fuchs GmbH

Comment Type E Comment Status D EZ

.. Is controlled using .

SuggestedRemedy

is controlled by using .

Proposed Response Response Status W

PROPOSED REJECT.
 "Controlled by using" doesn't show up at all in section 4 of 802.3-2015.

"Controlled using" shows up many times.

Cl 45 SC 45.2.1.174b.6 P 35 L 16 # 341
 Graber, Steffen Pepperl+Fuchs GmbH

Comment Type E Comment Status X EZ

When read as zero ...

SuggestedRemedy

When read as a zero . (align with other text parts of Clause 45)

Proposed Response Response Status W

PROPOSED ACCEPT.
 Change from,
 "When read as zero"

to,
 "When read as a zero"

Cl 45 SC 45.2.1.174b.6 P 35 L 16 # 342
 Graber, Steffen Pepperl+Fuchs GmbH

Comment Type E Comment Status X EZ

When read as one ...

SuggestedRemedy

When read as a one . (align with other text parts of Clause 45)

Proposed Response Response Status W

PROPOSED ACCEPT.
 Change from,
 "When read as one"

to,
 "When read as a one"

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

Cl 45 SC 45.2.1.174b.6 P 35 L 17 # 343
 Graber, Steffen Pepperl+Fuchs GmbH

Comment Type E Comment Status D EZ

. that the polarity of receiver is reversed.

SuggestedRemedy

. that the polarity of the receiver is reversed.

Proposed Response Response Status W

PROPOSED ACCEPT.

Change from,
 the polarity of receiver

to,
 the polarity of the receiver

Cl 45 SC 45.2.1.174d P 36 L 38 # 453
 Brandt, David Rockwell Automation

Comment Type T Comment Status D PMA Discuss

10BASE-T1S PMA control register lacks loopback

SuggestedRemedy

Copy: Table 45-142a, 1.2294.13,
 Insert in Table 45-142d as 1.2299.13.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Task Force to discuss. In draft 1.2, there is no 10BASE-T1S PMA loopback. It is referenced to be discussed in the Editor's note on page 149. If this comment is accepted, text needs to be added to clause 147 as well.

If accepted, change as proposed is to:

In Table 45-142d, change the reserved row from 1.2299.13:12 to 1.2299.12

Insert new bit after 1.2299.14

Bit(s): 1.2299.13

Name: Loopback ability

Description:

1 = PHY has loopback ability

0 = PHY has no loopback ability

R/W: RO

Cl 45 SC 45.2.1.174d P 37 L 11 # 454
 Brandt, David Rockwell Automation

Comment Type T Comment Status D PMA Discuss

10BASE-T1S PMA control register lacks loopback

SuggestedRemedy

Insert before 45.2.1.174d.2 and re-number rest of clause:

45.2.1.174d.2 Loopback (1.2299.13)

The 10BASE-T1S PMA shall be placed in loopback mode of operation when loopback bit 1.2299.13 is set to a one, and PLCA enable bit in MDIO register 3.2291.13 is set to a zero. When in loopback the 10BASE-T1S PMA shall accept data on the transmit path and return it on the receive path. The default value of bit 1.2299.13 is zero. Bit 1.2299.13 is a copy of 1.0.0 and setting or clearing either bit shall set or clear the other bit. Setting either bit shall enable loopback.

Proposed Response Response Status W

PROPOSED ACCEPT.

Task Force to discuss. In draft 1.2, there is no 10BASE-T1S PMA loopback. It is referenced to be discussed in the Editor's note on page 149. If this comment is accepted, text needs to be added to clause 147 as well.

If accepted, change as proposed is to:

Insert before 45.2.1.174d.2 Transmit disable (1.2299.14) and re-number rest of clause:

45.2.1.174d.2 Loopback (1.2299.13)

The 10BASE-T1S PMA shall be placed in loopback mode of operation when loopback bit 1.2299.13 is set to a one, and PLCA enable bit in MDIO register 3.2291.13 is set to a zero. When in loopback the 10BASE-T1S PMA shall accept data on the transmit path and return it on the receive path. The default value of bit 1.2299.13 is zero. Bit 1.2299.13 is a copy of 1.0.0 and setting or clearing either bit shall set or clear the other bit. Setting either bit shall enable loopback.

Cl 45 SC 45.2.1.174d.3 P 37 L 22 # 464
 Brandt, David Rockwell Automation

Comment Type E Comment Status D EZ

2 reference errors

SuggestedRemedy

Change 1.2294.11 to 1.2299.11, 2 places in paragraph.

Proposed Response Response Status W

PROPOSED ACCEPT.

Change1.2294.11 to 1.2299.11 in two locations in clause 45.2.1.174d.3

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

Cl 45 SC 45.2.1.174e P 38 L 9 # 455
Brandt, David Rockwell Automation

Comment Type T Comment Status D PMA Discuss

10BASE-T1S PMA status register lacks loopback

SuggestedRemedy

Copy: Table 45-142b, 1.2295.13,
Insert in Table 45-142e as 1.2300.13.

Proposed Response Response Status W

PROPOSED ACCEPT.

Task Force to discuss. In draft 1.2, there is no 10BASE-T1S PMA loopback. It is referenced to be discussed in the Editor's note on page 149. If this comment is accepted, text needs to be added to clause 147 as well.

In Table 45-142e, change the reserved row from 1.2300.15:12 to 1.2300.15:14

Insert new bit after reserved row 1.2300.15:14

Bit(s): 1.300.13

Name: Loopback ability

Description:

1 = PHY has loopback ability

0 = PHY has no loopback ability

R/W: RO

Insert new reserved row after new 1.300.13

Bit(s): 1.300.12

Name: Reserved

Description:

Value always 0

R/W: RO

Cl 45 SC 45.2.1.174e P 38 L 33 # 456
Brandt, David Rockwell Automation

Comment Type T Comment Status D PMA Discuss

10BASE-T1S PMA status register lacks loopback

SuggestedRemedy

Insert before 45.2.1.174e.1 and re-number:

45.2.1.174e.1 Loopback ability (1.2300.13)

When read as one, this bit indicates that the 10BASE-T1S PHY supports PMA loopback.

When read as

zero, this bit indicates that the 10BASE-T1S PHY does not support PMA loopback.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Task Force to discuss. In draft 1.2, there is no 10BASE-T1S PMA loopback. It is referenced to be discussed in the Editor's note on page 149. If this comment is accepted, text needs to be added to clause 147 as well.

Insert before 45.2.1.174e.1 10BASE-T1S OAM ability (1.2300.11) and re-number rest of clause:

45.2.1.174e.1 Loopback ability (1.2300.13)

When read as a one, this bit indicates that the 10BASE-T1S PHY supports PMA loopback.

When read as a zero, this bit indicates that the 10BASE-T1S PHY does not support PMA loopback.

Cl 45 SC 45.2.1.174h.1 P 41 L 31 # 465
Brandt, David Rockwell Automation

Comment Type E Comment Status D EZ

Wrong link

SuggestedRemedy

Change 147.5.2, text and link to 147.5.1

Proposed Response Response Status W

PROPOSED ACCEPT.

Change from,
147.5.2

to,
147.5.1

and update link

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

CI 45 SC 45.2.1.174i P 41 L 34 # 388
CORDARO, Jay BROADCOM

Comment Type TR Comment Status D Cable Diagnostics Discuss
Add PMA register for Cable Diagnostics Control (1.2304)

SuggestedRemedy

Bit(s)	Name	Description	R/Wa
2	Cable Diagnostics Control Mode	1= Through 0= Reflection	RW
1	Cable Diagnostics Control	1= Cable Diagnostics on 0= Cable diagnostics off	RW
0	Cable Diagnostics Supported	1= Cable Diagnostics Supported 0= Cable Diagnostics not Supported	RO

Proposed Response Response Status W
PROPOSED ACCEPT IN PRINCIPLE.

Task Force to discuss along with presentation. Consider after comment #389 is resolved.

If accepted, change as proposed is to:

Insert Table 45-142i - Cable diagnostics control register bit definitions on line 36

Bit(s): 1.2304.15:3
Name: Reserved
Description:
Value always 0
R/W^a: RO

Bit(s): 1.2304.2
Name: Cable diagnostics control mode
Description:
1 = Through
0 = Reflection
R/W^a: RW

Bit(s): 1.2304.1
Name: Cable diagnostics control
Description:
1 = Cable diagnostics on
0 = Cable diagnostics off
R/W^a: RW

Bit(s): 1.2304.0
Name: Cable diagnostics supported
Description:
1 = Cable diagnostics supported
0 = Cable diagnostics not supported

R/W^a: RO

Bottom table row: ^aRO = Read only, R/W = Read/Write

CI 45 SC 45.2.1.174i.1 P 41 L 36 # 389
CORDARO, Jay BROADCOM

Comment Type TR Comment Status D Cable Diagnostics Discuss
Add description for Cable Diagnostics Control

SuggestedRemedy

When supported, if bit 1 is set to '1', normal opertaion is suspended and a cable diagnostics signal is passed to the PMA consisting of the following: 16 bit times where PMD drives a differential voltage of 0 V or high impedance then 16 bit times where a Ga32 SYNC word is transmitted then 16 bit times where the PMD drives a differential voltage of 0 V or high impedance, then a 16 bit time Gb32 BEACON word, followed finally by 16 bit times where the PMD drives a differential voltage of 0 V or high impedance.

Proposed Response Response Status W
PROPOSED ACCEPT IN PRINCIPLE.

Task Force to discuss along with presentation. Consider after comment #389 is resolved.

If accepted, change as proposed is to:

If comment #388 is accepted, insert new clause after new Table 45-142i,

45.2.1.174i.1 Cable diagnostics control (1.2304.2:0)
When supported, if bit 1 is set to '1', normal opertaion is suspended and a cable diagnostics signal is passed to the PMA consisting of the following: 16 bit times where PMD drives a differential voltage of 0 V or high impedance then 16 bit times where a Ga32 SYNC word is transmitted then 16 bit times where the PMD drives a differential voltage of 0 V or high impedance, then a 16 bit time Gb32 BEACON word, followed finally by 16 bit times where the PMD drives a differential voltage of 0 V or high impedance.

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

CI 45 SC 45.2.1.174j P 41 L 38 # 390
CORDARO, Jay BROADCOM

Comment Type TR Comment Status X Cable Diagnostics Discuss

Add Registers for Reflection Cable Diagnostics status (1.2305)

SuggestedRemedy

Reflection Cable Diagnostics status

Bit(s) | Name | Description | R/Wa

15:8 | distance to first reflection in tenths of meter | RO

3:0 | Reflection Cable Diagnostics Status | 111 = cable status indeterminate | RO
110 = one wire shorted to ground or voltage

101 =one wire open

100 = reserved

011 = high impedance

010 = cable wires shorted

001 = cable open/high impedance

000 = normal cable

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Task Force to discuss along with presentation. Consider after comment #389 is resolved.

If accepted, change as proposed is to:

Insert Table 45-142j - Reflection cable diagnostics status register bit definitions after new clause 45.2.1.174i.1 Cable diagnostics control (1.2304.2:0)

Bit(s): 1.2305.15:8

Name: Distance to first reflection in tenths of meter

Description:

R/W^a: RO

Bit(s): 1.2305.7:3

Name: Reserved

Description:

Value always 0

R/W^a: RO

Bit(s): 1.2305.2:0

Name: Cable diagnostics control

Description:

111 = cable status indeterminate

110 = one wire shorted to ground or voltage

101 =one wire open

100 = reserved

011 = high impedance

010 = cable wires shorted

001 = cable open/high impedance

000 = normal cable

R/W^a: RO

Bottom table row: ^aRO = Read only

Insert new clauses after new Table 45-142j,

45.2.1.174.j.1 Distance to first reflection in tenths of meter (1.2305.15:18)

Bits 15:8 indicate the distance to first reflection in tenths of meter (TBD).

45.2.1.174.j.2 Cable diagnostics control (1.2305.2:0)

Bits 2:0 indicate the electrical status of the cable (TBD).

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

CI 45 SC 45.2.1.174k P 41 L 40 # 391
CORDARO, Jay BROADCOM

Comment Type TR Comment Status D Cable Diagnostics Discuss
Add Registers for Transmission Cable Diagnostics status (1.2305)

SuggestedRemedy

Through Cable Diagnostics status
Bit(s) | Name | Description | R/Wa
15:10 | Reserved
9 | Cable Diagnostic Through Polarity | 1 = Polarity flipped from transmit node to receive node
0 = Polarity not flipped from transmit node to receive node
8:3 | Cable Diagnostic through Peak | 64 = highest | RO
...
0 = lowest
2:0 | Estimated Signal Quality Index (SQI) | 111 = SQI = 7 (Best) | RO
110 =
101 =
100 =
011 =
010 =
001 =
000 = SQi = 0 (worst)

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Task Force to discuss along with presentation.Consider after comment #389 is resolved.

If accepted, change as proposed is to:

Insert Table 45-142k - Through cable diagnostics status register bit definitions after new clause 45.2.1.174.j.2 Cable diagnostics control (1.2305.2:0)

Bit(s): 1.2306.15:10
Name: Reserved
Description:
Value always 0
R/W^a: RO

Bit(s): 1.2306.9
Name: Cable diagnostic through polarity
Description:
1 = Polarity flipped from transmit node to receive node
0 = Polarity not flipped from transmit node to receive node
R/W^a: RO

Bit(s): 1.2306.8:3
Name: Cable diagnostics through peak
Description:
64 = highest
0 = lowest
R/W^a: RO

Bit(s): 1.2306.2:0
Name: Estimated signal quality index (SQI)
Description:
111 = SQI = 7 (best)
110 = SQI = 6
101 = SQI = 5
100 = SQI = 4
011 = SQI = 3
010 = SQI = 2
001 = SQI = 1
000 = SQI = 0 (worst)
R/W^a: RO

Bottom table row: ^aRO = Read only

CI 45 SC 45.2.1.174k P 41 L 42 # 392
CORDARO, Jay BROADCOM

Comment Type T Comment Status D Cable Diagnostics Discuss
Add description for Transmission Cable Diagnostics status polarity (1.2305.9)

SuggestedRemedy

Bit 9 indicates if the polarity of the wiring between the transmit and received node is flipped during a through cable diagnostic measurement.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Task Force to discuss along with presentation. Consider after comment #389 is resolved.

If accepted, change as proposed is to:

If comment #391 is accepted, insert new clause after new Table 45-142k,

45.2.1.174.k.1 Cable diagnostic through polarity (1.2306.9)
Bit 9 indicates if the polarity of the wiring between the transmit and received node is flipped during a through cable diagnostic measurement.

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

Cl 45 **SC 45.2.1.174k** **P 41** **L 44** # **393**
CORDARO, Jay BROADCOM

Comment Type T **Comment Status X** **Cable Diagnostics Discuss**

Add description for Transmission Cable Diagnostics estimated correlation peak (1.2305.8:3)

SuggestedRemedy

Bits 8:3 list the correlation peak measured during a through measurement. This indicates the attenuation

Proposed Response **Response Status W**

PROPOSED ACCEPT IN PRINCIPLE.

Task Force to discuss along with presentation. Consider after comment #389 is resolved.

If accepted, change as proposed is to:

If comment #391 is accepted, insert new clause after new 45.2.1.174.k.1 Cable diagnostic through polarity (1.2306.9),

45.2.1.174.k.2 Cable diagnostics through peak (1.2306.8:3)

Bits 8:3 list the correlation peak measured during a through measurement. This indicates the attenuation.

Cl 45 **SC 45.2.1.174k** **P 41** **L 46** # **394**
CORDARO, Jay BROADCOM

Comment Type T **Comment Status X** **Cable Diagnostics Discuss**

Add description for Transmission Cable Diagnostics Estimated Signal Quality Index (1.2305.2:0)

SuggestedRemedy

Bits 2:0 list the estimated signal quality index for the through cable diagnostic from the transmitted node to the received node based upon the cable diagnostic signal. The estimated signal quality index can be derived by taking the L2 norm of the received cable diagnostics signal. The estimated signal quality may be measured periodically over the lifetime of the harness to determine harness aging and degradation.

Proposed Response **Response Status W**

PROPOSED ACCEPT IN PRINCIPLE.

Task Force to discuss along with presentation. Consider after comment #389 is resolved.

If accepted, change as proposed is to:

If comment #391 is accepted, insert new clause after new 45.2.1.174.k.2 Cable diagnostics through peak (1.2306.8:3),

45.2.1.174.k.3 Estimated signal quality index (SQI) (1.2306.2:0)

Bits 2:0 list the estimated signal quality index for the through cable diagnostic from the transmitted node to the received node based upon the cable diagnostic signal. The estimated signal quality index can be derived by taking the L2 norm of the received cable diagnostics signal. The estimated signal quality may be measured periodically over the lifetime of the harness to determine harness aging and degradation.

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

CI 45 SC 45.2.3.58c P 45 L 8 # 458
Brandt, David Rockwell Automation

Comment Type T Comment Status D PLCA
10BASE-T1S PCS control register lacks "PLCA enable" bit and status register lacks "PLCA ability" bit

SuggestedRemedy

Insert in Table 45-220c:

Bit(s): 3.2291.13
Name: PLCA enable
Description: 1 = Enable PLCA mode
0 = Disable PLCA mode
R/W: R/W

Insert in Table 45-220d:

Bit(s): 3.2292.13
Name: PLCA ability
Description: 1 = Supports PLCA mode
0 = Does not support PLCA mode
R/W: R/O

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE. In Table 45-220c, change the reserved row from 3.2291.13:0 to 3.2291.12:0

Insert new bit after row 3.2291.14 Loopback

Bit(s): 3.2291.13
Name: PLCA enable
Description:
1 = Enable PLCA mode
0 = Disable PLCA mode
R/W: R/W

In Table 45-220d, change the reserved row from 3.2292.15:12 to 3.2292.15:14

Insert new bit after new reserved row 3.2292.15:14

Bit(s): 3.2292.13
Name: PLCA ability
Description:
1 = Supports PLCA mode
0 = Does not support PLCA mode
R/W: RO

Insert new reserved row after new 3.2292.13 PLCA ability

Bit(s): 3.2292.12
Name: Reserved

Description:
Value always 0
R/W: RO

CI 45 SC 45.2.3.58c P 45 L 35 # 460
Brandt, David Rockwell Automation

Comment Type T Comment Status D PLCA
10BASE-T1S PCS control register lacks "PLCA reset" bit

SuggestedRemedy

Insert:

45.2.3.58c.4 PLCA reset (3.2291.12)

Resetting the 10BASE-T1S PCS PLCA state is accomplished by setting bit 3.2291.12 to a one. As a consequence, this action may change the internal state of the 10BASE-T1S PCS and the state of the physical link. This bit is self-clearing, and the 10BASE-T1S PCS shall return a value of one in bit 3.2291.12 when a PLCA reset is in progress; otherwise, it shall return a value of zero.

NOTE-This operation may interrupt data communication.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

If comment #458 is accepted, insert new clause after new 45.2.3.58c.3 PLCA enable (3.2291.13)

45.2.3.58c.4 PLCA reset (3.2291.12)

Resetting the 10BASE-T1S PCS PLCA state is accomplished by setting bit 3.2291.12 to a one. As a consequence, this action may change the internal state of the 10BASE-T1S PCS and the state of the physical link. This bit is self-clearing, and the 10BASE-T1S PCS shall return a value of one in bit 3.2291.12 when a PLCA reset is in progress; otherwise, it shall return a value of zero.

NOTE-This operation may interrupt data communication.

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

CI 45 SC 45.2.3.58c P 45 L 35 # 459
Brandt, David Rockwell Automation

Comment Type T Comment Status X PLCA

10BASE-T1S PCS control register lacks "PLCA enable" bit

SuggestedRemedy

Insert:

45.2.3.58c.3 PLCA enable (3.2291.13)

The 10BASE-T1S PCS shall be placed in PLCA mode of operation when bit 3.2291.13 is set to a one.

The default value of bit 3.2291.13 is zero.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

If comment #458 is accepted, insert new clause after 45.2.3.58c.2 Loopback (3.2291.14)

45.2.3.58c.3 PLCA enable (3.2291.13)

The 10BASE-T1S PCS shall be placed in PLCA mode of operation when bit 3.2291.13 is set to a one. The default value of bit 3.2291.13 is zero.

CI 45 SC 45.2.3.58g P 45 L 39 # 382
CORDARO, Jay BROADCOM

Comment Type TR Comment Status D OAM Discuss

Delete OAM registers 3.2296,3.2297,3.3.2298

SuggestedRemedy

Delete OAM registers 3.2296,3.2297,3.3.2298 from Table Table 45-220g

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Task Force to discuss retaining OAM but cutting it to one register. Currently, there is no OAM channel in clause 147.

Editor proposes to delete entire register.

Note: Change as proposed is to:

If comment #383 is accepted, delete the rows for the following bits from Table 45-220g:

3.2296.15:8
3.2296.7:0
3.2297.15:8
3.2297.7:0
3.2298.15:8
3.2298.7:0

CI 45 SC 45.2.3.58d P 45 L 41 # 462
Brandt, David Rockwell Automation

Comment Type T Comment Status D PLCA

10BASE-T1S PCS status register lacks PLCA ability bit

SuggestedRemedy

Insert before 45.2.3.58d.1 and re-number:

45.2.3.58d.1 PLCA ability (1.2292.13)

When read as one, this bit indicates that the 10BASE-T1S PHY supports PLCA. When read as zero, this bit indicates that the 10BASE-T1S PHY does not support PLCA.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE. Insert new clause before 45.2.3.58d.1 Tx LPI received (3.2292.11) and re-number subsequent clauses.

45.2.3.58d.1 PLCA ability (1.2292.13)

When read as a one, this bit indicates that the 10BASE-T1S PHY supports PLCA. When read as a zero, this bit indicates that the 10BASE-T1S PHY does not support PLCA.

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

Cl 45 SC 45.2.3.58e.1 P 47 L 35 # 466
 Brandt, David Rockwell Automation
 Comment Type T Comment Status D EZ
 Missing definition
 SuggestedRemedy
 PCS_status is not defined in 147.3.7.1, nor anywhere else in the draft.
 Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.
 Delete,
 This bit is a reflection of the PCS_status variable defined in 147.3.7.1.

Cl 45 SC 45.2.3.58e.2 P 47 L 41 # 467
 Brandt, David Rockwell Automation
 Comment Type T Comment Status D EZ
 Missing definition
 SuggestedRemedy
 hi_rfer is not defined in 147.3.7.1, nor anywhere else in the draft.
 Proposed Response Response Status W
 PROPOSED ACCEPT.
 Delete.
 This bit is a reflection of the state of the hi_rfer variable defined in 147.3.7.1.

Cl 45 SC 45.2.3.58e.3 P 47 L 47 # 468
 Brandt, David Rockwell Automation
 Comment Type T Comment Status D EZ
 Missing definition
 SuggestedRemedy
 block_lock is not defined in 147.3.7.1, nor anywhere else in the draft.
 Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.
 Delete,
 This bit is a reflection of the state of the block_lock variable defined in 147.3.7.1.

Cl 45 SC 45.2.3.58e.6 P 48 L 14 # 469
 Brandt, David Rockwell Automation
 Comment Type T Comment Status D EZ
 Missing definition
 SuggestedRemedy
 RFER_count is not defined in 147.3.7.2, nor anywhere else in the draft.
 Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.
 Delete,
 The BER counter formed by bits 3.2293.5:0 is a six bit count as defined by RFER_count in 147.3.7.2.

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

Cl 45 SC 45.2.3.58g P 50 L 27 # 383
CORDARO, Jay BROADCOM

Comment Type TR Comment Status D OAM Discuss

Delete OAM registers 3.2296,3.2297,3.3.2298

SuggestedRemedy

45.2.3.58g 10BASE-T1S OAM message register (Register 3.2295)
The 10BASE-T1S OAM message register contains the 2 octet 10BASE-T1S OAM message data to be transmitted.
The 8 octet message data is user defined and its definition is outside the scope of this standard. See Table 45-220g.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Task Force to discuss retaining OAM but cutting it to one register. Currently, there is no OAM channel in clause 147.

Editor proposes to delete entire register.

Note: Change as proposed is to:

In clause title, change from,
(Registers 3.2295 to 3.2298)

to,
(Register 3.2295)

On line 29, change from,
8 octet 10BASE-T1S OAM

to,
2 octet 10BASE-T1S OAM

Cl 45 SC 45.2.3.58i P 51 L 1 # 386
CORDARO, Jay BROADCOM

Comment Type TR Comment Status D OAM Discuss

Change Table 45-220h- to Table 45-220i (swap positions of these tables in the document) and take out OAM registers for messages 2-6 so it looks like:

SuggestedRemedy

Bit(s) |Name | Description | R/Wa
3.2300.15:8 |Link partner 10BASE-T1S OAM message 1 |Message octet 1. LSB received first. | RO
3.2300.7:0 |Link partner 10BASE-T1S OAM message 0 |Message octet 0. LSB received first. RO

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Task Force to discuss retaining OAM but cutting it to one register. Currently, there is no OAM channel in clause 147.

Editor proposes to delete entire register.

Note: Change as proposed is to:

If comment #385 is accepted, delete the rows for the following bits from Table 45-220h:

3.2301.15:8
3.2301.7:0
3.2302.15:8
3.2302.7:0
3.2303.15:8
3.2303.7:0

Swap positions of Table 45-220h, 45.2.3.58h, 45.2.3.58h.1, 45.2.3.58h.2, 45.2.3.58h.3, and 45.2.3.58h.4 with Table 45-220i and 45.2.3.58i and re-number.

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

CI 45 SC 45.2.3.58h P 51 L 24 # 385
CORDARO, Jay BROADCOM

Comment Type TR Comment Status D OAM Discuss

Change description for 45.2.3.58h.1

SuggestedRemedy

Bit 3.2299.15 shall be set to one when the 10BASE-T1S OAM message from the link partner is stored into registers 3.2300 and the message number in 3.2299.11:8. This register shall be cleared when register 3.2303 is read.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Task Force to discuss retaining OAM but cutting it to one register. Currently, there is no OAM channel in clause 147.

Editor proposes to delete entire register.

Note: Change as proposed is to:

In clause 45.2.3.58h.1 Link partner 10BASE-T1S OAM message valid (3.2299.15) replace,

is stored into registers 3.2300, 3.2301, 3.2302, and 3.2303

with,

is stored into registers 3.2300

CI 45 SC 45.2.3.58i P 51 L 44 # 387
CORDARO, Jay BROADCOM

Comment Type TR Comment Status D OAM Discuss

Change text to read as follows:

SuggestedRemedy

45.2.3.58i Link partner 10BASE-T1S OAM message register (Register 3.2300)
The link partner 10BASE-T1S OAM message register contains the 2 octet 10BASE-T1S OAM message data from the link partner. Bit 3.2299.15 shall be cleared when register 3.2303 is read. The assignment of bits in the Link partner 10BASE-T1S OAM message register bit is shown in Table 45-220i

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Task Force to discuss retaining OAM but cutting it to one register. Currently, there is no OAM channel in clause 147.

Editor proposes to delete entire register.

Note: Change as proposed is to:

If comment #385 is accepted, in clause title, change from,
(Registers 3.2300 to 3.2303)

to,
(Register 3.2300)

On line 46, change from,
8 octet 10BASE-T1S OAM

to,
2 octet 10BASE-T1S OAM message

Add a period at the end of the sentence on line 48.

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

CI 45 SC Table 45-220i- P 52 L 1 # 384
CORDARO, Jay BROADCOM

Comment Type TR Comment Status D OAM Discuss
(editorial) Table 45-220i- Change table to 45-220h (swap this table's position with table 45-220h) & (technical) Change description for register 15 to following

SuggestedRemedy

3.2299.15 Link partner 10BASE-T1S OAM message valid
This bit is used to indicate message data in registers
3.2299.11:8, 3.2300, are stored and ready to be read.
This bit shall self clear when register 3.2317 is read.
1 = Message data in registers are valid
0 = Message data in registers are not valid
RO, SC

Proposed Response Response Status W
PROPOSED ACCEPT IN PRINCIPLE.

Task Force to discuss retaining OAM but cutting it to one register. Currently, there is no OAM channel in clause 147.

Editor proposes to delete entire register.

Note: Change as proposed is to:

If comment #385 is accepted, replace the row for 3.2299.15 in original Table 45-220i as follows:

Bit(s): 3.2299.15
Name: Link partner 10BASE-T1S OAM message valid
Description: This bit is used to indicate message data in registers
3.2299.11:8, 3.2300, are stored and ready to be read. This bit shall self clear when register 3.2317 is read.
1 = Message data in registers are valid
0 = Message data in registers are not valid
R/W^a: RO, SC

CI 45 SC 45.5 P 53 L 1 # 401
Zimmerman, George CME Consulting et al

Comment Type E Comment Status D EZ
PICS for clause 45 need completing

SuggestedRemedy

PICS editor to fill in from changes in clause 45

Proposed Response Response Status W
PROPOSED ACCEPT.

Chief Editor to coordinate with Curtis Donahue to develop PICS for clause 45.

CI 78 SC 78 P 55 L 1 # 344
Graber, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status D EEE
EEE Timing Parameters missing

SuggestedRemedy

Please replace chapter by text being provided in "Energy Efficient Ethernet.pdf" (see also presentation "10BASE-T1L Energy Efficient Ethernet.pdf").

Proposed Response Response Status W
PROPOSED ACCEPT IN PRINCIPLE.
Task Force to review presentation.

Incorporate text, except for entry for 10BASE-T1S in Table 78-1.

CI 78 SC 78.1.4 P 55 L 4 # 402
Zimmerman, George CME Consulting et al

Comment Type T Comment Status D EEE
10BASE-T1L needs to be defined for EEE as per the objectives. (10BASE-T1S is naturally EEE)

SuggestedRemedy

Bring 78.1.4 and Table 78-1 into draft, and insert 10BASE-T1L , clause 146 as new first (content) row, above 10BASE-Te. Bring 78.2 and Table 78-2 into draft, and new first row for 10BASE-T1L (leave values TBD for now). Similarly, bring 78.5 and Table 78-4 into draft and insert new first row for 10BASE-T1L with values TBD.

Proposed Response Response Status W
PROPOSED ACCEPT IN PRINCIPLE.
Resolved by comment 344

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

Cl 98 SC 98.2.1.1.2 P 55 L 15 # 470
 Brandt, David Rockwell Automation
 Comment Type E Comment Status D AutoNeg
 Undefined terms "in high speed mode" and "in low speed mode"
 SuggestedRemedy
 "for 100BASE-T1 or 1000BASE-T1" and "for 10BASE-T1L and 10BASE-T1S in half-duplex"
 Proposed Response Response Status W
 PROPOSED REJECT.
 Terms are used and defined throughout the changed text.

Cl 98 SC 98.5.2 P 58 L 34 # 297
 Graber, Steffen Pepperl+Fuchs GmbH
 Comment Type T Comment Status D AutoNeg_timers
 backoff_timer
 SuggestedRemedy
 backoff_timer_[HSM] (reference that this timer is used in high speed Auto-Negotiation mode)
 Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.
 Change "backoff_timer" to "backoff_timer_[HSM]" and update subsequent text and state diagram references.
 Task Force to discuss nomenclature of all AutoNeg_timers comments

Cl 98 SC 98.5.2 P 58 L 37 # 346
 Graber, Steffen Pepperl+Fuchs GmbH
 Comment Type E Comment Status X EZ
 If T[4] bit is 0 then the timer duration is set as .
 SuggestedRemedy
 If T[4] bit is 0, then the timer duration will be set as . (add comma and use will be instead of is)
 Proposed Response Response Status W
 Change "If T[4] bit is 0 then the timer duration is set as" to "If T[4] is 0, the timer duration is"

Cl 98 SC 98.5.2 P 58 L 37 # 345
 Graber, Steffen Pepperl+Fuchs GmbH
 Comment Type E Comment Status D EZ
 If T[4] bit is 1 then the timer duration is set as .
 SuggestedRemedy
 If T[4] bit is 1, then the timer duration will be set as . (add comma and use will be instead of is)
 Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.
 Change "If T[4] bit is 1 then the timer duration is set as" to "If T[4] is 1, the timer duration is"

Cl 98 SC 98.5.2 P 58 L 44 # 194
 Graber, Steffen Pepperl+Fuchs GmbH
 Comment Type T Comment Status D AutoNeg_timers
 blind_timer
 SuggestedRemedy
 blind_timer_[HSM] (reference that this timer is used in high speed Auto-Negotiation mode)
 Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.
 Change "blind_timer" to "blind_timer_[HSM]" and update subsequent text and state diagram references.
 Task Force to discuss nomenclature of all AutoNeg_timers comments

Cl 98 SC 98.5.2 P 58 L 47 # 196
 Graber, Steffen Pepperl+Fuchs GmbH
 Comment Type T Comment Status D AutoNeg_timers
 clock_detect_max_timer
 SuggestedRemedy
 clock_detect_max_timer_[HSM] (reference that this timer is used in high speed Auto-Negotiation mode)
 Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.
 Change "clock_detect_max_timer" to "clock_detect_max_timer_[HSM]" and update subsequent text and state diagram references.
 Task Force to discuss nomenclature of all AutoNeg_timers comments

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

Cl 98 SC 98.5.2 P 58 L 47 # 195
Graber, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status D AutoNeg_timers
break_link_timer

SuggestedRemedy

break_link_timer_[HSM] (reference that this timer is used in high speed Auto-Negotiation mode)

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.
Change "break_link_timer" to "break_link_timer_[HSM]" and update subsequent text and state diagram references.

Task Force to discuss nomenclature of all AutoNeg_timers comments

Cl 98 SC 98.5.2 P 59 L 1 # 197
Graber, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status D AutoNeg_timers
clock_detect_min_timer

SuggestedRemedy

clock_detect_min_timer_[HSM] (reference that this timer is used in high speed Auto-Negotiation mode)

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.
Change "clock_detect_min_timer" to "clock_detect_min_timer_[HSM]" and update subsequent text and state diagram references.

Task Force to discuss nomenclature of all AutoNeg_timers comments

Cl 98 SC 98.5.2 P 59 L 5 # 198
Graber, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status D AutoNeg_timers
data_detect_max_timer

SuggestedRemedy

data_detect_max_timer_[HSM] (reference that this timer is used in high speed Auto-Negotiation mode)

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.
Change "..._timer" to "..._timer_[HSM]" and update subsequent text and state diagram references.

Task Force to discuss nomenclature of all AutoNeg_timers comments

Cl 98 SC 98.5.2 P 59 L 10 # 199
Graber, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status D AutoNeg_timers
data_detect_min_timer

SuggestedRemedy

data_detect_min_timer_[HSM] (reference that this timer is used in high speed Auto-Negotiation mode)

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.
Change "..._timer" to "..._timer_[HSM]" and update subsequent text and state diagram references.

Task Force to discuss nomenclature of all AutoNeg_timers comments

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

Cl 98	SC 98.5.2	P 59	L 15	# 200
Graber, Steffen		Pepperl+Fuchs GmbH		
Comment Type T	Comment Status D		AutoNeg_timers	
interval_timer				
SuggestedRemedy				
interval_timer_[HSM] (reference that this timer is used in high speed Auto-Negotiation mode)				
Proposed Response	Response Status W			
PROPOSED ACCEPT IN PRINCIPLE. Change "..._timer" to "..._timer_[HSM]" and update subsequent text and state diagram references.				
Task Force to discuss nomenclature of all AutoNeg_timers comments				

Cl 98	SC 98.5.2	P 59	L 19	# 201
Graber, Steffen		Pepperl+Fuchs GmbH		
Comment Type T	Comment Status D		AutoNeg	
link_fail_inhibit_timer				
SuggestedRemedy				
Remove this timer, the explanation, and the associated note (lines 19 to 27) from this position of the document (as this timer is not depending on high speed or low speed autoneg mode, but on the selected PHY type and the associated training time, it will be reapplied to another position of the document by a later comment)				
Proposed Response	Response Status W			
PROPOSED ACCEPT.				

Cl 98	SC 98.5.2	P 59	L 28	# 202
Graber, Steffen		Pepperl+Fuchs GmbH		
Comment Type T	Comment Status D		AutoNeg_timers	
page_test_max_timer				
SuggestedRemedy				
page_test_max_timer_[HSM] (reference that this timer is used in high speed Auto-Negotiation mode)				
Proposed Response	Response Status W			
PROPOSED ACCEPT IN PRINCIPLE. Change "..._timer" to "..._timer_[HSM]" and update subsequent text and state diagram references.				
Task Force to discuss nomenclature of all AutoNeg_timers comments				

Cl 98	SC 98.5.2	P 59	L 32	# 203
Graber, Steffen		Pepperl+Fuchs GmbH		
Comment Type T	Comment Status D		AutoNeg_timers	
receive_DME_timer				
SuggestedRemedy				
receive_DME_timer_[HSM] (reference that this timer is used in high speed Auto-Negotiation mode)				
Proposed Response	Response Status W			
PROPOSED ACCEPT IN PRINCIPLE. Change "..._timer" to "..._timer_[HSM]" and update subsequent text and state diagram references.				
Task Force to discuss nomenclature of all AutoNeg_timers comments				

Cl 98	SC 98.5.2	P 59	L 35	# 204
Graber, Steffen		Pepperl+Fuchs GmbH		
Comment Type T	Comment Status D		AutoNeg_timers	
rx_wait_timer				
SuggestedRemedy				
rx_wait_timer_[HSM] (reference that this timer is used in high speed Auto-Negotiation mode)				
Proposed Response	Response Status W			
PROPOSED ACCEPT IN PRINCIPLE. Change "..._timer" to "..._timer_[HSM]" and update subsequent text and state diagram references.				
Task Force to discuss nomenclature of all AutoNeg_timers comments				

Cl 98	SC 98.5.2	P 59	L 40	# 205
Graber, Steffen		Pepperl+Fuchs GmbH		
Comment Type T	Comment Status D		AutoNeg_timers	
silent_timer				
SuggestedRemedy				
silent_timer_[HSM] (reference that this timer is used in high speed Auto-Negotiation mode)				
Proposed Response	Response Status W			
PROPOSED ACCEPT IN PRINCIPLE. Change "..._timer" to "..._timer_[HSM]" and update subsequent text and state diagram references.				
Task Force to discuss nomenclature of all AutoNeg_timers comments				

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

CI 98 SC 98.5.2 P 59 L 45 # 206
 Graber, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status D AutoNeg_timers
 backoff_timer

SuggestedRemedy
 backoff_timer_[LSM] (reference that this timer is used in low speed Auto-Negotiation mode)

Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.
 Change "..._timer" to "..._timer_[LSM]" and update subsequent text and state diagram references.

Task Force to discuss nomenclature of all AutoNeg_timers comments

CI 98 SC 98.5.2 P 59 L 48 # 347
 Graber, Steffen Pepperl+Fuchs GmbH

Comment Type E Comment Status D EZ
 If T[4] bit is 1 then the timer duration is set as .

SuggestedRemedy
 If T[4] bit is 1, then the timer duration will be set as . (add comma and use will be instead of is)

Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.
 Change "If T[4] bit is 1 then the timer duration is set as" to
 "If T[4] is 1, the timer duration is"

CI 98 SC 98.5.2 P 59 L 48 # 207
 Graber, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status D AutoNeg
 If T[4] bit is 1 then the timer duration is set as (145712 ns to 148912 ns) + (random integer from 0 to 15) × (18728 ns to 19788 ns).
 If T[4] bit is 0 then the timer duration is set as (155341 ns to 158541 ns) + (random integer from 0 to 15) × (18728 ns to 19788 ns).

SuggestedRemedy
 If T[4] bit is 1 then the timer duration is set as (145668 ns to 148868 ns) + (random integer from 0 to 15) × (20868 ns to 24068 ns).
 If T[4] bit is 0 then the timer duration is set as (156902 ns to 160102 ns) + (random integer from 0 to 15) × (20868 ns to 24068 ns). (see presentation "10BASE-T1L Auto-Negotiation")

Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE. Change "If T[4] bit is 1 then the timer duration is set as (145712 ns to 148912 ns) + (random integer from 0 to 15) × (18728 ns to 19788 ns).
 If T[4] bit is 0 then the timer duration is set as (155341 ns to 158541 ns) + (random integer from 0 to 15) × (18728 ns to 19788 ns)."
 to
 "If T[4] is 1, the timer duration is (145668 ns to 148868 ns) + (random integer from 0 to 15) × (20868 ns to 24068 ns).
 If T[4] is 0, the timer duration is (156902 ns to 160102 ns) + (random integer from 0 to 15) × (20868 ns to 24068 ns).

CI 98 SC 98.5.2 P 59 L 50 # 348
 Graber, Steffen Pepperl+Fuchs GmbH

Comment Type E Comment Status D EZ
 If T[4] bit is 0 then the timer duration is set as .

SuggestedRemedy
 If T[4] bit is 0, then the timer duration will be set as . (add comma and use will be instead of is)

Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE. Change "If T[4] bit is 0 then the timer duration is set as" to
 "If T[4] is 0, the timer duration is"

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

CI 98 SC 98.5.2 P 60 L 1 # 208
 Graber, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status D AutoNeg_timers
 blind_timer

SuggestedRemedy
 blind_timer_[LSM] (reference that this timer is used in low speed Auto-Negotiation mode)

Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.
 Change "..._timer" to "..._timer_[LSM]" and update subsequent text and state diagram references.

Task Force to discuss nomenclature of all AutoNeg_timers comments

CI 98 SC 98.5.2 P 60 L 3 # 209
 Graber, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status D AutoNeg
 18728 ns

SuggestedRemedy
 20868 ns (see presentation "10BASE-T1L Auto-Negotiation")

Proposed Response Response Status W
 PROPOSED ACCEPT.

CI 98 SC 98.5.2 P 60 L 5 # 210
 Graber, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status D AutoNeg_timers
 break_link_timer

SuggestedRemedy
 break_link_timer_[LSM] (reference that this timer is used in low speed Auto-Negotiation mode)

Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.
 Change "..._timer" to "..._timer_[LSM]" and update subsequent text and state diagram references.

Task Force to discuss nomenclature of all AutoNeg_timers comments

CI 98 SC 98.5.2 P 60 L 6 # 211
 Graber, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status D AutoNeg
 The timer shall expire TBD μ s to TBD μ s after being started.

SuggestedRemedy
 The timer shall expire 300 μ s to 305 μ s after being started. (see presentation "10BASE-T1L Auto-Negotiation")

Proposed Response Response Status W
 PROPOSED ACCEPT.

CI 98 SC 98.5.2 P 60 L 9 # 212
 Graber, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status D AutoNeg_timers
 clock_detect_max_timer

SuggestedRemedy
 clock_detect_max_timer_[LSM] (reference that this timer is used in low speed Auto-Negotiation mode)

Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.
 Change "..._timer" to "..._timer_[LSM]" and update subsequent text and state diagram references.

Task Force to discuss nomenclature of all AutoNeg_timers comments

CI 98 SC 98.5.2 P 60 L 13 # 213
 Graber, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status D AutoNeg_timers
 clock_detect_min_timer

SuggestedRemedy
 clock_detect_min_timer_[LSM] (reference that this timer is used in low speed Auto-Negotiation mode)

Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.
 Change "..._timer" to "..._timer_[LSM]" and update subsequent text and state diagram references.

Task Force to discuss nomenclature of all AutoNeg_timers comments

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

CI 98 SC 98.5.2 P 60 L 16 # 214
 Graber, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status D AutoNeg_timers
 data_detect_max_timer

SuggestedRemedy
 data_detect_max_timer_[LSM] (reference that this timer is used in low speed Auto-Negotiation mode)

Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.
 Change "..._timer" to "..._timer_[LSM]" and update subsequent text and state diagram references.

Task Force to discuss nomenclature of all AutoNeg_timers comments

CI 98 SC 98.5.2 P 60 L 22 # 215
 Graber, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status D AutoNeg_timers
 data_detect_min_timer

SuggestedRemedy
 data_detect_min_timer_[LSM] (reference that this timer is used in low speed Auto-Negotiation mode)

Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.
 Change "..._timer" to "..._timer_[LSM]" and update subsequent text and state diagram references.

Task Force to discuss nomenclature of all AutoNeg_timers comments

CI 98 SC 98.5.2 P 60 L 27 # 216
 Graber, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status D AutoNeg_timers
 interval_timer

SuggestedRemedy
 interval_timer_[LSM] (reference that this timer is used in low speed Auto-Negotiation mode)

Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.
 Change "..._timer" to "..._timer_[LSM]" and update subsequent text and state diagram references.

Task Force to discuss nomenclature of all AutoNeg_timers comments

CI 98 SC 98.5.2 P 60 L 30 # 217
 Graber, Steffen Pepperl+Fuchs GmbH

Comment Type E Comment Status D EZ
 Editor's Note

SuggestedRemedy
 Please remove Editor's note.

Proposed Response Response Status W
 PROPOSED ACCEPT.
 Delete Editor's Note on lines 31-34.

CI 98 SC 98.5.2 P 60 L 35 # 218
 Graber, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status D AutoNeg
 link_fail_inhibit_timer

SuggestedRemedy
 Remove this timer, the explanation, and the associated note (lines 35 to 43) from this position of the document (as this timer is not depending on high speed or low speed autoneg mode, but on the selected PHY type and the associated training time, it will be reapplied to another position of the document by a later comment)

Proposed Response Response Status W
 PROPOSED ACCEPT.

CI 98 SC 98.5.2 P 60 L 45 # 219
 Graber, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status D AutoNeg_timers
 page_test_max_timer

SuggestedRemedy
 page_test_max_timer_[LSM] (reference that this timer is used in low speed Auto-Negotiation mode)

Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.
 Change "..._timer" to "..._timer_[LSM]" and update subsequent text and state diagram references.

Task Force to discuss nomenclature of all AutoNeg_timers comments

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

Cl 98 SC 98.5.2 P 60 L 48 # 220
Graber, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status D AutoNeg_timers
receive_DME_timer

SuggestedRemedy

receive_DME_timer_[LSM] (reference that this timer is used in low speed Auto-Negotiation mode)

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.
Change "..._timer" to "..._timer_[LSM]" and update subsequent text and state diagram references.

Task Force to discuss nomenclature of all AutoNeg_timers comments

Cl 98 SC 98.5.2 P 60 L 49 # 221
Graber, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status D AutoNeg
The timer shall expire 145712 ns to 148912 ns after being started.

SuggestedRemedy

The timer shall expire 145668 ns to 148868 ns after being started. (see presentation "10BASE-T1L Auto-Negotiation")

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 98 SC 98.5.2 P 60 L 52 # 222
Graber, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status D AutoNeg_timers
rx_wait_timer

SuggestedRemedy

rx_wait_timer_[LSM] (reference that this timer is used in low speed Auto-Negotiation mode)

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.
Change "..._timer" to "..._timer_[LSM]" and update subsequent text and state diagram references.

Task Force to discuss nomenclature of all AutoNeg_timers comments

Cl 98 SC 98.5.2 P 61 L 1 # 223
Graber, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status D AutoNeg
The rx_wait_timer shall expire TBD μ s to TBD μ s after being started or restarted.

SuggestedRemedy

The rx_wait_timer shall expire 300 μ s to 340 μ s after being started or restarted. (see presentation "10BASE-T1L Auto-Negotiation")

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 98 SC 98.5.2 P 61 L 5 # 225
Graber, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status D AutoNeg
The timer shall expire 18728 ns to 19788 ns after being started.

SuggestedRemedy

The timer shall expire 20868 ns to 24068 ns after being started. (see presentation "10BASE-T1L Auto-Negotiation")

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 98 SC 98.5.2 P 61 L 5 # 224
Graber, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status D AutoNeg_timers
silent_timer

SuggestedRemedy

silent_timer_[LSM] (reference that this timer is used in low speed Auto-Negotiation mode)

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Change "..._timer" to "..._timer_[LSM]" and update subsequent text and state diagram references.

Task Force to discuss nomenclature of all AutoNeg_timers comments

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

CI 98 SC 98.5.2 P 61 L 7 # 226
 Graber, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status D AutoNeg
 link_fail_inhibit_timer

SuggestedRemedy

Describe the behavior of the PHY type dependent link_fail_inhibit_timer at this position in the following way: Depending on the selected PHY type, done by Auto-Negotiation, the following timer values shall be used: (new line) link_fail_inhibit_timer_[HCD] (new line) Timer for qualifying a link_status=FAIL indication or a link_status=OK indication when a specific technology link is first being established. A link will only be considered "failed" if the link_fail_inhibit_timer_[HCD] has expired and the link has still not gone into the link_status=OK state. The expiration time of the link_fail_inhibit_timer_[HCD] shall be dependent on the selected PHY type. For all PHY types, except 10BASE-T1L this timer shall expire 97 ms to 98 ms after entering the AN GOOD CHECK state. For a 10BASE-T1L PHY this timer shall expire 3030 to 3090 ms after entering the AN GOOD CHECK state. The link_fail_inhibit_timer expiration value is greater than the time required for the link partner to complete Auto-Negotiation after the local device has completed Auto-Negotiation plus the time required for the specific technology to enter the link_status=OK state. (Remark (not to write in the standards text): This assumes that a 10BASE-T1S PHY at maximum starts up in less than 97 ms which likely will be true, but needs to get confirmation.)

Proposed Response Response Status W
 PROPOSED ACCEPT.

CI 98 SC 98.5.6 P 61 L 17 # 227
 Graber, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status D AutoNeg

A PHY supporting only one Auto-Negotiation speed shall implement the behavior shown in Figure 98-12, depending on the supported Auto-Negotiation speed.

SuggestedRemedy

A PHY supporting only one Auto-Negotiation speed shall implement the behavior as shown in Figures 98-7, 98-8, 98-9 and 98-10 without any further modification, using the associated timer values for high speed mode (HSM) or low speed mode (LSM) Auto-Negotiation as described in Clause 98.5.2. (see presentation "10BASE-T1L Auto-Negotiation")

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE. Change "A PHY supporting only one Auto-Negotiation speed shall implement the behavior shown in Figure 98-12, depending on the supported Auto-Negotiation speed."

to

"A PHY supporting only one Auto-Negotiation speed shall implement the behavior as shown in Figures 98-7, 98-8, 98-9 and 98-10 without any further modification, using the associated timer values for high speed mode (HSM) or low speed mode (LSM) Auto-Negotiation as described in 98.5.2. "

(deleted "Clause" from suggested remedy)

CI 98 SC 98.5.6 P 61 L 21 # 228
 Graber, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status D AutoNeg
 Figure 98-11

SuggestedRemedy

Modify Figure 98-11 according to presentation "10BASE-T1L Auto-Negotiation", slide 9.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

CI 98 SC 98.5.6 P 62 L 1 # 229
 Graber, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status D AutoNeg
 Figure 98-12

SuggestedRemedy

Please remove Figure 98-12. (see presentation "10BASE-T1L Auto-Negotiation")

Proposed Response Response Status W

PROPOSED ACCEPT.

Delete Figure 98-12.

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

Cl 98 SC 98.5.6.1 P 62 L 22 # 230
 Graber, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status D AutoNeg

This variable is set by the management entity to restart the Auto-Negotiation process.

SuggestedRemedy

If two different Auto-Negotiation speeds are implemented and this variable is set to TRUE by the management entity, the state machine described in Figure 98-11 and subsequently also the state machines described in Figures 98-7, 98-8, 98-9 and 98-10 are resetted. If only single speed Auto-Negotiation is implemented, variable mr_main_reset has to be used instead as described in Clause 98.5.1. (see presentation "10BASE-T1L Auto-Negotiation")

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

On line 22, replace,
 This variable is set by the management entity to restart the Auto-Negotiation process.

With,

If two different Auto-Negotiation speeds are implemented and this variable is set to TRUE by the management entity, then the state machine described in Figure 98-11 and, subsequently, also the state machines described in Figure 98-7, Figure 98-8, Figure 98-9, and Figure 98-10, are restarted. If only single speed Auto-Negotiation is implemented, variable mr_main_reset has to be used instead as described in 98.5.1.

Editor: Among other editorial corrections, resetted was changed to retarted

Cl 98 SC 98.5.6.1 P 62 L 26 # 231
 Graber, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status X AutoNeg

pwr_on_reset (complete section)

SuggestedRemedy

Replace this section by variable power_on and reference this to Clause 98.5.1. In Clause 98.5.1 add in the description for power_on also the 10BASE-T1L PHY: Condition that is true until such time as the power supply for the device that contains the Auto-Negotiation state diagrams has reached the operating region or the device has low-power mode set via 1000BASE-T1 PMA control register bit 1.2304.11 or via 10BASE-T1L PMA control register bit 1.2294.11. (see presentation "10BASE-T1L Auto-Negotiation")

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Replace,
 pwr_on_reset
 This variable is set to TRUE for the first cycle after applying power to initiate the Auto-Negotiation process.
 Values: TRUE or FALSE

With,
 power_on
 See 98.5.1.

Insert the following after 98.5 Detailed functions and state diagrams,

98.5.1 State diagram variables

Change the variable for power-on as follows:

power_on
 Condition that is true until such time as the power supply for the device that contains the Auto-Negotiation state diagrams has reached the operating region or the device has low-power mode set via 1000BASE-T1 PMA control register bit 1.2304.11 <start underline> or via 10BASE-T1L PMA control register bit 1.2294.11 <end underline>.
 Values:
 false: the device is completely powered (default)
 true: the device has not been completely powered

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

CI 98 SC 98.5.6.1 P 62 L 28 # 232
Graber, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status D AutoNeg
Add missing variables.

SuggestedRemedy

Please add the following variables with reference to Clause 98.5.1 (and sort the variables afterwards in alphabetic order): mr_restart_negotiation, mr_autoneg_enable, mr_main_reset, and an_link_good (the explanation of these variables is already done in Clause 98.5.1) (see presentation "10BASE-T1L Auto-Negotiation")

Proposed Response Response Status W
PROPOSED ACCEPT IN PRINCIPLE.

Add the following variables to 98.5.6.1 in alphabetical order:

mr_restart_negotiation
See 98.5.1.

an_link_good
See 98.5.1.

mr_main_reset
See 98.5.1.

mr_autoneg_enable
See 98.5.1.

CI 98 SC 98.5.6.2 P 62 L 32 # 233
Graber, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status D AutoNeg
auto_negotiation done

SuggestedRemedy

Remove this function, at it is replaced by variable mr_autoneg_complete. (see presentation "10BASE-T1L Auto-Negotiation")

Proposed Response Response Status W
PROPOSED ACCEPT.
Delete,

auto_negotiation done
This function returns TRUE, if the under laying Auto-Negotiation state machines have completed the Auto-Negotiation process, otherwise the function returns the value FALSE.
Values: TRUE or FALSE

CI 98 SC 98.5.6.2 P 62 L 39 # 234
Graber, Steffen Pepperl+Fuchs GmbH

Comment Type E Comment Status D AutoNeg
., otherwise this function returns false.

SuggestedRemedy

., otherwise this function returns FALSE. (write FALSE in capital letters)

Proposed Response Response Status W
PROPOSED ACCEPT.

On line 40, change "false" to "FALSE".

CI 98 SC 98.5.6.2 P 62 L 43 # 235
Graber, Steffen Pepperl+Fuchs GmbH

Comment Type E Comment Status D AutoNeg
This function returns TRUE, if at least the last 12 received DME pulses are within the allowed range for the high speed Auto-Negotiation communication (400 ns to 3600 ns pulse width) including the violations of the DME encoding within the start delimiter.

SuggestedRemedy

This function returns TRUE, if at least the last 12 received DME pulses are within the allowed range for the low speed Auto-Negotiation communication (400 ns to 3600 ns pulse width) including the violations of the DME encoding within the start delimiter, otherwise this function returns FALSE. (replace high speed by low speed and add FALSE condition)

Proposed Response Response Status W
PROPOSED ACCEPT.

On line 45, replace, "high speed" with "low speed"

On line 46, "start delimiter." with "start delimiter, otherwise this function returns FALSE."

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

CI 98 SC 98.5.6.2 P 62 L 49 # 236
 Graber, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status D AutoNeg
 energy_detected

SuggestedRemedy

Remove energy_detected function and description, as this is not needed anymore. (see presentation "10BASE-T1L Auto-Negotiation")

Proposed Response Response Status W
 PROPOSED ACCEPT.

Delete,
 energy_detected

This function returns TRUE, if signal energy is detected on the link segment and the pulse width of at least the last 12 received pulses is within the allowed range for the high speed Auto-Negotiation DME communication (15 ns to 135 ns pulse width) or the low speed Auto-Negotiation DME communication (400 ns to 3600 ns pulse width).
 Values: TRUE or FALSE

CI 98 SC 98.5.6.3 P 63 L 3 # 237
 Graber, Steffen Pepperl+Fuchs GmbH

Comment Type E Comment Status D Editorial
 Editor's Note

SuggestedRemedy

Please remove Editor's Note.

Proposed Response Response Status W
 PROPOSED ACCEPT.

CI 98 SC 98.5.6.3 P 63 L 11 # 238
 Graber, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status D AutoNeg
 Timer value: TBD

SuggestedRemedy

Timer value: (2.5 ms ± 0.1 ms) + (random integer from 0 to 15) x (0.5 ms ± 0.05 ms)

Proposed Response Response Status W
 PROPOSED ACCEPT.

CI 98 SC 98.5.6.3 P 63 L 13 # 239
 Graber, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status D AutoNeg
 Timer value: TBD

SuggestedRemedy

Timer value: 100 ms ± 1 ms

Proposed Response Response Status W
 PROPOSED ACCEPT.

CI 98 SC 98.6.8 P 63 L 46 # 240
 Graber, Steffen Pepperl+Fuchs GmbH

Comment Type E Comment Status D Editorial
 Editor's Note

SuggestedRemedy

Please remove Editor's Note.

Proposed Response Response Status W
 PROPOSED ACCEPT.

CI 98 SC 98.6.8 P 64 L 4 # 241
 Graber, Steffen Pepperl+Fuchs GmbH

Comment Type E Comment Status D AutoNeg_timers
 timer values are listed in table without references to high speed ([HSM]) or low speed ([LSM]) auto-negotiation modes.

SuggestedRemedy

Suggestion is to keep the table from the timer references as they are and not to add [HSM] and [LSM] referrers, as this seems to make the readability worse. Alternatively the timers could be referenced with additional [HSM] and [LSM] text, splitted, and made optional, depending on the supported auto-negotiation speed grades (in this case there is also need to add the splitting for the backoff_timer). The group needs to decide, which style to use.

Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.

Make PICS consistent with resolution of naming of "AutoNeg_timers" comments, referencing the timers as named.

Currently proposed ACCEPT, (Split the rows to show the additional [HSM], [LSM] text and made optional depending on whether auto-negotiation speed is supported)

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

CI 98 SC 98.6.8 P 64 L 5 # 349
Graber, Steffen Pepperl+Fuchs GmbH

Comment Type E Comment Status D EZ

All value/comment fields in the table start with "Expire".

SuggestedRemedy

Please change "Expire" to "Expires" in each row of the table, as only a single timer is referenced.

Proposed Response Response Status W

PROPOSED ACCEPT.

CI 98 SC 98.6.8 P 64 L 6 # 242
Graber, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status D AutoNeg

. and 15000 ns to 15900 ns in low speed mode.

SuggestedRemedy

. and 17668 ns to 20868 ns in low speed mode.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Make PICS consistent with resolution of timer comments

CI 98 SC 98.6.8 P 64 L 10 # 243
Graber, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status D AutoNeg

Expire 300 μ s to 305 μ s after being started in high speed mode and TBD μ s to TBD μ s in low speed mode.

SuggestedRemedy

Expire 300 μ s to 305 μ s after being started (the timer value is the same for both high speed and low speed mode).

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Make PICS consistent with resolution of timer comments

Keep high speed and low speed separate:

e.g.,

Change "Expire 300 μ s to 305 μ s after being started in high speed mode and TBD μ s to TBD μ s in low speed mode." to

"Expire 300 μ s to 305 μ s after being started in high speed mode and 300 μ s to 305 μ s in low speed mode."

just in case we change the values

CI 98 SC 98.6.8 P 64 L 35 # 244
Graber, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status D AutoNeg

Expire 97 ms to 98 ms after entering the AN GOOD CHECK state in high speed mode and TBD ms to TBD ms in low speed mode.

SuggestedRemedy

Expire 3030 ms to 3090 ms after entering the AN GOOD CHECK state for a 10BASE-T1L PHY and 97 ms to 98 ms for all other BASE-T1 PHYs.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Replace SD11 with,

Expire <striketrough>97<underline>3030 ms to <striketrough>98<underline>3039 ms after entering the AN GOOD CHECK <begin underline> state for a 10BASE-T1L PHY and 97 ms to 98 ms for all other BASE-T1 PHYs<end underline>.

CI 98 SC 98.6.8 P 64 L 44 # 245
Graber, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status X AutoNeg

. and 143040 ns to 147140 ns in low speed mode.

SuggestedRemedy

. and 145668 ns to 148868 ns in low speed mode.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Make PICS consistent with resolution of timer comments

CI 98 SC 98.6.8 P 64 L 48 # 246
Graber, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status D AutoNeg

. and TBD μ s to TBD μ s in low speed mode.

SuggestedRemedy

. and 300 μ s to 340 μ s in low speed mode.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Make PICS consistent with resolution of timer comments

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

CI 98 SC 98.6.8 P 64 L 52 # 247
 Graber, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status D AutoNeg

. and 15900 ns to 16800 ns in low speed mode.

SuggestedRemedy

. and 20868 ns to 24068 ns in low speed mode.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Make PICS consistent with resolution of timer comments

CI 104 SC 104.1.3 P 65 L 10 # 395
 Zimmerman, George CME Consulting et al

Comment Type T Comment Status D Power

Due to the similar requirements of the MDI Return Loss a type A or type C PoDL interface should be compatible with 100BASE-T1S. 100BASE-T1S needs to be added here.

SuggestedRemedy

Change "A Type A or Type C PSE and Type A or Type C PD is compatible with 100BASE-T1 PHYs." to "A Type A or Type C PSE and Type A or Type C PD is compatible with 100BASE-T1 or 10BASE-T1S PHYs.", and change line 12 from "A Type C PSE and Type C PD is compatible with both 100BASE-T1 and 1000BASE-T1 PHYs." to "A Type C PSE and Type C PD is compatible with 10BASE-T1S, 100BASE-T1 and 1000BASE-T1 PHYs."

Proposed Response Response Status W

PROPOSED ACCEPT.

Make the following changes showing strikeouts and underlines as appropriate:

Change from,

"A Type A or Type C PSE and Type A or Type C PD is compatible with 100BASE-T1 PHYs."

to,

"A Type A or Type C PSE and Type A or Type C PD is compatible with 100BASE-T1 or 10BASE-T1S PHYs.",

and change line 12 from,

"A Type C PSE and Type C PD is compatible with both 100BASE-T1 and 1000BASE-T1 PHYs."

to,

"A Type C PSE and Type C PD is compatible with 10BASE-T1S, 100BASE-T1 and 1000BASE-T1 PHYs."

CI 104 SC 104.6.2 P 69 L 42 # 407
 Zimmerman, George CME Consulting et al

Comment Type T Comment Status D EZ

The PI for Type E PSEs and PDs shall meet the fault tolerance requirements as specified in 146.8.xxx. - needs to be filled in. Since Type E is only for 10BASE-T1L, this is only for clause 146.

SuggestedRemedy

Change 146.8.xxx to 146.8.4 (cross reference)

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Duplicate of Comment 248

Same resolution - change 146.8.xxx to 146.8.4

CI 104 SC 104.6.2 P 69 L 43 # 248
 Graber, Steffen Pepperl+Fuchs GmbH

Comment Type E Comment Status D EZ

. as specified in 146.8.xxx.

SuggestedRemedy

. as specified in 146.8.4.

Proposed Response Response Status W

PROPOSED ACCEPT.

CI 104 SC 104.7.1.3 P 73 L 12 # 249
 Graber, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status D Power

72 (TBD)

SuggestedRemedy

80 (suggestion is to go to 80 ns as a typical fieldbus type A cable is having approx. 70 nF capacitance per 1000 m. Thus 72 nF seem to be too close to the typical values, and 80 nF would provide a higher margin).

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Change "72 (TBD)" to "80"

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

Cl 104 SC 104.7.1.3 P 73 L 12 # 400
Zimmerman, George CME Consulting et al

Comment Type T Comment Status D Power
TBD for max bus capacitance has been under review without comment

SuggestedRemedy

Delete TBD

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Resolved by comment 249, changed value to 80 and deleted TBD.

Cl 146 SC 146 P 77 L 1 # 354
Grabner, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status D EEE
Energy Efficient Ethernet description is missing in Clause 146.

SuggestedRemedy

Please add text and modify state machines as described in "Energy Efficient Ethernet.pdf" (see also presentation "10BASE-T1L Energy Efficient Ethernet.pdf").

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Incorporate modifications to PCS Receive and PMA state diagrams on slides 5 and 6 of 10BASE-T1L Energy Efficient Ethernet.pdf
Incorporate timer values on slides 3 and 4 in clause 78 tables 78-2 (T_q, T_s and T_r) and 78-4 (T_w_PHY, T_w_sys_tx, T_w_sys_rx, T_phy_shrink_tx, T_phy_shrink_rx)

MASTER EEE_T1L

Cl 146 SC 146.1 P 77 L 9 # 334
Shariff, Masood CommScope

Comment Type E Comment Status D EZ
Improve sentence.

Provided in this clause are fully functional and electrical specifications for the type 10BASE-T1L PCS and PMA.

SuggestedRemedy

Provided in this clause are fully functional and electrical specifications for the type 10BASE-T1L PCS and PMA.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Resolved by comment 471

Cl 146 SC 146.1 P 77 L 9 # 471
Brandt, David Rockwell Automation

Comment Type E Comment Status D EZ
Type

SuggestedRemedy

Change "fully functional and electrical specifications" to "full functional and electrical specifications"

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Change "Provided in this clause are fully functional and electrical specifications for type 10BASE-T1L PCS and PMA." to
"Provided in this clause are fully functional and electrical specifications for type 10BASE-T1L PCS, PMA, and MDI."

Cl 146 SC 146.1 P 77 L 23 # 350
Grabner, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status D EEE
Editor's Note

SuggestedRemedy

Please replace Editor's Note with the following text: This clause also specifies an optional Energy-Efficient Ethernet (EEE) capability. A 10BASE-T1L PHY that supports this capability may enter a Low Power Idle (LPI) mode of operation during periods of low link utilization as described in Clause 78.

Proposed Response Response Status W

PROPOSED ACCEPT.

#EEE_T1L

Cl 146 SC 146.1.2 P 78 L 36 # 397
Zimmerman, George CME Consulting et al

Comment Type E Comment Status D EEE
Editor's note has served its purpose, Text has been reviewed through 2 cycles, AND is redundant with other notes

SuggestedRemedy

Delete editor's note at P78 line 36

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Resolved by comment 351

#EEE_T1L

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

Cl 146 SC 146.1.2 P 78 L 36 # 250
Graber, Steffen Pepperl+Fuchs GmbH

Comment Type E Comment Status D
Editor's Note

SuggestedRemedy

Remove all text besides last line from Editor's Note.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.
Resolved by comment 351 which removed the editor's note and accomplished all the items in it.
#EEE_T1L

Cl 146 SC 146.1.2 P 78 L 36 # 351
Graber, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status D
Editor's Note

SuggestedRemedy

Please replace Editor's Note with the following text: A 10BASE-T1L PHY may optionally support Energy-Efficient Ethernet (see Clause 78) and advertise the EEE capability during Auto-Negotiation as described in Annex 98C.5. The EEE capability is a mechanism by which 10BASE-T1L PHYs are able to reduce power consumption during periods of low link utilization.

Proposed Response Response Status W

PROPOSED ACCEPT.
#EEE_T1L

Cl 146 SC 146.1.2 P 79 L 4 # 403
Zimmerman, George CME Consulting et al

Comment Type T Comment Status D
EEE must be advertised during autoneg - training sequence doesn't support it.

SuggestedRemedy

Insert new 3rd sentence following "link utilization.": "EEE capability is advertised during the Auto-Negotiation process." - delete editor's note on line 5

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.
Resolved by comment 351
#EEE_T1L

Cl 146 SC 146.1.2 P 79 L 5 # 251
Graber, Steffen Pepperl+Fuchs GmbH

Comment Type E Comment Status D
Editor's Note

SuggestedRemedy

Please remove Editor's Note (EEE is advertised using next page mechanism during Autoneg and can be set by PMA control register, if Autoneg is not present or disabled).

Proposed Response Response Status W

PROPOSED ACCEPT.
#EEE_T1L

Cl 146 SC 146.1.2 P 79 L 13 # 396
Zimmerman, George CME Consulting et al

Comment Type E Comment Status D
Editor's note has served its purpose, Text has been reviewed through 2 cycles

SuggestedRemedy

Delete editor's note at P79 line 13

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 146 SC 146.1.2 P 79 L 13 # 252
Graber, Steffen Pepperl+Fuchs GmbH

Comment Type E Comment Status D
Editor's Note

SuggestedRemedy

Please remove Editor's Note, as the text has been added for review in D1.1 and therefore has been reviewed and commented in the meantime.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.
Duplicate of comment 396

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

Cl 146 SC 146.2 P 81 L 1 # 253
Graber, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status D Primitives
PMA_LINK.request (link_control) is missing.

SuggestedRemedy

Please add PMA_LINK.request before PMA_LINK.indication (link_control)

Proposed Response Response Status W

PROPOSED ACCEPT.
#PRIMITIVES

Cl 146 SC 146.2 P 81 L 10 # 254
Graber, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status D Primitives
TX_EN

SuggestedRemedy

Change TX_EN to tx_enable_mii (in PCS the TX_EN signal form MII is preprocessed in dependence of the current tx_mode and the resulting signal fed into PMA is tx_enable_mii).

Proposed Response Response Status W

PROPOSED ACCEPT.
#PRIMITIVES

Cl 146 SC 146.2 P 81 L 11 # 255
Graber, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status D Primitives
Description of Service Primitives is missing.

SuggestedRemedy

Please add text suggested in "Service Primitives.pdf"

Proposed Response Response Status W

PROPOSED ACCEPT.
MASTER PRIMITIVES COMMENT

Cl 146 SC 146.3.1 P 82 L 22 # 256
Graber, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status D Primitives
Signal tx_enable_mii going to PMA is missing.

SuggestedRemedy

Please add singnal tx_enable_mii from block PCS DATA TRANSMISSION ENABLE to PMA service interface.

Proposed Response Response Status W

PROPOSED ACCEPT.
#PRIMITIVES

Cl 146 SC 146.3.1 P 82 L 38 # 257
Graber, Steffen Pepperl+Fuchs GmbH

Comment Type E Comment Status D EZ
Font for MEDIA INDEPENDENT INTERFACE and PMA SERVICE INTERFACE does not match.

SuggestedRemedy

Please match used font to rest of the document.

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 146 SC 146.3.3.1.1 P 85 L 36 # 258
Graber, Steffen Pepperl+Fuchs GmbH

Comment Type E Comment Status D Editorial
Editor's Note

SuggestedRemedy

Please remove Editor's Note as it is just an explantion for what loc_lpi_req variable is being used. That EEE definitions are missing is stated already at other positions in the document.

Proposed Response Response Status W

PROPOSED ACCEPT.

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

Cl 146 SC 146.3.4.1.1 P 96 L 22 # 352
Graber, Steffen Pepperl+Fuchs GmbH

Comment Type E Comment Status D EZ

. received that this not allowed .

SuggestedRemedy

. received that is not allowed .

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 146 SC 146.3.4.1.1 P 96 L 25 # 353
Graber, Steffen Pepperl+Fuchs GmbH

Comment Type E Comment Status D EZ

. in Figure 146-10 else it is set .

SuggestedRemedy

.. in Figure 146-10, else it is set . (comma is missing)

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.
Change "Figure 146-10 else it is set to FALSE." to
"Figure 146-10 and set FALSE otherwise"

Cl 146 SC 146.4 P 99 L 10 # 259
Graber, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status D Primitives

TX_EN

SuggestedRemedy

tx_enable_mii (the variable is not directly coming from MII, but from the PCS Data
Transmission Enabling state diagram)

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.
Change signal name in diagram from TX_EN to tx_enable_mii.
(the signal name at the PMA service interface)

#PRIMITIVES

Cl 146 SC 146.4.3 P 100 L 38 # 299
Maguire, Valerie The Siemon Company

Comment Type E Comment Status D Editorial

Align media references with revised objectives.

SuggestedRemedy

Replace, "single pair" with "single balanced pair"

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.
Change "PMA Receive has the ability to translate the received signals on the single pair
into the PMA_UNITDATA.indication parameter rx_symb_vector"

to "PMA Receive has the ability to translate the received signals at the MDI into the
PMA_UNITDATA.indication parameter rx_symb_vector"

Cl 146 SC 146.4.4 P 101 L 23 # 261
Graber, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status D EZ

PMA_CONFIG

SuggestedRemedy

variable config

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.
Change PMA_CONFIG to "the configuration of the PMA" on lines 23 and 26

Cl 146 SC 146.4.4 P 101 L 23 # 260
Graber, Steffen Pepperl+Fuchs GmbH

Comment Type E Comment Status D EZ

AUTONEG mode

SuggestedRemedy

Auto-Negotiation

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.
Change AUTONEG to Auto-Negotiation on lines 23 and 26.

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

Cl **146** SC **146.4.4** P **101** L **25** # **263**
 Graber, Steffen Pepperl+Fuchs GmbH
 Comment Type **T** Comment Status **D** EZ
 PMA_CONFIG
 SuggestedRemedy
 variable config
 Proposed Response Response Status **W**
 PROPOSED ACCEPT IN PRINCIPLE.
 Resolved by comment 261

Cl **146** SC **146.4.4** P **101** L **25** # **262**
 Graber, Steffen Pepperl+Fuchs GmbH
 Comment Type **E** Comment Status **D** EZ
 AUTONEG mode
 SuggestedRemedy
 Auto-Negotiation
 Proposed Response Response Status **W**
 PROPOSED ACCEPT IN PRINCIPLE.
 Resolved by comment 260

Cl **146** SC **146.5.1** P **104** L **48** # **418**
 Zimmerman, George CME Consulting et al
 Comment Type **T** Comment Status **D** PMA Electrical
 Editor's note is unnecessary. EMC is being discussed. Note just gives general information.
 SuggestedRemedy
 Delete editor's note.
 Proposed Response Response Status **W**
 PROPOSED ACCEPT.

Cl **146** SC **146.5.2** P **105** L **31** # **404**
 Zimmerman, George CME Consulting et al
 Comment Type **E** Comment Status **D** PMA Electrical
 Editor's note has served its purpose
 SuggestedRemedy
 delete editor's note as per instruction
 Proposed Response Response Status **W**
 PROPOSED ACCEPT IN PRINCIPLE.
 Duplicate of comment 264

Cl **146** SC **146.5.2** P **105** L **32** # **264**
 Graber, Steffen Pepperl+Fuchs GmbH
 Comment Type **E** Comment Status **D** PMA Electrical
 Editor's Note
 SuggestedRemedy
 Please remove Editor's Note, as the test mode 3 in the meantime has been added to the draft.
 Proposed Response Response Status **W**
 PROPOSED ACCEPT.

Cl **146** SC **146.5.4.1** P **106** L **42** # **265**
 Graber, Steffen Pepperl+Fuchs GmbH
 Comment Type **T** Comment Status **D** Editorial
 Default setting is to use Auto-Negotiation.
 SuggestedRemedy
 Default setting is to use Auto-Negotiation, if available.
 Proposed Response Response Status **W**
 PROPOSED ACCEPT IN PRINCIPLE.
 Change "Default setting is to use Auto-Negotiation." to "The default setting is to use Auto-Negotiation, if available."

(Auto-Negotiation is not required for the PHY operation)

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

Cl 146 SC 146.5.4.4 P 107 L 3 # 405
Zimmerman, George CME Consulting et al

Comment Type E Comment Status D PMA Electrical
All values in the document are subject to change, and editor's note has served its purpose.

SuggestedRemedy

Delete editor's note saying "the values of the mask are and power level are TBD"

Proposed Response Response Status W
PROPOSED ACCEPT.

Cl 146 SC 146.5.4.4 P 107 L 4 # 266
Graber, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status D PMA Electrical
Editor's Note

SuggestedRemedy

PSD mask limits are already in since D1.1 for commenting. Please remove Editor's note. If other comments related to the PSD mask are available during this meeting cycle, the PSD mask can be adjusted accordingly. Otherwise comments related to the PSD mask are also possible during Working Group Ballot.

Proposed Response Response Status W
PROPOSED ACCEPT IN PRINCIPLE.
Resolved by comment 405

Cl 146 SC 146.5.4.4 P 107 L 28 # 406
Zimmerman, George CME Consulting et al

Comment Type E Comment Status D Editorial
Editor's note has served its purpose

SuggestedRemedy

delete editor's note as specified in instruction.

Proposed Response Response Status W
PROPOSED ACCEPT IN PRINCIPLE.
Resolved by comment 267.

Cl 146 SC 146.5.4.4 P 107 L 28 # 267
Graber, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status D Editorial
Editor's Note

SuggestedRemedy

Please remove Editor's note in the next draft, as the drawing has been in for commenting since D1.2.

Proposed Response Response Status W
PROPOSED ACCEPT.

Cl 146 SC 146.5.5.3 P 109 L 3 # 268
Graber, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status D PMA Electrical
Editor's Note

SuggestedRemedy

During the meeting in Rosemont, there were some discussions about noise tests and outcome of the discussions was, not to implement the summed transmitter noise test for now. Therefore suggestion is to remove the Editor's note and stay with the Alien Crosstalk noise test like it is currently specified in D1.2. If then during Working Group Ballot another reasonable noise test is found, it can be added later on.

Proposed Response Response Status W
PROPOSED ACCEPT IN PRINCIPLE.
Delete editor's note

Cl 146 SC 146.5.5.3 P 109 L 3 # 398
Zimmerman, George CME Consulting et al

Comment Type T Comment Status D PMA Electrical
Text has resolved the technical issues in the editor's note.

SuggestedRemedy

Delete editor's note at P109 L3

Proposed Response Response Status W
PROPOSED ACCEPT IN PRINCIPLE.
Resolved by comment 268

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

CI **146** SC **146.5.5.3** P **109** L **34** # **269**
 Graber, Steffen Pepperl+Fuchs GmbH

Comment Type **T** Comment Status **D** PMA Electrical
 Editor's Note

SuggestedRemedy

Outcome of the discussions in Rosemont was, to stay with the current Alien Crosstalk test and not use a summed transmitter test. As there will be different link segment descriptions for the 1.0 Vpp and the 2.4 Vpp transmitter which are adapted according to the lower transmit power, there is no need to specify different noise levels for 1.0 Vpp and 2.4 Vpp transmit amplitudes. As long as shielded cables (shield attenuation typ. 60 dB for E3 additionally to the mode conversion of the twisted pair) are used, the margin seems to be ok (typ. 100 dB attenuation). For unshielded twisted pairs (see link segment definitions) further investigation is necessary. But as this is handled in the link segment section, please remove the Editor's Note at this position.

Proposed Response Response Status **W**

PROPOSED ACCEPT IN PRINCIPLE.
 Resolved by comment 408.

Task force still needs to determine which transmit voltage setting is intended for alien crosstalk test, so part of the note stays.

CI **146** SC **146.5.5.3** P **109** L **34** # **408**
 Zimmerman, George CME Consulting et al

Comment Type **T** Comment Status **D** PMA Electrical
 Many issues in the editor's note have been resolved and discussed. The only issue left is how this test relates to the transmit voltage option.

SuggestedRemedy

Delete "several points here..." through end of editor's note. Insert "how alien noise test relates to transmit amplitude option." so that the editor's note body text reads: "Task Force needs to discuss how alien noise test relates to transmit amplitude option."

Proposed Response Response Status **W**

PROPOSED ACCEPT IN PRINCIPLE.

See comment 269 Suggested remedy for further information.

CI **146** SC **146.5.6** P **109** L **46** # **271**
 Graber, Steffen Pepperl+Fuchs GmbH

Comment Type **T** Comment Status **D** PMA Electrical
 1.15 Vpp

SuggestedRemedy

1.10 Vpp (5 % tolerance of output voltage, 20 % droop (+/- 10 %) using test mode 2 pulses, which are 10 bit times long, see 146.5.4.2. As the maximum pulse length in the 4B3T encoded signal form is only 5 bit times instead of 10 bit times, during normal communication the droop shall be less than 10 % (+/- 5 %). Thus the maximum peak-to-peak voltage will be 1.10 Vpp instead of 1.15 Vpp.

Proposed Response Response Status **W**

PROPOSED ACCEPT.

CI **146** SC **146.5.6** P **109** L **46** # **270**
 Graber, Steffen Pepperl+Fuchs GmbH

Comment Type **T** Comment Status **D** PMA Electrical
 2.76 Vpp

SuggestedRemedy

2.64 Vpp (5 % tolerance of output voltage, 20 % droop (+/- 10 %) using test mode 2 pulses, which are 10 bit times long, see 146.5.4.2. As the maximum pulse length in the 4B3T encoded signal form is only 5 bit times instead of 10 bit times, during normal communication the droop shall be less than 10 % (+/- 5 %). Thus the maximum peak-to-peak voltage will be 2.64 Vpp instead of 2.76 Vpp.

Proposed Response Response Status **W**

PROPOSED ACCEPT.

CI **146** SC **146.5.6** P **109** L **50** # **399**
 Zimmerman, George CME Consulting et al

Comment Type **E** Comment Status **D** PMA Electrical
 Editor's note has served its purpose - issues have been considered in recirc

SuggestedRemedy

Delete editor's note at P109 L50

Proposed Response Response Status **W**

PROPOSED ACCEPT IN PRINCIPLE.

Resolved by comment 399

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

Cl 146 SC 146.5.6 P 109 L 50 # 272
 Graber, Steffen Pepperl+Fuchs GmbH
 Comment Type E Comment Status D PMA Electrical
 Editor's Note
 SuggestedRemedy
 Please remove Editor's Note, see the two comments above this comment.
 Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.
 Delete Editor's note
 See comments 270 and 271

Cl 146 SC 146.6.1 P 110 L 47 # 273
 Graber, Steffen Pepperl+Fuchs GmbH
 Comment Type T Comment Status D AutoNeg
 Editor's Note
 SuggestedRemedy
 Please remove Editor's Note and add the following text instead: If Auto-Negotiation is enabled, the MASTER-SLAVE configuration between the PHYs is established using the method being described in Clause 98.2.1.2.5 and Table 98-4. If there is no Auto-Negotiation functionality preset or if Auto-Negotiation function has been disabled, then the MASTER-SLAVE configuration is done separately for each PHY using bit 1.2100.14 (BASE-T1 PMA/PMD control register).
 Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.
 Delete Editor's Note.
 Insert new paragraph at line 47:
 "If Auto-Negotiation is available and enabled, the MASTER-SLAVE configuration between the PHYs is established using the method being described in 98.2.1.2.5 and Table 98-4. If there is no Auto-Negotiation functionality present or if Auto-Negotiation function has been disabled, the MASTER-SLAVE configuration is performed for each PHY using bit 1.2100.14 (BASE-T1 PMA/PMD control register) or equivalent functionality.

Cl 146 SC 146.6.2 P 111 L 11 # 274
 Graber, Steffen Pepperl+Fuchs GmbH
 Comment Type T Comment Status D EZ
 Default setting is to use Auto-Negotiation.
 SuggestedRemedy
 Default setting is to use Auto-Negotiation, if available.
 Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.
 Change "Default setting is to use Auto-Negotiation."
 to "The default setting is to use Auto-Negotiation, if available."

Cl 146 SC 146.6.3 P 111 L 26 # 275
 Graber, Steffen Pepperl+Fuchs GmbH
 Comment Type E Comment Status D EZ
 10BASE-T1 PMA/PMD control register
 SuggestedRemedy
 BASE-T1 PMA/PMD control register
 Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.
 Change "10BASE-T1" to "BASE-T1"
 Cl 146 SC 146.6.3 P 111 L 28 # 276
 Graber, Steffen Pepperl+Fuchs GmbH
 Comment Type E Comment Status D EZ
 10BASE-T1 PMA/PMD control register
 SuggestedRemedy
 BASE-T1 PMA/PMD control register
 Proposed Response Response Status W
 PROPOSED ACCEPT IN PRINCIPLE.
 Change 10BASE-T1 to BASE-T1

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

CI 146 SC 146.7.1.2 P 113 L 5 # 314
Horrn Meyer, Bernd Phoenix Contact

Comment Type TR Comment Status D Link Segment

Equation gives 13,25 dB, but figure 146-23 shows 13,5 dB

SuggestedRemedy

Change '13.25 dB' in eq. 146-11 to '13.5 dB'

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE. Equation 146-11 at 0.5 MHz is 13.5 dB.
Change P113, L5: 13.25 dB to 13.5 dB

Typo in implementing slide 5
diminico_02_0318.pdf

CI 146 SC 146.7.1.3 P 113 L 42 # 335
Shariff, Masood CommScope

Comment Type ER Comment Status D Link Segment

This is an international standard and should use the SI system for conductor diameter globally.

SuggestedRemedy

Globally use soft conversions of AWG to SI as shown below. Eg. 14 AWG (1.63 mm)

AWG D(ins) D(mm) CA(mm2)

110.09072.304.17

120.08082.053.31

130.07201.832.63

140.06411.632.08

150.05711.451.65

160.05081.291.31

170.04531.151.04

180.04031.020.82

190.03590.910.65

200.03200.810.52

210.02850.720.41

220.02540.650.33

230.02260.570.26

240.02010.510.20

250.01790.450.16

260.01590.400.13

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE. Add mm dimension to AWG globally e.g., 14 AWG (1.63 mm).

For committee discussion

CI 146 SC 146.7.1.5 P 114 L 27 # 364
Schicketanz, Dieter Reutlingen University

Comment Type T Comment Status D Link Segment

Coupling attenuation: there are similar measurement limitations as for the electromagnetic classification, therefore standardized set ups specify coupling attenuation from 30 MHz upwards only. As there is a need now to have a standardized set ups below 30MHz IEC TC46 decided last week to start a project on the basis of already published standards IEC62153-4-x (x = 2, 7, 9 and others) which already specifies measurements of coupling attenuation below 20 MHz. Taking a presentation from Proceedings of the 62nd IWCS Conference (http://www.bedeia.com/images/PDF/Messtechnik/english/IWCS%20-%20Halme_Mund%20-%20EMC%20of%20Cables,%20Connectors.pdf) it can be seen in fig.6 that the coupling attenuation has a slope of about 20 dB/dec below 100 MHz till it ends in noise below 20 MHz. The measurement goes down to 350 KHz. An explanation is prepared to be presented May 9.

SuggestedRemedy

On the basis of the measurements presented it is proposed to use the known values (ISO.802.3bp Schicketanz122017_10SPE_01_adhoc Page 7) of coupling attenuation at 100 MHz and add later , if needed , a formula presented by IEC TC46. In Table 146-6 coupling attenuation replace frequency range with 0.1 <f< 20, E1 with 40, E2 with 50, and E3 with 60. Delete editors note at line 35.

Proposed Response Response Status W

PROPOSED REJECT.

For committee discussion of cited presentation

CI 146 SC 146.7.1.6 P 115 L 6 # 363
Schicketanz, Dieter Reutlingen University

Comment Type T Comment Status D Link Segment

Table 146-7 electromagnetic classification. Due to measurement limitations CISPR has divided up the frequency range in radiated emissions for frequencies higher than 80MHz, and conducted RF below 80 MHz. It is therefore not necessary to specify the radiated emission as outside the frequency range of T1L

SuggestedRemedy

Delete line 1 Radiated RF-AM from Table 146-7

Proposed Response Response Status W

PROPOSED REJECT.

The basis for removing radiated RF-AM needs to be based on PHY considerations not a statement on CISPR measurement limitations.

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

CI 146 SC 146.8 P 116 L 23 # 409
Zimmerman, George CME Consulting et al

Comment Type E Comment Status D Editorial

Editor's note has served its purpose, this text has now been recirculated twice

SuggestedRemedy

Delete editor's note

Proposed Response Response Status W

PROPOSED ACCEPT.

CI 146 SC 146.7.2.3 P 116 L 23 # 277
Graber, Steffen Pepperl+Fuchs GmbH

Comment Type E Comment Status D Link Segment

Editor's Note

SuggestedRemedy

Please remove Editor's Note as the referenced text is already in since D1.1 and has been discussed during the meeting is Rosemont.

Proposed Response Response Status W

PROPOSED ACCEPT.

CI 146 SC 146.8.1 P 116 L 40 # 278
Graber, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status D MDI

For industrial applications . defined in 146.7.

SuggestedRemedy

Please replace the complete sentence by: For industrial applications also a two pin M8/M12 connector according to IEC 61076-3-125, a four pin M8 connector according to IEC 61076-2-104, a four pin M12 connector according to IEC 61076-2-101, or a four pin 7/8" connector may be used as long as it conforms to the requirements of the link segment defined in 146.7. For the four pin connectors the following pinout shall be used: Pin 1 - BI_DA+, Pin 2 - Shield or drain wire, Pin 3 - BI_DA-. If a metal connector housing is being used, this housing may also be connected to the cable shield.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.
Resolved by resolution to comment 315.
#MDI_CONNECTORS

CI 146 SC 146.8 P 116 L 40 # 356
Fritsche, Matthias HARTING Technology

Comment Type T Comment Status D MDI

According to the editor note a "better specificity of "lower environmental requirements", e.g., MICE1 or IP20" is needed. From my point of view the MICE classifications are useful here.

SuggestedRemedy

Alternatively for MICE 1 applications with lower environmental requirements a TBD connector may be used.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.
Resolved by resolution to comment 315.
#MDI_CONNECTORS

CI 146 SC 146.8 P 116 L 40 # 355
Fritsche, Matthias HARTING Technology

Comment Type E Comment Status D MDI

During the comment resolution discussion of comment 138 we lost the two pin versions. See comment 138 on Draft 1.1.

SuggestedRemedy

For industrial applications also a two or four pin M8/M12 according to IEC 61076-3-125 or a two or four pin 7/8" connector may be used as long as it conforms to the requirements of the link segment defined in 146.7.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.
Resolved by resolution to comment 315.
#MDI_CONNECTORS

CI 146 SC 146.8.1 P 116 L 40 # 310
Maguire, Valerie The Siemon Company

Comment Type T Comment Status D MDI

It's too early in the amendment development process to be explicitly calling out a specific M8/M12 interface. The sentence structure could be improved.

SuggestedRemedy

Replace, "For industrial applications also a four pin M8/M12 according to IEC 61076-3-125 or a four pin 7/8" connector may be used" with, "For industrial applications, a four pin M8/M12 or a four pin 7/8" connector may be used".

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.
Resolved by resolution to comment 315.
#MDI_CONNECTORS

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

Cl 146 SC 146.8.1 P 116 L 40 # 410

Zimmerman, George

CME Consulting et al

Comment Type T Comment Status D MDI

Previous comments have been accepted asking us to consider ISO/IEC and TIA connector processes in our MDI connector selection. The selection of a connector here is unnecessary for technical completeness and premature

SuggestedRemedy

Delete lines 40 through 49 (paragraphs 2 & 3 as well as editor's note in 146.8.1)

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.
Resolved by resolution to comment 315.
#MDI_CONNECTORS

Cl 146 SC 146.8.1 P 116 L 40 # 315

Hormmeyer, Bernd

Phoenix Contact

Comment Type TR Comment Status D MDI

There are several connectors announced as suitable for SPE. Therefore TIA and ISO/IEC introduced a selecting process for MICE1 and MICE3 connectors. IEEE802.3 asked also these SDO's via the liasion process for recommendations. So, cg should wait for results until defining a specific type.

SuggestedRemedy

For applications in a MICE1 environment a connector according to IEC [tbd] and for application in a MICE2 or 3 environment a connector according to IEC [tbd] may be used . Alternatively for applications with specific requirements another connector may be used as long as it conforms to the requirements of the link segment defined in 146.7. (Editor's note: tbd to be replaced prior to draft 2.0)

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.
MASTER COMMENT MDI_CONNECTORS
Delete P116 lines 40-50:

"For industrial applications also a four pin M8/M12 according to IEC 61076-3-125 or a four pin 7/8" connector may be used as long as it conforms to the requirements of the link segment defined in 146.7. Alternatively for applications with lower environmental requirements a TBD connector may be used. In this case pin TBD (BI_DA+) and pin TBD (BI_DA-) of the connector shall be used."

The sense of the Task Force has been towards an optional MDI connector (a recommendation), so specifying a connector isn't essential to technical completeness. A recommendation can be added later.

This resolves the existing TBDs, doesn't add another TBD to the draft, and aligns the draft with our response to comment 76 on D1.1 (responses of ISO and TIA groups should be considered before making any decision). We can add when we get responses from ISO and TIA.

Also, the current text incorrectly states the requirement (the full MDI connector isn't part of the link segment. - despite the ambiguity of the mating interface - but the connector itself isn't conforming to the link segment requirements.)

This leaves the section 146.8.1 MDI Connectors reading simply:

"The mechanical interface to the balanced cabling is a 3-pin connector (BI_DA+, BI_DA-, and SHIELD) or alternatively a 2-pin connector with an additional mechanical shield connection which conforms to the link segment specification defined in 146.7."

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

CI 146 SC 146.8.1 P 116 L 43 # 279
 Graber, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status D MDI

Alternatively for applications . shall be used.

SuggestedRemedy

Please replace the complete paragraph by: Alternatively for applications with lower environmental requirements, like MICE E1 or IP20 a RJ45 connector may be used. In this case pin 3 (BI_DA+) and pin 6 (BI_DA-) of the connector shall be used. (I would recommend also using a RJ45 connector, if there is need for another TBD connector with TBD pinout, and there is a suggestion, what to use, we could add this additionally in (also at a later time during WG ballot).

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.
 Resolved by resolution to comment 315.
 #MDI_CONNECTORS

CI 146 SC 146.8.1 P 116 L 43 # 337
 Shariff, Masood CommScope

Comment Type T Comment Status D MDI

Improve specificity and provide references to the statement as requested in the Editors note on line 46.

"Alternatively for applications with lower environmental requirements a TBD connector may be used."

SuggestedRemedy

"Alternatively for applications in M111C1E1 environments (e.g. commercial buildings, hospitality, education) a connector specified by IEC SC48B (e.g. IEC 63171-1 Ed1) and selected by ISO/IEC/JTC1/SC 25/WG 3 may be used."

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.
 Resolved by resolution to comment 315.
 #MDI_CONNECTORS

CI 146 SC 146.8.1 P 116 L 46 # 280
 Graber, Steffen Pepperl+Fuchs GmbH

Comment Type E Comment Status D MDI

Editor's Note

SuggestedRemedy

Please remove Editor's Note, see previous comment.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.
 Resolved by resolution to comment 315.
 (editor's note deleted)
 #MDI_CONNECTORS

CI 146 SC 146.8.3 P 117 L 7 # 281
 Graber, Steffen Pepperl+Fuchs GmbH

Comment Type T Comment Status D MDI

Editor's Note

SuggestedRemedy

Please remove Editor's Note and replace the MDI return loss formula by the formula given in presentation "10BASE-T1L MDI Return Loss.pdf", page "MDI Return Loss Limit Curve".

Proposed Response Response Status W

PROPOSED ACCEPT.

CI 146 SC 146.8.3 P 117 L 14 # 333
 Shariff, Masood CommScope

Comment Type T Comment Status D MDI

Delete editors note on lines 7 - 10 and change equation 146-16 to use the proposed RL values in the remedy

SuggestedRemedy

Use these values for the RL from TIA-568.5 draft 0.5a

0.1 <= f < 0.5 9+9(f)
 0.5 <= f <= 20 13.25

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.
 Resolved by comment 281.
 MDI return loss is not the same as channel, cabling, or connecting hardware return loss in TIA or ISO/IEC specifications. Must include effect of passive PHY circuitry

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

Cl **146** SC **146.8.3** P **117** L **19** # **411**
 Zimmerman, George CME Consulting et al

Comment Type **E** Comment Status **D** Editorial

All values are subject to change. Editor's note is unnecessary

SuggestedRemedy

Delete Editor's note

Proposed Response Response Status **W**

PROPOSED ACCEPT.

Cl **146** SC **146.8.3** P **117** L **20** # **282**
 Graber, Steffen Pepperl+Fuchs GmbH

Comment Type **E** Comment Status **D** Editorial

Editor's Note

SuggestedRemedy

Please remove Editor's Note, see previous comment.

Proposed Response Response Status **W**

PROPOSED ACCEPT IN PRINCIPLE.
 Resolved by comment 411.

Cl **146** SC **146.9.1** P **118** L **10** # **412**
 Zimmerman, George CME Consulting et al

Comment Type **T** Comment Status **D** Editorial

Isolation ad hoc is not changing the sections in the base standard this is modifying.
 Editor's note is unnecessary.

SuggestedRemedy

Delete editor's note.

Proposed Response Response Status **W**

PROPOSED ACCEPT.

Cl **146** SC **146.9.2** P **118** L **23** # **336**
 Shariff, Masood CommScope

Comment Type **ER** Comment Status **D** Editorial

Simplify and improve sentence:

"In industrial applications, all 10BASE-T1L cabling shall be routed according to any applicable local, state or national standards considering all relevant safety requirements."

SuggestedRemedy

"In industrial applications, 10BASE-T1L cabling shall be routed in accordance with applicable local, state or national safety requirements."

Proposed Response Response Status **W**

PROPOSED ACCEPT.

Cl **146** SC **146.11.3** P **121** L **38** # **283**
 Graber, Steffen Pepperl+Fuchs GmbH

Comment Type **T** Comment Status **D** AutoNeg

1.0 Vpp operating mode

SuggestedRemedy

2.4 Vpp operating mode (1.0 Vpp has been changed to be the default mode, 2.4 Vpp to be the additional option)

Proposed Response Response Status **W**

PROPOSED ACCEPT IN PRINCIPLE.
 Align with decision on operating mode text (see clause 45 comments)

Cl **146** SC **146.11.4.2.2** P **126** L **42** # **284**
 Graber, Steffen Pepperl+Fuchs GmbH

Comment Type **T** Comment Status **D** PMA Electrical

Less than 2.76 Vpp for the 2.4 Vpp operating mode and less than 1.15 Vpp for the 1.0 Vpp operating mode.

SuggestedRemedy

Less than 2.64 Vpp for the 2.4 Vpp operating mode and less than 1.10 Vpp for the 1.0 Vpp operating mode. (has been changed to align the maximum signal amplitude test with the droop test levels)

Proposed Response Response Status **W**

PROPOSED ACCEPT IN PRINCIPLE.
 Align with resolution of comment 270

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

Cl 147 **SC 147.1** **P 129** **L 8** # **472**
Brandt, David Rockwell Automation

Comment Type **E** **Comment Status** **D** **EZ**
Typo

SuggestedRemedy

Change from "PCS, and PMA" to "PCS and PMA"

Proposed Response **Response Status** **W**

PROPOSED ACCEPT.

Change "the PCS, and PMA sublayers" to "the PCS and PMA sublayers"

Cl 147 **SC 147.1** **P 129** **L 9** # **473**
Brandt, David Rockwell Automation

Comment Type **E** **Comment Status** **D** **EZ**
Typo

SuggestedRemedy

Change "fully functional and electrical specifications" to "full functional and electrical specifications"

Proposed Response **Response Status** **W**

PROPOSED ACCEPT.

Change "clause are fully functional and electrical" to "clause are full functional and electrical"

Cl 147 **SC 147.1** **P 129** **L 23** # **413**
Zimmerman, George CME Consulting et al

Comment Type **T** **Comment Status** **D** **EEE**
DME 10BASE-T1S is inherently energy efficient. No need to transmit separate LPIs.

SuggestedRemedy

Delete editor's note. Insert New paragraph in its place. "DME-based 10BASE-T1S is silent during Idle symbols making it inherently energy efficient and without the need for a separate low-power-idle (LPI) mode such as is defined in Clause 78."

Proposed Response **Response Status** **W**

PROPOSED ACCEPT IN PRINCIPLE.

2 changes:

- Delete editor's note.

- Insert New paragraph in its place: "DME-based 10BASE-T1S is silent during Idle symbols making it inherently energy efficient and without the need for a separate low-power-idle (LPI) mode, as is defined in Clause 78."

Cl 147 **SC 147.1** **P 129** **L 28** # **451**
Pannell, Don NXP (donald.pannell@

Comment Type **E** **Comment Status** **D** **Editorial**

"An optional support for PHY Level Collision Avoidance (PLCA) functions, described in Clause 148, is also specified in this clause."

SuggestedRemedy

Change to "Optional support for PHY Level Collision Avoidance (PLCA) functions are described in Sub-clause 147.3.7 and Clause 148."

Proposed Response **Response Status** **W**

PROPOSED ACCEPT IN PRINCIPLE.

Change this:

====

An optional support for PHY Level Collision Avoidance (PLCA) functions, described in Clause 148, is also specified in this clause.

====

to this:

====

Optional support for PHY Level Collision Avoidance (PLCA) functions are described in 147.3.7 and Clause 148.

====

Cl 147 **SC 147.1.1** **P 129** **L 36** # **360**
iyer, venkat microchip

Comment Type **T** **Comment Status** **D** **Autoneg**

as discussed in ad-hoc, autonegotiation is N/A for half duplex or multi-drop

SuggestedRemedy

Add (Auto negotiation is not defined 10BASE-T1S PHY operating in half-duplex mode or multi-drop situation)

Proposed Response **Response Status** **W**

PROPOSED ACCEPT IN PRINCIPLE.

Change this:

====

defined in Clause 22.

====

to this:

====

defined in Clause 22. Auto negotiation is not defined 10BASE-T1S PHY operating in full-duplex point-to-point mode or multi-drop situation.

====

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

Cl 147 SC 147.1.2 P 129 L 44 # 477
Brandt, David Rockwell Automation

Comment Type E Comment Status D TBDs

TBDs exist. Page 151 line 1 already indicates "up to at least eight nodes and 25 m of cabling".

SuggestedRemedy

Replace paragraph:

Additionally, the 10BASE-T1S PHY may operate using half-duplex multidrop communications on a mixing segment using a single twisted-pair copper cable interconnecting up to at least TBD in-line PHYs with up to 10 cm stubs and supporting up to at least TBD meters, achieving an overall effective rate of 10 Mb/s, shared among the nodes.

With:

Additionally, the 10BASE-T1S PHY may operate using half-duplex multidrop communications on a mixing segment using a single twisted-pair copper cable, interconnecting up to at least eight PHYs, to a trunk up to at least 25 m. PHYs may be attached in-line with the trunk or at the end of stubs up to 10 cm. An overall effective rate of 10 Mb/s is shared among the nodes. Larger PHY count and reach are desirable in some applications and are not precluded.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Change this:

====

Additionally, the 10BASE-T1S PHY may operate using half-duplex multidrop communications on a mixing segment using a single twisted-pair copper cable interconnecting up to at least TBD in-line PHYs with up to 10 cm stubs and supporting up to at least TBD meters, achieving an overall effective rate of 10 Mb/s, shared among the nodes.

====

to this:

====

Additionally, the 10BASE-T1S PHY may operate using half-duplex multidrop communications on a mixing segment using a single twisted-pair copper cable, interconnecting up to at least 8 PHYs, to a trunk up to at least 25 m. PHYs may be attached in-line with the trunk or at the end of stubs up to 10 cm. An overall effective rate of 10 Mb/s is shared among the nodes. Larger PHY count and reach may be achieved provided the mixing segment specifications in 147.8 are met.

====

Note: spaces between values and units is to be non-breaking

Cl 147 SC 147.1.2 P 129 L 45 # 439
Pannell, Don NXP (donald.pannell@

Comment Type TR Comment Status D TBDs

Page 151 sub-clause 147.8 line 1 states "A mixing segment is specified based on automotive cabling supporting up to at least eight nodes and 25 m of cabling". But page 129 sub-clause 147.1.2 line 45 states "up to at least TBD in-line PHYs with up to 10 cm stubs and supporting at least TBD meters"

SuggestedRemedy

Get rid of the TBD's on page 129 by referring to section 147.8 so these numbers are only in one place in the document (so if they change you will change all occurrences).

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Already dealt with by #414

Cl 147 SC 147.1.2 P 129 L 45 # 414
Zimmerman, George CME Consulting et al

Comment Type E Comment Status D TBDs

"interconnecting up to at least TBD in-line PHYs with up to 10 cm stubs and supporting up to at least TBD meters," - has been defined as 8 in-line PHYs with up to at least 25 meters

SuggestedRemedy

Change to read "interconnecting up to at least 8 in-line PHYs with up to 10 cm stubs and supporting up to at least 25 meters,"

Proposed Response Response Status W

PROPOSED ACCEPT.

Change this:

====

interconnecting up to at least TBD in-line PHYs with up to 10 cm stubs and supporting up to at least TBD meters,

====

to this:

====

interconnecting up to at least 8 in-line PHYs with up to 10 cm stubs and supporting up to at least 25 meters,

====

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

CI 147 SC 147.1.2 P 129 L 53 # 415
Zimmerman, George CME Consulting et al

Comment Type T Comment Status D EZ

"12.5 MBd rate (+/- TBD). " - rate is redundant (Bd is rate), and tolerance is inappropriate here - this is not the specification for the signalling rate - this is general description.

SuggestedRemedy

Change "12.5 MBd rate (+/- TBD)." to "12.5 MBd."

Proposed Response Response Status W

PROPOSED ACCEPT.
Change "12.5 MBd rate" to "12.5 MBd"

CI 147 SC 147.1.2 P 129 L 53 # 317
Orzelli, Antonio Canova Tech

Comment Type T Comment Status D Scrambler

Add scrambler proposal as in
http://www.ieee802.org/3/cg/public/adhoc/beruto_3cg_scrambler.pdf

SuggestedRemedy

change "at a 12.5 MBd rate ($\pm$ TBD). 4B/5B encoding is used to further improve EMC performance" with "at a 12.5 MBd rate ($\pm$ TBD). A 17-bit self-synchronizing scrambler is used to improve the EMC performance. 4B/5B encoding is used to further improve EMC performance"

See attached PDF (slide 3).

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.
TASK FORCE TO DISCUSS
#scrambler (THIS is the MASTER)
Carry out first (red-ish) block of changes shown at page 3/17 of beruto_3cg_29_0418.pdf

CI 147 SC 147.1.2 P 130 L 2 # 318
Orzelli, Antonio Canova Tech

Comment Type T Comment Status D Scrambler

Add scrambler proposal as in
http://www.ieee802.org/3/cg/public/adhoc/beruto_3cg_scrambler.pdf

SuggestedRemedy

change "The 4B/5B mapping is contained in the PCS" with "The 4B/5B mapping and the scrambler are contained in the PCS"

See attached PDF (slide 3).

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.
TASK FORCE TO DISCUSS
#scrambler (MASTER is #317)
Carry out second (red-ish) block of changes shown at page 3/17 of beruto_3cg_29_0418.pdf

CI 147 SC 147.1.2 P 130 L 3 # 474
Brandt, David Rockwell Automation

Comment Type E Comment Status D EZ

Wrong link

SuggestedRemedy

Change text and link from 147.5 to 147.4.

Proposed Response Response Status W

PROPOSED ACCEPT.
Change link "147.5" to "147.4"

CI 147 SC 147.2 P 131 L 4 # 452
Pannell, Don NXP (donald.pannell@

Comment Type TR Comment Status D EZ

Right side of the figure is cut off.

SuggestedRemedy

Readjust the size of the figure so that all of it's text shows.

Proposed Response Response Status W

PROPOSED ACCEPT.
Fix figure

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

Cl 147 SC Figure 147-2 P 131 L 5 # 475
Brandt, David Rockwell Automation

Comment Type E Comment Status D EZ

Figure is chopped off at right

SuggestedRemedy

Adjust figure

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Already dealt with by #452

Cl 147 SC 147.2 P 131 L 37 # 429
Pannell, Don NXP (donald.pannell@

Comment Type E Comment Status D Editorial

"The 10BASE-T1S PHY used the Media Independent Interface (MII) as specified in Clause 22 instead of a Gigabit Media Independent Interface (GMII)."

SuggestedRemedy

Change to "The 10BASE-T1S PHY used the Media Independent Interface (MII) as specified in Clause 22." Don't need to specify what it isn't. That list would be huge.

Proposed Response Response Status W

PROPOSED ACCEPT.

Change "The 10BASE-T1S PHY uses the Media Independent Interface (MII) as specified in Clause 22 instead of a Gigabit Media Independent Interface (GMII)." to "The 10BASE-T1S PHY uses the Media Independent Interface (MII) as specified in Clause 22."

Cl 147 SC 147.3.2.2 P 133 L 29 # 457
Brandt, David Rockwell Automation

Comment Type T Comment Status D PCS

PCS signal plca_en lacks reference to management interface register

SuggestedRemedy

Replace:

The plca_en signal described in 148.4.5.2.

With:

The plca_en signal controls the optional PLCA function in the PCS. This signal is set to ON when PLCA ability bit in MDIO register 3.2292.13 is set to a one and PLCA enable bit in MDIO register 3.2291.13 is set to a one. This signal is set to OFF when PLCA ability bit in MDIO register 3.2292.13 is set to a zero or PLCA enable bit in MDIO register 3.2291.13 is set to a zero.

Values: ON or OFF

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Change this:

====

The plca_en signal described in 148.4.5.2.

When the optional PLCA RS is not implemented, plca_en shall be set to OFF

====

to this:

====

The plca_en signal, described in 148.4.5.2, controls the optional PLCA function in the PCS. When PLCA is implemented and both, the "PLCA ability" in MDIO register 3.2292.13 and "PLCA enable" bit in MDIO register 3.2291.13, bits are set, plca_en shall be set to ON, otherwise it shall be set of OFF.

Values: ON or OFF

====

Note: MDI registers may need to be links to C45

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

CI 147 SC 147.3.2.1 P 133 L 52 # 368
CORDARO, Jay BROADCOM

Comment Type TR Comment Status D Scrambler

if proposed preamble adopted, replace the paragraph beginning at line 52 with the following:

SuggestedRemedy

Upon the assertion of TX_EN, the PCS Transmit function passes the Ga32 SYNC word to the PMA, which replaces the first 16 bits of the preamble. After the Ga32 SYNC word, 24 bits of data are transmitted. It is recommended the data be random to prevent the multiplicative scrambler from aligning with the payload and causing a peak emissions issue. Twenty-four bit times after Ga32 SYNC word, if OAM is supported, two OAM octets are transmitted into 5B symbols using the encoding rules specified in Table 147-1. After the two OAM words, starting with the 7th preamble octet, TXD<3:0> is encoded into 5B symbols using encoding rules specified in Table 147-1, until TX_EN is deasserted. If the PMA does not support OAM transmission, 24 bit times after the Ga32 SYNC word, TXD<3:0> is encoded into 5B symbols using encoding rules specified in Table 147-1, until TX_EN is deasserted.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

TASK FORCE TO DISCUSS

#Golay (MASTER is #369)

NOTE: Consider comments #388 and #393 immediately after resolution of all #Golay comments

Replace this:

=====

Upon the assertion of TX_EN, the PCS Transmit function passes a group of three SYNC symbols to the PMA, followed by an SSD, which replaces the first 16 bits of the preamble. Following SSD, TXD<3:0> is encoded into 5B symbols using encoding rules specified in Table 147-1, until TX_EN is deasserted.

=====

with this:

=====

Upon the assertion of TX_EN, the PCS Transmit function passes the Ga32 SYNC word to the PMA, which replaces the first 16 bits of the preamble. After the Ga32 SYNC word, 24 bits of data are transmitted. It is recommended the data be random to prevent the multiplicative scrambler from aligning with the payload and causing a peak emissions issue. Twenty-four bit times after Ga32 SYNC word, if OAM is supported, two OAM octets are transmitted into 5B symbols using the encoding rules specified in Table 147-1. After the two OAM words, starting with the 7th preamble octet, TXD<3:0> is encoded into 5B symbols using encoding rules specified in Table 147-1, until TX_EN is deasserted. If the PMA does not support OAM transmission, 24 bit times after the Ga32 SYNC word, TXD<3:0> is encoded into 5B symbols using encoding rules specified in Table 147-1, until

TX_EN is deasserted.

=====

CI 147 SC 147.3.2.1 P 134 L 2 # 367
CORDARO, Jay BROADCOM

Comment Type TR Comment Status D Scrambler

Add support for end delimiter for differential detection

SuggestedRemedy

Replace text as follows: "Following the deassertion of TX_EN, the PCS Transmit generates a special code ESD, followed by either ESDOK or ESDERR when a transmit error is encountered. ESDOK or ESDERR followed by a DME zero to assist in differential decoding.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

TASK FORCE TO DISCUSS

#DME_delimiter (MASTER is #366)

Replace this:

=====

Following the deassertion of TX_EN, the PCS Transmit generates a special code ESD, followed by either ESDOK or ESDERR when a transmit error is encountered.

=====

with this:

=====

Following the deassertion of TX_EN, the PCS Transmit generates a special code ESD, followed by either ESDOK or ESDERR when a transmit error is encountered. ESDOK or ESDERR followed by a DME zero to assist in differential decoding.

=====

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

CI 147 SC 147.3.2.2 P 135 L 9 # 369
CORDARO, Jay BROADCOM

Comment Type TR Comment Status X Scrambler

If proposed preamble is adopted, replace current SYNC/SSD with proposed preamble text.

SuggestedRemedy

Replace "Sync and SSD" with Ga32 -- a 32 bit Sync word defined as [1 0 1 1 0 1 1 1 0 1 1 0 1 1 0 1 0 0 0 1 1 1 0 1 1 1 0 0 0] which is biphase modulated and transmitted from left to right, top to bottom. The timing for the SYNC word is T3 so the SYNC word fits in the first 16 bits of the preamble.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.
TASK FORCE TO DISCUSS
#Golay (THIS is the MASTER)
NOTE: Consider comments #388 and #393 immediately after resolution of all #Golay comments
3 changes:
- Replace "SYNC" with "Ga32, a 32 bit sync word defined as [1 0 1 1 0 1 1 1 0 1 1 0 1 1 1 0 1 1 0 0 0 1 1 1 0 1 1 1 0 0 0] which is biphase modulated and transmitted from left to right, top to bottom. The timing for the SYNC word is T3 so the SYNC word fits in the first 16 bits of the preamble.
- Remove "SSD"
- Remove "5B symbol defined as 'K' in 4B/5B encoding (see also Table 147-1)"

CI 147 SC 147.3.2.2 P 135 L 20 # 366
CORDARO, Jay BROADCOM

Comment Type TR Comment Status D Scrambler

Add support for end delimiter for differential detection

SuggestedRemedy

DZ - a symbol consisting of a DME zero transmitted after final 4B/5B encoded R or H symbol. The purpose of this symbol is to assist in differential decoding of the DME encoded 10BASE-T1S packet.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.
TASK FORCE TO DISCUSS
#DME_delimiter (THIS is the MASTER)
2 changes:
- Place the following new paragraph between the paragraph that ends P134/2 and the one that begins P134/4:
====
The 10BASE-T1S has one special 5B symbol 'I' (binary vector of 1,1,1,1,1) which represents SILENCE. When the PHY is operating in half-duplex multidrop mode, the PMA Transmit functions shall put the PMD into a high impedance state on reception of this symbol from the PCS Transmit. When operating in point-to-point mode, the PMA shall drive a zero voltage level on the line on receipt of the 'I' symbol.
====
Note: check capitalization to harmonize with the rest of the text
- Insert the following new variable definition after that of tx_sym in sub-clause "147.3.2.2 Variables":
====
tx_dz
-> An end delimiter consisting of a logical zero.
====
Note (on both changes): see also page 3 of 3 of figures_for_Gergely_2_1.docx from Mr. Cordaro

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

CI 147 SC 147.3.2.3 P 135 L 27 # 319
Orzelli, Antonio Canova Tech

Comment Type T Comment Status D Scrambler

Add scrambler proposal as in
http://www.ieee802.org/3/cg/public/adhoc/beruto_3cg_scrambler.pdf

SuggestedRemedy

change ENCODE function description from "In the PCS transmit process, this function takes as its arguments the pcs_txd input data and returns the corresponding 5B symbol as defined in Table 147-1." to "In the PCS transmit process, this function takes as its arguments one data nibble, scrambles it into Sdn[3:0] as defined in 147.3.2.5 and returns the corresponding 5B symbol as defined in Table 147-1."

See attached PDF (slide 4).

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.
TASK FORCE TO DISCUSS
#scrambler (MASTER is #317)
Carry out first (red) block of changes shown at page 4/17 of beruto_3cg_29_0418.pdf
Note: mind the link

CI 147 SC 147.3.2.3 P 135 L 36 # 370
CORDARO, Jay BROADCOM

Comment Type TR Comment Status D Scrambler

If proposed preamble is adopted, remove 4B/5B code words for JK in 4B5B Encoding table

SuggestedRemedy

remove J and K rows from Table 147-1-4B/5B Encoding

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.
TASK FORCE TO DISCUSS
#Golay (MASTER is #369)
NOTE: Consider comments #388 and #393 immediately after resolution of all #Golay comments
2 changes:
- Remove "I N/A 11111 SILENCE" from "Table 147-1-4B/5B Encoding"
- Remove "J N/A 11000 SYNC" from "Table 147-1-4B/5B Encoding"

CI 147 SC 147.3.2.3 P 136 L 5 # 371
CORDARO, Jay BROADCOM

Comment Type TR Comment Status D Scrambler

If proposed preamble is adopted, remove 4B/5B code word for BEACON in 4B5B Encoding table

SuggestedRemedy

remove N row from Table 147-1-4B/5B Encoding

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.
TASK FORCE TO DISCUSS
#Golay (MASTER is #369)
NOTE: Consider comments #388 and #393 immediately after resolution of all #Golay comments
Remove "N N/A 01000 BEACON" from "Table 147-1-4B/5B Encoding"

CI 147 SC 147.3.2.3 P 136 L 25 # 372
CORDARO, Jay BROADCOM

Comment Type TR Comment Status D Scrambler

If proposed preamble adopted, add a table (Table 147-2) with 3 rows and 3 columns

SuggestedRemedy

create table with 3 rows:
Row 1: Name|Sequence |Special
Function
Row2: Ga32| 1 0 1 1 0 1 1 1 1 0 1 1 0 1 1 0 1 0 0 0 1 1 1 1 0 1 1 1 0 0 0 | SYNC
Row3: Gb32| 0 0 0 1 1 1 0 1 0 0 0 1 1 1 0 1 1 1 0 1 1 0 1 0 0 0 1 0 0 1 0 | BEACON
below table Note: Timing for each symbol in Ga32 and Gb32 is T3 so they fit into 16 T2 data bits as shown in Table 147-2

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.
TASK FORCE TO DISCUSS
#Golay (MASTER is #369)
NOTE: Consider comments #388 and #393 immediately after resolution of all #Golay comments
2 changes:
- Create a new table as shown at page 5/5 of figures_for_Gergely.docx
- Put the note shown at page 5/5 of figures_for_Gergely.docx underneath in a non-breaking manner
Note: in case of final acceptabnce, check preferred/best place for this with Mr. Cordaro

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

CI 147 SC 147.3.2.3 P 137 L 18 # 373
CORDARO, Jay BROADCOM

Comment Type TR Comment Status D Scrambler

Replace Figure 147-4 with revised figure indicating transition from SILENT to SYNC (transmitting Ga32) to "A"

SuggestedRemedy

replace figure 147-4 with proposed figure

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.
TASK FORCE TO DISCUSS
#Golay (MASTER is #369)
NOTE: Consider comments #388 and #393 immediately after resolution of all #Golay comments
Replace current figure 147-4 by the figure shown at page 4/5 of figures_for_Gergely.docx

CI 147 SC 147.3.2.3 P 138 L 32 # 374
CORDARO, Jay BROADCOM

Comment Type TR Comment Status D Scrambler

Add a final state for both BAD_ESD and GOOD_ESD to transmit DZ for differential detection

SuggestedRemedy

replace figure Figure 147-5 with slightly revised figure to show DZ appended after GOOD_ESD and BAD_ESD.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.
TASK FORCE TO DISCUSS
#DME_delimiter (MASTER is #366)
Replace figure 147-5 with the one at page 2 of 3 of figures_for_Gergely_2_1.docx from Mr. Cordaro

CI 147 SC 147.3.2.5 P 138 L 44 # 320
Orzelli, Antonio Canova Tech

Comment Type T Comment Status D Scrambler

Add scrambler proposal as in
http://www.ieee802.org/3/cg/public/adhoc/beruto_3cg_scrambler.pdf

SuggestedRemedy

Add paragraph 147.3.2.5 as reported in attached PDF (slide 5)

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.
TASK FORCE TO DISCUSS
#scrambler (MASTER is #317)
3 changes:
- Add all red text shown at page 5/17 of beruto_3cg_29_0418.pdf
- Add new (named) formula from the same page
- Add new figure from the same page and make sure text reference to it is correct

CI 147 SC 147.3.3 P 139 L 1 # 375
CORDARO, Jay BROADCOM

Comment Type TR Comment Status D Scrambler

if proposed preamble accepted text for PCS RX and figure needs to change

SuggestedRemedy

The finite state machine defined in Figure 147-6 is triggered by the detection of Ga32 SYNC symbol from the PMA receive function.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.
TASK FORCE TO DISCUSS
#Golay (MASTER is #369)
NOTE: Consider comments #388 and #393 immediately after resolution of all #Golay comments
Replace current figure 147-6 by the figure shown at page 4/5 of figures_for_Gergely.docx

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

Cl 147 SC 147.3.3.1 P 139 L 25 # 322
Orzelli, Antonio Canova Tech

Comment Type T Comment Status D Scrambler

Add scrambler proposal as in
http://www.ieee802.org/3/cg/public/adhoc/beruto_3cg_scrambler.pdf

SuggestedRemedy

Add variable "precnt" with description "counter for preamble regeneration"

See attached PDF (slide 7).

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.
TASK FORCE TO DISCUSS
#scrambler (MASTER is #317)
Add the red-ish text shown at page 7/17 of beruto_3cg_29_0418.pdf

Cl 147 SC 147.3.3.2 P 139 L 42 # 321
Orzelli, Antonio Canova Tech

Comment Type T Comment Status D Scrambler

Add scrambler proposal as in
http://www.ieee802.org/3/cg/public/adhoc/beruto_3cg_scrambler.pdf

SuggestedRemedy

change DECODE function description from "In the PCS Receive process, this function takes as its arguments the RX input data from PMA and returns the corresponding 4B MII data as defined in Table 147-1. If a violation of the encoding rules is detected, PCS Receive asserts the signal RX_ER for at least one symbol period" to "In the PCS Receive process, this function takes as its arguments one 5B symbol, decodes the corresponding nibble as defined in Table 147-1 and returns the descrambled result as defined in 147.3.3.4. If a violation of the encoding rules is detected, PCS Receive asserts the signal RX_ER for at least one symbol period"

See attached PDF (slide 6).

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.
TASK FORCE TO DISCUSS
#scrambler (MASTER is #317)
Carry out all red changes shown at page 6/17 of beruto_3cg_29_0418.pdf
Note: mind the links

Cl 147 SC 147.3.3.4 P 139 L 51 # 323
Orzelli, Antonio Canova Tech

Comment Type T Comment Status D Scrambler

Add scrambler proposal as in
http://www.ieee802.org/3/cg/public/adhoc/beruto_3cg_scrambler.pdf

SuggestedRemedy

Add paragraph 147.3.3.4 as reported in attached PDF (slide 8)

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.
TASK FORCE TO DISCUSS
#scrambler (MASTER is #317)
2 changes:
- Add all red text shown at page 8/17 of beruto_3cg_29_0418.pdf
- Add new figure from the same page and make sure text reference to it is correct

Cl 147 SC 147.3.3.3 P 140 L # 361
iyer, venkat microchip

Comment Type T Comment Status D State Diagram

PRE2/3 actions need to be filled in

SuggestedRemedy

copy actions from PRE1

Proposed Response Response Status W

PROPOSED REJECT.
It appears in IEEE state diagram style definition you shall not repeat assignments unless you want to "refresh" the variable (for variables that do something on write despite the value that is being written) but indeed this is not the case.

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

CI 147 SC 147.3.3 P 140 L 1 # 316
Orzelli, Antonio Canova Tech

Comment Type T Comment Status D State Diagram

In figure 147-6 some errors occurred when porting the picture to Frame from draft 1.0

SuggestedRemedy

In figure 147-6 substitute "pcs_rxer <= TRUE" with "pcs_rxer <= FALSE" in BAD_SSD state

In figure 147-6 add missing transition from WAIT_SSD state to WAIT_SSD state with "ELSE" condition.

See attached PDF (slide 2).

Proposed Response Response Status W

PROPOSED ACCEPT.

2 changes to figure 147-6:

- Change "pcs_rxer <= TRUE" to "pcs_rxer <= FALSE" in BAD_SSD
- Add missing transition from WAIT_SSD state to WAIT_SSD state with label "ELSE"

CI 147 SC 147.3.3 P 140 L 17 # 376
CORDARO, Jay BROADCOM

Comment Type TR Comment Status X Scrambler

if proposed preamble accepted text for PCS RX and figure needs to change

SuggestedRemedy

replace figure Figure 147-6 with proposed figure

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

TASK FORCE TO DISCUSS

#Golay (MASTER is #369)

NOTE: Consider comments #388 and #393 immediately after resolution of all #Golay comments

Replace current figure 147-6 by the 2 figures shown at pages 2/5 and 3/5

figures_for_Gergely.docx

Note: in case of acceptance, consider merging these 2 into 1, or even merging 147-7 into this merged 147-7, as otherwise optionally requested by #324

CI 147 SC 147.3.3 P 140 L 25 # 324
Orzelli, Antonio Canova Tech

Comment Type T Comment Status D Scrambler

Add scrambler proposal as in

http://www.ieee802.org/3/cg/public/adhoc/beruto_3cg_scrambler.pdf

SuggestedRemedy

In figure 147-6 add "precnt <= 0" in state WAIT_SSD.

In figure 147-6 change state "PRE1" in state "PRE"; add "precnt <= precnt + 1" in state PRE; add transition from PRE to PRE with condition "RSCD * precnt ? 9"; add transition from PRE to "A" with condition "RSCD * precnt = 9".

In figure 147-6 remove state PRE2 and state PRE3 with relative transitions.

In figure 147-7 remove state PRE3 with relative transitions.

In figure 147-7 add transition from "A" to DATA.

Add editorial note: "figure 147-6 and 147-7 could be merged".

See attached PDF (slide 9).

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

TASK FORCE TO DISCUSS

#scrambler (MASTER is #317)

2 changes:

- Carry out all red changes shown at page 9/17 of beruto_3cg_29_0418.pdf
- If merging 147-6 and 147-7 is possible (= fitst), do it

CI 147 SC 147.3.3.3 P 141 L # 362
iyer, venkat microchip

Comment Type T Comment Status D State Diagram

PRE4 actions need to be filled in

SuggestedRemedy

copy actions from PRE1

Proposed Response Response Status W

PROPOSED REJECT.

Already dealt with by #361

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

CI **147** SC **147.3.3** P **141** L **8** # **377**
CORDARO, Jay BROADCOM

Comment Type **TR** Comment Status **X** Scrambler

if proposed preamble accepted text for PCS RX and figure needs to change

SuggestedRemedy

replace figure Figure 147-7 with proposed figure

Proposed Response Response Status **W**

PROPOSED ACCEPT IN PRINCIPLE.

TASK FORCE TO DISCUSS

#Golay (MASTER is #369)

NOTE: Consider comments #388 and #393 immediately after resolution of all #Golay comments

Replace current figure 147-7 by the figure shown at page 1/5 of figures_for_Gergely.docx

CI **147** SC **147.3.3.3** P **141** L **23** # **357**
iyer, venkat microchip

Comment Type **T** Comment Status **D** PCS

Exit condition from DATA to GOOD_ESD should look at RX(n-2) for ESD and RX(n-1) for ESDOK

SuggestedRemedy

change as indicated in comment

Proposed Response Response Status **W**

PROPOSED REJECT.

See http://www.ieee802.org/3/cg/public/Jan2018/beruto_3cg_01_0118.pdf slides 2 & 3.

The difference between the two branches is to maintain decoding on an even nibble boundary:

In DATA state we're decoding RXn-4

- GOOD ESD case: It is correct to exit when the {ESD, ESDOK} symbols are found in RXn-3 and RXn-2 respectively, otherwise you are going to miss the last data symbols.

- BAD ESD case: The MAC expects the PHY to always decode an even number of nibbles, otherwise an alignment error is reported, and therefore, we look for an ESDERR one symbol earlier than in the GOOD ESD case and stop decoding on an even boundary.

CI **147** SC **147.3.7.1** P **143** L **10** # **430**
Pannell, Don NXP (donald.pannell@

Comment Type **TR** Comment Status **D** PLCA

"When a sequence of at least two consecutive 'N' symbols is received" & on page 168 line 21 Sub-clause 148.4.5.3 states that the BEACON_TIMER's "Duration shall be enough to allow all PHYs to properly recover the BEACON indication."

SuggestedRemedy

Page 143's text appears to be an indirect 'shall' as an extension of the previous paragraph's 'shall'. But page 168's text's 'shall' does not state what is required for "all PHYs to properly recover the BEACON indication". This should have a minimum value of 15 bit times so that at least 3 BEACON symbols are transmitted during each BEACON signal.

Proposed Response Response Status **W**

PROPOSED ACCEPT IN PRINCIPLE.

ACCEPT IN PRINCIPLE

Change this:

====

Times the duration of the BEACON signal. Timer value shall be defined within specific Reconciliation sublayers. Duration shall be enough to allow all PHYs to properly recover the BEACON indication.

====

to this:

====

Times the duration of the BEACON signal. Timer value shall be 20 bit times.

====

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

CI 147 SC 147.3.7.1 P 143 L 10 # 378
CORDARO, Jay BROADCOM

Comment Type TR Comment Status D Scrambler
see comment on row 13, above

SuggestedRemedy

When a Gb32 BEACON is received (see Table 147-2), the MII signals RX_DV, RX_ER and RXD shall be set to the BEACON indication as shown in Table 22-2, overriding the current state. Override shall cease as soon as the the BEACON timer has expired.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.
TASK FORCE TO DISCUSS
#Golay (MASTER is #369)
NOTE: Consider comments #388 and #393 immediately after resolution of all #Golay comments
Replace the following paragraph:

====
When a sequence of at least two consecutive 'N' symbols is received (see Table 147-1), the MII signals RX_DV, RX_ER and RXD shall be set to the BEACON indication as shown in Table 22-2, overriding the current state. Override shall cease as soon as the currently received symbol is anything other than a 'N' code.

====
by this:

====
When a Gb32 BEACON is received (see Table 147-2), the MII signals RX_DV, RX_ER and RXD shall be set to the BEACON indication as shown in Table 22-2, overriding the current state. Override shall cease as soon as the BEACON timer has expired.

====
Note: mind the 2 table links

CI 147 SC 147.3.7.2 P 143 L 19 # 379
CORDARO, Jay BROADCOM

Comment Type TR Comment Status D Scrambler
see comment on row 13, above

SuggestedRemedy

When a Ga32 SYNC signal is detected, the MII signals RX_DV, RX_ER and RXD shall be set to the COMMIT indication as shown in Table 22-2, overriding the current state. Override shall cease as soon as SYNC timer has expired.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.
TASK FORCE TO DISCUSS
#Golay (MASTER is #369)
NOTE: Consider comments #388 and #393 immediately after resolution of all #Golay comments
Replace the following paragraph:

====
When a sequence of at least two consecutive 'J' symbols is received (see Table 147-1), the MII signals RX_DV, RX_ER and RXD shall be set to the COMMIT indication as shown in Table 22-2, overriding the current state. Override shall cease as soon as the currently received symbol is anything other than a 'J' code.

====
by this:

====
When a Ga32 SYNC signal is detected, the MII signals RX_DV, RX_ER and RXD shall be set to the COMMIT indication as shown in Table 22-2, overriding the current state. Override shall cease as soon as SYNC timer has expired.

====
Note: mind the table link

CI 147 SC 147.4.2 P 144 L 42 # 433
Pannell, Don NXP (donald.pannell@

Comment Type TR Comment Status D PMA
Parameter T1's description in Table 147-2 ends with an "*".

SuggestedRemedy

Remove the "*" or complete the description.

Proposed Response Response Status W

PROPOSED ACCEPT.
Change "Delay between transmissions *" to "Delay between transmissions"

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

CI 147 SC 147.4.2 P 144 L 50 # 416
Zimmerman, George CME Consulting et al

Comment Type E Comment Status D Editorial

Editor's note is unclear in itself and adds to lack of clarity - just what requirement is meant? The timing requirements belong in the PMA.

SuggestedRemedy

Delete editors note.

Proposed Response Response Status W

PROPOSED ACCEPT.

CI 147 SC 147.4.25 P 145 L 15 # 380
CORDARO, Jay BROADCOM

Comment Type TR Comment Status D Scrambler

replace figure 147-9 if proposed preamble accepted with figure which will be provided which shows Ga32 preamble with DME encoded DATA and then I (SILENCE)

SuggestedRemedy

Replace Figure 147-9

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.
TASK FORCE TO DISCUSS

#Golay (MASTER is #369)

NOTE: Consider comments #388 and #393 immediately after resolution of all #Golay comments

Replace figure 147-9 with the one at page 1 of 3 of figures_for_Gergely_2_1.docx from Mr. Cordaro

Note: the "don't care" (transient) states under "." and "DATA" can use any other (unambiguous) symbol, according to eh 802.3 habits and the capabilities of Frame

CI 147 SC 147.4.2 P 145 L 16 # 434
Pannell, Don NXP (donald.pannell@

Comment Type TR Comment Status D PMA

Figure 147-9, while it is just an example, is confusing when the figure goes from 'I' to only one 'J' and then the 'K' when sub-clause 147.4.3 line 39 (just below the figure) indicates that "At the start of transmission, the symbol sequence J/J/J/K" is used.

SuggestedRemedy

Fix the figure.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

3 changes:

- Change the "K (10001)" to "J (11000)"

- Change the waveform below ex-K/now-J to reflect 000111

- Move the arrow "Positive differential voltage" to the 1st or 3rd bit of ex-K/now-J

CI 147 SC 147.4.3 P 145 L 31 # 298
Maguire, Valerie The Siemon Company

Comment Type E Comment Status D Editorial

Align media references with revised objectives.

SuggestedRemedy

Replace, "single pair" with "single balanced pair"

Proposed Response Response Status W

PROPOSED ACCEPT.

Change "on the single pair into" to "on the single balanced pair into"

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

CI 147 SC 147.4.3 P 145 L 35 # 437
Pannell, Don NXP (donald.pannell@

Comment Type TR Comment Status D PMA

Line 35 states "The PMA receive function shall recover encoded clock" and line 39 states "the sequence J/J/J/K". "is meant to allow the receiver to achieve such synchronization." It is not clear that all the reciever's PPL's will be able to lock their clocks such that no more than a single 'J' symbol is missed (i.e., in 1 symbol time). Consider the maximum number of PHYs on the net (say 16) and all are quiet. The only clock comes from the BEACON which is separated by 16 x 200 ns (as no one sends anything during idles). When some other PHY wants to Tx, all the other PHY's must lock to the Tx PHY's clock. In 10BASE-T the 7 byte preamble is used for this purpose and most of the preable time was needed in the Rx PHY to prevent CRC errors in the received frame.

SuggestedRemedy

The 'J/K' Start of Stream Delimiter was added in 100BASE-TX where the size of the preamble was not as critical since the idle symbols were constantly transmitted allowing the clocks to always remain locked. These active idle times are the reason Energy Efficient Ethernet (EEE) was not needed for 10BASE-T, but was for any faster PHYs. Where is the analysis that shows no more than one 'J' symbol will ever be lost and that that is suficient to lock all PHYs on the shared media? At the very least add an SSD_TIMER in sub-clause 148.4.5.4 that defines in symbol increments how many 'J's should be transmitted at the start of the MAC's preamble before a 'K' is inserted. Valid #'s are 0 (no SSD), 1, 3, 5, 7, 9, 11). Or removed the SSD as 10BASE-T does not have this, & let the PHYs lock their clocks as done in 10BASE-T.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Replace the following sentences:

=====

5B boundary. At the start of each transmission, the symbol sequence J/J/J/K which replaces the first 20 bit of packet preamble is meant to allow the receiver to achieve such synchronization.

=====

by these:

=====

5B boundary within 1.2 us.

=====

Note: use Greek small mu instead of u

CI 147 SC 147.4.3 P 145 L 39 # 436
Pannell, Don NXP (donald.pannell@

Comment Type TR Comment Status D PMA

Line 39 states "which replaces the first 20 bit of packet preamble". But the preamble from the MAC's point of view is 4 bit nibbles.

SuggestedRemedy

To make this clear change "the first 20 bit of packet preamble" with "the first 20 bits (in the 5b space) of packet preamble".

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Change "the first 20 bit of packet preamble" to "the first 20 bits (in the 5B domain) of the packet preamble"

CI 147 SC 147.4.3 P 145 L 39 # 381
CORDARO, Jay BROADCOM

Comment Type TR Comment Status D Scrambler

PMA receive updated to show Ga32 as preamble

SuggestedRemedy

At the start of each packet transmission, the Ga32 SYNC sequence replaces the first 16 bits of the the preamble. The Ga32 SYNC sequence is meant to allow the receiver to achieve robust synchronization

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

TASK FORCE TO DISCUSS

#Golay (MASTER is #369)

NOTE: Consider comments #388 and #393 immediately after resolution of all #Golay comments

Replace the following paragraph:

=====

At the start of each transmission, the symbol sequence J/J/J/K which replaces the first 20 bit of packet preamble is meant to allow the receiver to achieve such synchronization.

=====

by this:

=====

At the start of each packet transmission, the Ga32 SYNC sequence replaces the first 16 bits of the the preamble. The Ga32 SYNC sequence is meant to allow the receiver to achieve robust synchronization.

=====

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

Cl 147 SC 147.4.3 P 145 L 39 # 435
Pannell, Don NXP (donald.pannell@

Comment Type TR Comment Status D PMA

Line 35 states "The PMA receive function shall recover encoded clock" and line 39 states "the sequence J/J/J/K". "is meant to allow the receiver to achieve such synchronization." It is assumed "such synchronization" is referring to "recover encoded clock" but since these are two separate paragraphs it is not clear.

SuggestedRemedy

If this connection is correct, combine these two paragraphs into one.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Change this:

====

The PMA receive function shall recover encoded clock and data information from the DME encoded stream received at the MDI. In order to accomplish this task, the PMA Receive shall achieve proper synchronization on both the DME stream and the 5B boundary. At the start of each transmission, the symbol sequence J/J/J/K which replaces the first 20 bit of packet preamble is meant to allow the receiver to achieve such synchronization.

====

to this:

====

The PMA Receive function shall recover encoded clock and data information from the DME encoded stream received at the MDI. In order to accomplish this task, the PMA Receive shall achieve proper synchronization on both the DME stream and the 5B boundary, which is accomplished by the symbol sequence J/J/J/K replacing the first 20 bit of packet preamble.

====

Cl 147 SC 147.5 P 145 L 51 # 417
Zimmerman, George CME Consulting et al

Comment Type T Comment Status D PMA

Copy in text from Clauses 146.5.1.1 and 146.5.1.2 as 147.5.

SuggestedRemedy

Copy in text and structure from 146.5.1, 146.5.1.1 and 146.5.1.2 as 147.5.1, 147.5.1.1, and 147.5.1.2. Renumber subsequent clauses, starting with 147.5.2 (currently 147.5.1)

Proposed Response Response Status W

PROPOSED ACCEPT.

Cl 147 SC 147.5.1 P 146 L 16 # 358
iyer, venkat microchip

Comment Type T Comment Status D Test Mode

DME doesn't define +1, -1

SuggestedRemedy

replace with "repeatedly transmit DME encoded 1"

Proposed Response Response Status W

PROPOSED REJECT.

We are not talking about DME here

Cl 147 SC 147.5.1 P 146 L 19 # 359
iyer, venkat microchip

Comment Type T Comment Status D Test Mode

DME doesn't define +1, -1

SuggestedRemedy

remove test mode 2 since there is no droop with DME

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

There is droop in DME (there can be droop in 80ns).

Todo: add a new Editor's Note that says "Droop Specification is needed"

Cl 147 SC 147.5.1 P 146 L 22 # 419
Zimmerman, George CME Consulting et al

Comment Type T Comment Status D Test Mode

Generation of pseudorandom sequence is described in text that follows. Editor's note is no longer necessary

SuggestedRemedy

Delete editor's note

Proposed Response Response Status W

PROPOSED ACCEPT.

Delete the following editor's note:

====

Editor's Note (to be removed prior to draft 2.0):

How to generate the sequence below needs to be determined.

====

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

CI **147** SC **147.5.2** P **146** L **35** # **420**
Zimmerman, George CME Consulting et al

Comment Type **E** Comment Status **D** Editorial

The text on line 35 should refer to Figure 147-11.

SuggestedRemedy

Test fixtures: Change title of 147.5.2 to Test fixtures. Change text at line 35 from Figure 147-10 to Figure 147-11. Move anchor for Figure 147-11 to P146 L35.

Proposed Response Response Status **W**

PROPOSED ACCEPT.

3 changes:

- Change title of 147.5.2 from "Test fixture" to "Test fixtures"
- Change "shown in Figure 147-10, or" to "shown in Figure 147-11, or" (use llink)
- Move anchor of Figure 147-11 to 146/35

CI **147** SC **147.5.2** P **146** L **46** # **422**
Zimmerman, George CME Consulting et al

Comment Type **E** Comment Status **D** Editorial

The Transmitter test fixture for the PSD mask is shown in the PSD mask section. Figure 146-10 is a duplicate

SuggestedRemedy

Delete figure 146-10

Proposed Response Response Status **W**

PROPOSED ACCEPT IN PRINCIPLE.

Delete figure 147-10

Note: check renumbering to go OK

CI **147** SC **147.5.2.1** P **147** L **1** # **423**
Zimmerman, George CME Consulting et al

Comment Type **E** Comment Status **D** Editorial

147.5.2.1 should be 147.5.3, and 147.5.3 is blank.

SuggestedRemedy

Delete 147.5.2.1 and editor's note on P147 line 3-6. Change 147.5.3 (currently blank), so that 147.5.3 is Transmitter electrical specifications and 147.5.3.1 is Transmitter output voltage

Proposed Response Response Status **W**

PROPOSED ACCEPT IN PRINCIPLE.

3 changes to be done:

- Delete 147.5.2.1 along with the editor's note it has
- Change the number of 147.5.3 from "" to "Transmitter electrical specification"

CI **147** SC **147.5.3.1** P **147** L **21** # **421**
Zimmerman, George CME Consulting et al

Comment Type **T** Comment Status **D** Editorial

"Transmitter output voltage can be set..." There is only one transmitter output voltage setting.

SuggestedRemedy

Delete last 2 sentences of first paragraph of 147.5.3.1 (lines 21 - 23), starting with "Transmitter output voltage can be set...", and also delete editor's note on lines 44-48. Delete lines 1 through 3 on page 148."Fixed transmitter driving levels..." through "another interface."

Proposed Response Response Status **W**

PROPOSED ACCEPT.

2 changes:

- Remove this:

====

Transmitter output voltage can be set using the management interface or by hardware default set-up. Optionally, Auto-Negotiation can be used to find a common transmitter output voltage for the two PHYs.

====

- Remove editor's note from 147/44-48.

CI **147** SC **147.5.3.4** P **149** L **23** # **365**
CORDARO, Jay BROADCOM

Comment Type **TR** Comment Status **D** TBDs

± 100 ppm accuracy will not preclude operation of 802.1AS. Note to editor: Looser accuracy is possible especially with differential detection however it will preclude operation of 802.1AS.

SuggestedRemedy

The symbol transmission rate shall be within the range 12.5 MBd ± 100 ppm.

Proposed Response Response Status **W**

PROPOSED ACCEPT.

Change "12.5 MBd ± TBD ppm" to "12.5 MBd ± 100 ppm"

Note: all the spaces shall we non-breaking (see other similar formulae)

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

CI **147** SC **147.5.3.4** P **149** L **23** # **438**
Pannell, Don NXP (donald.pannell@

Comment Type **TR** Comment Status **D** PMA

"The symbol transmission rate shall be withing the range of 12.5 MBd +/- TDB ppm." does not help with network clock locking times.

SuggestedRemedy

Fill in the "TBD" with some target number that is cost effective so that network clock locking analysis can started. Us the same number from 10BASE-T or 100BASE-TX.

Proposed Response Response Status **W**

PROPOSED ACCEPT IN PRINCIPLE.
Already dealt with by #365

CI **147** SC **147.8.1** P **151** L **25** # **440**
Pannell, Don NXP (donald.pannell@

Comment Type **TR** Comment Status **D** PMD

"specified for link segments in 147.8.1" points to itself.

SuggestedRemedy

Add in the Return loss content and refer to it or change the 1st sentence to "specified for link segments as specified below".

Proposed Response Response Status **W**

PROPOSED ACCEPT IN PRINCIPLE.

3 changes to be done:

- Swap (the title of) "147.8.1 Return loss" and "147.8.2 Insertion loss", so that we get the following output:

====

"147.8.1 Insertion loss"

"147.8.2 Return loss"

====

- Change "segments in 147.8.1 at any" to "segments in 147.7.1 at any" (needs to be link)

- Change "segments in 147.8.2

between any" to "segments in 147.7.2

between any" (needs to be link)

CI **147** SC **147.8.1** P **151** L **26** # **479**
Brandt, David Rockwell Automation

Comment Type **T** Comment Status **D** PMD

Return Loss conditions are not specific enough. "All other MDI attachment points" does not say how many other attachment points, the physical location of the attachment points, and whether they are attached by stubs or in-line.
http://www.ieee802.org/3/cg/public/Mar2018/brandt_cg_01a_0318.pdf provides some guidance. Worst case should be determined.

SuggestedRemedy

Change from:

The mixing segment shall meet the return loss characteristics specified for link segments in 147.8.1 at any MDI attachment point, including ends of the mixing segment, with all other MDI attachment points disconnected or terminated in a minimum 10 kOhm impedance.

To:

The mixing segment shall meet the return loss characteristics specified for link segments in 147.8.1 at any MDI attachment point, including ends of the mixing segment, and at the end of stubs of length up to 10 cm, and with any combinations of up to at least seven other MDIs presenting minimum parallel load attached at any combination of permissible MDI attachment points. A reference configuration TBD is shown.

Proposed Response Response Status **W**

PROPOSED ACCEPT IN PRINCIPLE.

Change this:

====

The mixing segment shall meet the return loss characteristics specified for link segments in 147.8.1 at any MDI attachment point, including ends of the mixing segment, with all other MDI attachment points disconnected or terminated in a minimum 10 kOhm impedance.

====

to this:

====

The mixing segment shall meet the return loss characteristics specified for link segments in 147.8.1 at any MDI attachment point and with any combinations of up to at least seven other MDIs presenting minimum parallel load attached at any combination of permissible MDI attachment points.

====

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

CI **147** SC **147.8.2** P **151** L **32** # **480**
 Brandt, David Rockwell Automation

Comment Type **T** Comment Status **D** PMD

Insertion Loss conditions are not specific enough. "All other MDI attachment points" does not say how many other attachment points, the physical location of the attachment points, and whether they are attached by stubs or in-line.
http://www.ieee802.org/3/cg/public/Mar2018/brandt_cg_01a_0318.pdf provides some guidance. Worst case should be determined.

SuggestedRemedy

Change from:

The mixing segment shall meet the insertion loss characteristics specified for link segments in 147.8.2 between any two MDI attachment points of the mixing segment, with all other MDI attachment points disconnected or terminated in a minimum 10 kOhm impedance.

To:

The mixing segment shall meet the insertion loss characteristics specified for link segments in 147.8.2 between any two MDI attachment points, including ends of the mixing segment, and at the end of stubs of length up to 10 cm, and with any combinations of up to at least seven other MDIs presenting minimum parallel load attached at any combination of permissible MDI attachment points. A reference configuration TBD is shown.

Proposed Response Response Status **W**

PROPOSED ACCEPT IN PRINCIPLE.

Change this:

====

The mixing segment shall meet the insertion loss characteristics specified for link segments in 147.8.2 between any two MDI attachment points of the mixing segment, with all other MDI attachment points disconnected or terminated in a minimum 10 kOhm impedance.

====

to this:

====

The mixing segment shall meet the insertion loss characteristics specified for link segments in 147.8.2 between any two MDI attachment and at the end of stubs of length up to 10 cm, and with any combinations of up to at least seven other MDIs presenting minimum parallel load attached at any combination of permissible MDI attachment points.

====

CI **147** SC **147.8.2** P **151** L **38** # **441**
 Pannell, Don NXP (donald.pannell@

Comment Type **TR** Comment Status **D** PMD

"specified for link segments in 147.8.2" points to itself.

SuggestedRemedy

Add in the Insertion loss content and refer to it or change the 1st sentence to "specified for link segments as specified below".

Proposed Response Response Status **W**

PROPOSED ACCEPT IN PRINCIPLE.

Already dealt with by #440

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

CI 147 SC 147.8.3 P 151 L 38 # 481
Brandt, David Rockwell Automation

Comment Type T Comment Status D PMD

Mode Conversion Loss conditions are not specific enough. "All other MDI attachment points" does not say how many other attachment points, the physical location of the attachment points, and whether they are attached by stubs or in-line. Worst case should be determined.

SuggestedRemedy

Change from:

The mixing segment shall meet the mode conversion loss characteristics specified for link segments in 147.8.3 at any MDI attachment point, including ends of the mixing segment, with all other MDI attachment points disconnected or terminated in a minimum 10 kOhm impedance.

To:

The mixing segment shall meet the mode conversion loss characteristics specified for link segments in 147.8.3 at any MDI attachment points, including ends of the mixing segment, and at the end of stubs of length up to 10 cm, and with any combinations of up to at least seven other MDIs presenting minimum parallel load attached at any combination of permissible MDI attachment points. A reference configuration TBD is shown.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

2 changes:

- Change this:

====

The mixing segment shall meet the mode conversion loss characteristics specified for link segments in 147.8.3 at any MDI attachment point, including ends of the mixing segment, with all other MDI attachment points disconnected or terminated in a minimum 10 kOhm impedance.

====

to this:

====

The mixing segment shall meet the mode conversion loss characteristics specified for link segments in 147.8.3 at any MDI attachment points and with any combinations of up to at least seven other MDIs presenting minimum parallel load attached at any combination of permissible MDI attachment points.

====

- Change "segments in 147.8.3 at any" to "segments in 147.7.3 at any"

CI 147 SC 147.9.1 P 152 L 3 # 424
Zimmerman, George CME Consulting et al

Comment Type T Comment Status D MDI

MDI connectors can be filled in simply without choosing a connector.

SuggestedRemedy

"The mechanical interface to the balanced cabling is a 3-pin connector (BI_DA+, BI_DA-, and SHIELD) or alternatively a 2-pin connector with an additional mechanical shield connection which conforms to the link segment specification defined in 147.7 or to the mixing segment specification defined in 147.8."

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Add the following text (paragraph) to under "147.9.1 MDI connectors" (links must be taken care of):

====

The mechanical interface to the balanced cabling is a 3-pin connector (BI_DA+, BI_DA-, and SHIELD) or alternatively a 2-pin connector with an additional mechanical shield connection which conforms to the link segment specification defined in 147.7 or to the mixing segment specification defined in 147.8.

====

Notes:

- This is an <exact> copy of "146.8.1 MDI Connectors"

- Fix capitaliatoin mismatch between 147.9.2.1 vs 146.8.3, and 147.9.1 vs. 146.8.1 (those of 147 are preferred)

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

CI 147 SC 147.9.2 P 152 L 5 # 478
Brandt, David Rockwell Automation

Comment Type T Comment Status D MDI

Minimum impedance is not specified for the MDI. The following submission establishes an initial concept and values:

http://www.ieee802.org/3/cg/public/Mar2018/brandt_cg_01a_0318.pdf

SuggestedRemedy

Insert the following in

The MDI shall present a minimum parallel impedance across the MDI attachment points based on the following impedance equation and limits for R, L, and C over the stated frequency range:

$$Z = 1/\sqrt{(1/R)^2 + (1/(2\pi f L) - 2\pi f C)^2}$$

$$R > 5 \text{ k}\Omega$$

$$440\mu\text{H} < L < 1 \text{ mH}$$

$$C < 4.5 \text{ pF}$$

$$0.3 \text{ MHz} < f < \text{TBD MHz}$$

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

TF to discuss proposed resolution.

Insert the following text to "147.9.2 MDI electrical specification":

====

The MDI shall present a minimum parallel impedance across the MDI attachment points based on the following impedance equation and limits for R, L, Ctot and Cnode over the stated

frequency range, where Ctot is the total capacitance across all attachment points while

Cnode is the max capacitance for each attachment point:

$$Z = 1/\sqrt{(1/R)^2 + (1/(2\pi f L) - 2\pi f C_{\text{node}})^2}$$

$$R > 5 \text{ k}\Omega$$

$$440\mu\text{H} < L < 1 \text{ mH}$$

$$C_{\text{tot}} < 180 \text{ pF}$$

$$C_{\text{node}} < 4.5 \text{ pF}$$

$$0.3 \text{ MHz} \leq f \leq 40 \text{ MHz}$$

====

Notes:

- Equations should be numbered equations

- In Cnode, node is lower-index (several places)

- In Ctot, tot is lower-index (several places)

For all details, see "mail_gerge.ly.docx" from Piergiorgio

CI 147 SC 147.9.2.1 P 152 L 9 # 425
Zimmerman, George CME Consulting et al

Comment Type T Comment Status D MDI

MDI return loss specifies the termination. Requiring the termination of the MDI would specify an implementation.

SuggestedRemedy

Change "In multidrop configuration the MDI shall be terminated by two 100 ? (nominal) impedances

satisfying Equation (147-6) when measured with 100 ? ±1% impedance at the edges." to

"The MDI return loss (RL) shall meet or exceed Equation (147-6) for all frequencies

specified (with 100 ? ± 0.1 % reference impedance) at all times when the PHY is

transmitting data."

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Change "In multidrop configuration the MDI shall be terminated by two 100 ? (nominal)

impedances satisfying Equation (147-6) when measured with 100 CAP_OMEGA ±1%

impedance at the edges." to "The MDI return loss (RL) shall meet or exceed Equation (147-

6) for all frequencies specified (with 100 CAP_OMEGA ± 0.1 % reference impedance) at all

times when the PHY is transmitting data."

Notes:

- CAP_OMEGA is capital omega

- spaces before CAP_OMEGA and ± are non-breaking

CI 147 SC 147.9.2.1 P 152 L 14 # 426
Zimmerman, George CME Consulting et al

Comment Type T Comment Status D TBDs

Upper frequency for MDI return loss should be consistent with mixing segment upper frequency - 40 MHz.

SuggestedRemedy

Fill in TBD upper frequency in Equation 147-6 (lines 14 and 17) with 40 MHz.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

2 changes:

- Replace the 2 TBDs by "40"

- Make the interval closed by replacing "< TBD" by "<= 40"

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

CI 148 SC 148.2 P 157 L 18 # 332
Orzelli, Antonio Canova Tech

Comment Type T Comment Status D Editorial

Proposal for PLCA Overview.

SuggestedRemedy

Add text to paragraph 148.2 as reported in attached PDF (slide 17).

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Editor suggests a more compact description.

Replace editor's note in subclause 148.2 with the following text:

"The working principle of PLCA is that each PHY on a multidrop network is granted, in turn, a single transmit opportunity based on its assigned unique node ID.

At any time, only the PHY owning a transmit opportunity is allowed to send data over the medium, therefore avoiding physical collisions.

Transmit opportunities are generated in a round-robin fashion every time the PHY with node ID = 0 signals a BEACON on the medium, indicating the start of a new cycle. This can only happen after each PHY has been given exactly one transmit opportunity, thus ensuring media access fairness.

PLCA relies on CSMA/CD functions to have the MAC delay a transmissions until a transmit opportunity is met."

CI 148 SC 148.4.4.1.1 P 161 L 43 # 442
Pannell, Don NXP (donald.pannell@

Comment Type TR Comment Status D Primitives

"PHY specifications are free to map the BEACON request to any suitable coding as long as the requirement defined herein are met." Since this section is talking about the MII interface, which can be an exposed interface, allowing for custom codes does not allow for interoperability.

SuggestedRemedy

Change this to a shall use the code defined in Table 22-1. If this is not the intention, then this sentence needs to be clarified.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Change "PHY specifications are free to map the BEACON request to any suitable coding as long as the requirement defined herein are met."

to "PHY specifications are free to map the BEACON request to any suitable line coding as long as the requirement defined herein are met."

This sentence actually refers to the BEACON at the MDI. The change now refers to "line coding" to avoid confusion with MII codes.

CI 148 SC 148.4.4.1.2 P 162 L 1 # 443
Pannell, Don NXP (donald.pannell@

Comment Type TR Comment Status D Primitives

"PHY specifications are free to map the COMMIT request to any suitable coding as long as the requirement defined herein are met." Since this section is talking about the MII interface, which can be an exposed interface, allowing for custom codes does not allow for interoperability.

SuggestedRemedy

Change this to a shall use the code defined in Table 22-1. If this is not the intention, then this sentence needs to be clarified.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Change "PHY specifications are free to map the COMMIT request to any suitable coding as long as the requirement defined herein are met."

to "PHY specifications are free to map the COMMIT request to any suitable line coding as long as the requirement defined herein are met."

This sentence actually refers to the COMMIT at the MDI. The change now refers to "line coding" to avoid confusion with MII codes.

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

CI 148 SC 148.4.4.2.4 P 163 L 3 # 427
Zimmerman, George CME Consulting et al

Comment Type E Comment Status D Editorial

Editor's note has served its purpose

SuggestedRemedy

Delete editor's note

Proposed Response Response Status W

PROPOSED ACCEPT.

CI 148 SC 148.4.5.1 P 163 L 20 # 428
Zimmerman, George CME Consulting et al

Comment Type E Comment Status D EZ

Figure 148-TBD appears to refer to Figures 148-3 and 148-4.

SuggestedRemedy

Change Figure 148-TBD to "Figure 148-3 and Figure 148-4" (cross references)

Proposed Response Response Status W

PROPOSED ACCEPT.

CI 148 SC 148.4.5.1 P 163 L 26 # 444
Pannell, Don NXP (donald.pannell@

Comment Type E Comment Status D EZ

"with local_nodeID variable set to 0 immediately"

SuggestedRemedy

Change to "with local_nodeID variable set to 0, immediately" i.e., add in the ',' after the '0'.

Proposed Response Response Status W

PROPOSED ACCEPT.

CI 148 SC 148.4.5.1 P 163 L 26 # 327
Orzelli, Antonio Canova Tech

Comment Type T Comment Status D State Diagram

The node with ID = 0 could be reset in the middle of a BEACON cycle and start over sending a new BEACON while other PHYs are still in the process of transmitting / waiting their TO.

To avoid this the node with ID = 0 could start in recovery mode and wait for the media to be silent before sending the BEACON.

SuggestedRemedy

change "When PLCA functions are enabled, the PHY with local_nodeID variable set to 0 immediately switches to SEND_BEACON state..." with "When PLCA functions are enabled, the PHY with local_nodeID variable set to 0 immediately switches to RECOVER state and waits for all other PHYs to be silent for at least RECV_BEACON_TIMER. Then it switches to SEND_BEACON state..."

See attached PDF (slide 12).

Proposed Response Response Status W

PROPOSED ACCEPT.

Replace text:

"When PLCA functions are enabled, the PHY with local_nodeID variable set to 0 immediately switches to SEND_BEACON state to have all other PHYs synchronize their own transmit opportunity counter and related timer."

With:

"When PLCA functions are enabled, the PHY with local_nodeID variable set to 0 immediately switches to RECOVER state and waits for all other PHYs to be silent for at least RECV_BEACON_TIMER. Then it switches to SEND_BEACON state to have all other PHYs synchronize their own transmit opportunity counter and related timer."

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

Cl 148 SC 148.4.5.1 P 163 L 28 # 445
Pannell, Don NXP (donald.pannell@

Comment Type E Comment Status D State Diagram
"Slave PHYs wait"

SuggestedRemedy

Change to "Slave PHYs (i.e., those with local_nodeID variable not set to 0) wait".

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Change "Slave PHYs" to "PHYs with nonzero local_nodeID"

This should have been fixed by comment 168 on d1p1 which was part of a number of comments removing the term "Slave PHYs" and "MASTER PHY" from PLCA. Comment 168 fixed other parts of the sentence but missed the term "Slave PHYs" at the start of this sentence.

Cl 148 SC 148.4.5.1 P 165 L 10 # 328
Orzelli, Antonio Canova Tech

Comment Type T Comment Status D State Diagram

The node with ID = 0 could be reset in the middle of a BEACON cycle and start over sending a new BEACON while other PHYs are still in the process of transmitting / waiting their TO.
To avoid this the node with ID = 0 could start in recovery mode and wait for the media to be silent before sending the BEACON.

SuggestedRemedy

In Figure 148-3 add a transition from DISABLE state to RECOVER state with description

"plca_en = ON * local_nodeID = 0".

In Figure 148-3 change transition from DISABLE to RESYNC state from "plca_en = ON" to "plca_en = ON * ELSE".

See attached PDF (slide 13).

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

ELSE is not appropriate from an editorial point of view in this case.

In Figure 148-3 add a transition from DISABLE state to RECOVER state with description

"plca_en = ON * local_nodeID = 0".

In Figure 148-3 change transition from DISABLE to RESYNC state from "plca_en = ON" to "plca_en = ON * local_nodeID != 0".

Where '!=' stands for the "not equal" symbol

Cl 148 SC Figure 148-4 P 166 L 11 # 483
Brandt, David Rockwell Automation

Comment Type T Comment Status D State Diagram
The exist conditions from WAIT_TO are ambiguous.

SuggestedRemedy

Change to:

curlD = local_nodeID * packetPending= FALSE * plca_eri = FALSE

curlD = local_nodeID * packetPending = TRUE * plca_eri = FALSE

TO_TIMER done * curlD != local_nodeID * plca_eri = FALSE

plca_eri = TRUE

Proposed Response Response Status W

PROPOSED ACCEPT.

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

CI 148 SC 148.4.5.2 P 167 L 3 # 476
Brandt, David Rockwell Automation

Comment Type T Comment Status D Management

RS signal plca_reset lacks reference to management interface register

SuggestedRemedy

Replace:

Generated by management interface (register TBD), resets the RS.

With:

The plca_reset signal is used to reset the optional PLCA function in the RS. This signal maps to ON when aPLCAReset is enabled and to OFF when aPLCAAdminState is normal, but is further qualified.

This signal is only set to ON when PLCA ability bit in MDIO register 3.2292.13 is set to a one and PLCA enable bit in MDIO register 3.2291.13 is set to a one. This signal is set to OFF when PLCA ability bit in MDIO register 3.2292.13 is set to a zero or PLCA enable bit in MDIO register 3.2291.13 is set to a zero.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Replace:

Generated by management interface (register TBD), resets the RS.

With:

The plca_reset signal is used to reset the optional PLCA function in the RS. This signal maps to ON when aPLCAReset is enabled and to OFF when aPLCAAdminState is normal, but is further qualified.

When the MDIO is present, this signal is only set to ON when PLCA ability bit in MDIO register 3.2292.13 is set to a one and PLCA enable bit in MDIO register 3.2291.13 is set to a one. This signal is set to OFF when PLCA ability bit in MDIO register 3.2292.13 is set to a zero or PLCA enable bit in MDIO register 3.2291.13 is set to a zero. When MDIO is not present, the functionality of 3.2291.13 and 3.2291.13 can be provided by equivalent means.

CI 148 SC 148.4.5.2 P 167 L 9 # 463
Brandt, David Rockwell Automation

Comment Type T Comment Status D Management

RS signal plca_en lacks reference to management interface register

SuggestedRemedy

Replace:

Generated by management interface (register TBD), enables PLCA functions.

With:

The plca_en signal controls the optional PLCA function in the RS. This signal maps to ON when aPLCAAdminState is enabled and to OFF when aPLCAAdminState is disabled.

This signal is set to ON when PLCA ability bit in MDIO register 3.2292.13 is set to a one and PLCA enable bit in MDIO register 3.2291.13 is set to a one. This signal is set to OFF when PLCA ability bit in MDIO register 3.2292.13 is set to a zero or PLCA enable bit in MDIO register 3.2291.13 is set to a zero.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Replace:

Generated by management interface (register TBD), enables PLCA functions.

With:

The plca_en signal controls the optional PLCA function in the RS. This signal maps to ON when aPLCAAdminState is enabled and to OFF when aPLCAAdminState is disabled.

When the MDIO is present, this signal is set to ON when PLCA ability bit in MDIO register 3.2292.13 is set to a one and PLCA enable bit in MDIO register 3.2291.13 is set to a one. This signal is set to OFF when PLCA ability bit in MDIO register 3.2292.13 is set to a zero or PLCA enable bit in MDIO register 3.2291.13 is set to a zero. When MDIO is not present, the functionality of 3.2291.13 and 3.2291.13 can be provided by equivalent means.

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

CI 148 SC 148.4.5.2 P 167 L 38 # 446
Pannell, Don NXP (donald.pannell@

Comment Type TR Comment Status D State Diagram

"Values: integer value from 0 to 255." does not match what is stated in sub-clause 147.8.

SuggestedRemedy

Change to: "Values: 8-bit integer in the range defined in Table-XYZ in section 147.8."
This clearly defines the size of the field and the expected range for conformance all in one place.

Proposed Response Response Status W

PROPOSED REJECT.

The local_nodeID range should not be tied to a specific PHY in this generic RS.
PLCA is designed for networks with a small number of nodes (see 148.1) and 255 is already an oversized value.

Additionally, there is no reference to this in 147.8 as the commenter suggests.

CI 148 SC 148.4.5.2 P 167 L 48 # 447
Pannell, Don NXP (donald.pannell@

Comment Type TR Comment Status D State Diagram

"Values: integer value from 0 to 255." does not match what is stated in sub-clause 147.8.

SuggestedRemedy

Change to: "Values: 8-bit integer in the range defined in Table-XYZ in section 147.8."
This clearly defines the size of the field and the expected range for conformance all in one place.

Proposed Response Response Status W

PROPOSED REJECT.

The local_nodeID range should not be tied to a specific PHY in this generic RS.
PLCA is designed for networks with a small number of nodes (see 148.1) and 255 is already an oversized value.

Additionally, there is no reference to this in 147.8 as the commenter suggests.

CI 148 SC 148.4.5.4 P 168 L 20 # 431
Pannell, Don NXP (donald.pannell@

Comment Type TR Comment Status D State Diagram

"Times the duration of the BEACON signal." does not specify the units.

SuggestedRemedy

Specify the units of this timer and its size (8-bits?). I suggest the units should be in number of BEACON symbols and not bit times. Else you have to define the proper operation for bit time values that are for a non-integer number of symbols!

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Resolve with comment 430. (on clause 147)

Change "BEACON_TIMER Times the duration of the BEACON signal. Timer value shall be defined within specific Reconciliation sublayers. Duration shall be enough to allow all PHYs to properly recover the BEACON indication."

to

"BEACON_TIMER Times the duration of the BEACON signal.

Duration: 20 bit times."

CI 148 SC 148.4.5.4 P 168 L 25 # 448
Pannell, Don NXP (donald.pannell@

Comment Type TR Comment Status D State Diagram

The RECV_TIMER's units are not specified.

SuggestedRemedy

Define the size of the RECV_TIMER (8-bit or 16-bit integer) and define its units. I recommend 5-bit symbols as the units to be consistent with the BEACON_TIMER.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Change line 27 from: "The actual value of this timer is implementation..." to
"Duration: This timer is implementation..." on line 27.

The comment suggests that the timer is a reported value rather than a timer in a state diagram. The description of the timer says that its duration is implementation-specific. Timers in 802.3 state diagrams do not state numbers of bits in representation nor units (unless the units are to define the duration). See 40.4.5.2 (referencing 14.2.3.2) in IEEE Std 802.3-2015, defining how timers operate.

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

Cl 148 SC 148.4.5.4 P 168 L 37 # 449
Pannell, Don NXP (donald.pannell@

Comment Type TR Comment Status D State Diagram

The TO_TIMER's units are specified as bit times. But are these media bit times or MII bit times (i.e., are we in the 4b space or the 5b space).

SuggestedRemedy

The size of the TO_TIMER is implied, but I would define it clearer to be a 16-bit integer and define its units. I recommend 5-bit symbols as the units to be consistent with the BEACON_TIMER.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.
Change "Value" to "Duration" on page 168 line 37.

Clause 148 is not specific to c147, it's generic. Besides, the PLCA control state machine is not tied to any specific clock, as a result, bit times are specified as the duration.

The comment suggests that the timer is a reported value rather than a timer in a state diagram. Timers in 802.3 state diagrams do not state numbers of bits in representation nor units (unless the units are to define the duration). See 40.4.5.2 (referencing 14.2.3.2) in IEEE Std 802.3-2015, defining how timers operate.

Cl 148 SC 148.4.5.4 P 168 L 43 # 450
Pannell, Don NXP (donald.pannell@

Comment Type TR Comment Status D State Diagram

The RECV_BEACON_TIMER's units are not specified.

SuggestedRemedy

Define the size of the RECV_TIMER (16-bit integer) and define its units. I recommend 5-bit symbols as the units to be consistent with the BEACON_TIMER.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.
Change line 41 from "This timer value shall be set at least to TO_TIMER * MAX_ID + BEACON_TIMER for safe operations."
to "Duration: The duration of this timer is controllable and should be at least TO_TIMER * MAX_ID + BEACON_TIMER for reliable operations."

See comment 448 for a discussion of timers and units.

Cl 148 SC 148.4.6.1 P 169 L 14 # 482
Brandt, David Rockwell Automation

Comment Type E Comment Status D Editorial

The variable delay line is not adequately described.

SuggestedRemedy

The variable delay line in Figure 148-2
Change from:

During the HOLD state the PLCA Control state machine is notified via the packetPending variable that data is available to be transmitted. At next transmit opportunity the PLCA Control state machine eventually allow transmitting the delayed data by setting the "committed" variable to TRUE. In such case the PLCA Data state machine switches to TRANSMIT state to actually deliver the data for the PHY to encode and transmit on the medium.

To:

During the HOLD state the PLCA Control state machine is notified via the packetPending variable that data is available to be transmitted and the beginning of the transmission is held in the variable delay line. At next transmit opportunity the PLCA Control state machine allow transmitting the delayed data by setting the "committed" variable to TRUE. In such case the PLCA Data state machine switches to TRANSMIT state to actually deliver the data for the PHY to encode and transmit on the medium.

The variable delay line is a small buffer that is necessary in order to avoid physical collisions by delaying transmission to the MII interface until the exclusive transmit opportunity for the node arrives. The variable delay line length is no greater than TO_TIMER * MAX_ID.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

The BEACON_TIMER should also be taken into account while computing the maximum delay line size.

Replace text:

"During the HOLD state the PLCA Control state machine is notified via the packetPending variable that data is available to be transmitted. At next transmit opportunity the PLCA Control state machine eventually allow transmitting the delayed data by setting the "committed" variable to TRUE. In such

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

case the PLCA

Data state machine switches to TRANSMIT state to actually deliver the data for the PHY to encode and transmit on the medium."

To:

"During the HOLD state the PLCA Control state machine is notified via the packetPending variable that data is available to be transmitted and the beginning of the transmission is held in the variable delay line. At next transmit opportunity the PLCA Control state machine allow transmitting the delayed data by setting the "committed" variable to TRUE. In such case the PLCA Data state machine switches to TRANSMIT state to actually deliver the data for the PHY to encode and transmit on the medium."

The variable delay line is a small buffer that is necessary in order to avoid physical collisions by delaying transmission to the MII interface until the exclusive transmit opportunity for the node arrives. The variable delay line length is no greater than $TO_TIMER * MAX_ID + BEACON_TIMER$."

CI 148 SC 148.4.6.1 P 169 L 19 # 329
Orzelli, Antonio Canova Tech

Comment Type T Comment Status D TX_ER
PLCA is not handling TX_ER. Add ABORT state in PLCA Data state machine to handle it.

SuggestedRemedy

Add text "If TX_ER is asserted during the HOLD state, the PLCA_Data state machine switches to ABORT state to assert packetPending = FALSE and to wait the MAC to stop sending data. The aborted packet will not be transmitted on the medium."

See attached PDF (slide 14).

Proposed Response Response Status W
PROPOSED ACCEPT IN PRINCIPLE.

According to clause 22.2.2.5, TX_ER (transmit coding error) does not affect data transmission when operating at 10 Mb/s.

TF to provide presentation with text to remove TX_ER handling from both T1S and T1L PHY.

TF to discuss whether to include TX_ER handling in 10BASE-T1 and eventually amend clause 22.

CI 148 SC 148.4.6.1 P 169 L 23 # 325
Orzelli, Antonio Canova Tech

Comment Type T Comment Status D State Diagram

In mis-configured networks physical collisions might happen.

In such case setting packetPending flag in PLCA Data state machine in COLLIDE state may cause trouble (e.g. COMMITTING while JAMMING).

SuggestedRemedy

change "During the COLLIDE state, the PLCA Data state machine asserts CARRIER_STATUS = CARRIER_ON via the PLS_CARRIER.indication primitive to prevent the MAC to make new..." with "During the COLLIDE state, the PLCA Data state machine asserts packetPending = FALSE and CARRIER_STATUS = CARRIER_ON via the PLS_CARRIER.indication primitive. When the MAC has finished to send the jam bits as described in Clause 4 it waits for the next transmit opportunity by switching to PENDING state.

During the PENDING state, the PLCA Data state machine asserts packetPending = TRUE and keeps CARRIER_STATUS = CARRIER_ON via the PLS_CARRIER.indication primitive to prevent the MAC to make new..."

See attached PDF (slide 10).

Proposed Response Response Status W
PROPOSED ACCEPT.

Replace Text:

"During the COLLIDE state, the PLCA Data state machine asserts CARRIER_STATUS = CARRIER_ON via the PLS_CARRIER.indication primitive to prevent the MAC to make new"

With:

"During the COLLIDE state, the PLCA Data state machine asserts packetPending = FALSE and CARRIER_STATUS = CARRIER_ON via the PLS_CARRIER.indication primitive. When the MAC has finished to send the jam bits as described in Clause 4 it waits for the next transmit opportunity by switching to PENDING state.

During the PENDING state, the PLCA Data state machine asserts packetPending = TRUE and keeps CARRIER_STATUS = CARRIER_ON via the PLS_CARRIER.indication

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

Cl **148** SC **148.4.6** P **170** L **45** # **331**
Orzelli, Antonio Canova Tech

Comment Type **T** Comment Status **D** TX_ER

PLCA is not handling TX_ER. Add ABORT state in PLCA Data state machine to handle it.

SuggestedRemedy

In Figure 148-5 add state "ABORT" with description "packetPending <= FALSE".

In Figure 148-5 add a transition from HOLD state to ABORT state with condition "committed = FALSE * TX_ER = TRUE".

In Figure 148-5 add a transition from ABORT state to IDLE state with condition "plca_txen = FALSE".

In Figure 148-5 change transition from HOLD state to HOLD state condition from "MCD * committed = FALSE" to "MCD * ELSE".

See attached PDF (slide 16).

Proposed Response Response Status **W**

PROPOSED ACCEPT IN PRINCIPLE.

According to clause 22.2.2.5, TX_ER (transmit coding error) does not affect data transmission when operating at 10 Mb/s.

TF to provide presentation with text to remove TX_ER handling from both T1S and T1L PHY.

TF to discuss whether to include TX_ER handling in 10BASE-T1 and eventually amend clause 22.

Cl **148** SC **148.4.6.1** P **171** L **7** # **326**
Orzelli, Antonio Canova Tech

Comment Type **T** Comment Status **D** State Diagram

In mis-configured networks physical collisions might happen.

In such case setting packetPending flag in PLCA Data state machine in COLLIDE state may cause trouble (e.g. COMMITTING while JAMMING).

SuggestedRemedy

In Figure 148-6 substitute "packetPending <= TRUE" with "packetPending <= FALSE" in state COLLIDE.

In Figure 148-6 add "packetPending <= TRUE" in state PENDING.

See attached PDF (slide 11).

Proposed Response Response Status **W**

PROPOSED ACCEPT.

Cl **148** SC **148.4.6.1** P **171** L **30** # **432**
Pannell, Don NXP (donald.pannell@

Comment Type **TR** Comment Status **D** State Diagram

On page 143 line 19 Sub-clause 147.3.7.2 states "When a sequence of at least two consecutive 'J' symbols is received" & on page 148 line 39 Sub-clause 147.4.3 states that "At the start of transmission, the symbol sequence J/J/J/K" implies that 3 'J's are transmitted, but the state diagram in Fig 148-6 does not show the 1st two octets of the MAC's preamble being converted into the J/J/J/K sequence.

SuggestedRemedy

Show in Fig 148-6 the translation of the MAC's preamble octets into the the SSD (Start of Stream Delimiter) required for this PHY. Or define this as a 'shall' somewhere.

Proposed Response Response Status **W**

PROPOSED REJECT.

I believe the commenter is referring to page 145 line 39, not 148 line 39 (page 148 is the PSD mask).

Generation of the PHY-specific SYNC, SYNC, SYNC, SSD (J/J/J/K) is specified in clause 147. (see figure 147-4, and associated "shall" at P 133 L 45)

Cl **148** SC **148.4.6.2** P **172** L **25** # **330**
Orzelli, Antonio Canova Tech

Comment Type **T** Comment Status **D** TX_ER

PLCA is not handling TX_ER. Add ABORT state in PLCA Data state machine to handle it.

SuggestedRemedy

Add variable description "TX_ER The MII signal TX_ER."

See attached PDF (slide 15).

Proposed Response Response Status **W**

PROPOSED ACCEPT IN PRINCIPLE.

According to clause 22.2.2.5, TX_ER (transmit coding error) does not affect data transmission when operating at 10 Mb/s.

TF to provide presentation with text to remove TX_ER handling from both T1S and T1L PHY.

TF to discuss whether to include TX_ER handling in 10BASE-T1 and eventually amend clause 22.

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

CI 200 SC 200A.1.1.2 P 200 L 21 # 305
Maguire, Valerie The Siemon Company

Comment Type T Comment Status D Link Segment
Trunk link sections and spur link sections are undefined.

SuggestedRemedy

Insert the following sentences before the sentence on line 21, "A trunk link section provides the feed to the the first PD or PSE in a 10BASE-T1L link segment. A spur link section feeds subsequent PDs or PSEs."

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Insert the following sentences before the sentence on line 21, The trunk link section provides power to the single pair field switches. The TBD link section interconnects the field switches. The spur link sections provides power to the PDs.

TBD for committee discussion.
Figure 200A-2 illustrates three link sections.
Power distributed hierarchically
(1)Trunk>main switch to field switches
(2)Spur>field switches to PDs
(3)TBD> field switch to field switch

CI 200 SC 200A.1.1.2 P 200 L 30 # 306
Maguire, Valerie The Siemon Company

Comment Type T Comment Status D Link Segment
Clarify if this is a spur link section or a trunk link section. Align media references.

SuggestedRemedy

Replace, "Powered Single-pair link section" with "Powered single balanced pair spur link section" in Figure 200A-2.

Proposed Response Response Status W

PROPOSED ACCEPT IN PRINCIPLE.

Resolve with comment#305

CI 200 SC 200A.1.1.2 P 200 L 30 # 307
Maguire, Valerie The Siemon Company

Comment Type T Comment Status D Link Segment
Clarify media in figure.

SuggestedRemedy

Insert "single balanced pair" after "AWG" in three locations in Figure 200A-2.

Proposed Response Response Status W

PROPOSED ACCEPT.

CI 200 SC 200A.1.1.2 P 200 L 30 # 309
Maguire, Valerie The Siemon Company

Comment Type T Comment Status D Link Segment
Clarify what gage conductors and length are used for this section.

SuggestedRemedy

Replace, "(e.g., 24V dc power) with "(e.g., XX Type E PoDL, 14 - 18 AWG single balanced pair cable, up to 1000m length). Commenter's note: Replace "XX" with correct voltage.

Proposed Response Response Status W

PROPOSED REJECT.

200A.1.1.2 Powered trunk cable topologies
DCR characteristics and class power requirements have not been agreed to by the Task Group.
See editors notes under 200A.1.1.2.1 Powered trunk cable DCR characteristics and 200A.1.1.2.2 Powered trunk cable class power requirements.

CI 200 SC 200A.1.1.2 P 200 L 30 # 308
Maguire, Valerie The Siemon Company

Comment Type T Comment Status D Link Segment
This is just an example, but it would be nice to reference PoDL power.

SuggestedRemedy

Replace "dc power" with "Type E PoDL" in four locations in Figure 200A-2 (e.g., "48V dc power" becomes "XX V Type 3 PoDL" - Commenter's note: replace XX with correct voltage).

Proposed Response Response Status W

PROPOSED REJECT

DCR characteristics and class power requirements have not been agreed to by the Task Group.
See editors notes under 200A.1.1.2.1 Powered trunk cable DCR characteristics and 200A.1.1.2.2 Powered trunk cable class power requirements.

I Management Parameters for 10 Mb/s Operation over Single Balanced Twisted-pair Cabling and Associat

CI 200 SC 200A.1.1.2 P 200 L 185 # 304
Maguire, Valerie The Siemon Company

Comment Type E Comment Status D Link Segment
Align media references with revised objectives.

SuggestedRemedy

Replace 4 occurrences of the phrase "Single-pair" in Figure 200A-2 with "single balanced pair" (Commenter's note: single should not be capitalized).

Proposed Response Response Status W
PROPOSED ACCEPT.