

IEEE 802.3da SPMD TF: Mixing Segment Musings

Peter Jones - Cisco

Background

- Use case library
(https://www.ieee802.org/3/SPMD/usecase/SPMD_Usecase_Library.pdf)
 - Multiple cases requested more nodes/longer reach(e.g., 32/75, 64/75, 24/75, 16/60, 32/100)
- Strawman objectives September 2019
(https://www.ieee802.org/3/SPMD/public/sep19/spmd_pjones_03a_0919.pdf)
 - “Define performance characteristics of a mixing segment with a single balanced pair of conductors supporting up to at least 32 nodes, for up to at least 75 m reach”
- Strawman objectives November 2019
(https://www.ieee802.org/3/SPMD/public/sep19/spmd_pjones_03a_0919.pdf)
 - “Define performance characteristics of a mixing segment with a single balanced pair of conductors supporting up to at least 16 nodes, for up to at least 50m reach”
- Objective 1 (https://www.ieee802.org/3/da/802d3da_objectives.pdf)
 - “Define performance characteristics of a mixing segment for 10Mb/s multidrop single balanced pair networks supporting up to at least 16 nodes, for up to at least 50m reach.”

Things to consider

- 10BASE-2: 30 nodes, 185m
- CAN: 32 nodes, 100m @ 500Kb/s
- DALI: 64 devices, 300m
- AS-I: 62 Nodes, 100m
- BacNet MS/TP*: 32 Nodes, 100m+
- DMX512*: 32 "unit loads", 400m
- Profibus*: 32 Nodes, 100m
- <next target technology>

*RS485 based systems

More things to consider

- Silicon gets cheaper over time, magnetics, MDI etc, not so much.
- We will end up coming back to do higher speeds, let's keep that in mind.
- We need to be credible compared to the technologies we want to replace.
- We can "extend" SPMD using Two Port MAC Relay's, but we want that to be the exception, not the rule.

Takeaways

- We need to make conscious decisions when trading off mixing segment, PHY and powering circuitry
- We should consider, and hopefully accept, PHYs more complex than Clause 147 to expand the supported scenarios/use cases
- We need to consider the value (and interpretation) of “Support interoperability with Clause 147 multidrop” vs the value of expanded target application support.

I

Consensus

WE BUILD IT.

Connect with us on:

 **Facebook:** <https://www.facebook.com/ieeesa>

 **Twitter:** @ieeesa

 **LinkedIn:** <http://www.linkedin.com/groups/IEEESA-Official-IEEE-Standards-Association-1791118>

 **IEEE-SA Standards Insight blog:** <http://standardsinsight.com>

 **YouTube:** IEEE-SA Channel

IEEE
standards.ieee.org
Phone: +1 732 981 0060 Fax: +1 732 562 1571
© IEEE