

224G PAM4 CR+/CR Channels and Their Characteristics

Mike Peng Li, Jenny Xiaohong Jiang, Hsinho Wu, Masashi Shimanouchi, Itamar Levin,
Ariel Cohen, Stas Litski, Zhiguo Qian, Ram Muthukaruppan, Ajay Balankutty, Jihwan Kim

Intel Corporation

Samuel Kocsis, Ali Hammoodi, Michael Rowlands


Amphenol

Mar 22th, 2022

Method and Objectives


- Two channels, 28 dB CR+, and 26 dB CR (BGA-to-BGA, at 56 GHz, the Nyquist of 224G-PAM4) supporting 1 m cable, were built/synthesized (they are subjected to further improvements).
- They will be used to conduct simulations/modelings (e.g., COM) to demonstrate the 802.3df CR+/CR-PAM4 feasibility and solution space, using the reference die and package models/parameters (see [mli_3df_02a_220316](#)) extracted from test chips/packages.

224 Gbps-PAM4 CR+/CR Channel Structure



224 Gbps-PAM4 CR+ Channel Characteristics

Channel Viewer: [29] FR: Sdd21




- IL: 28.05dB @ 56GHz
- ILD \approx 1dB (<56GHz)
- RL \approx 10dB (<56GHz)
- FEXT < 54dB (<56GHz)


Channel Viewer: [8] CP: ILD




Channel Viewer: [9] CP: Return Loss



Channel Viewer: [10] CP: ICR




Channel Viewer: [27] FR: Sdd21




224 Gbps-PAM4 CR Channel Characteristics

Channel Viewer: [12] FR: Sdd21




- IL: 25.94dB @ 56GHz
- ILD \approx 1dB (<56GHz)
- RL \approx 10dB (<56GHz)
- FEXT < 54dB (<56GHz)


Channel Viewer: [14] CP: ILD




Channel Viewer: [15] CP: Return Loss



Channel Viewer: [16] CP: ICR



Channel Viewer: [17] SBR: Sdd21



Thank You!