

# **Proposed Objectives – P802.3dj PAR**

## **IEEE P802.3df Task Force**

**John D'Ambrosia,  
Chair, IEEE P802.3df Task Force  
Futurewei, U.S. Subsidiary of Huawei**

**Mark Nowell  
Vice-Chair, IEEE P802.3df Task Force  
Cisco**

**12 July 2022**

# Proposed (1 of 2)

- **Non-Rate Specific**

- Support full-duplex operation only
- Preserve the Ethernet frame format utilizing the Ethernet MAC
- Preserve minimum and maximum FrameSize of current IEEE 802.3 standard
- Support a BER of better than or equal to  $10^{-13}$  at the MAC/PLS service interface (or the frame loss ratio equivalent)
- Provide support to enable mapping over OTN

- **200 Gb/s Related**

- Support a MAC data rate of 200 Gb/s
- Support optional single-lane 200 Gb/s attachment unit interfaces for chip-to-module and chip-to-chip applications
- Define a physical layer specification that supports 200 Gb/s operation:
  - over 1 pair of copper twin-axial cables in each direction with a reach of up to at least 1.0 meter
  - over 1 pair of SMF with lengths up to at least 500 m
  - over 1 pair of SMF with lengths up to at least 2 km

- **400 Gb/s Related**

- Support a MAC data rate of 400 Gb/s
- Support optional two-lane 400 Gb/s attachment unit interfaces for chip-to-module and chip-to-chip applications
- Define a physical layer specification that supports 400 Gb/s operation:
  - over 2 pairs of copper twin-axial cables in each direction with a reach of up to at least 1.0 meter
  - over 2 pairs of SMF with lengths up to at least 500 m

# Proposed Objectives (2 of 2)

- **800 Gb/s Related**

- Support a MAC data rate of 800 Gb/s
- Support optional four-lane 800 Gb/s attachment unit interfaces for chip-to-module and chip-to-chip applications
- Define a physical layer specification that supports 800 Gb/s operation:
  - over 4 pairs of copper twin-axial cables in each direction with a reach of up to at least 1.0 meter
  - over 4 pairs of SMF with lengths up to at least 500 m
  - over 4 pairs of SMF with lengths up to at least 2 km
  - over 4 wavelengths over a single SMF in each direction with lengths up to at least 2 km
  - over a single SMF in each direction with lengths up to at least 10 km
  - over a single SMF in each direction with lengths up to at least 40 km

- **1.6 Tb/s Related**

- Support a MAC data rate of 1.6 Tb/s
- Support optional sixteen-lane 1.6 Tb/s attachment unit interfaces for chip-to-module and chip-to-chip applications
- Support optional eight-lane 1.6 Tb/s attachment unit interfaces for chip-to-module and chip-to-chip applications
- Define a physical layer specification that supports 1.6 Tb/s operation:
  - over 8 pairs of copper twin-axial cables in each direction with a reach of up to at least 1.0 meter
  - over 8 pairs of SMF with lengths up to at least 500 m
  - over 8 pairs of SMF with lengths up to at least 2 km