


A 212.5 Gbps-PAM4 Chip-to-Module Channel for “Universal Port” and Its Characteristics: Design A

Mike Li, Jenny Jiang, Yi Heng Khor, Hsinho Wu, Masashi Shimanouchi,
Ilia Radashkevich, Itamar Levin, Ariel Cohen (Intel)
Ali Hammoodi, Jose Paniagua, Michael Rowlands, Sam Kocsis (Amphenol)

June 14, 2023

Background and Introduction (I)

- An important and common Chip-to-Module (C2M) Channel is the so-called “Universal Port” C2M, as shown in the following diagram





- The loss of the C2M channel (TP0-TP1A) budget is determined/bounded by the bump-to-bump, ref PKG, and DAC loss budget, which are trending ≤ 40 dB, ~ 6 dB, ~ 16 dB, for 212.5 Gbps-PAM4 signaling.

Background and Introduction (II)

- We leveraged our established/validated C2M channel design tool-flow-methodology (TFM) (e.g., oif2022.355.00, oif2022.498.00, oif2023.032.00) to create this C2M channel design A to support 212.5 Gbps-PAM4 “Universal Port”.




C2M Channel Design A for “Universal Port”



Component	Insertion Loss TP0-TP1a (dB) @ 53.125GHz
	Design A
Host PCB via	0.75 dB
Host PCB Trace	4.5 inch (1.27 dB/inch)
Connector	1.46 dB
HCB	3.42 dB
Total *	11.6 dB



* Not lineally added

C2M Channel Design A Characteristics (I)




TP0-TP1a Characteristics (DC-53.125GHz)

- IL: 11.6dB @ 53.125GHz
- RL \sim 12.0dB (<53.125GHz)
- FEXT < 37.3dB (<53.125GHz)
- NEXT < 47.5dB (<53.125GHz)





C2M Channel Design A Characteristics (II)



- $ILD < \pm 1 \text{ dB} (< 53.125 \text{ GHz})$
- $ICR > 25 \text{ dB} (< 53.125 \text{ GHz})$

C2M Channel Design A Characteristics (III)



[S] parameter BW DC-120GHz

Summary

- We have created a C2M channel Design A supporting “Universal Port” at 212.5 Gbps-PAM4
- This C2M channel includes PCB-Via, PCB, connector, and HCB
- This C2M channel has:
 - An IL (TP0-TP1A) of ~ 11.6 dB at 53.125 GHz
 - $RL < \sim 12.0$ dB at ≤ 53.125 GHz
 - $FEXT < 37.3$ dB, $NEXT < 47.5$ dB, at ≤ 53.125 GHz
 - PCB IL of 5.7 dB/reach of 4.5 inch (with 1.27 dB/inch) at 53.125 GHz