

#### 56.3.6.1.4 Timers

omp\_timer

This timer is used to measure the arrival rate of OMP frames in the link. Failure to receive frames is considered a fatal fault and requires a hard reset to the OMP functional block.

#### 56.3.6.1.5 Messages

**Editor's note: To be removed prior to publication. parameters of primitives should be more elaborately described either in a table or as list following primitive introduction.**

~~MA\_DATAOMP.request(outgoing, DA, SA, m\_sdu)~~

The service primitive used by a client to request an OMP functional block function with the specified request\_operands.

Three interfaces to this function exist with the respective indexes of:

GATE: ~~MA\_DATAOMP.request(DA, SA, m\_sdu)~~

REPORT: ~~MA\_DATAOMP.request(DA, SA, m\_sdu)~~

DISCOVERY: ~~MA\_DATAOMP.request(DA, SA, m\_sdu)~~

~~MA\_DATAOMP.indication(incoming, DA, SA, timestamp, opcode, m\_sdu)~~

The service primitive used by the OMP functional block to signal the client an event with specified parameters.

Three interfaces to this function exist with the respective indexes of:

GATE: ~~MA\_DATAOMP.indication(DA, SA, timestamp, opcode, m\_sdu)~~

REPORT: ~~MA\_DATAOMP.indication(DA, SA, timestamp, opcode, m\_sdu)~~

DISCOVERY: ~~MA\_DATAOMP.indication(DA, SA, timestamp, opcode, m\_sdu)~~

~~MA\_CONTROL.request(DA, SA, m\_sdu opcode, request operand list)~~

The service primitive used by a client to request a MAC Control sublayer function with the specified request\_operands.

~~MA\_CONTROL.indication(DA, SA, m\_sdu opcode, indication operand list)~~

The service primitive used by MAC Control sublayer to signal the client an event with specified parameters.