



TS-1000 implementation and the harmonization with EFM



Makoto Kadowaki
NEC Corporation




contents

- Comparison of the ER between IEEE and TTC
- An actual optical transceiver satisfying TTC TS-1000 class S spec
- Typical data example of extinction ratio and receive sensitivity

Comparison of the ER between IEEE and TTC (1)

$$ER = 10 \log(P_1/P_0)$$



- ER stability is strongly dependent on mechanism of APC.
- If APC is conventional type (i.e. only LD bias is compensated), ER will change according to the mark density of transmission data.
- The mark density of 4B/5B line coding will vary from 40% to 60%.
- Pseudo-random pattern is almost equal to 50% mark density.

Comparison of the ER between IEEE and TTC (2)

Estimated ER when using conventional (LD bias only compensated) APC


	Pseudo-random	4B/5B("1"=40%)
ER	8.2dB	6.6dB
	7.2dB	6dB
	XdB	YdB

$$Y = 10 \log \left(1 + \frac{10^{X/10} - 1}{1 + 0.1(10^{X/10} - 1)} \right)$$

An actual optical transceiver satisfying TTC TS-1000 class S spec (1)


Single fiber bi-directional transceiver module

- Integrating 1.3mm/1.5mm WDM function
- Small Form Factor (2x5) implementation
- 10 to 155 Mbps continuous-mode transmitter / receiver
- Signal Detect (S.D.) function
- Single power supply voltage of +3.3V



An actual optical transceiver satisfying TTC TS-1000 class S spec (2)

Parameter	Unit	1.5μm transmit / 1.3μm receive	1.3μm transmit / 1.5μm receive
Bit rate	Mbps		10 ~ 155.52
Laser Diode type	-		MLM-LD
Center wavelength	nm	1480 ~ 1580	1260 ~ 1360
Spectral width (RMS)	Nm	<6.0	<7.7
Mean output power	dBm		-14 ~ -8
Extinction ratio	dB		> 8.2
Overload	dBm		-8
Sensitivity	dBm		-30
Optical input Signal Detect (S.D.)	-	Normal Operation = High Level Fault Condition = Low Level	
Transmitter disable function (TDis)	-	Optical output enable = Low Level Optical output disable = High Level	
Ambient Temperature	°C		0 ~ +70
Power Supply Voltage	V		3.3(+/-5%)



Typical data example of extinction ratio and receive sensitivity

Item	Unit	TTC	IEEE	Remarks
Code		PRBS23-1	EFM test pattern(*)	
Extinction ratio	dB	11.1	11.1	
Receive sensitivity	dBm	-36.0	-33.9	BER=1E-12

Note *: IEEE802.3ah Table60-11-Example of Unbalanced pattern