

IEEE 802.3 Ethernet Working Group
DRAFT Liaison Communication

Source: IEEE 802.3 Working Group¹

To: Greg Sandels Chair, TIA TR-42 Engineering Committee
gsandels@ofsoptics.com

CC: Konstantinos Karachalios Secretary, IEEE-SA Standards Board
Secretary, IEEE-SA Board of Governors
sasecretary@ieee.org

Paul Nikolich Chair, IEEE 802 LMSC
p.nikolich@ieee.org

Adam Healey Vice-chair, IEEE 802.3 Ethernet Working Group
adam.healey@broadcom.com

Jon Lewis Secretary, IEEE 802.3 Ethernet Working Group
jon.lewis@dell.com

Henry Franc TIA TR-42 Engineering Committee Vice Chair
henry.franc@belden.com

Jonathan Jew TIA TR-42 Engineering Committee Secretary
jew@j-and-m.com

Bradley Woodman TIA TR-42.9 Subcommittee Chair
bradley.woodman@molex.com

Chris DiMinico IEEE 802.3 Working Group Liaison to TIA
cdiminico@ieee.org

Teesha Jenkins TIA Manager, Standards Secretariat Services
tjenkins@tiaonline.org

From: David Law Chair, IEEE 802.3 Ethernet Working Group
dlaw@hpe.com

Subject: Liaison reply to TR42

Approval: Agreed to at IEEE 802.3 Closing Plenary Teleconference, July 23, 2020

Dear Mr. Sandels,

Thank you very much for your letter. In your letter, you address the Chair of 802.3cg. It is our pleasure to inform you that the 802.3cg Task Force has concluded its work.

IEEE 802.3 Ethernet specifications are interoperability specifications and do not specify the electromagnetic performance of the attached devices. Electromagnetic compatibility is outside the scope of 802.3 interface specifications. From IEEE 802.3cg 146.9.2.2:

¹ This document solely represents the views of the IEEE 802.3 Working Group, and does not necessarily represent a position of the IEEE, the IEEE Standards Association, or IEEE 802.

A system integrating the 10BASE-T1L PHY is expected to comply with all applicable local and national codes for electromagnetic compatibility.

When designing systems to meet their application requirements for electromagnetic capability, a vendor is responsible for using the noise tolerance performance of the included PHY component(s) along with the common mode rejection and insertion loss characteristics of the cabling and the MDI.

The absolute common mode voltage range varies by application, and as such is outside the scope of IEEE 802.3 standards.

Sincerely,

David Law

Chair, IEEE 802.3 Ethernet Working Group

DRAFT