

PDCC Ad Hoc Closing Report

13 July 2022

Chad Jones

Cisco Systems, Inc.

PDCC Private Area

- https://www.ieee802.org/3/ad_hoc/PDCC/private/index.html

IEEE 802.3 PDCC Ad Hoc Private Area

The documents available on this page and subpages, and the access information for this page, shall not be copied or redistributed to others in violation of document copyrights.

[IEC 63315 liaison documents](#)

[IEC TC64/PT716 liaison documents](#)

[IEEE WG3.6.7 documents for review](#)

[ITU-T K.147 documents for review](#)

[IEC 61375 documents for review](#)

[IEC 11801 documents for review](#)

Ad Hoc Activity this week

- Met Tuesday for one hour
- Reviewed a proposed contribution from the IEEE 802.3 WG to ISO/IEC SC25/WG3
- Assembled a delegation for the September SC25 meeting to present and discuss the contribution

Proposed Contribution from 802.3

11801 and Use of 4P Cable for 1P Applications

Chad Jones

Chair, 802.3 PDCC Ad Hoc

This document solely represents the views of the IEEE 802.3 Working Group and does not necessarily represent a position of the IEEE, the IEEE Standards Association, or IEEE 802

Preface

- I don't want to get into wordsmithing slides in this meeting.
- If you have something to address, we can address this in the weekly PDCC Ad Hoc meetings (Wednesdays, 1PM ET, on the 802.3 call and meeting calendar).

Proposed Contribution from 802.3

Issue at hand

The IEEE 802.3 Working Group (WG) is aware that SC25/WG3 is drafting standards and technical reports (e.g. ISO/IEC 11801-1 Amd1 and ISO/IEC TR 11801-9911) that support use and reuse of 4P/multipair Category cabling classes to be used in 1P applications with the restriction of 0.75A per pair.

This restriction breaks the IEEE 802.3 'plug-and-play' interoperability model. As such, the WG feels the need to make a presentation to ISO/IEC JTC 1/SC 25, something that hasn't happened before as the work between the two groups has always had common goals.

Proposed Contribution from 802.3

The problem with 0.75A

- Using 4P cabling in 1P applications disallows the full current capabilities of Single Pair Ethernet (SPE)
- Cabling would limit PSEs to 0.75A
 - IEEE 802.3 PSEs or PDs do not know what kind of cabling is connected. Allowing a 0.75A option constrains ALL options to 0.75A – which is well below the current needed to deliver the power levels desired, for both current classes and future planned classes.
 - Note that this is a problem with having any two levels of maximum current.
- Installation guidance becomes overly complicated
 - A lot of work has gone into appropriate bundle sizing for 4P cabling, designed around the worst case 90W PoE current of 0.433A (particularly in the United States' National Electrical Code). A 'second tier' of 0.75A limit complicates this carefully crafted guidance.
 - The possibility of 1, 2, or 3 pairs being energized in shared-sheath cabling as well as grounding issues further complicate the guidance.

Proposed Contribution from 802.3

Future SPoE Plans

- Limiting SPoE to 0.75A will keep 11801-1 cabling and perhaps SPoE from addressing the full market
 - Note that 750mA only supports up to PoDL Class 14, which is 20W at the PD.
- Similar to 4P PoE, there are plans to raise the power from an SPE PSE to what's allowed under LPS, i.e. 100W max (90W with margin)
- Of course, this power is only extended to systems that can efficiently provide the power. This implies a max allowed loop resistance which further implies reach limitations. This is a long way of saying the 1km SPE links won't be capable.
 - PoDL Class 15 power can be delivered up to 158 meters and 400 meters with 18 AWG and 14 AWG twisted pair, respectively.
- The present requirements of Clause 104 are only a single example. Other powering schemes, outside of IEEE Std 802.3 use the full extent of NEC Class 2 limits of 2A. Today, non-802.3 power sources dominate the single-pair powering landscape.

Proposed Contribution from 802.3

Use Cases

- Powering beyond 20W delivered are required for a variety of applications
 - Media converters extending line powering to existing Class 4 PoE devices will require this (30W PoE pass thru + power of device)
 - Line-powered PoE field switches, will require greater than 20W even with minimal PoE capability (multiple PoE pass thru ports, likely at 15.4W at each port + device)
 - Many sensors, such as field cameras with pan-tilt-zoom and/or heat element capability today require > 20 W delivered
 - High-transient-current actuators would require additional cost of local energy storage without the ability to provide > 0.75A
- Class 2 power supplies today are used for a variety of non-Ethernet applications on single pairs that SPE seeks to replace
- Experience with 4-pair PoE has shown a need to deliver as much power as possible (initial release at 15.4W, revised twice to raise power).

Proposed Contribution from 802.3

IEEE 802.3 Requests

- The IEEE 802.3 WG requests that reuse of 4-pair cable for SPE be abandoned. The addition of cable reuse permits sections of the cable plant to not meet the full requirements, converting this from a plug and play system to an engineered system.
- Separate 1P from 4P
 - Remove all single pair information from 11801-1 Amd 1 and placed in a new standard, avoiding confusion
 - Many other standards point to 11801 assuming 4P cabling; the inclusion of 1P will require some rewrite of those other standards

Proposed Contribution from 802.3

Requirements if Use of 4P Cable for 1P Applications is Maintained

- CURRENT CARRYING CAPACITY SHOULD MATCH FROM BEGINNING TO END
 - Wire gauge shall match end-to-end, or at least be no smaller than that presented at the user interfaces (disallow hiding smaller wire gauge behind a larger gauge at the user interface)
- CLEARLY IDENTIFY ANY RESTRICTED CURRENT CHANNELS
 - Examples might be different color connectors or mandatory labelling
- PREVENT ACCIDENTAL MISCONFIGURATION
 - Different or keyed connectors to disallow interconnection of the disparate channels
 - One might think it's ok to plug a 0.75A cable into a 2.0A as the 2.0A channel can support the 0.75A requirements, but the guidance must disallow a 2.0A cable being the visible connection with 0.75A cable behind the wall.
- DISCOURAGE USE OF 4P CABLE FOR 1P APPLICATIONS FOR NEW INSTALLATIONS

Proposed Contribution from 802.3

Backup

Proposed Contribution from 802.3

802.3 Actions

- Members of the IEEE 802.3 Working Group are discussing adding text to expressly require cabling with current capacity of at least 2.0 A for SPE applications with IEEE 802.3 defined powering

Proposed Contribution from 802.3

Previous experience of IEEE 802.3

- Some have suggested that multiple current capabilities is no different than having different category cables for performance or too great of cable resistance for PoE
 - The primary effect of either of these is that the system does not perform to IEEE Std 802.3 specifications – no harm is done, and within the scope of 802.3
- Allowing reduced current carrying capacity could create a situation where the current carrying capacity of the link is exceeded by the attached application
 - Requires IEEE Std 802.3 to disallow easily misconfigured cabling or risk additional restrictions placed on the use of SPoE by other standards such as IEC 60364 Low-voltage electrical installations originating in IEC TC64

5. This slide to add

Title: Considering dependency of wire diameter and current carrying capacity

As wire diameter is a key parameter for current carrying capacity, smaller diameters will not allow the same amount of current per conductor. Therefore, the powering classes must be split into 2 groups:

- Maximum current carrying capacity (today 2A) for AWG18 wires to provide the maximum power to the PD. This includes a future proof current increasement from todays 1.6A to 2.0A per conductor.**
- Reduced current carrying capacity for AWG23 wires to provide reduced power of maximum 20W to the PD. All devices, sensors and actors which require more power must be wired with AWG18 wires only.**
- Keyed connectors shall be used to avoid a wrong insertion of small wire diameters into a PSE capable to deliver the maximum power.**

Motion PDCC1

- Move that the IEEE 802.3 Working Group approve https://www.ieee802.org/3/ad_hoc/PDCC/public/11801_cable_reuse_071322.pdf with editorial license granted to the Chair (or his appointed agent) as contribution from the IEEE 802.3 Working Group to ISO/IEC SC25 WG3 for their September 2022 Plenary.
- M: Chad Jones
- S:

Motion PDCC2

- Move that the IEEE 802.3 Working Group the delegation of George Zimmerman, Chad Jones, David Law, Geoff Thompson, and Bob Voss as IEEE 802.3 representatives from the IEEE 802.3 Working Group to ISO/IEC SC25 WG3.
- M: Chad Jones
- S:

Thank You