10GBASE-LRM CLOSING REPORT TO IEEE 802.3

9th March 2006 David Cunningham

IEEE 802.3aq TASK FORCE, Denver, CO., USA, 6-10 March 2006

Outline

- IEEE802.3aq Officers
- Reflector and Web details
- 10GBASE-LRM Objectives
- Project schedule
- Initial Sponsor Ballot and Confirmation Ballot Results
- Goals for this meeting
- Plan for this week

IEEE 802.3aq Officers

- Task Force Chair: David Cunningham
- Editor: Nick Weiner
- Web Master: Piers Dawe
- TP2 weekly call leader: Tom Lindsay
- TP3 weekly call leader: Jim McVey
- Channel Ad hoc Chair: Ian White
 - Task 1 (OM1, OM2, OM3 & connectors) leader: Richard Penty
 - Task 2 (Time variation of channel & MN): Jonathan King
 - Task 3 (Input-output parameters) leader: Lars Thon
 - Task 4 (Launch & Mode Filtering) leader: Yu Sun
 - Task 5 (Validation) leader: Nick Weiner

REFLECTOR AND WEB

There is a reflector set up

To subscribe, use this URL:

http://ieee802.org/3/aq/reflector.html

To subscribe via e-mail send this message

 stds-802-3-10gmmf <yourfirstname> <yourlastname> to ListServ@ieee.org

The IEEE 802 web page URL: http://ieee802.org/3

10GBASE-LRM web page URL:

http://ieee802.org/3/aq

GOALS FOR THIS MEETING

• The purpose of the meeting is comment resolution on Draft P802.3aq/D3.1

Agenda for March '06 Interim Meeting

Wednesday 8th

- Opening Remarks
- Editors report
- Comment resolution

 Cunningham_1_0306
 Dawe_1_0306
 Gomatam_1_0306
 Break
 Lunch
 Break
 Social

- 8:30 AM 9:15 AM
- 9:15 AM 10:00 AM
- 10:15 AM 10:00 PM

10:00 AM - 10:15 AM 12:30 PM - 13:30 PM 15:00 AM - 15:15 AM 19:00 PM - 20:00 PM

Comment resolution agenda.

	Wednesday 8th March				
	E, ER and GR comments: 1, 40, 41, 42,	F	PRBS9: 28, 36, 37		
	6 E comments – Proposed motion in comment 13				
	Break				
	Noise component of Comp. Stressed Receiver Test. David C (20)., Piers D (30). and Badri G. (15) presentations.		Split symmetric receiver test stressor: Paul K. (10) and John A. (10) presentations. John A. 2, (3), 4, 8, 11, (29),		
	Comments 3, 5, 6, 7, 29, 30	(30)			
	Lunch				
TWDP value and Tx Power: Tom L. (20) Presentation. 31, 34, 35, 38, 39				Jitter: 3	32 33.
	Break				
	Operating Range: 9, 10	Installation (use of patch cords): 12			

• Carefully considered all comments.

Comment #33 Clause 68, 68.6.11, Page 49, 12 Comment Type: TR

Currently jitter is added only to a clean eye. Please see comments 45 & 66 on D3.0

Suggested Remedy

Jitter needs to be included in the comp. stressed rx. To keep the test simple to implement a single value (375KHz,1UI) for the jitter is proposed.

Response:

Straw poll:

Those in favour in accept or accept in principle with test point TBD: 7 Those in favour of rejection: 7

Proposed reject:

Combining jitter tolerance test with comp. rx test would preclude an inexpensive XAUI based tester. For: 12 Against: 5

Abstain: 4

Tiostum T

Proposed reject:


Combining the jitter tolerance test with the comp. rx test would complicate the test without proven significant benefit.

For: 11

Against: 7

Abstain: 3

There is no consensus within the comment resolution committee to make a change.



Draft Timeline: 10GBASE-LRM Working Group and Sponsor

- Will continue recirculation's as required.
- Planning to put final approval of the draft for publication on REVCOM/SB agenda out of July Plenary meeting.