802.3 RE 5 Criteria (DRAFT 1.0)

RESG

18 November 2004

1st. Draft

Straw Poll Y: 23 N: 0 A:0

Market Potential

- Moves Ethernet into big new markets with the potential to eventually dominate
 - Consumer electronics companies will be producing Ethernet equipment
- Current home Ethernet ports are in the millions; new capabilties will increase this number
- CE products (100's million of potential ports)
 - DVD, TV, AVR, DVRs, speakers, etc.
 - Portable A/V products, musical instruments
- Attractive alternative/upgrade to current 1394-based and proprietary solutions
 - Make Ethernet become a "household" word

Compatibility

- Fully 802.3 compatible
 - Fully compliant with existing frame format
 - Fully compatible with 802.3 in best-effort MAC services
 - May require augmentation of MAC with time-sensitive MAC services
 - RE will have to augment the MAC-client interface to exchange time information
- Fully 802.1 compatible
 - Anticipated that it will be fully compatible for best-effort service with possible 802.1 work to add time-sensitive service.
- RE features may need to be auto-negotiated
 - Time-sensitive mode is a highest-common denominator
- Based on existing PHYs
- Supports PoE

Distinct Identity

- No time-sensitive MAC services in 802.3
 - No provisioning in 802.3 yet
 - No latency max in 802.3 yet
 - RE may leverage parts of 802.3ah

Expect to have a separate clause

Technical Feasibility

- Feasibility proven by existing 802.3 technologies
 - Existing PHYs
 - Add clock to MAC (already done for EPON)
- Mostly adding a set of rules for sending timesensitive in addition to best-effort frames on existing MAC
- Requires some coordination with 802.1 for provisioning extensibility
- Time-sensitive services are already present in other common technologies, e.g. IEEE 1394, SONET, T-1, etc.

Economic Feasibility

- Development investment is relatively low
- High product value due to increased capabilities
- Significantly reduces system cost
 - Removes many connectors, cables etc.
 - Reduces processing core (cheaper CPU, memory)
- Leverage CE volumes for silicon (adds 100's of millions of ports)
 - Enable significantly higher levels of integration and functionality
- Incremental cost to consumer will be negligible in near term (1st or 2nd generation product)
- CE manufacturers (silicon customers) want it ASAP