

TGB Sponsor Ballot

Conditional approval request

- WG Letter recirculation Ballot 17 approved with 94%
 - 81 approve, 5 disapprove, 3 abstain
- 2 of the 5 “no” votes converted to “yes” bringing approval at 96.5%
 - 2 of the remaining 3 “no” voters were contacted and declined to convert.
 - 1 of the “no” voters was not available.
- New Draft has been completed and ready for distribution pending conditional approval by Excom
- Motion to submit for conditional approval for sponsor Ballot passed with unanimous vote.

“No “ Vote issues

- The existence of options.
- Refusal to accept any backward compatibility mechanisms to accommodate the existing low rate FH standard
- Recommendation to replace the approved waveform with the optional.

Consideration to “no” vote comments

- All of the remaining “no” vote comments have been addressed through numerous motions during several interim and/or plenary meetings .
- The extensive discussions of these related motions resulted to consensus on the present draft.

No comment from J. Fischer

- The PBCC mode should not be optional. The CCK modulation is inherently very weak by today's communications standards. If the PBCC is not used then the only way to make this waveform useful is with a severe measure of equalization. Therefore the only way to make this standard a useful one depends on a companies implementation, not on the standard waveform itself. By making the PBCC a requirement then the standard waveform itself will have inherent utility.
- Make this mode required for a standard implementation.

802.11 response to J. Fischer

- REJECTED: as per LB16 with the following comment:
- Due to market considerations CCK has been adopted as a mandatory modulation. PBCC has been added as an option to allow a potentially higher performance upgrade. Use of the CCK or PBCC modulation allows complete interoperability through the use of the same PLCP header.

No comment from J. Cafarella

- The FH option contained in the draft violates the PAR restriction to a single PHY. Anyone can build a dual-mode transceiver if desired, but specifying how to do this violates our PAR.
- Separate from the fact that our PAR restricts the high-rate solution to a single PHY, it is important to realize that the FH PHY is limited by regulatory agencies (at least in the US) to low data rates, while DS signaling can effect much higher rates for reasonable E_B/N_0 values. It makes no sense to constrain any aspect of the future technology.
- Remove FH material from HR DSSS PHY standard

802.11 response to J. Cafarella

- ACCEPTED on LB 16, the FH option was eliminated in favor of a channel agility capability.

No comment from D. Bagby

- The PHY specification contains options.
- 802.11 has voted that options shall be minimized and included only when absolutely necessary (see previous meeting minutes). The presence of following options mandate a No vote:
 - Short PLCP frame format
 - FH PLCP frame format
 - DSSS/PBCC Data Modulation and Modulation rate
 - Delete or make mandatory the short preamble option.
 - Make mandatory the FH option.
 - Delete the PBCC option

802.11 response to D.Bagby

- Partially Rejected, the FH PLCP frame format option has been deleted. IEEE802.11 Task Group B has considered this comment at length but respectfully declines the proposed changes.
- The group understands and appreciates fully IEEE802.11's agreed position on options within the standard and its charter to produce a single IEEE802.11 high rate PHY. It is our belief that we have not violated either requirement. Our reasoning is based on both logical argument and considering and comparing to prior policy in other task groups under the same committee working to the same agreed guidelines. Several motions were put forth with the exact concerns expressed here and were voted down by the group.

802.11 response to D.Bagby, 2

- Consideration of this comment started with the question of whether the draft standard as published represents a single PHY. To resolve this question one has to agree on what defines a single PHY. One way to define this is to consider that the specification represents a single PHY if all implementations interoperate successfully. When tested against this criterion the published draft does represent a single PHY. Where there are options, sufficient thought has been given to ensure that these do not sacrifice interoperability.

802.11 response to D.Bagby, 3

- As an example, consider the current published IEEE802.11 standard. The two PHY layers defined at 2.4GHz do not interoperate at all. They are clearly understood to be two separate PHY layers. Consider next the IEEE802.11 MAC. It is common knowledge that IEEE802.11 has one MAC. That was the working group charter. However, this MAC contains at least four options: WEP security, the point coordination function, a strictly ordered service class and multiple outstanding MSDU support. None of these options affect base interoperability. Indeed, experience is now revealing an excellent degree of interoperability between different vendors products. We do not argue that IEEE802.11 has multiple MAC layers just because it has

802.11 response to D.Bagby, 4

- The group considered the IEEE802.11 guidelines on options; a position that we understand to have been based on an attempt to achieve the greatest chance of successful interoperability. We reviewed each of the three options within the HR DSSS draft and feel that each offers a given advantage but at a cost. Having such diversity in the standard is not necessarily bad. It allows product differentiation without sacrificing interoperability and allows a spectrum of cost/performance products to come to market. We also note that there is a standard method of dealing with optional items so that their significance is clear to implementers, suppliers, acquirers, users and protocol testers. That mechanism is the PICS. We assume

802.11 response to D.Bagby, 5

- We are aware that the inclusion of options can be criticized as the inability to reach a consensus. Indeed the PCF option in the IEEE802.11 MAC is interpreted by many as a political compromise between the CSMA distributed and polled deterministic MAC protocols that competed during the development of the standard. If consensus can be reached by making a function an option without sacrificing interoperability then perhaps this is a successful strategy.
- Based on this reasoning and looking to the example of other task groups in IEEE802.11 we reached our consensus

Schedule

- Recirculation
 - start March 15
 - closure March 30.
 - Comment resolution by teleconference on March 31
 - Start of sponsor ballot April 1
 - Close of Sponsor ballot May 1
 - Comment resolution starts on May 3
- Good likelihood on meeting original schedule for completion of Tgb (December 1999).